

This is a preview - click here to buy the full publication



IEC 61108-7

Edition 1.0 2024-05

INTERNATIONAL STANDARD

**Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) –
Part 7: Satellite based augmentation system (SBAS) L1 – Receiver equipment –
Performance standards, methods of testing and required test results**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060.30; 33.060.20

ISBN 978-2-8322-8555-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	10
3.1 Terms and definitions.....	10
3.2 Abbreviated terms.....	11
4 Minimum GNSS and SBAS performance standard	13
4.1 General.....	13
4.2 SBAS L1 receiver equipment	13
4.2.1 Minimum facilities	13
4.2.2 Configuration.....	14
4.2.3 Quality assurance.....	14
4.3 Performance standards for SBAS L1 receiver equipment	14
4.3.1 General	14
4.3.2 Equipment output	14
4.3.3 Accuracy	16
4.3.4 Acquisition.....	17
4.3.5 Availability	17
4.3.6 Dynamic range	17
4.3.7 Effects of specific interfering signals.....	17
4.3.8 Position update.....	18
4.3.9 SBAS input and processing	18
4.3.10 Navigational status indications.....	19
4.3.11 Operation under typical interference conditions	23
4.3.12 Output of COG, SOG and UTC	23
5 SBAS technical characteristics	24
5.1 General.....	24
5.2 SBAS L1 SIS RF characteristics	25
5.3 SBAS L1 SIS message characteristics	25
5.3.1 Identification.....	25
5.3.2 L1 C/A PRN Code for SBAS	26
5.3.3 SBAS data format	27
6 Methods of testing and required test results	28
6.1 Test sites	28
6.2 Test sequence	29
6.3 Test signals	29
6.4 Determination of accuracy	30
6.5 Environmental conditions	31
6.6 General requirements	31
6.7 Alert requirements	31
6.8 Presentation requirements	31
6.9 Performance check.....	31
6.10 SBAS L1 receiver tests descriptions	32
6.10.1 SBAS L1 receiver equipment	32
6.10.2 Configuration.....	32

6.10.3	Position output.....	32
6.10.4	Equipment output	32
6.10.5	Static accuracy and availability.....	32
6.10.6	Static accuracy with angular movement of the antenna.....	33
6.10.7	Dynamic accuracy	33
6.10.8	Acquisition.....	33
6.10.9	Sensitivity and dynamic range	34
6.10.10	Effects on specific interfering signals.....	34
6.10.11	Position update.....	34
6.10.12	SBAS input and processing	35
6.10.13	SBAS message processing.....	35
6.10.14	SBAS GEO satellite selection and switching	38
6.10.15	Navigational status indications.....	39
6.10.16	Test for typical interference conditions.....	41
6.10.17	Accuracy of COG and SOG.....	43
6.10.18	Validity of COG and SOG information	44
6.10.19	Output of UTC	44
6.10.20	Validation material for tropospheric model.....	44
Annex A (normative) High level procedure for SBAS navigation computation		45
A.1	GPS L1 signal processing	45
A.2	SBAS L1 signal processing	45
A.3	Application of SBAS messages	45
A.4	SBAS position computation.....	47
A.4.1	General	47
A.4.2	Weighted least squares algorithm	47
A.4.3	SBAS-based standard residual error.....	48
Annex B (normative) Sentences to support SBAS L1 receiver operation		49
B.1	General.....	49
B.2	80GBS – GNSS satellite fault detection	49
B.3	GFA – GNSS Fix Accuracy and Integrity	51
B.4	GNS – GNSS fix data.....	52
B.5	GRS – GNSS Range residuals	58
B.6	GSA – GNSS DOP and active satellites	61
B.7	GSN – GNSS SBAS navigation message	65
B.8	GSV – GNSS Satellites in View.....	66
B.9	RMC – Recommended minimum specific GNSS data	69
B.10	VTG – Course over ground and ground speed	71
Annex C (informative) GNSS interference, jamming and spoofing		72
C.1	General.....	72
C.2	Interference	72
C.3	Jamming	72
C.4	Spoofing	73
Annex D (normative) Alert management.....		74
Bibliography.....		75
Table 1 – Output sentences defined for positioning purposes.....		15
Table 2 – Output sentences for integration in other navigational aids.....		16

Table 3 – Required horizontal position accuracy and integrity for general navigation	19
Table 4 – Accuracy of COG	24
Table 5 – SBAS L1 SIS RF characteristics	25
Table 6 – SBAS Ranging C/A Codes	26
Table 7 – SBAS message format	27
Table 8 – SBAS Message Types	28
Table 9 – Broad-band interference	42
Table 10 – Pulsed interference	42
Table 11 – Continuous wave interference	42
Table 12 – Broad-band interference	43
Table D.1 – Required alerts and their classification.....	74

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – GLOBAL NAVIGATION SATELLITE SYSTEMS (GNSS) –

Part 7: Satellite based augmentation system (SBAS) L1 – Receiver equipment – Performance standards, methods of testing and required test results

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61108-7 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1104/FDIS	80/1114A/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61108 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

Satellite based augmentation system (SBAS) is designed to augment Global Navigation Satellite System (GNSS) by broadcasting additional signals from geostationary (GEO) satellites. The basic scheme is to use a set of ground monitoring stations (at precisely surveyed locations) to receive GNSS signals that are processed and transmitted to the master station(s) which formulates the correction messages applicable to users within the service area (i.e. ionospheric errors, satellite position/clock errors, etc.). These corrections are then transmitted to navigation payloads via uplink stations on GEO satellites. The GEO satellites then transmit these corrections in a GNSS-like signal across the service area. An integrity message is also broadcasted enabling receivers to remove errors in the GNSS signal for increased position accuracy and integrity. Users are notified within a few seconds of information that could lead to position error.

SBAS are civil aviation safety-critical system and are designed according to an international standard (SARPs:2023). So far, SBAS have already been commissioned by the US (Wide Area Augmentation System – WAAS), Europe (European Geostationary Navigation Overlay Service – EGNOS), Japan (Michibiki Satellite Augmentation System – MSAS) and India (GPS Aided GEO Augmented Navigation – GAGAN). At September 2022, analogous systems are under commissioning or development in other regions of the world such as BeiDou Satellite Based Augmentation System – BDSBAS in China, System of Differential Correction and Monitoring – SDCM in Russia, Korea Augmentation Satellite System – KASS in Republic of Korea, Southern Positioning Augmentation System – SouthPAN in Australia and New Zealand, Augmented Navigation for Africa – ANGA and the Solución de Aumentación para Caribe, Centro y Sudamérica – SACCSA in South/Central America and the Caribbean.

The maritime community is interested in using SBAS for ocean waters, coastal waters and harbour entrances/approaches in order to fulfil the agreed international operational performance requirements (IMO Resolution A.1046(27)), especially where there is no other augmentation service available (i.e. DGPS/DGLONASS) or in poorly covered environments. Besides, when Ground Based Augmentation Systems (GBAS) are available, SBAS could become either the primary augmentation system or could act as a back-up. SBAS aims at providing satellite clock/ephemeris corrections, ionospheric corrections and integrity information to GNSS signals that meet maritime requirements, enhanced accuracy and integrity information.

IMO MSC.401(95) and IEC 61108-4 (Shipborne DGPS and DGLONASS maritime radio beacon receiver equipment) allow the use of different augmentation signals in shipborne receivers but there is neither an IMO or IEC standard on how to process and implement SBAS signals in shipborne receivers. One of the operational and functional requirements (Module B) of IMO Resolution MSC.401(95) is that the equipment has the facilities to process augmentation data in accordance with the appropriate methods, e.g. Recommendation ITU-R M.823, RTCM 10410, or other relevant standards, already existing or still to be developed in particular for satellite based augmentation system (SBAS) adoption. This document provides the requested standard for SBAS L1 augmenting GPS L1.

Most of recent maritime GNSS receiver models are SBAS compatible but present important differences in their performance since they are not certified according to any specific test standard.

IEC 61108 is a series of IEC standards for "Maritime navigation and radio-communication equipment and systems – Global navigation satellite systems (GNSS)". IEC has published International Standards for the following GNSS systems: IEC 61108-1 for GPS, IEC 61108-2 for GLONASS, IEC 61108-3 for Galileo, IEC 61108-5 for BDS and IEC 61108-6 for IRNSS. In addition, IEC has published International Standard IEC 61108-4 for DGPS and DGLONASS which are Differential Global Navigation Satellite System (DGNSS) enhancing the primary GNSS constellations (GPS and GLONASS).

This document includes the minimum performances for the shipborne receivers, using SBAS L1 signals augmenting GPS L1, in order to be compliant with the IMO Resolution A.1046(27) operational requirements for ocean waters, harbour entrances, harbour approaches and coastal waters, along with the methods of testing and required test results.

Satellite Based Augmentation Systems (SBAS) are available in several regions worldwide to augment GPS L1 frequency by broadcasting additional SBAS L1 signals:

- SBAS are designed according to the same international standard (SARPs:2023).
- GPS L1 signal specification is presented in the GPS Interference Specification (IS-GPS-200).

A description of the GPS Standard Positioning Service Performance Standard (GPS-SPS-PS) is available at <https://www.gps.gov>.

NOTE A standard including dual-frequency multi-constellation (DFMC) SBAS services will be considered when appropriate.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – GLOBAL NAVIGATION SATELLITE SYSTEMS (GNSS) –

Part 7: Satellite based augmentation system (SBAS) L1 – Receiver equipment – Performance standards, methods of testing and required test results

1 Scope

This part of IEC 61108 specifies the minimum performance standards, methods of testing and required test results for Satellite based augmentation system (SBAS) shipborne receiver equipment, which uses L1 signals from GPS and satellite based augmentation system (SBAS) in order to improve the estimated GPS position.

This document addresses the use of SBAS L1 to provide augmentation to the GPS shipborne receiver (IMO Resolution MSC.112(73)). This document includes the minimum performances for SBAS L1 maritime receivers to be obtained by the receiver equipment under coverage of SBAS service in order to be compliant with the IMO Resolution A.1046(27) describing operational requirements for ocean waters, harbour entrances, harbour approaches and coastal waters.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60721-3-6:1987, *Classification of environmental conditions – Part 3: Classification of groups of environmental parameters and their severities – Ship environment*

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108-1:2003, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 1: Global positioning system (GPS) – Receiver equipment – Performance standards, methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 61162-450, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 450: Multiple talkers and multiple listeners – Ethernet interconnection*

IEC 62923-1, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results*

IEC 62923-2, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 2: Alert and cluster identifiers and other additional features*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required test results*

RTCA DO-229F:2020, *Minimum Operational Performance Standards (MOPS) for Global Positioning System/Satellite-Based Augmentation System Airborne Equipment.*