

INTERNATIONAL STANDARD

IEC 61951-2

Second edition
2003-04

**Secondary cells and batteries containing
alkaline or other non-acid electrolytes –
Portable sealed rechargeable single cells –**

**Part 2:
Nickel-metal hydride**

*This **English-language** version is derived from the original **bilingual** publication by leaving out all French-language pages. Missing page numbers correspond to the French-language pages.*



Reference number
IEC 61951-2:2003(E)

INTERNATIONAL STANDARD

IEC 61951-2

Second edition
2003-04

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Portable sealed rechargeable single cells –

Part 2: Nickel-metal hydride

© IEC 2003 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

U

For price, see current catalogue

CONTENTS

FOREWORD	7
1 Scope	11
2 Normative references.....	11
3 Definitions	11
4 Parameter measurement tolerances.....	13
5 Cell designation and marking.....	15
5.1 Cell designation.....	15
5.1.1 Small prismatic cells	15
5.1.2 Cylindrical cells.....	15
5.1.3 Button cells.....	17
5.2 Cell termination	17
5.3 Marking	17
5.3.1 Small prismatic cells and cylindrical cells.....	17
5.3.2 Button cells.....	19
6 Dimensions.....	19
6.1 Small prismatic cells and cylindrical cells.....	19
6.1.1 Small prismatic cells.....	21
6.1.2 Cylindrical cells.....	21
6.2 Button cells.....	23
7 Electrical tests	25
7.1 Charging procedure for test purposes.....	25
7.2 Discharge performance.....	25
7.2.1 Discharge performance at 20 °C.....	25
7.2.2 Discharge performance at 0 °C.....	27
7.2.3 Discharge performance for rapid charge cells (R cells)	29
7.3 Charge (capacity) retention.....	29
7.4 Endurance.....	29
7.4.1 Endurance in cycles.....	29
7.4.2 Permanent charge endurance	35
7.5 Charge acceptance at constant voltage	37
7.6 Overcharge.....	39
7.6.1 Small prismatic, L, M, H or X cylindrical, and button cells	39
7.6.2 LT, MT or HT cylindrical cells.....	39
7.6.3 R cylindrical cells.....	39
7.7 Safety device operation	41
7.8 Storage.....	41
7.9 Charge acceptance at +55 °C for LT, MT or HT cylindrical cells.....	43
7.10 Internal resistance	43
7.10.1 Measurement of the internal a.c. resistance.....	43
7.10.2 Measurement of the internal d.c. resistance.....	45
8 Mechanical tests.....	45

9	Type approval and batch acceptance	47
9.1	Batch approval	47
9.1.1	Type approval for small prismatic cells and button cells	47
9.1.2	Type approval for cylindrical cells	47
9.2	Batch acceptance	49
	Bibliography	53
	Figure 1 – Jacketed cylindrical cells	19
	Figure 2 – Jacketed small prismatic cells	19
	Figure 3 – Button cells	23
	Table 1 – Dimensions of jacketed small prismatic cells	21
	Table 2 – Cylindrical cells dimensionally interchangeable with primary batteries	21
	Table 3 – Dimensions of jacketed cylindrical cells not dimensionally interchangeable with primary batteries	23
	Table 4 – Dimensions of button cells	25
	Table 5 – Discharge performance at 20 °C for small prismatic cells and cylindrical cells	27
	Table 6 – Discharge performance at 20 °C for button cells	27
	Table 7 – Discharge performance at 0 °C for small prismatic cells and cylindrical cells	27
	Table 8 – Discharge performance at 0 °C for button cells	29
	Table 9 – Endurance in cycles for small prismatic, button and cylindrical cells	31
	Table 10 – Endurance in cycles for H or X cells	31
	Table 11 – Endurance in cycles for X cells	33
	Table 12 – Endurance in cycles for HR or XR cells	33
	Table 13 – Permanent charge endurance for L, M, H or X cells	35
	Table 14 – Permanent charge endurance for LT, MT or HT cells	37
	Table 15 – Overcharge at 0 °C	39
	Table 16 – Charge and discharge at +55 °C	43
	Table 17 – Constant discharge currents used for measurement of d.c. resistance	45
	Table 18 – Sequence of tests for type approval for small prismatic cells and for button cells	47
	Table 19 – Sequence of tests for type approval for cylindrical cells	49
	Table 20 – Recommended test sequence for batch acceptance	51

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE
OR OTHER NON-ACID ELECTROLYTES –
PORTABLE SEALED RECHARGEABLE SINGLE CELLS –**

Part 2: Nickel-metal hydride

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61951-2 has been prepared by subcommittee 21A: Secondary cells and batteries containing alkaline or other non-acid electrolytes, of IEC technical committee 21: Secondary cells and batteries.

This second edition cancels and replaces the first edition published in 2001 of which it constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
21A/374/FDIS	21A/380/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61951 series, published under the general title *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Portable sealed rechargeable single cells*, consists of the following parts:

- Part 1: Nickel-cadmium
- Part 2: Nickel-metal hydride.

The committee has decided that the contents of this publication will remain unchanged until 2008-06. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

Withdrawn

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – PORTABLE SEALED RECHARGEABLE SINGLE CELLS –

Part 2: Nickel-metal hydride

1 Scope

This part of IEC 61951 specifies marking, designation, dimensions, tests and requirements for portable sealed nickel-metal hydride, small prismatic, cylindrical and button rechargeable single cells, suitable for use in any orientation.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-486, *International Electrotechnical Vocabulary – Chapter 486: Secondary cells and batteries*

IEC 60051 (all parts), *Direct acting indicating analogue electrical measuring instruments and their accessories*

IEC 60086 (all parts), *Primary batteries*

IEC 60410, *Sampling plans and procedures for inspection by attributes*

IEC 60485, *Digital electronic d.c. voltmeters and d.c. electronic analogue-to-digital converters*

IEC 61959, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Mechanical tests for sealed portable secondary cells and batteries¹*

¹ To be published.