

This is a preview - click here to buy the full publication



IEC 60728-2

Edition 2.0 2010-01

INTERNATIONAL STANDARD

**Cable networks for television signals, sound signals and interactive services –
Part 2: Electromagnetic compatibility for equipment**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XA**

ICS 33.060.40, 33.100

ISBN 978-2-88910-262-4

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references.....	10
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Terms and definitions.....	11
3.2 Symbols.....	16
3.3 Abbreviations.....	17
4 Methods of measurements.....	17
4.1 General operating conditions.....	17
4.2 Disturbance voltages from equipment.....	18
4.2.1 Disturbance voltages from equipment in the frequency range from 9 kHz to 30 MHz.....	18
4.2.2 Disturbance voltages from equipment at the AC mains frequency and its harmonics.....	18
4.2.3 Measurement of input terminal disturbance voltage.....	18
4.3 Radiation from active equipment.....	19
4.3.1 Introduction.....	19
4.3.2 General measurement requirements.....	19
4.3.3 Methods of measurements.....	20
4.4 Immunity of active equipment.....	29
4.4.1 General.....	29
4.4.2 Performance criterion.....	29
4.4.3 Measurement of the external immunity to ambient fields.....	30
4.4.4 Internal immunity (immunity to unwanted signals).....	36
4.5 Screening effectiveness of passive equipment.....	41
4.5.1 Introduction.....	41
4.5.2 General measurement requirements.....	41
4.5.3 Methods of measurements.....	41
4.6 Electrostatic discharge immunity test for active equipment.....	42
4.7 Electrical fast transient/burst immunity test for AC power ports.....	43
4.8 Methods of measurement for telecom signal ports of multimedia network equipment.....	43
5 Performance requirements.....	43
5.1 General.....	43
5.1.1 Emission performance requirements.....	43
5.1.2 Immunity performance requirements.....	43
5.2 Disturbance voltages from equipment.....	43
5.2.1 Limits of mains terminal disturbance voltage.....	43
5.2.2 Limits of input terminal disturbance voltages.....	43
5.3 Radiation.....	44
5.3.1 Radiation from active equipment.....	44
5.3.2 Local oscillator power at the outdoor unit input.....	44
5.4 Immunity of active equipment.....	45
5.4.1 External immunity to electromagnetic fields.....	45
5.4.2 Internal immunity.....	45
5.4.3 Immunity of outdoor units to image frequency signals.....	50

5.5	Screening effectiveness of passive equipment	50
5.6	Electrostatic discharge immunity test for active equipment	50
5.7	Electrical fast transient/burst immunity test for AC power ports	50
5.8	Performance requirements for telecom signal ports of multimedia network equipment	51
5.9	Applicability of EMC performance requirements and methods of measurement to different types of equipment	51
	Bibliography.....	53
	Figure 1 – Measurement set-up for radiation measurements in the frequency range 5 MHz to 30 MHz using the coupling unit method.....	21
	Figure 2 – Absorbing clamp method (30 MHz to 950 MHz).....	23
	Figure 3 – Example of general measurement set-up	24
	Figure 4 – Example of measurement set-up for measurements on the input port of active equipment.....	24
	Figure 5 – Measurement set-up for the "substitution" radiation method – First measurement step	26
	Figure 6 – Measurement set-up for the substitution radiation method – Second measurement step	27
	Figure 7 – Frequency allocation for out-of-band immunity measurement of active equipment with nominal frequency range below 950 MHz for AM applications (Example: VHF broadband amplifier; bandwidth 40 MHz to 450 MHz)	30
	Figure 8 – Frequency allocation for out-of-band immunity measurement of active equipment with nominal frequency range above 950 MHz for FM applications (Example: IF amplifier; bandwidth 950 MHz to 1750 MHz)	31
	Figure 9 – Frequency allocation for in-band immunity measurement of active equipment with nominal frequency range below 950 MHz for AM applications (Example: broadband amplifier; bandwidth 40 MHz to 862 MHz).....	34
	Figure 10 – Frequency allocation for in-band immunity measurement of active equipment with nominal frequency range above 950 MHz for FM applications (Example: IF amplifier; bandwidth 950 MHz to 3000 MHz)	34
	Figure 11 – Measurement set-up for internal immunity test	36
	Figure 12 – Levels of wanted and unwanted signals for the internal immunity of FSS receiving outdoor units.....	39
	Figure 13 – Levels of wanted and unwanted signals for the internal immunity of BSS receiving outdoor units.....	40
	Figure 14 – Levels of unwanted signals for the internal immunity of active equipment in Band I (47 MHz to 68 MHz).....	46
	Figure 15 – Levels of unwanted signals for the internal immunity of active equipment in Band II (87,5 MHz to 108 MHz)	47
	Figure 16 – Levels of unwanted signals for the internal immunity of active equipment in Band III (174 MHz to 230 MHz)	48
	Figure 17 – Levels of unwanted signals for the internal immunity of active equipment in Band IV/V (470 MHz to 862 MHz).....	49
	Table 1 – Port structure of different network equipment	9
	Table 2 – Limits of mains terminal disturbance voltage	43
	Table 3 – Limits of input terminal disturbance voltages	44
	Table 4 – Limits of radiated disturbance power	44
	Table 5 – Limits of local oscillator terminal power	44

Table 6 – Limits of out-of-band immunity (lowest level/field strength for compliance with performance criterion, given in 4.4.2)	45
Table 7 – Limits of in-band immunity (lowest level/field strength for compliance with performance criterion, given in 4.4.2).....	45
Table 8 – Test specification for internal immunity.....	46
Table 9 – Limits of immunity to image frequency signals in terms of image suppression ratio	50
Table 10 – Limits of screening effectiveness of passive equipment within the nominal frequency ranges	50
Table 11 – Test specifications for electrostatic discharge immunity test for active equipment.....	50
Table 12 – Test specifications for electrical fast transient/burst immunity test.....	51
Table 13 – Port types and environmental conditions for EMC performance requirements and methods of measurement.....	51
Table 14 – Emission parameters	51
Table 15 – Immunity and screening effectiveness parameters.....	52

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 2: Electromagnetic compatibility for equipment

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-2 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition published in 2002, of which it constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- updated scope, added some new terms and definitions;
- added methods of measurement and performance requirements for telecom signal ports of multimedia network equipment;
- updated methods of measurement for immunity and emissions;

- applicability of EMC performance requirements and methods of measurement to different types of equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/1620/FDIS	100/1640/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60728 series, under the general title *Cable networks for television signals, sound signals and interactive services*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals, interactive services signals, interfaces and their associated data signals, using all applicable transmission media.

This includes

- CATV¹-networks,
- MATV-networks and SMATV-networks,
- individual receiving networks,

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardization work is from the antennas, special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardization of any user terminals (i.e. tuners, receivers, decoders, terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

¹ This word encompasses the HFC networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 2: Electromagnetic compatibility for equipment

1 Scope

This part of IEC 60728 applies to the radiation characteristics and immunity to electromagnetic disturbance of EM-active equipment (active and passive equipment) for the reception, processing and distribution of television, sound and interactive multimedia signals as dealt with in the following parts of the IEC 60728 series:

- IEC 60728-3 Active wideband equipment for coaxial cable networks
- IEC 60728-4 Passive wideband equipment for coaxial cable networks
- IEC 60728-5 Headend equipment
- IEC 60728-6 Optical equipment

It covers the following frequency ranges:

- | | |
|--|--------------------------------------|
| – Disturbance voltage injected into the mains | 9 kHz to 30 MHz |
| – Radiation from active equipment | 5 MHz to 25 GHz |
| – Immunity of active equipment | 150 kHz to 25 GHz |
| – Screening effectiveness of passive equipment | 5 MHz to 3 GHz (25 GHz) ² |

This standard specifies requirements for maximum allowed radiation, minimum immunity and minimum screening effectiveness and describes test methods for conformance testing.

Due to the fact that cable networks, the former cabled distribution systems for television and sound signals, are more and more used for interactive services, these networks may incorporate also equipment, which carry besides the cable network equipment ports also one or more telecom signal port(s) as well as one Ethernet (IP) port. This equipment should be named as multimedia network equipment.

The EMC behaviour of cable network equipment, telecommunication network equipment and multimedia network equipment may be described by the following port structure (see Table 1).

² For screening effectiveness of passive equipment no requirements apply at present for the frequency range 3 GHz to 25 GHz. Methods of measurement and limits are investigated for inclusion in a future amendment or revised edition.

Table 1 – Port structure of different network equipment

Port name	Cable network equipment	Telecommunication network equipment	Multimedia network equipment
Enclosure	X	X	X
Earth	X	X	X
AC/DC power supply	X	X	X
Control (e.g. alarm)	X	X	X
Antenna input port	X		X
RF network port	X		X
Telecom signal port		X	X
Ethernet (IP) port			X

Table 1 shows that cable network equipment and telecommunication network equipment have four common ports and one respectively two individual port each. Multimedia network equipment carries besides the common ports an antenna input port and/or a RF network port as well as a telecom signal port.

The electromagnetic compatibility requirements for telecommunication network equipment only are standardized in EN 300 386 (mainly) and in EN 301 489-4, those for cable network equipment only are given in this IEC 60728-2.

Equipment for multimedia networks of the above mentioned type has to work under the same EMC conditions as equipment, which is falling under the cable network and the telecommunication network EMC-standards. Due to the fact, that this equipment has to work in close proximity, e.g. in the same operating room, the EMC environmental conditions for all three types of equipment are the same.

This means that multimedia network equipment has to fulfil the EMC requirements of one of the above mentioned standards and in addition the EMC requirements, laid down in the other EMC standard, for the additional port, by which it is connected to the other network.

By this procedure it is ensured that multimedia network equipment fulfils the EMC conditions of one of the above mentioned networks and will neither disturb the respective other system nor will be disturbed by the respective other system via the connecting port.

Coaxial cables for cable networks do not fall under the scope of this standard. Reference is made to the European Standard series EN 50117.

This standard also covers active indoor antennas for which the requirements and the applicable methods of measurement are limited to the radiation and the electrostatic discharge phenomena.

Standardisation in the field of electromagnetic compatibility for any broadcast terminals (e.g. tuners, receivers, decoders, etc.) is covered by the International Standards CISPR 13 and CISPR 20 and for multimedia terminals by CISPR 22 and CISPR 24.

Requirements for the electromagnetic compatibility of receiver leads are laid down in IEC 60966-2-4, IEC 60966-2-5 and IEC 60966-2-6.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 13, *Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement*

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 20, *Sound and television broadcast receivers and associated equipment – Immunity characteristics – Limits and methods of measurement*

CISPR 22, *Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement*

CISPR 24, *Information technology equipment – Immunity characteristics – Limits and methods of measurement*

IEC 60050-161, *International Electrotechnical Vocabulary – Chapter 161: Electromagnetic compatibility*

IEC 60617, *Graphical symbols for diagrams*

IEC 60728 (all parts), *Cable networks for television signals, sound signals and interactive services*

IEC 60728-3:2005, *Cable networks for television signals, sound signals and interactive services – Part 3: Active wideband equipment for coaxial cable networks*

IEC 60966-2-4, *Radio frequency and coaxial cable assemblies – Part 2-4: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-2 connectors*

IEC 60966-2-5, *Radio frequency and coaxial cable assemblies – Part 2-5: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 1 000 MHz, IEC 61169-2 connectors*

IEC 60966-2-6, *Radio frequency and coaxial cable assemblies – Part 2-6: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors*

IEC 61000-3-2, *Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)*

IEC 61000-4-3, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*

IEC 61000-4-4, *Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test*

IEC 61000-4-6, *Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields*

IEC 61000-6-1:2005, *Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments*

IEC 61079-1:1992, *Methods of measurement on receivers for satellite broadcast transmissions in the 12 GHz band – Part 1: Radio-frequency measurements on outdoor units*

EN 300 386 V1.3.3 (2005), *Electromagnetic compatibility and Radio spectrum Matters (ERM); Telecommunication network equipment; ElectroMagnetic Compatibility (EMC) requirements*

EN 301 489-4 V1.3.1 (2002) *Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 4: Specific conditions for fixed radio links and ancillary equipment and services*

EN 50117 (all parts), *Coaxial cables used in cabled distribution networks*