



TECHNICAL SPECIFICATION

**Electric vehicles conductive charging system –
Part 3-5: DC EV supply equipment where protection relies on double or
reinforced insulation – Pre-defined communication parameters and general
application objects**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 43.120

ISBN 978-2-8322-5770-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|--|----|
| FOREWORD | 12 |
| INTRODUCTION | 14 |
| 1 Scope | 15 |
| 2 Normative references | 15 |
| 3 Terms and definitions | 15 |
| 4 Symbols and abbreviated terms | 15 |
| 5 Pre-defined communication objects | 16 |
| 5.1 General | 16 |
| 5.1.1 Overview | 16 |
| 5.1.2 Object 1000 _h : Device type | 16 |
| 5.1.3 Object 1001 _h : Error register | 17 |
| 5.1.4 Object 1003 _h : Pre-defined error field | 17 |
| 5.1.5 Object 1005 _h : COB-ID SYNC | 17 |
| 5.1.6 Object 1006 _h : Communication cycle period | 17 |
| 5.1.7 Object 1007 _h : Communication window length | 18 |
| 5.1.8 Object 1016 _h : Heartbeat consumer time | 18 |
| 5.1.9 Object 1017 _h : Heartbeat producer time | 18 |
| 5.1.10 Object 1018 _h : Identity | 18 |
| 5.1.11 Object 1029 _h : Error behaviour | 18 |
| 5.2 PDO communication | 19 |
| 6 General application objects for CANopen devices | 19 |
| 6.1 General | 19 |
| 6.2 Application objects produced by CANopen devices with NMT slave functionality | 20 |
| 6.2.1 General | 20 |
| 6.2.2 Object 6000 _h : Supported virtual devices | 20 |
| 6.2.3 Object 6002 _h : Status word | 23 |
| 6.2.4 Object 6003 _h : Device capability | 25 |
| 6.2.5 Object 6004 _h : System date and time (optional) | 27 |
| 6.2.6 Object 6005 _h : Device unique part number (optional) | 28 |
| 6.2.7 Object 6006 _h : Device electronic production date (optional) | 28 |
| 6.2.8 Object 6007 _h : Device installation date (optional) | 29 |
| 6.2.9 Object 6008 _h : Device nominal voltage (optional, mandatory for active devices) | 30 |
| 6.2.10 Object 6009 _h : Device alarm status | 32 |
| 6.2.11 Object 600A _h : Device alarm capability | 33 |
| 6.2.12 Object 600B _h : Device warning status (optional) | 35 |
| 6.2.13 Object 600C _h : Device warning capability (optional) | 37 |
| 6.2.14 Object 600E _h : Implemented specification versions | 39 |
| 6.2.15 Object 6020 _h : Device request dynamic voltage limitation | 41 |
| 6.2.16 Object 6022 _h : Device request dynamic current input limitation | 42 |

| | | |
|--------|--|----|
| 6.2.17 | Object 6023 _h : Device request dynamic current output limitation | 44 |
| 6.2.18 | Object 6024 _h : Device maximum continuous input current | 46 |
| 6.2.19 | Object 6025 _h : Device maximum continuous output current | 48 |
| 6.2.20 | Object 6026 _h : Device maximum voltage | 49 |
| 6.2.21 | Object 6027 _h : Device minimum voltage | 51 |
| 6.2.22 | Object 6039 _h : Device actual external voltage (optional)..... | 52 |
| 6.2.23 | Object 603A _h : Device peak input current | 54 |
| 6.2.24 | Object 603B _h : Device peak input current time (optional)..... | 55 |
| 6.2.25 | Object 603C _h : Device peak output current (optional) | 57 |
| 6.2.26 | Object 603D _h : Device peak output current time (optional)..... | 58 |
| 6.2.27 | Object 603E _h : Device actual current..... | 59 |
| 6.2.28 | Object 6040 _h : Device actual voltage | 61 |
| 6.2.29 | Object 6042 _h : Device internal temperature (optional) | 62 |
| 6.2.30 | Object 6043 _h : Device time on (optional) | 64 |
| 6.2.31 | Object 6044 _h : Device time standby (optional) | 64 |
| 6.2.32 | Object 6045 _h : Device switch on counter (optional)..... | 65 |
| 6.2.33 | Object 6060 _h : CANopen device measurement timing (optional) | 65 |
| 6.2.34 | Object 6064 _h : Device maximum AUX continuous input current (optional)..... | 69 |
| 6.2.35 | Object 6065 _h : Device maximum AUX continuous output current (optional) | 70 |
| 6.2.36 | Object 6066 _h : Device maximum AUX voltage (optional)..... | 72 |
| 6.2.37 | Object 6067 _h : Device minimum AUX voltage (optional)..... | 73 |
| 6.2.38 | Object 6070 _h : Device actual AUX current (optional)..... | 75 |
| 6.2.39 | Object 6071 _h : Device actual AUX voltage (optional) | 77 |
| 6.2.40 | Object 6072 _h : Device available output voltage | 78 |
| 6.2.41 | Object 6073 _h : Device available output current | 79 |
| 6.2.42 | Object 6074 _h : Device available input current (optional) | 81 |
| 6.3 | Security | 82 |
| 6.3.1 | General | 82 |
| 6.3.2 | Object 6311 _h : Locking status..... | 83 |
| 6.4 | Application objects consumed by CANopen devices with NMT slave functionality (mandatory)..... | 84 |
| 6.4.1 | General | 84 |
| 6.4.2 | Object 6001 _h : Control word | 85 |
| 6.4.3 | Object 6046 _h : Device set maximum voltage..... | 86 |
| 6.4.4 | Object 6047 _h : Device set minimum voltage..... | 88 |
| 6.4.5 | Object 604A _h : Device set maximum continuous input current | 89 |
| 6.4.6 | Object 604B _h : Device set maximum continuous output current | 90 |
| 6.4.7 | Object 604C _h : Device set maximum peak input current | 91 |
| 6.4.8 | Object 604D _h : Device set maximum peak input current time | 92 |
| 6.4.9 | Object 604E _h : Device set maximum peak output current..... | 93 |
| 6.4.10 | Object 604F _h : Device set maximum peak output current time | 94 |

| | | |
|-------|--|-----|
| 6.5 | Application objects consumed by CANopen devices with NMT slave functionality (optional)..... | 95 |
| 6.5.1 | General | 95 |
| 6.5.2 | Object 600D _h : Error behaviour at process interface (optional) | 95 |
| 6.5.3 | Object 6058 _h : Device security key (optional) | 96 |
| 6.5.4 | Object 6059 _h : Devices' user name and address (optional) | 97 |
| 6.5.5 | Object 605A _h : Device password (optional)..... | 99 |
| 6.5.6 | Object 6053 _h : Prefixes and SI units for analogue values (optional)..... | 100 |
| 7 | Application objects relevant for fleet management (optional) | 103 |
| 7.1 | General..... | 103 |
| 7.2 | Object 63D5h: Travelled distance | 103 |
| 7.3 | Object 63D6h: Travelled distance current trip..... | 104 |
| 7.4 | Object 63D7 _h : Travelled time | 105 |
| 7.5 | Object 63D8 _h : Travelled time current trip | 106 |
| 7.6 | Object 63D9 _h : Transferred watt hours..... | 107 |
| 7.7 | Object 63DA _h : Current trip transferred watt hours | 108 |
| 8 | Stationary applications (optional)..... | 110 |
| 8.1 | General application objects relevant for stationary applications | 110 |
| 8.2 | Object 6010 _h : Ambient temperature | 110 |
| 8.3 | Object 6011 _h : Phase 1 AC Current | 111 |
| 8.4 | Object 6012 _h : Phase 2 AC Current | 113 |
| 8.5 | Object 6013 _h : Phase 3 AC Current | 114 |
| 8.6 | Object 6014 _h : Phase 1 AC voltage..... | 115 |
| 8.7 | Object 6015 _h : Phase 2 AC voltage..... | 117 |
| 8.8 | Object 6016 _h : Phase 3 AC voltage..... | 118 |
| 8.9 | Object 6017 _h : Line 12 AC voltage | 120 |
| 8.10 | Object 6018 _h : Line 23 AC voltage | 121 |
| 8.11 | Object 6019 _h : Line 13 AC voltage | 123 |
| 8.12 | Object 601A _h : Phase 1 AC reactive power..... | 124 |
| 8.13 | Object 601B _h : Phase 2 AC reactive power..... | 126 |
| 8.14 | Object 601C _h : Phase 3 AC reactive power..... | 127 |
| 8.15 | Object 601D _h : Phase 1 AC apparent power | 129 |
| 8.16 | Object 601E _h : Phase 2 AC apparent power | 130 |
| 8.17 | Object 601F _h : Phase 3 AC apparent power..... | 132 |
| 8.18 | Object 6030 _h : Phase 1 AC real power..... | 134 |
| 8.19 | Object 6031 _h : Phase 2 AC real power..... | 135 |
| 8.20 | Object 6032 _h : Phase 3 AC real power..... | 137 |
| 8.21 | Object 6033 _h : Total AC reactive power | 138 |
| 8.22 | Object 6034 _h : Total AC apparent power..... | 140 |
| 8.23 | Object 6035 _h : Total AC real power..... | 141 |
| 8.24 | Object 6036 _h : Phase1 power factor (cos phi) | 143 |
| 8.25 | Object 6037 _h : Phase 2 power factor (cos phi) | 144 |

| | |
|---|-----|
| 8.26 Object 6038 _h : Phase 3 power factor (cos phi) | 146 |
| 8.27 Object 6050 _h : AC Frequency | 147 |
| 8.28 Object 6051 _h : Isolation resistance | 149 |
| 8.29 Object 6052 _h : Rated power..... | 150 |
| Annex A (informative) Measured values | 152 |
| A.1 General..... | 152 |
| A.2 Actual voltage | 152 |
| Annex B (normative) Process data object (PDO) communication for EMS | 153 |
| B.1 General..... | 153 |
| B.2 Specification of messages | 153 |
| B.3 Allocation of PDOs to virtual devices | 153 |
| B.4 Detailed PDO parameters | 159 |
| B.4.1 General | 159 |
| B.4.2 PDO parameters for message number 1 | 159 |
| B.4.3 PDO parameters for message number 2 | 162 |
| B.4.4 PDO parameters for message number 3 | 164 |
| B.4.5 PDO parameters for message number 4 to 9 | 167 |
| B.4.6 PDO parameters for message number 10 | 168 |
| B.4.7 PDO parameters for message number 12 | 170 |
| Bibliography..... | 173 |
| Figure 1 – Object structure | 16 |
| Figure 2 – Object structure supported virtual devices..... | 20 |
| Figure 3 – Object structure device status | 23 |
| Figure 4 – Value structure..... | 25 |
| Figure 5 – Value structure..... | 32 |
| Figure 6 – Value structure..... | 33 |
| Figure 7 – Value structure..... | 35 |
| Figure 8 – Value structure..... | 37 |
| Figure 9 – Value structure..... | 39 |
| Figure 10 – Object structure security status | 83 |
| Figure 11 – Value structure..... | 85 |
| Figure 12 – Object structure for prefixes | 101 |
| Figure A.1 – Voltage measurement at generic active device | 152 |
| Table 1 – Value definition for the bit field additional information..... | 16 |
| Table 2 – Object description | 17 |
| Table 3 – Entry description | 17 |
| Table 4 – Default value definition object 1005 _h | 17 |
| Table 5 – Value definition | 18 |
| Table 6 – Object description (optional)..... | 18 |
| Table 7 – Entry description | 19 |
| Table 8 – Value definition for bit fields | 21 |
| Table 9 – Object description | 22 |

| | |
|---|----|
| Table 10 – Entry description | 22 |
| Table 11 – Value definition device status | 23 |
| Table 12 – Object description | 24 |
| Table 13 – Entry description | 24 |
| Table 14 – Value definition | 25 |
| Table 15 – Object description | 26 |
| Table 16 – Entry description | 26 |
| Table 17 – Object description | 27 |
| Table 18 – Entry description | 27 |
| Table 19 – Object description | 28 |
| Table 20 – Entry description | 28 |
| Table 21 – Object description | 28 |
| Table 22 – Entry description | 29 |
| Table 23 – Object description | 29 |
| Table 24 – Entry description | 30 |
| Table 25 – Object description | 30 |
| Table 26 – Entry description | 31 |
| Table 27 – Value definition | 32 |
| Table 28 – Object description | 33 |
| Table 29 – Entry description | 33 |
| Table 30 – Value definition | 34 |
| Table 31 – Object description | 35 |
| Table 32 – Entry description | 35 |
| Table 33 – Value definition | 36 |
| Table 34 – Object description | 37 |
| Table 35 – Entry description | 37 |
| Table 36 – Value definition | 37 |
| Table 37 – Object description | 38 |
| Table 38 – Entry description | 39 |
| Table 39 – Value definition | 39 |
| Table 40 – Object description | 40 |
| Table 41 – Entry description | 40 |
| Table 42 – Value definition | 41 |
| Table 43 – Object description | 41 |
| Table 44 – Entry description | 41 |
| Table 45 – Value definition | 43 |
| Table 46 – Object description | 43 |
| Table 47 – Entry description | 43 |
| Table 48 – Value definition | 45 |
| Table 49 – Object description | 45 |
| Table 50 – Entry description | 45 |
| Table 51 – Object description | 46 |
| Table 52 – Entry description | 47 |

| | |
|-------------------------------------|----|
| Table 53 – Object description | 48 |
| Table 54 – Entry description | 48 |
| Table 55 – Object description | 49 |
| Table 56 – Entry description | 50 |
| Table 57 – Object description | 51 |
| Table 58 – Entry description | 51 |
| Table 59 – Object description | 53 |
| Table 60 – Entry description | 53 |
| Table 61 – Object description | 54 |
| Table 62 – Entry description | 54 |
| Table 63 – Object description | 56 |
| Table 64 – Entry description | 56 |
| Table 65 – Object description | 57 |
| Table 66 – Entry description | 57 |
| Table 67 – Object description | 58 |
| Table 68 – Entry description | 59 |
| Table 69 – Object description | 60 |
| Table 70 – Entry description | 60 |
| Table 71 – Object description | 61 |
| Table 72 – Entry description | 61 |
| Table 73 – Object description | 63 |
| Table 74 – Entry description | 63 |
| Table 75 – Object description | 64 |
| Table 76 – Entry description | 64 |
| Table 77 – Object description | 64 |
| Table 78 – Entry description | 64 |
| Table 79 – Object description | 65 |
| Table 80 – Entry description | 65 |
| Table 81 – Object description | 66 |
| Table 82 – Entry description | 66 |
| Table 83 – Object description | 69 |
| Table 84 – Entry description | 69 |
| Table 85 – Object description | 70 |
| Table 86 – Entry description | 71 |
| Table 87 – Object description | 72 |
| Table 88 – Entry description | 72 |
| Table 89 – Object description | 74 |
| Table 90 – Entry description | 74 |
| Table 91 – Object description | 75 |
| Table 92 – Entry description | 75 |
| Table 93 – Object description | 77 |
| Table 94 – Entry description | 77 |
| Table 95 – Object description | 78 |

| | |
|---|-----|
| Table 96 – Entry description | 78 |
| Table 97 – Object description | 80 |
| Table 98 – Entry description | 80 |
| Table 99 – Object description | 81 |
| Table 100 – Entry description | 81 |
| Table 101 – Value definition security status | 83 |
| Table 102 – Object description..... | 83 |
| Table 103 – Entry description | 84 |
| Table 104 – Value definition..... | 85 |
| Table 105 – Object description..... | 85 |
| Table 106 – Entry description | 86 |
| Table 107 – Object description..... | 87 |
| Table 108 – Entry description | 87 |
| Table 109 – Object description..... | 88 |
| Table 110 – Entry description | 88 |
| Table 111 – Object description..... | 89 |
| Table 112 – Entry description | 89 |
| Table 113 – Object description..... | 90 |
| Table 114 – Entry description | 90 |
| Table 115 – Object description..... | 91 |
| Table 116 – Entry description | 91 |
| Table 117 – Object description..... | 92 |
| Table 118 – Entry description | 92 |
| Table 119 – Object description..... | 93 |
| Table 120 – Entry description | 93 |
| Table 121 – Object description..... | 94 |
| Table 122 – Entry description | 94 |
| Table 123 – Value definition..... | 95 |
| Table 124 – Object description..... | 95 |
| Table 125 – Entry description | 96 |
| Table 126 – Object description..... | 97 |
| Table 127 – Entry description | 97 |
| Table 128 – Object description..... | 98 |
| Table 129 – Entry description | 98 |
| Table 130 – Object description..... | 99 |
| Table 131 – Entry description | 99 |
| Table 132 – Additional units..... | 101 |
| Table 133 – Allocation of powerlines to sub-indices | 101 |
| Table 134 – Object description..... | 101 |
| Table 135 – Entry description | 101 |
| Table 136 – Object description..... | 103 |
| Table 137 – Entry description | 104 |
| Table 138 – Object description..... | 105 |

| | |
|-------------------------------------|-----|
| Table 139 – Entry description | 105 |
| Table 140 – Object description..... | 106 |
| Table 141 – Entry description | 106 |
| Table 142 – Object description..... | 107 |
| Table 143 – Entry description | 107 |
| Table 144 – Object description..... | 108 |
| Table 145 – Entry description | 108 |
| Table 146 – Object description..... | 109 |
| Table 147 – Entry description | 109 |
| Table 148 – Object description..... | 110 |
| Table 149 – Entry description | 110 |
| Table 150 – Object description..... | 111 |
| Table 151 – Entry description | 112 |
| Table 152 – Object description..... | 113 |
| Table 153 – Entry description | 113 |
| Table 154 – Object description..... | 114 |
| Table 155 – Entry description | 114 |
| Table 156 – Object description..... | 116 |
| Table 157 – Entry description | 116 |
| Table 158 – Object description..... | 117 |
| Table 159 – Entry description | 117 |
| Table 160 – Object description..... | 118 |
| Table 161 – Entry description | 119 |
| Table 162 – Object description..... | 120 |
| Table 163 – Entry description | 120 |
| Table 164 – Object description..... | 121 |
| Table 165 – Entry description | 122 |
| Table 166 – Object description..... | 123 |
| Table 167 – Entry description | 123 |
| Table 168 – Object description..... | 124 |
| Table 169 – Entry description | 124 |
| Table 170 – Object description..... | 126 |
| Table 171 – Entry description | 126 |
| Table 172 – Object description..... | 127 |
| Table 173 – Entry description | 128 |
| Table 174 – Object description..... | 129 |
| Table 175 – Entry description | 129 |
| Table 176 – Object description..... | 131 |
| Table 177 – Entry description | 131 |
| Table 178 – Object description..... | 132 |
| Table 179 – Entry description | 132 |
| Table 180 – Object description..... | 134 |
| Table 181 – Entry description | 134 |

| | |
|---|-----|
| Table 182 – Object description..... | 135 |
| Table 183 – Entry description | 136 |
| Table 184 – Object description..... | 137 |
| Table 185 – Entry description | 137 |
| Table 186 – Object description..... | 138 |
| Table 187 – Entry description | 139 |
| Table 188 – Object description..... | 140 |
| Table 189 – Entry description | 140 |
| Table 190 – Object description..... | 141 |
| Table 191 – Entry description | 142 |
| Table 192 – Object description..... | 143 |
| Table 193 – Entry description | 143 |
| Table 194 – Object description..... | 144 |
| Table 195 – Entry description | 145 |
| Table 196 – Object description..... | 146 |
| Table 197 – Entry description | 146 |
| Table 198 – Object description..... | 147 |
| Table 199 – Entry description | 148 |
| Table 200 – Object description..... | 149 |
| Table 201 – Entry description | 149 |
| Table 202 – Object description..... | 150 |
| Table 203 – Entry description | 151 |
| Table B.1 – PDO mapping entries | 153 |
| Table B.2 – PDO assignment for active devices | 154 |
| Table B.3 – PDO assignment for VCU 9 to 16 | 156 |
| Table B.4 – Additional PDO assignment for some active devices | 156 |
| Table B.5 – PDO assignment for passive devices | 158 |
| Table B.6 – Object description | 159 |
| Table B.7 – Entry description | 159 |
| Table B.8 – Object description | 161 |
| Table B.9 – Entry description | 161 |
| Table B.10 – Object description | 162 |
| Table B.11 – Entry description | 162 |
| Table B.12 – Object description | 164 |
| Table B.13 – Entry description | 164 |
| Table B.14 – TPDO communication parameter..... | 165 |
| Table B.15 – Entry description | 165 |
| Table B.16 – Object description | 166 |
| Table B.17 – Entry description | 167 |
| Table B.18 – Object description | 168 |
| Table B.19 – Entry description | 168 |
| Table B.20 – Object description | 169 |
| Table B.21 – Entry description | 170 |

| | |
|---------------------------------------|-----|
| Table B.22 – Object description | 170 |
| Table B.23 – Entry description | 171 |
| Table B.24 – Object description | 172 |
| Table B.25 – Entry description | 172 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 61851-3-5 has been prepared by s IEC technical committee 69: Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

| Draft | Report on voting |
|------------|---------------------------------|
| 69/651/DTS | 69/672/RV DTS 69/672A/RV DTS |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The following print types are used:

- requirements: in roman type;
- notes: in small roman type;
- **text formatted in bold and using mixed capital and underline are used as state names and are not to be translated.**

A list of all parts in the IEC 61851 series, published under the general title *Electric vehicles conductive charging system*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This document is published in separate parts according to the following structure:

IEC TS 61851-3-1, *Electric vehicles conductive charging system – Part 3-1: DC EV supply equipment where protection relies on double or reinforced insulation – General rules and requirements for stationary equipment*

IEC TS 61851-3-2, *Electric vehicles conductive charging system – Part 3-2: DC EV supply equipment where protection relies on double or reinforced insulation – Particular requirements for portable and mobile equipment*

IEC TS 61851-3-4, *Electric vehicles conductive charging system – Part 3-4: DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

IEC TS 61851-3-5, *Electric vehicles conductive charging system – Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects*

IEC TS 61851-3-6, *Electric vehicles conductive charging system – Part 3-6: DC EV supply equipment where protection relies on double or reinforced insulation – Voltage converter unit communication*

IEC TS 61851-3-7, *Electric vehicles conductive charging system – Part 3-7: DC EV supply equipment where protection relies on double or reinforced insulation – Battery system communication*

ELECTRIC VEHICLES CONDUCTIVE CHARGING SYSTEM –

Part 3-5: DC EV supply equipment where protection relies on double or reinforced insulation – Pre-defined communication parameters and general application objects

1 Scope

This part of IEC 61851, which is a Technical Specification, applies to CANopen communication for the conductive transfer of electric power between the supply network and an electric road vehicle or a removable RESS or traction-battery of an electric road vehicle.

This document provides specifications with regard to the pre-defined communication parameters and general application objects.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 61851-3-1:2023, *Electric vehicles conductive charging system – Part 3-1: DC EV supply equipment where protection relies on double or reinforced insulation – General rules and requirements for stationary equipment*

IEC TS 61851-3-4:2023, *Electric vehicles conductive charging system – Part 3-4: DC EV supply equipment where protection relies on double or reinforced insulation – General definitions and requirements for CANopen communication*

EN 50325-4:2002: *Industrial communications subsystem based on ISO 11898 (CAN) For controller-device interface - Part 4: Canopen*

CiA 302-2:2009, *CANopen additional application layer functions – Part 2: Network management* (available at www.can-cia.org)