This is a preview - click here to buy the full publication

IEC 61156-6

Edition 3.1 2012-12

INTERNATIONAL STANDARD

colour inside

withdrawn

Multicore and symmetrical pair/quad cables for digital communications – Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-0562-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

This is a preview - click here to buy the full publication

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms and definitions 7
4 Installation considerations 7
4.1 Climatic conditions 7
5 Materials and cable construction 7
5.1 General remarks 7
5.2 Cable construction 7
5.2.1 Conductor 7
5.2.2 Insulation 7
5.2.3 Cable element 7
5.2.4 Cable make-up 8
5.2.5 Screening of the cable core 8
5.2.6 Sheath 8
5.2.7 Identification 8
6 Characteristics and requirements 8
6.1 General remarks 8
6.2 Electrical characteristics and tests 9
6.2.1 Conductor resistance 9
6.2.2 Resistance unbalance 9
6.2.3 Dielectric strength 9
6.2.4 Insulation resistance 9
6.2.5 Mutual capacitance 9
6.2.6 Capacitance unbalance 9
6.2.7 Transfer impedance 9
6.2.8 Coupling attenuation 10
6.2.9 Current-carrying capacity 11
6.3 Transmission characteristics 11
6.3.1 Velocity of propagation (phase velocity) 11
6.3.2 Phase delay and differential delay (delay skew) 11
6.3.3 Attenuation 11
6.3.4 Unbalance attenuation 12
6.3.5 Near-end crosstalk ($NEXT$) 13
6.3.6 Attenuation to crosstalk ratio far end ($PS\ ACR\text{-}F$) 13
6.3.7 Alien (exogenous) near end crosstalk 14
6.3.8 Alien (exogenous) far-end crosstalk ($AACR\text{-}F$) 14
6.3.9 Alien (exogenous) crosstalk of bundled cables 14
6.3.10 Impedance 14
6.3.11 Return loss (RL) 15
6.4 Mechanical and dimensional characteristics and requirements 16
6.4.1 Dimensional requirements 16
6.4.2 Elongation at break of the conductors 16
6.4.3 Tensile strength of the insulation 16
6.4.4 Elongation at break of the insulation 16
6.4.5 Adhesion of the insulation to the conductor 16

Withdrawn

This is a preview - click here to buy the full publication

6.4.6 Elongation at break of the sheath 16
6.4.7 Tensile strength of the sheath 16
6.4.8 Crush test of the cable 16
6.4.9 Impact test of the cable 17
6.4.10 Bending under tension 17
6.4.11 Repeated bending of the cable 17
6.4.12 Tensile performance of the cable 17
6.4.13 Shock-test requirements of the cable 17
6.4.14 Bump-test requirements of the cable 17
6.4.15 Vibration-test requirements of a cable 17
6.5 Environmental characteristics 17
6.5.1 Shrinkage of the insulation 17
6.5.2 Wrapping test of the insulation after thermal ageing 17
6.5.3 Bending test of the insulation at low temperature 17
6.5.4 Elongation at break of the sheath after ageing 17
6.5.5 Tensile strength of the sheath after ageing 17
6.5.6 Sheath pressure test at high temperature 18
6.5.7 Cold bend test of the cable 18
6.5.8 Heat shock test 18
6.5.9 Damp heat steady state 18
6.5.10 Solar radiation 18
6.5.11 Solvents and contaminating fluids 18
6.5.12 Salt mist and sulphur dioxide 18
6.5.13 Water immersion 18
6.5.14 Hygroscopicity 18
6.5.15 Wicking 18
6.5.16 Flame propagation characteristics of a single cable 18
6.5.17 Flame propagation characteristics of bunched cables 18
6.5.18 Halogen gas evolution 18
6.5.19 Smoke generation 19
6.5.20 Toxic gas emission 19
6.5.21 Integrated fire test 19
7 Introduction to the blank detail specification 19
Bibliography 20

Figure 1 – Impedance template 15

Table 1 – Cable categories 6
Table 2 – Transfer impedance 10
Table 3 – Coupling attenuation 10
Table 4 – Attenuation, constant values 12
Table 5 – Near-end unbalance attenuation 12
Table 6 – Worst pair *PS NEXT* values 13
Table 7 – Worst pair *PS ACR-F* 13
Table 8 – *PS ANEXT* 14
Table 9 – *PS AACR-F* (*PS AELFEXT*) 14
Table 10 – Return loss 16

Withdrawn

This is a preview - click here to buy the full publication

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification

Withdrawn

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of IEC 61156-6 consists of the third edition (2010) [documents 46C/903/FDIS and 46C/908/RVD] and its amendment 1 (2012) [documents 46C/955/CDV and 46C/968/RVC]. It bears the edition number 3.1.

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience. A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

This is a preview - click here to buy the full publication

International Standard IEC 61156-6 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This edition includes the following significant technical changes with respect to the previous edition:

a) new requirements for new cables $Cat6_A$, $Cat7_A$;
b) revised requirements and tests for the cables.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This standard shall be read in conjunction with IEC 61156-1:2007.

The list of all the parts of the IEC 61156 series, under the general title: *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

Withdrawn

This is a preview - click here to buy the full publication

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification

1 Scope

This part of IEC 61156 makes reference to IEC 61156-1. The cables described herein are intended primarily for work area wiring as defined in ISO/IEC 11801 and ISO/IEC 24702.

It covers individually screened, common screened and unscreened pairs or quads. The transmission characteristics and the frequency range (see Table 1) of the cables are specified at 20 °C.

Table 1 – Cable categories

Cable designation	**Maximum referenced frequency** MHz
Category 5e	100
Category 6	250
Category 6_A	500
Category 7	600
Category 7_A	1 000

These cables can be used for various communication channels which use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems.

The cables covered by this standard are intended to operate with voltages and currents normally encountered in communication systems. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains, they are intended to be used to support the delivery of low voltage and power applications such as IEEE's 802.3af (Power over Ethernet) and 802.3at (Power over Ethernet Plus).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-6-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 6-1: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Blank detail specification*

Withdrawn

This is a preview - click here to buy the full publication

IEC 62153-4-5, *Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

Withdrawn