

This is a preview - click here to buy the full publication



IEC 61158-6-13

Edition 1.0 2007-12

# INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –  
Part 6-13: Application layer protocol specification – Type 13 elements**

Withhold

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE **XB**

ICS 35.100.70; 25.040.40

ISBN 2-8318-9488-3

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
1.1 General.....	8
1.2 Specifications.....	8
1.3 Conformance.....	8
2 Normative references.....	9
3 Terms, definitions, symbols, abbreviations and conventions.....	9
3.1 ISO/IEC 7498-1 terms.....	9
3.2 ISO/IEC 8822 terms.....	10
3.3 ISO/IEC 9545 terms.....	10
3.4 ISO/IEC 8824 terms.....	10
3.5 Terms and definitions from IEC 61158-5-13.....	11
3.6 Other terms and definitions.....	11
4 FAL syntax description.....	12
4.1 General.....	12
4.2 FAL-AR PDU abstract syntax.....	12
4.3 Abstract syntax of Asyn2 pduBody.....	15
5 Transfer syntax.....	21
5.1 Encoding of data types.....	21
6 FAL protocol state machines.....	27
7 AP context state machine.....	28
8 FAL service protocol machine.....	28
9 AR protocol machine.....	28
9.1 Buffered-network-scheduled bi-directional pre-established connection (BNB-PEC) ARPM.....	28
9.2 Buffered-network-scheduled uni-directional pre-established connection (BNU-PEC) ARPM.....	30
9.3 Queued user-triggered uni-directional (QUU) ARPM.....	33
9.4 Queued user-triggered bi-directional connectionless (QUB-CL) ARPM.....	35
9.5 Queued user-triggered bi-directional connection-oriented with segmentation (QUB-COS) ARPM.....	40
10 DLL mapping protocol machine.....	58
10.1 Primitive definitions.....	58
10.2 DMPM state machine.....	59
Annex A (normative) – Constant value assignments.....	61
A.1 Values of abort-code.....	61
A.2 NMT-command-ID.....	62
A.3 Type 13 specific error-code constants.....	62
A.4 EPL-node-list.....	64
Bibliography.....	65
Figure 1 – Encoding of Time of Day value.....	26
Figure 2 – Encoding of Time Difference value.....	26
Figure 3 – Primitives exchanged between protocol machines.....	27

Figure 4 – State transition diagram of BNB-PEC ARPM .....	29
Figure 5 – State transition diagram of BNU-PEC ARPM .....	32
Figure 6 – State transition diagram of QUU ARPM.....	34
Figure 7 – State transition diagram of QUB-CL ARPM .....	38
Figure 8 – State transition diagram of QUB-COS (CmdL) ARPM .....	44
Figure 9 – State transition diagram of QUB-COS (SeqL) ARPM .....	54
Figure 10 – State transition diagram of DMPM .....	59
Table 1 – Use of signaling-flags .....	14
Table 2 – Values of error-type.....	17
Table 3 – Transfer syntax for bit sequences.....	22
Table 4 – Transfer syntax for data type UNSIGNEDn.....	23
Table 5 – Transfer syntax for data type Integern .....	24
Table 6 – Primitives issued by user to BNB-PEC ARPM.....	28
Table 7 – Primitives issued by BNB-PEC ARPM to user.....	28
Table 8 – BNB-PEC ARPM state table – sender transactions.....	30
Table 9 – BNB-PEC ARPM state table – receiver transactions.....	30
Table 10 – Function BuildFAL-PDU.....	30
Table 11 – Primitives issued by user to BNU-PEC ARPM.....	31
Table 12 – Primitives issued by BNU-PEC ARPM to user.....	31
Table 13 – BNU-PEC ARPM state table – sender transactions.....	32
Table 14 – BNU-PEC ARPM state table – receiver transactions.....	32
Table 15 – Function BuildFAL-PDU.....	32
Table 16 – Primitives issued by user to QUU ARPM .....	33
Table 17 – Primitives issued by QUU ARPM to user .....	33
Table 18 – QUU ARPM state table – sender transactions .....	34
Table 19 – QUU ARPM state table – receiver transactions.....	35
Table 20 – Function BuildFAL-PDU.....	35
Table 21 – Primitives issued by user to QUB-CL ARPM .....	36
Table 22 – Primitives issued by QUB-CL ARPM to user .....	37
Table 23 – QUB-CL ARPM state table – sender transactions .....	39
Table 24 – QUB-CL ARPM state table – receiver transactions .....	40
Table 25 – Function BuildFAL-PDU.....	40
Table 26 – Primitives issued by user to QUB-COS (CmdL) ARPM.....	42
Table 27 – Primitives issued by QUB-COS (CmdL) ARPM to user.....	43
Table 28 – QUB-COS (CmdL) ARPM state table – sender transactions.....	45
Table 29 – QUB-COS (CmdL) ARPM state table – receiver transactions.....	47
Table 30 – Function BuildSegment .....	50
Table 31 – Function RoundUp.....	50
Table 32 – Function MoreFollows .....	50
Table 33 – Function AddSegment .....	51
Table 34 – Function GetIntermediatePDU .....	51

Table 35 – Primitives issued by QUB-COS (CmdL) to QUB-COS (SeqL).....	51
Table 36 – Primitives issued by QUB-COS (SeqL) to QUB-COS (CmdL).....	52
Table 37 – Parameters used with primitives exchanged between QUB-COS (SeqL) and QUB-COS (CmdL).....	52
Table 38 – QUB-COS (SeqL) ARPM states.....	53
Table 39 – QUB-COS (SeqL) ARPM state table – sender transactions.....	55
Table 40 – QUB-COS (SeqL) ARPM state table – receiver transactions.....	56
Table 41 – Function BuildFAL-PDU.....	57
Table 42 – Function IncrementCounter.....	58
Table 43 – Function AddToHistoryBuffer.....	58
Table 44 – Primitives issued by ARPM to DMPM.....	58
Table 45 – Primitives issued by DMPM to ARPM.....	58
Table 46 – Primitives issued by DMPM to data-link layer.....	59
Table 47 – Primitives issued by data-link layer to DMPM.....	59
Table 48 – DMPM state table – sender transactions.....	60
Table 49 – DMPM state table – receiver transactions.....	60
Table A.1 – Values of abort-code.....	61
Table A.2 – Values of NMTCommandID.....	62
Table A.3 – Type 13 specific error-code constants.....	63
Table A.4 – EPL-node-list format.....	64

Without

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

#### Part 6-13: Application layer protocol specification – Type 13 elements

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Use of some of the associated protocol Types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol Type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol Types in other combinations may require permission of their respective intellectual-property-right holders.

International Standard IEC 61158-6-13 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-6 subseries cancel and replace IEC 61158-6:2003. This edition of this part constitutes a technical addition. This part also replaces IEC/PAS 62408, published in 2005.

This edition of IEC 61158-6 includes the following significant changes from the previous edition:

- a) deletion of the former Type 6 fieldbus for lack of market relevance;
- b) addition of new types of fieldbuses;
- c) partition of part 6 of the third edition into multiple parts numbered -6-2, -6-3, ...

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/476/FDIS	65C/487/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

## INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

Withdrawn

## INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

### Part 6-13: Application layer protocol specification – Type 13 elements

#### 1 Scope

##### 1.1 General

The fieldbus application layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs.”

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 13 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard specifies interactions between remote applications and defines the externally visible behavior provided by the Type 13 fieldbus application layer in terms of

- a) the formal abstract syntax defining the application layer protocol data units conveyed between communicating application entities;
- b) the transfer syntax defining encoding rules that are applied to the application layer protocol data units;
- c) the application context state machine defining the application service behavior visible between communicating application entities;
- d) the application relationship state machines defining the communication behavior visible between communicating application entities.

The purpose of this standard is to define the protocol provided to

- 1) define the wire-representation of the service primitives defined in IEC 61158- 5-13, and
- 2) define the externally visible behavior associated with their transfer.

This standard specifies the protocol of the Type 13 fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI application layer structure (ISO/IEC 9545).

##### 1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-13.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in IEC 61158-6.

##### 1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.



Conformance is achieved through implementation of this application layer protocol specification.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-3-13, *Industrial communication networks – Fieldbus specifications - Part 3-13: Data-link layer service definition – Type 13 elements*

IEC 61158-4-13, *Industrial communication networks – Fieldbus specifications - Part 4-13: Data-link layer protocol specification – Type 13 elements*

IEC 61158-5-13, *Industrial communication networks – Fieldbus specifications - Part 5-13: Application layer service definition – Type 13 elements*

ISO/IEC 7498 (all parts), *Information technology – Open Systems Interconnection – Basic Reference Model*

ISO/IEC 8822, *Information technology – Open Systems Interconnection – Presentation service definition*

ISO/IEC 8824, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1)*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*