



IEEE

IEC 61588

Edition 2.0 2009-02

INTERNATIONAL STANDARD

IEEE 1588™

Precision clock synchronization protocol for networked measurement and control systems

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

XH

ICS 25.040.40; 35.110; 35.240.50

ISBN 978-2-88910-546-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Foreword.....	xi
IEEE introduction.....	xiv
1. Overview	1
1.1 Scope	1
1.2 Purpose	2
1.3 Layout of the document.....	2
2. Normative references.....	3
3. Definitions, acronyms, and abbreviations	4
3.1 Definitions	4
3.2 Acronyms and abbreviations	7
4. Conventions.....	8
4.1 Descriptive lexical form syntax	8
4.2 Word usage.....	9
4.3 Behavioral specification notation	10
5. Data types and on-the-wire formats in a PTP system.....	11
5.1 General	11
5.2 Primitive data type specifications	11
5.3 Derived data type specifications	12
5.4 On-the-wire formats	15
6. Clock synchronization model.....	16
6.1 General	16
6.2 Principle assumptions about the network and implementation recommendations.....	16
6.3 PTP systems.....	17
6.4 PTP message classes.....	17
6.5 PTP device types	18
6.6 Synchronization overview	29
6.7 PTP communications overview	37
7. Characterization of PTP entities	41
7.1 Domains.....	41
7.2 PTP timescale	41
7.3 PTP communications.....	42
7.4 PTP communication media.....	46
7.5 PTP ports	47
7.6 PTP device characterization	53
7.7 PTP timing characterization	61
8. PTP data sets	63
8.1 General specifications for data set members	63
8.2 Data sets for ordinary and boundary clocks.....	65
8.3 Data sets for transparent clocks	74
9. PTP for ordinary and boundary clocks	76
9.1 General protocol requirements for PTP ordinary and boundary clocks.....	76
9.2 State protocol.....	76
9.3 Best master clock algorithm	83
9.4 Grandmaster clocks	92
9.5 Message processing semantics	93
9.6 Changes in the local clock	107
10. PTP for transparent clocks.....	107
10.1 General requirements for both end-to-end and peer-to-peer transparent clocks.....	107
10.2 End-to-end transparent clock requirements	108

10.3 Peer-to-peer transparent clock requirements.....	108
11. Clock offset, path delay, residence time, and asymmetry corrections	108
11.1 General specifications.....	108
11.2 Computation of clock offset in ordinary and boundary clocks	109
11.3 Delay request-response mechanism.....	110
11.4 Peer delay mechanism	112
11.5 Transparent clock residence time correction for PTP version 2 events	117
11.6 Asymmetry correction for PTP version 2 event messages.....	120
12. Synchronization and syntonization of clocks	122
12.1 Syntonization	122
12.2 Synchronization	123
13. PTP message formats	124
13.1 General	124
13.2 General message format requirements.....	124
13.3 Header.....	124
13.4 Suffix	128
13.5 Announce message	128
13.6 Sync and Delay_Req messages.....	130
13.7 Follow_Up message	130
13.8 Delay_Resp message	130
13.9 Pdelay_Req message	131
13.10 Pdelay_Resp message.....	131
13.11 Pdelay_Resp_Follow_Up message.....	132
13.12 Signaling message	132
13.13 Management message.....	133
14. TLV entity specifications	133
14.1 General requirements.....	133
14.2 Experimental TLVs	134
14.3 Vendor and standard organization extension TLVs.....	135
15. Management	135
15.1 General	135
15.2 PTP management mechanism.....	136
15.3 Processing of management messages.....	136
15.4 Management message format.....	137
15.5 Management TLVs.....	138
16. General optional features.....	158
16.1 Unicast message negotiation (optional).....	158
16.2 Path trace (optional).....	163
16.3 Alternate timescales (optional).....	165
17. State configuration options.....	169
17.1 General	169
17.2 Data types for options.....	169
17.3 Grandmaster clusters (optional).....	170
17.4 Alternate master (optional).....	172
17.5 Unicast discovery (optional).....	173
17.6 Acceptable master table (optional).....	175
18. Compatibility requirements	177
18.1 Compatibility between version 2 and future versions.....	177
18.2 Compatibility between version 1 and version 2.....	177
18.3 Message formats and data types	178
18.4 Naming changes	183
18.5 Restrictions on mixed version 1 and version 2 systems.....	183

19. Conformance	184
19.1 Conformance objective	184
19.2 PTP conformance requirements	184
19.3 PTP profiles	185
Annex A (informative) Using PTP	187
Annex B (informative) Timescales and epochs in PTP	197
Annex C (informative) Examples of residence and asymmetry corrections	200
Annex D (normative) Transport of PTP over User Datagram Protocol over Internet Protocol Version 4 ..	219
Annex E (normative) Transport of PTP over User Datagram Protocol over Internet Protocol Version 6 ..	221
Annex F (normative) Transport of PTP over IEEE 802.3 /Ethernet	223
Annex G (normative) Transport of PTP over DeviceNET	225
Annex H (normative) Transport of PTP over ControlNET	228
Annex I (normative) Transport of PTP over IEC 61158 Type 10	230
Annex J (normative) Default PTP profiles	237
Annex K (informative) Security protocol (experimental)	241
Annex L (informative) Transport of cumulative frequency scale factor offset (experimental)	264
Annex M (informative) Bibliography	268
Annex N (informative) List of participants	270

TABLES

Table 1	—Primitive PTP data types	12
Table 2	—domainNumber	41
Table 3	—networkProtocol enumeration	46
Table 4	—Non-EUI-64 addressTechnology enumeration	51
Table 5	—clockClass specifications	55
Table 6	—clockAccuracy enumeration	56
Table 7	—timeSource enumeration	57
Table 8	—PTP state enumeration	73
Table 9	—Delay mechanism enumeration	74
Table 10	—PTP portState definition	77
Table 11	—Event applicability in boundary clocks	83
Table 12	—Information sources for data set comparison algorithm	88
Table 13	—Updates for state decision code M1 and M2	91
Table 14	—Updates for state decision code M3	91
Table 15	—Updates for state decision code P1, and P2	91
Table 16	—Updates for state decision code S1	92
Table 17	—Source identity comparisons	95
Table 18	—Common message header	124
Table 19	—Values of messageType field	125
Table 20	—Values of flagField	126
Table 21	—correctionField semantics	127
Table 22	—References for sequenceId value exceptions	127
Table 23	—controlField enumeration	128
Table 24	—Values of logMessageInterval field	128
Table 25	—Announce message fields	129
Table 26	—Sync and Delay_Req message fields	130
Table 27	—Follow_Up message fields	130
Table 28	—Delay_Resp message fields	130
Table 29	—Pdelay_Req message fields	131
Table 30	—Pdelay_Resp message fields	131
Table 31	—Pdelay_Resp_Follow_Up message fields	132
Table 32	—Acceptance of signaling messages	132
Table 33	—Signaling message fields	133

Table 34	—tlvType values	134
Table 35	—Organization specific TLV fields	135
Table 36	—Acceptance of management messages	136
Table 37	—Management message fields	137
Table 38	—Values of the actionField	138
Table 39	—Management TLV fields	139
Table 40	—managementId values	140
Table 41	—CLOCK_DESCRIPTION management TLV data field	141
Table 42	—clockType specification	142
Table 43	—USER_DESCRIPTION management TLV data field	144
Table 44	—INITIALIZE management TLV data field	145
Table 45	—INITIALIZATION_KEY enumeration	145
Table 46	—Fault log severityCode enumeration	145
Table 47	—FAULT_LOG management TLV data field	146
Table 48	—TIME management TLV data field	147
Table 49	—CLOCK_ACCURACY management TLV data field	147
Table 50	—DEFAULT_DATA_SET management TLV data field	148
Table 51	—PRIORITY1 management TLV data field	148
Table 52	—PRIORITY2 management TLV data field	149
Table 53	—DOMAIN management TLV data field	149
Table 54	—SLAVE_ONLY management TLV data field	149
Table 55	—CURRENT_DATA_SET management TLV data field	149
Table 56	—PARENT_DATA_SET management TLV data field	150
Table 57	—TIME_PROPERTIES_DATA_SET management TLV data field	151
Table 58	—UTC_PROPERTIES management TLV data field	152
Table 59	—TRACEABILITY_PROPERTIES management TLV data field	152
Table 60	—TIMESCALE_PROPERTIES management TLV data field	152
Table 61	—PORT_DATA_SET management TLV data field	153
Table 62	—LOG_ANNOUNCE_INTERVAL management TLV data field	154
Table 63	—ANNOUNCE_RECEIPT_TIMEOUT management TLV data field	154
Table 64	—LOG_SYNC_INTERVAL management TLV data field	154
Table 65	—DELAY_MECHANISM management TLV data field	155
Table 66	—LOG_MIN_PDELAY_REQ_INTERVAL management TLV data field	155
Table 67	—VERSION_NUMBER management TLV data field	155
Table 68	—TRANSPARENT_CLOCK_DEFAULT_DATA_SET management TLV data field	156

Table 69	—PRIMARY_DOMAIN management TLV data field.....	156
Table 70	—TRANSPARENT_CLOCK_PORT_DATA_SET management TLV data field.....	157
Table 71	—MANAGEMENT_ERROR_STATUS TLV format.....	157
Table 72	—managementErrorId enumeration.....	158
Table 73	—REQUEST_UNICAST_TRANSMISSION TLV format.....	160
Table 74	—GRANT_UNICAST_TRANSMISSION TLV format.....	161
Table 75	—CANCEL_UNICAST_TRANSMISSION TLV format.....	161
Table 76	—ACKNOWLEDGE_CANCEL_UNICAST_TRANSMISSION TLV format.....	162
Table 77	—UNICAST_NEGOTIATION_ENABLE management TLV data field.....	162
Table 78	—PATH_TRACE TLV format.....	164
Table 79	—PATH_TRACE_LIST management TLV data field.....	164
Table 80	—PATH_TRACE_ENABLE management TLV data field.....	164
Table 81	—ALTERNATE_TIME_OFFSET_INDICATOR TLV format.....	166
Table 82	—ALTERNATE_TIME_OFFSET_ENABLE management TLV data field.....	167
Table 83	—ALTERNATE_TIME_OFFSET_NAME management TLV data field.....	167
Table 84	—ALTERNATE_TIME_OFFSET_MAX_KEY management TLV data field.....	168
Table 85	—ALTERNATE_TIME_OFFSET_PROPERTIES management TLV data field.....	168
Table 86	—GRANDMASTER_CLUSTER_TABLE management TLV data field.....	171
Table 87	—Alternate master attributes.....	173
Table 88	—ALTERNATE_MASTER management TLV data field.....	173
Table 89	—UNICAST_MASTER_TABLE management TLV data field.....	174
Table 90	—UNICAST_MASTER_MAX_TABLE_SIZE management TLV data field.....	175
Table 91	—Operation of acceptable master table option.....	176
Table 92	—ACCEPTABLE_MASTER_TABLE management TLV data field.....	176
Table 93	—ACCEPTABLE_MASTER_MAX_TABLE_SIZE management TLV data field.....	177
Table 94	—ACCEPTABLE_MASTER_TABLE_ENABLED management TLV data field.....	177
Table 95	—Version 1 stratum to version 2 class.....	178
Table 96	—Version 2 clockClass to version 1 stratum.....	178
Table 97	—Version 1 to version 2 translation of grandmasterIsPreferred field.....	179
Table 98	—Version 2 to version 1 translation of the priority1 field.....	179
Table 99	—Version 1 clock identifier to version 2 clockAccuracy.....	179
Table 100	—Version 2 clockAccuracy to version 1 clock identifier.....	179
Table 101	—Version 1 to version 2 translation of grandmasterIsBoundaryClock field.....	180
Table 102	—Version 2 to version 1 translation of the priority2 field.....	180
Table 103	—Version 1 control field and version 2 messageType field mappings.....	180
Table 104	—Translation of flagField from version 1 to version 2.....	181

Table 105	—Translation of flagField from version 2 to version 1	181
Table 106	—Version 2 fields with no version 1 counterpart.....	182
Table 107	—Version 1 fields with no version 2 counterpart.....	183
Table 108	—Name correspondence.....	183
Table 109	—Mixed system restrictions	184
Table B.1	—Relationships between timescales.....	199
Table C.1	—Interpretation of Figure C.1 key values	202
Table C.2	—Interpretation of Figure C.2 key values	203
Table C.3	—Interpretation of Figure C.3 key values	205
Table C.4	—Interpretation of Figure C.4 key values	207
Table C.5	—Interpretation of Figure C.5 key values	209
Table C.6	—Interpretation of Figure C.6 key values	210
Table C.7	—Interpretation of Figure C.7 key values	211
Table C.8	—Interpretation of Figure C.8 key values	213
Table C.9	—Interpretation of Figure C.9 key values	215
Table C.10	—Interpretation of Figure C.10 key values.....	217
Table C.11	—Interpretation of Figure C.11 key values.....	218
Table D.1	—IPv4 multicast addresses.....	219
Table D.2	—transportSpecific field values.....	220
Table E.1	—IPv6 multicast addresses	222
Table F.1	—Multicast MAC addresses	223
Table F.2	—Ethernet transport specific field.....	224
Table G.1	—DeviceNet clockIdentity octets 0 through 7.....	226
Table G.2	—DeviceNet headers for all PTP message packets	226
Table H.1	—ControlNet clockIdentity octets 2 through 7.....	228
Table I.1	—Mapping of messages.....	231
Table I.2	—IEEE 802.3 DLPDU syntax	232
Table I.3	—Multicast MAC address.....	233
Table I.4	—LT (Length/Type).....	234
Table I.6	—Mapping of the parameter and attribute names	235
Table I.7	—Translation of flagField from PTP version 2 to PROFINET.....	236
Table K.1	—flagField.SECURE flag	242
Table K.2	—AUTHENTICATION TLV	260
Table K.3	—algorithmId values	261
Table K.4	—ICV and pad length.....	261
Table K.5	—AUTHENTICATION_CHALLENGE TLV	262

Table K.6—challengeType values	262
Table K.7—SECURITY_ASSOCIATION_UPDATE TLV	263
Table K.8—addressType values	263
Table L.1—CUM_FREQ_SCALE_FACTOR_OFFSET TLV format	266

Withdrawn

FIGURES

Figure 1	—Mealy state transition diagram	10
Figure 2	—Model of an ordinary clock	19
Figure 3	—Model of a boundary clock.....	21
Figure 4	—Model of an end-to-end transparent clock.....	22
Figure 5	—End-to-end residence time correction model.....	23
Figure 6	—Combined ordinary and end-to-end transparent clock.....	25
Figure 7	—Model of a peer-to-peer transparent clock.....	27
Figure 8	—Peer-to-peer residence time and link delay correction model.....	28
Figure 9	—Combined ordinary and peer-to-peer transparent clock.....	30
Figure 10	—Simple master-slave clock hierarchy	32
Figure 11	—Pruned mesh topology	33
Figure 12	—Basic synchronization message exchange	34
Figure 13	—Link delay measurement.....	35
Figure 14	—Timestamp generation model.....	36
Figure 15	—Hierarchical topology	37
Figure 16	—Linear topology.....	38
Figure 17	—Multiply connected topology.....	39
Figure 18	—Bridging disparate technologies.....	40
Figure 19	—Definition of latency constants.....	45
Figure 20	—Propagation asymmetry	47
Figure 21	—Port model	48
Figure 22	—Scaled log variance hysteresis	60
Figure 23	—State machine for a full implementation.....	78
Figure 24	—State machine for a slave-only implementation.....	79
Figure 25	—STATE_DECISION_EVENT logic	81
Figure 26	—State decision algorithm	87
Figure 27	—Data set comparison algorithm, part 1	89
Figure 28	—Data set comparison algorithm, part 2	90
Figure 29	—Receipt of Announce message logic.....	96
Figure 30	—Receipt of Sync message logic	98
Figure 31	—Receipt of Follow_Up message logic.....	100
Figure 32	—Receipt of Delay_Req message logic	101
Figure 33	—Receipt of Delay_Resp message logic.....	103
Figure 34	—Delay request-response path length measurement.....	110

Figure 35	—Peer delay link measurement	113
Figure 36	—Permitted mixed system configuration	183
Figure 37	—Profile print form	186
Figure C.1	—Master, end-to-end, and slave one-step clocks; no asymmetry correction	201
Figure C.2	—Master, end-to-end, and slave one-step clocks; with asymmetry correction	202
Figure C.3	—Master two-step and end-to-end transparent and slave one-step clocks; with asymmetry correction	204
Figure C.4	—Master and end-to-end transparent, two-step, and one-step, slave clocks; with asymmetry correction	206
Figure C.5	—One-step master, two-step end-to-end transparent, and one-step slave clocks; with asymmetry correction	208
Figure C.6	—One-step peer responder, end-to-end transparent, and peer requestor clocks; with asymmetry correction	210
Figure C.7	—One-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks; with asymmetry correction	211
Figure C.8	—Two-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks: option 1; with asymmetry correction	212
Figure C.9	—Two-step peer responder, two-step end-to-end transparent, and one-step peer requestor clocks: option 2; with asymmetry correction	214
Figure C.10	—Two-step peer responder, one-step end-to-end transparent, and one-step peer requestor clocks: option 2; with asymmetry correction	216
Figure C.11	—One-step peer master, two-step peer-to-peer transparent, and one-step peer slave clocks; time computation	217
Figure G.1	—Event message timestamp point	225
Figure I.1	—PROFINET region combined with domains	231
Figure K.1	—PTP secure message processing	252
Figure K.2	—Challenge processing	254
Figure K.3	—Secure transmit processing	256
Figure K.4	—Secure event processing	258

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PRECISION CLOCK SYNCHRONIZATION PROTOCOL
FOR NETWORKED MEASUREMENT AND CONTROL SYSTEMS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC/IEEE 61588 has been processed through subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2004. It constitutes a technical revision.

The text of this standard is based on the following documents:

IEEE Std	FDIS	Report on voting
1588 (2008)	65C/510/FDIS	65C/517/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this publication will remain unchanged until 2013.

IEC/IEEE Dual Logo International Standards

This Dual Logo International Standard is the result of an agreement between the IEC and the Institute of Electrical and Electronics Engineers, Inc. (IEEE). The original IEEE Standard was submitted to the IEC for consideration under the agreement, and the resulting IEC/IEEE Dual Logo International Standard has been published in accordance with the ISO/IEC Directives.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Use of an IEC/IEEE Dual Logo International Standard is wholly voluntary. The IEC and IEEE disclaim liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEC or IEEE Standard document.

The IEC and IEEE do not warrant or represent the accuracy or content of the material contained herein, and expressly disclaim any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEC/IEEE Dual Logo International Standards documents are supplied "AS IS".

The existence of an IEC/IEEE Dual Logo International Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEC/IEEE Dual Logo International Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEC and IEEE are not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Neither the IEC nor IEEE is undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEC/IEEE Dual Logo International Standards or IEEE Standards document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations – Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration.

Comments for revision of IEC/IEEE Dual Logo International Standards are welcome from any interested party, regardless of membership affiliation with the IEC or IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, USA and/or General Secretary, IEC, 3, rue de Varembe, PO Box 131, 1211 Geneva 20, Switzerland.

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

NOTE – Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents for which a license may be required by an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems

Sponsor

Technical Committee on Sensor Technology (TC-9)
of the
IEEE Instrumentation and Measurement Society

Approved 27 March 2008

IEEE-SA Standards Board

Abstract: A protocol is provided in this standard that enables precise synchronization of clocks in measurement and control systems implemented with technologies such as network communication, local computing, and distributed objects. The protocol is applicable to systems communicating via packet networks. Heterogeneous systems are enabled that include clocks of various inherent precision, resolution, and stability to synchronize. System-wide synchronization accuracy and precision in the sub-microsecond range are supported with minimal network and local clock computing resources. Simple systems are installed and operated without requiring the management attention of users because the default behavior of the protocol allows for it.

Keywords: boundary clock, clock, distributed system, master clock, measurement and control system, real-time clock, synchronized clock, transparent clock

IEEE Introduction

This standard defines a protocol enabling precise synchronization of clocks in measurement and control systems implemented with technologies such as network communication, local computing, and distributed objects. The clocks communicate with each other over a communication network. The protocol generates a master-slave relationship among the clocks in the system. All clocks ultimately derive their time from a clock known as the grandmaster clock. In its basic form, this protocol is intended to be administration free.

History

Measurement and control applications are increasingly using distributed system technologies such as network communication, local computing, and distributed objects. Without a standardized protocol for synchronizing the clocks in these devices, it is unlikely that the benefits will be realized in the multivendor system component market. Existing protocols for clock synchronization are not optimum for these applications. For example, Network Time Protocol (NTP) targets large distributed computing systems with millisecond synchronization requirements. The protocol proposed in this standard specifically addresses the following needs of measurement and control systems:

- Spatially localized
- Microsecond to sub-microsecond accuracy and precision
- Administration free
- Accessible for both high-end devices and low-cost, low-end devices

Notice to users

Laws and regulations

Users of these documents should consult all applicable laws and regulations. Compliance with the provisions of this standard does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Standards Association Web site at <http://ieeexplore.ieee.org/xpl/standards.jsp>, or contact the IEEE at the address listed previously.

For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA Web site at <http://standards.ieee.org>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/updates/errata/>. Users are encouraged to check this URL for errata periodically.

Interpretations

Current interpretations can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/interp/>.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. A patent holder or patent applicant has filed a statement of assurance that it will grant licenses under these rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses. Other Essential Patent Claims may exist for which a statement of assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions are reasonable or non-discriminatory. Further information may be obtained from the IEEE Standards Association.

IMPORTANT NOTICE: *This standard is not intended to assure safety, security, health, or environmental protection in all circumstances. Implementers of the standard are responsible for determining appropriate safety, security, environmental, and health practices or regulatory requirements.*

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading "Important Notice" or "Important Notices and Disclaimers Concerning IEEE Documents." They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

1.2 Purpose

Measurement and control applications are increasingly employing distributed system technologies such as network communication, local computing, and distributed objects. Many of these applications will be enhanced by having an accurate system-wide sense of time achieved by having local clocks in each sensor, actuator, or other system device. Without a standardized protocol for synchronizing these clocks, it is unlikely that the benefits will be realized in the multivendor system component market. Existing protocols for clock synchronization are not optimum for these applications. For example, the Network Time Protocol (NTP) targets large distributed computing systems with millisecond synchronization requirements. The protocol in this standard specifically addresses the needs of measurement and control and operational systems in the fields of test and measurement, industrial automation, military systems, manufacturing systems, power utility systems, and certain telecommunications applications. These applications need:

- Spatially localized systems with options for larger systems
- Microsecond to sub-microsecond accuracy
- Administration-free operation
- Applicability for both high-end devices and low-cost, low-end devices
- Provisions for the management of redundant and fault-tolerant systems

Several different application areas such as industrial automation, telecommunication, semiconductor manufacturing, military systems, and utility power generation have emerged that require the standard to be revised.

1.3 Layout of the document

This standard, which defines the Precision Time Protocol (PTP), is divided into 19 clauses:

Clause	Purpose
1	Provides the scope and benefits of this standard
2	Lists references to other standards
3	Provides definitions that are either not found in other standards or have been modified for use with this standard
4	Provides conventions for the notation used in this standard
5	Defines the data types used in this standard
6	Provides an overview of PTP
7	Defines characteristics of PTP entities
8	Defines PTP data sets
9	Defines PTP for ordinary and boundary clocks
10	Defines PTP for transparent clocks
11	Specifies PTP time computations and corrections
12	Specifies how to syntonize and synchronize clocks
13	Defines the format of messages passed between participating clocks
14	Specifies type, length, value (TLV) formats
15	Specifies management TLVs
16	Defines general optional features of this standard
17	Defines state configuration options of this standard
18	Defines forward and backward compatibility between versions
19	Defines requirements for conformance

Annexes are provided as follows:

Annex	Purpose
Annex A	Using PTP
Annex B	Defines timescales and epochs in PTP
Annex C	Examples of timing computations and message fields
Annex D	Defines mappings of PTP to User Datagram Protocol (UDP) over Internet Protocol version 4 (IPv4)
Annex E	Defines mappings of PTP to UDP over Internet Protocol version 6 (IPv6)
Annex F	Defines mappings of PTP over IEEE 802.3
Annex G	Defines mappings of PTP to DeviceNet ^{TM1}
Annex H	Defines mappings of PTP to ControlNet ^{TM2}
Annex I	Defines mappings of PTP to PROFINET ^{TM3}
Annex J	Default PTP Profile
Annex K	Defines an experimental security option
Annex L	Defines an experimental cumulative frequency TLV
Annex M	Bibliography

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

IEC 61158-3-2:2007, Industrial communication networks—Fieldbus specifications—Part 3-2: Data-link layer service definition—Type 2 elements.⁴

IEC 61158-4-2:2007, Industrial communication networks—Fieldbus specifications—Part 4-2: Data-link layer protocol specification—Type 2 elements.

IEC 61158-5-2:2007, Industrial communication networks—Fieldbus specifications—Part 5-2: Application layer service definition—Type 2 elements.

IEC 61158-5-10:2007, Industrial communication networks—Fieldbus specifications—Part 5-10: Application layer service definition—Type 10 elements.

IEC 61158-6-2:2007, Industrial communication networks—Fieldbus specifications—Part 6-2: Application layer protocol specification—Type 2 elements.

IEC 61158-6-10:2007, Industrial communication networks—Fieldbus specifications—Part 6-10: Application layer protocol specification—Type 10 elements.

¹DeviceNetTM is a trade name of Open DeviceNet Vendor Association, Inc. This information is given for the convenience of users of this standard and does not constitute an endorsement by the IEEE or IEC of these products. Equivalent products may be used if they can be shown to lead to the same results.

²ControlNetTM is a trade name of ControlNet International, Ltd. This information is given for the convenience of users of this standard and does not constitute an endorsement by the IEEE or IEC of these products. Equivalent products may be used if they can be shown to lead to the same results.

³PROFINETTM is the trade name of the non-profit organization PROFIBUS Nutzerorganisation e.V. (PNO). This information is given for the convenience of users of this standard and does not constitute an endorsement by the IEEE or IEC of these products. Equivalent products may be used if they can be shown to lead to the same results.

⁴IEC publications are available from the Sales Department of the International Electrotechnical Commission, Case Postale 131, 3, rue de Varembé, CH-1211, Genève 20, Switzerland/Suisse (<http://www.iec.ch/>). IEC publications are also available in the United States from the Sales Department, American National Standards Institute, 25 West 43rd Street, 4th Floor, New York, NY 10036, USA (<http://www.ansi.org/>).

IEC 61784-1:2007, Industrial communication networks—Profiles—Part 1: Fieldbus profiles.

IEC 61784-2:2007, Industrial communications networks—Profiles—Part 2: Additional fieldbus profiles for real-time networks based on ISO/IEC 8802-3.

IEC 62026-3:2008, Low-voltage switchgear and controlgear—Controller-device interfaces (CDIs)—Part 3: DeviceNet.

IEEE Std 802[®], IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture.^{5, 6}

IEEE Std 802.1AB[™], IEEE Standard for Local and Metropolitan Area Networks—Part 1AB: Station and Media Access Control Connectivity Discovery.

IEEE Std 802.1Q[™]-2005, IEEE Standard for Local and Metropolitan Area Networks—Part 1Q: Virtual bridged local area networks.

IEEE Std 802.3[™]-2005, IEEE Standard for Information Technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements—Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and Physical Layer specifications.

ISO/IEC 10646:2003, Information technology—Universal Multiple-Octet Coded Character Set (UCS)⁷.

⁵IEEE publications are available from the Institute of Electrical and Electronics Engineers, 445 Hoes Lane, Piscataway, NJ 08854, USA (<http://standards.ieee.org/>).

⁶The IEEE standards or products referred to in this clause are trademarks of the Institute of Electrical and Electronics Engineers, Inc.

⁷ISO/IEC publications are available from the ISO Central Secretariat, 1 chemin de la Voie-Creuse, CP 56, CH-1211, Genève 20, Switzerland/Suisse (<http://www.iso.ch/>). ISO/IEC publications are also available in the United States from Global Engineering Documents, 15 Inverness Way East, Englewood, Colorado 80112, USA (<http://global.ihs.com/>). Electronic copies are available in the United States from the American National Standards Institute, 25 West 43rd Street, 4th Floor, New York, NY 10036, USA (<http://www.ansi.org/>).