

IEC PAS 62264-6

Edition 1.0 2016-07

PUBLICLY AVAILABLE SPECIFICATION

Enterprise-control system integration
Part 6: Messaging Service Model

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 25.040.99; 35.100; 35.100.50

ISBN 978-2-8322-3487-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

-2-

FC	FOREWORD		
IN	TRODL	JCTION	8
1	Scop	re	10
2	Norm	native references	10
3		ns, definitions and abbreviations	
•	3.1	Terms and definitions	
	3.2	Abbreviations	
	3.3	Conventions	
4		Messaging Service Model	
4			
	4.1	Interface model	12 12
	4.2		
	4.3	Transaction model	
	4.4	Communicating applications	
	4.5	Managed communication channels	
	4.6	Notification services	
	4.7	MSM channel services	
	4.8	MSM publication channel services	
	4.8.1		
	4.9	MSM request channel services	_
_	4.9.1	'	
5		ods of operation of MSM channels	18
	5.1	Channel and topic identification	18
	5.2	Channel names and hierarchy	18
	5.2.1		18
	5.2.2	* / \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
	5.2.3		
	5.2.4	, \ \ \ ' \	
	5.2.5	\ \\ \ \ ' >	
	5.2.6		
	5.3	Message filtering	
	5.4	Publication expiration	
	5.5	Topics	
	5.5.1	•	
	5.5.2	•	
	5.6	MSM sessions	
	5.7	Security	
	5.7.1	Secure message exchanges	23
	5.7.2	,	
	5.7.3	Security token format	24
	5.7.4		
6	MSM	service definitions	24
	6.1	Type definitions	24
	6.2	MSM service returns and faults	25
	6.3	MSM channel management services	26
	6.3.1	Create channel	26
	6.3.2	Add security tokens	26

IEC PAS 62264-6:2016 © IEC 2016 - 3 -

	6.3.3	Remove security tokens	
	6.3.4	Delete channel	.27
	6.3.5	Get channel	.27
	6.3.6	Get channels	.28
	6.4	Notify listener service	
	6.4.1	Notify listener	.28
	6.5	MSM provider publication services	.28
	6.5.1	Open publication session	.28
	6.5.2	Post publication	.29
	6.5.3	Expire publication	.29
	6.5.4	Close publication session	.30
	6.6	MSM consumer publication services	.30
	6.6.1	Open subscription session	.30
	6.6.2	Read publication	.30
	6.6.3	Remove publication	.31
	6.6.4	Close subscription session	.31
	6.7		.32
	6.7.1	MSM provider request services	.32
	6.7.2	Read request	.32
	6.7.3	Remove request	.32
	6.7.4	Post response	.33
	6.7.5	Close provider request session	
	6.8	MSM consumer request services	.34
	6.8.1	Open consumer request session.	.34
	6.8.2	Post request	.34
	6.8.3	Read response	.34
	6.8.4	Remove response	
	6.8.5	Close consumer request session	
7	Scena	arios	
	7.1	Publish-subscribe scenarios	
	7.1.1		.36
	7.1.2		
	7.1.3		
	7.1.4	Multiple publishers scenario	
	7.1.5	Publish subscribe scenario with publication expiration	
		Request channel scenarios	
	7.2.1	Request-response scenario with notification	
	7.2.2	Request-response scenario without notification	
	7.2.3	Multiple providers	
3		Diance	
۸n		informative) MSM service provider considerations	
~ ()	,	·	
		Service provider considerations	
		Notification	
		Security considerations	
		MSM application implementation considerations	
		MSM channel security considerations	
		MSM session ID considerations	
		Data format validation	
	A.8	Allowed application checking	.45

- 4 - IEC PAS 62264-6:2016 © IEC 2016

A.9	Data exchange logging	45
A.10	Common error handling	45
A.11	Data transformation services	
A.12	Cross company bridges	
A.13	Message maintenance	
	(informative) Enterprise Service Buses	
Bibliogra	phy	50
_	 Steps in application-to-application communication 	
	– Application communication stack	
Figure 3	– Defined standards at each level	
Figure 4	– Messaging service model names	\
Figure 5	 MSM channel management services 	17
Figure 6		17
Figure 7		18
Figure 8	– Changes and checkpoint channel example	
Figure 9	 Security of channels 	24
Figure 10) – Publication scenario with notification	36
Figure 11	I – Publication scenario with multiple messages	37
Figure 12	2 – Publication scenario without notification	38
	B – Publication scenario with multiple provider applications	
	4 – Publication scenario with expired publications	
Figure 15	5 - GET/SHOW request service scenario	41
	6 - CHANGE RESPONSE request service scenario	
	7 – Multiple providers CHANGE/RESPONSE scenario	
_	1 - Transformation services with the MSM service provider	
	2 – Cross company bridge between multiple MSMs	
_	1 – Standard interface to ESBs and other message exchange systems	
rigaro B.	ctatagra interface to 2020 and other mossage exchange systems	
Table 1	MSM type definitions	25
	- MSM service returns and fault definitions	
	- Create channel	
	- Add security token	
	- Remove security token	
	- Delete channel	
	- Get channel	
	- Get channels	
	- Notify listener	
	- Open publication session	
	- Post publication	
	- Expire publication	
	- Close publication session	
	- Open subscription session	
Table 15	- Read publication	31

IEC PAS 62264-6:2016 © IEC 2016

– 5 –

Table 16 – Remove publication	31
Table 17 – Close subscription session	.31
Table 18 – Open provider request session	32
Table 19 – Read request	.32
Table 20 – Remove request	33
Table 21 – Post response	.33
Table 22 – Close provider request session	.33
Table 23 – Open consumer request session	34
Table 24 – Post request	34
Table 25 – Read response	35
Table 26 – Remove response	35
Table 27 – Close consumer request session	35

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ENTERPRISE-CONTROL SYSTEM INTEGRATION –

Part 6: Messaging Service Model

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and EC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC PAS 62264-6 has been processed by subcommittee 65E: Devices and integration in enterprise systems, of IEC technical committee 65: Industrial-process measurement, control and automation.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
65E/476/PAS	65E/502/RVD

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

IEC PAS 62264-6:2016 © IEC 2016

-7-

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single period up to a maximum of 3 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.



INTRODUCTION

- 8 -

This PAS is based of ISA-95 object models defined on the use ISA-95 Parts 2, 4 and 5 (Parts 1 and 3 do not contain object models) to define a set of services that may be used to exchange information messages. It is recognized that other, non-Part 6 sets of services are possible and are not deemed invalid as a result of this PAS. This PAS defines a Messaging Service Model (MSM) for exchanging data exchange messages in a publish/subscribe mode and a request/response mode. It defines a minimal interface subset to message exchange systems.

The Messaging Service Model provides a method for applications to send and receive messages from MSM service providers without regard to the underlying communication mechanism, as part of a complete application-to-application communication protocol.

This PAS defines a set of services definitions that are designed to provide the functionality needed for a vendor-independent method for sending and receiving data exchange messages on a message exchange system, such as an Enterprise Service Bus (ESB).

The knowledge requirements to interface to just one message exchange system can be immense, and are usually not transferable to a different system. MSM defines a single interface, independent of the underlying services, for Level 3-3 and Level 4-3 communications. This removes the need for vendors to build custom interface after custom interface, and for end users to get locked into a single vendor because their investment prevents them from reusing any of the integration efforts.

Enterprise-control system integration involves multiple different steps to exchange data between different computer system applications, as shown in Figure 1.

- a) The applications usually have different internal representations of exchanged objects in their own local data stores. This representation is usually converted from the local format to a commonly accepted global format. The ISA-95 Part 2 standard defines representations of a global format for Level 4-3 data exchanges. The Part 4 standard defines representations of a global format for Level 3-3 data exchanges. This conversion, from local to global and global to local, is usually performed twice for any two-way communications.
 - EXAMPLE 1 Assume two applications, ALPHA and BETA: the ALPHA application initiates a data exchange with the BETA application, and BETA responds back to ALPHA. The format conversions are: ALPHA's local format to global format for the request data, global format to BETA's local format for the response data, and global format to ALPHA's format for the response data.
- b) Conversion is performed to align the namespaces among the exchanging applications, and is usually performed four times for any two-way communications.
 - EXAMPLE 2 Names for elements of data may be codes, tag names, or equipment identifiers.
 - EXAMPLE 3 Data which are represented in one element namespace, such as codes 1,2,3,4, may have a different namespace in another application, such as codes Ok, Done, Error, Delay.
- c) Once information is in the global format with appropriate global names, the exchanged information is sent from one application to another application.
- d) Messages are transported from one application to another, either within the same computer environment or across computers. Transport mechanisms are defined in other standards, such as TCP/IP and Ethernet standards.
- e) When data exchange information is received, there are specific rules that define what resultant data are to be returned. The transaction rules are defined in the ISA-95 Part 5 standard.

IEC PAS 62264-6:2016 © IEC 2016

-9-




Figure 1 - Steps in application-to-application communication



ENTERPRISE-CONTROL SYSTEM INTEGRATION –

Part 6: Messaging Service Model

1 Scope

This part of IEC 62264, which is a PAS, defines a model of a set of messaging services for information exchanges across Levels 3 and 4, and within Level 3, between applications performing business and manufacturing activities. It defines a standard interface for information exchange between systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ANSI/ISA-95.00.01-2010 (IEC 62264-1 Mod), Enterprise Control System Integration – Part 1: Models and Terminology

ANSI/ISA-95.00.02-2010 (IEC 62264-2 Mod), Enterprise-Control System Integration – Part 2: Object Model Attributes

ANSI/ISA-95.00.04-2012, Enterprise-Control System Integration – Part 4: Objects and Attributes for Manufacturing Operations Management Integration

ANSI/ISA-95.00.05-2013, Enterprise-Control System Integration – Part 5: Business-to-Manufacturing Transactions