

IEC/TR 61292-6

Edition 1.0 2010-02

TECHNICAL REPORT



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

Т

ICS 33.160.10; 33.180.30

ISBN 978-2-88910-482-6

CONTENTS

FΟ	REW	ORD	4
INT	ROD	UCTION	6
1	Scop	pe	7
2	Norr	mative references	7
3	Abbr	reviated terms	8
4	Back	kground	8
	4.1	General	
	4.2	Raman amplification process	_
	4.3	Distributed vs. lumped amplification	10
	4.4	Distributed vs. lumped amplification Tailoring the Raman gain spectrum Forward and backward pumping configuration	10
	4.5	Forward and backward pumping configuration	11
	4.6	Typical performance of DRA	12
5	Appl	lications of distributed Raman amplification	13
	5.1	lications of distributed Raman amplification General All-Raman systems	13
	5.2	All-Raman systems	13
	5.3	Hybrid EDFA Raman systems 5.3.1 Long repeaterless links 5.3.2 Long span masking in multi-span links	14
		5.3.1 Long repeaterless links	14
		5.3.2 Long span masking in multi-span links	15
		5.3.3 High capacity long haul and ultra-long haul systems	15
6	Perf	formance characteristics and test methods	15
	6.1	General	15
	6.2	Performance of the Raman pump module	16
		6.2.1 Pump wavelengths	16
		6.2.2 Pump output power	16
		6.2.3 Pump degree-of-polarization (DOP)	17
		6.2.4 Pump relative intensity noise (RIN)	17
		6.2.5 (Insertion loss)	17
		6.2,6 Other passive characteristics	
	6.3	System level performance	
	<	6.3.1 On-off signal gain	
		6.3.2 Gain flatness	
		6.3.3 Polarization dependant gain (PDG)	
		6.3.4 Equivalent noise figure	
		6.3.5 Multi-path interference (MPI)	
7	Ope	rational issues	21
	7.1	General	21
	7.2	Dependence of Raman gain on transmission fibre	21
	7.3	Fibre line quality	
	7.4	High pump power issues	
		7.4.1 Laser safety	
		7.4.2 Damage to the fibre line	
8		clusions	
Bib	liogra	aphy	25

TR 61292-6 © IEC:2010(E)

- 3 -

Figure 1 – Stimulated Raman scattering process (left) and Raman gain spectrum for silica fibres (right)	9
Figure 2 – Distributed vs. lumped amplification	10
Figure 3 – The use of multiple pump wavelengths to achieve flat broadband gain	11
Figure 4 – Simulation results showing pump and signal propagation along an SMF span in forward (right plot) and backward (left plot) pumping configurations	11
Figure 5 – On-off gain and equivalent NF for SMF using a dual pump backward DRA with pumps at 1 424 nm and 1 452 nm	13
Figure 6 – Typical configuration of an amplification site in an all-Raman system	14
Figure 7 – Typical configuration of a Raman pump module used for counter-propagating DRA	16
Figure 8 – Model for signal insertion loss (IL) of a Raman pump module used for counter-propagating DRA	18
Figure 9 – Typical configuration used to measure on of gain (a) for co-propagating DRA and (b) for counter-propagating DRA	19
Figure 10 – Variations of Raman on-off gain for different transmission fibres	22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL AMPLIFIERS -

Part 6: Distributed Raman amplification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (Precediter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as hearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and in some areas access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEO technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 61292-6, which is a technical report, has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86C/910/DTR	86C/936/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

TR 61292-6 © IEC:2010(E)

- 5 **-**

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61292 series, published under the general title *Optical amplifiers*, can be found on the IEC website.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed.
- · withdrawn,
- · replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.



-6-


INTRODUCTION

Distributed Raman amplification (DRA) describes the process whereby Raman pump power is introduced into the transmission fibre, leading to signal amplification within the transmission fibre though stimulated Raman scattering. This technology has become increasingly widespread in recent years due to the many advantage that it offers optical system designers, including improved system optical signal-to-noise ratio (OSNR), and the ability to tailor the gain spectrum to cover any or several transmission bands.

A fundamental difference between distributed Raman amplification and amplification using discrete amplifiers, such as erbium-doped fibre amplifiers (EDFAs), is that the latter can be described using a black box approach, while the former is an inherent part of the system in which it is deployed. Thus, a discrete amplifier is a unique and separate element with a well defined input and output ports, allowing rigorous specifications of the amplifiers performance characteristics and the methods used to test these characteristics On the other hand, a distributed Raman amplifier is basically a pump module, with the actual amplification process taking place along the transmission fibre. This means that many of the performance characteristics of distributed Raman amplification are inherently coupled to the system in which it is deployed.

This technical report provides an overview of DRA and its applications. It also provides a detailed discussion of the various performance characteristics related to DRA, some of the methods that can be used to test these characteristics, and some of the operational issues related to the distributed nature of the amplification process, such as the sensitivity to transmission line quality and eye-safety.

The material provided is intended to provide a basis for future development of specifications and test method standards related to DRA.



TR 61292-6 © IEC:2010(E)

-7-

OPTICAL AMPLIFIERS -

Part 6: Distributed Raman amplification

1 Scope

This part of IEC 61292, which is a technical report, deals with distributed Raman amplification (DRA). The main purpose of the report is to provide background material for future standards (specifications, test methods and operating procedures) relating to DRA. The report covers the following aspects:

- general overview of Raman amplification;
- applications of DRA;
- performance characteristics and test methods related to DRA;
- operational issues relating to the deployment of DRA

As DRA is a relatively young technology, and still rapidly evolving, some of the material in this report may become obsolete or irrelevant in a relatively short period. This technical report will be frequently updated in order to minimize this possibility.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60825-2, Safety of laser products - Part 2: Safety of optical fibre communication systems (OFCS)

IEC 61290-3, Optical amplifiers - Test/methods - Part 3: Noise figure parameters

IEC 61290-3-1, Optical amplifiers – Test methods – Part 3-1: Noise figure parameters – Optical spectrum analyzer method

IEC 61290-3-2, Optical amplifiers – Test methods – Part 3-2: Noise figure parameters – Electrical spectrum analyzer method

IEC 61290-7-1, Optical amplifiers – Test methods – Part 7-1: Out-of-band insertion losses – Filtered optical power meter method

IEC 61291-1, Optical amplifiers – Part 1: Generic specification

IEC/TR 61292-3, Optical amplifiers – Part 3: Classification, characteristics and applications

IEC/TR 61292-4, Optical amplifiers – Part 4: Maximum permissible optical power for the damage-free and safe use of optical amplifiers, including Raman amplifiers

ITU-T G.664, Optical safety procedures and requirements for optical transport systems

ITU-T G.665, Generic characteristics of Raman amplifiers and Raman amplified subsystems

NOTE A list of informative references is given in the Bibliography.

