



TECHNICAL REPORT



**Process management for avionics – Electronic components capability in operation –
Part 1: Temperature uprating**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XA**

ICS 03.100.50; 31.020; 49.060

ISBN 978-2-83220-739-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and abbreviations	7
3.1 Terms and definitions	7
3.2 Abbreviations	10
4 Selection provisions	10
4.1 General.....	10
4.2 Device selection, usage and alternatives	10
4.2.1 General	10
4.2.2 Alternatives	11
4.2.3 Device technology	11
4.2.4 Compliance with the electronic component management plan.....	11
4.3 Device capability assessment.....	12
4.3.1 General	12
4.3.2 Device package and internal construction capability assessment.....	12
4.3.3 Risk assessment (assembly level).....	12
4.3.4 Device uprating methods	13
4.3.5 Device reliability assurance	14
4.4 Device quality assurance in wider temperature ranges	15
4.4.1 General.....	15
4.4.2 Device parameter re-characterisation testing.....	15
4.4.3 Device parameter conformance testing	15
4.4.4 Higher assembly level testing	15
4.4.5 Semiconductor device change monitoring	16
4.4.6 Failure data collection and analysis	16
4.5 Documentation.....	16
4.6 Device identification	16
Annex A (informative) Device parameter re-characterisation	20
Annex B (informative) Stress balancing.....	32
Annex C (informative) Parameter conformance assessment.....	42
Annex D (informative) Higher assembly level testing.....	49
Bibliography.....	52
Figure 1 – Flow chart for semiconductor devices in wider temperature ranges	18
Figure 2 – Report form for documenting device usage in wider temperature ranges	19
Figure A.1 – Parameter re-characterisation.....	21
Figure A.2 – Flow diagram of parameter re-characterisation capability assurance process.....	23
Figure A.3 – Margin in electrical parameter measurement based on the results of the sample test.....	26
Figure A.4 – Schematic diagram of parameter limit modifications.....	27
Figure A.5 – Parameter re-characterisation device quality assurance	28
Figure A.6 – Schematic of outlier products that may invalidate sample testing	29

Figure A.7 – Example of intermediate peak of an electrical parameter: voltage feedback input threshold change for Motorola MC34261 power factor controller.	30
Figure A.8 – Report form for documenting device parameter re-characterisation.....	31
Figure B.1 – Iso- T_J curve: the relationship between ambient temperature and dissipated power.....	34
Figure B.2 – Graph of electrical parameters versus dissipated power.....	35
Figure B.3 – Iso- T_J curve for the Fairchild MM74HC244	38
Figure B.4 – Power versus frequency curve for the Fairchild MM74HC244.....	39
Figure B.5 – Flow chart for stress balancing	40
Figure B.6 – Report form for documenting stress balancing	41
Figure C.1 – Relationship of temperature ratings, requirements and margins.....	43
Figure C.2 – Typical fallout distribution versus $T_{req-max}$	45
Figure C.3 – Parameter conformance assessment flow.....	47
Figure C.4 – Report form for documenting parameter conformance testing	48
Figure D.1 – Flow chart of higher level assembly testing.....	50
Figure D.2 – Report form for documenting higher level assembly test at temperature extremes.....	51
Table A.1 – Example of sample size calculation.....	24
Table A.2 – Parameter re-characterisation example: SN74ALS244 Octal Buffer/Driver	27

Withold

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROCESS MANAGEMENT FOR AVIONICS – ELECTRONIC COMPONENTS CAPABILITY IN OPERATION –

Part 1: Temperature uprating

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC/TR 62240-1, which is a technical report, has been prepared by IEC technical committee 107: Process management for avionics.

This first edition cancels and replaces IEC/TR 62240 published in 2005. This edition constitutes a technical revision.

This edition includes the following significant changes:

- a) Document is revised from IEC/TR 62240 to IEC/TR 62240-1.
- b) Revised wording in clauses/subclauses: Introduction and Clauses 1 to 4 including paragraph clarifications and corrections.

- c) Removed all “shall” terms from document.
- d) Updated paragraphs, including addition of references to the utilization of samples from a single lot, and the fact that performance of uprating is repeated if significant changes are implemented by device manufacturer, as well as the reference that the manufacturer’s warranty may be eliminated if uprating is performed.
- e) Added an abbreviations subclause, 3.2.
- f) Reworded 4.3.5, item b), reference pertaining to default margin of 20 °C below the absolute maximum junction temperature.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
107/199/DTR	107/203/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62240 series, published under the general title *Process management for avionics – Electronic components capability in operation*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

INTRODUCTION

Traditionally, industries that produced electronic equipment for ADHP (aerospace, defence and high performance) applications have relied on the military specification system for semiconductor device standards and upon manufacturers of military-specified devices as device sources. This assured the availability of semiconductor devices specified to operate over the temperature ranges required for electronic equipment in ADHP applications. In the past, several device manufacturers have exited the military market, resulting in the decreased availability of devices specified to operate over wide temperature ranges. Following are some typical ambient temperature ranges at which devices are marketed:

Military:	–55 °C to + 125 °C
Automotive:	–40 °C to + 125 °C
Industrial:	–40 °C to + 85 °C
Commercial:	0 °C to + 70 °C

If there are no reasonable or practical alternatives, then a potential response is for equipment manufacturers to use devices at temperature ranges that are wider than those specified by the device manufacturer.

This technical report provides information to select semiconductor devices, to assess their capability to operate, and to assure their intended quality in the wider temperature ranges. It also reports the need for documentation of such usage.

This can be supported by exchanging technical information with the original device manufacturer.

Operation of the device beyond the manufacturer's limits may result normally in loss of warranty by the device manufacturer.

PROCESS MANAGEMENT FOR AVIONICS – ELECTRONIC COMPONENTS CAPABILITY IN OPERATION –

Part 1: Temperature uprating

1 Scope

This Technical Report provides information when using semiconductor devices in wider temperature ranges than those specified by the device manufacturer. The uprating solutions described herein are considered exceptions, when no reasonable alternatives are available; otherwise devices are utilized within the manufacturers' specifications.

The terms "uprating" and "thermal uprating" are being used increasingly in avionics industry discussions and meetings, and clear definitions are included in Clause 3. They were coined as shorthand references to a special case of methods commonly used in selecting components for circuit design.

This technical report describes the methods and processes for implementing this special case. All of the elements of these methods and processes employ existing, commonly used best engineering practices. No new or unique engineering knowledge is needed to follow these processes: only a rigorous application of the overall approach.

Even though the device is used at wider temperatures, the wider temperatures usage will be limited to those that do not compromise applications performance and reliability, particularly for devices with narrow feature size geometries (e.g., 90 nm and less). This technical report does not imply that applications use the device to function beyond the absolute maximum rating limits of the device specified by the original device manufacturer and assumes that:

- device usage outside the original device manufacturers' specified temperature ranges is done only when no reasonable alternative approach is available and is performed with appropriate justification;
- if it is necessary to use devices outside the original device manufacturers' specified temperature ranges, it is done with documented and controlled processes that assure integrity of the equipment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC/TS 62239-1, *Process management for avionics – Management plan – Part 1: Preparation and maintenance of an electronic components management plan*