

This is a preview - click here to buy the full publication

STANDARD


**ISO/IEC
14496-10**

Sixth edition
2010-12-15

Information technology — Coding of audio-visual objects

Part 10: Advanced Video Coding

*Technologies de l'information — Codage des objets audiovisuels
Partie 10: Codage visuel avancé*



Reference number
ISO/IEC 14496-10:2010(E)



© ISO/IEC 2010

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
0 Introduction	xvi
0.1 Prologue	xvi
0.2 Purpose	xvi
0.3 Applications	xvi
0.4 Publication and versions of this Specification	xvi
0.5 Profiles and levels	xvii
0.6 Overview of the design characteristics	xviii
0.6.1 Predictive coding	xviii
0.6.2 Coding of progressive and interlaced video	xix
0.6.3 Picture partitioning into macroblocks and smaller partitions	xix
0.6.4 Spatial redundancy reduction	xix
0.7 How to read this Specification	xix
1 Scope.....	1
2 Normative references	1
3 Definitions	1
4 Abbreviations	9
5 Conventions	10
5.1 Arithmetic operators.....	10
5.2 Logical operators.....	11
5.3 Relational operators.....	11
5.4 Bit-wise operators	11
5.5 Assignment operators.....	11
5.6 Range notation.....	12
5.7 Mathematical functions	12
5.8 Order of operation precedence	13
5.9 Variables, syntax elements, and tables	14
5.10 Text description of logical operations	14
5.11 Processes	15
6 Source, coded, decoded and output data formats, scanning processes, and neighbouring relationships	16
6.1 Bitstream formats	16
6.2 Source, decoded, and output picture formats	16
6.3 Spatial subdivision of pictures and slices	21
6.4 Inverse scanning processes and derivation processes for neighbours	22
6.4.1 Inverse macroblock scanning process	22
6.4.2 Inverse macroblock partition and sub-macroblock partition scanning process	23
6.4.3 Inverse 4x4 luma block scanning process	25
6.4.4 Inverse 4x4 Cb or Cr block scanning process for ChromaArrayType equal to 3	25
6.4.5 Inverse 8x8 luma block scanning process	25
6.4.6 Inverse 8x8 Cb or Cr block scanning process for ChromaArrayType equal to 3	26
6.4.7 Derivation process of the availability for macroblock addresses	26
6.4.8 Derivation process for neighbouring macroblock addresses and their availability	26
6.4.9 Derivation process for neighbouring macroblock addresses and their availability in MBAFF frames	27
6.4.10 Derivation processes for neighbouring macroblocks, blocks, and partitions	28
6.4.11 Derivation process for neighbouring locations	33
6.4.12 Derivation processes for block and partition indices	36
7 Syntax and semantics	37
7.1 Method of specifying syntax in tabular form	37
7.2 Specification of syntax functions, categories, and descriptors	38
7.3 Syntax in tabular form	40
7.3.1 NAL unit syntax	40
7.3.2 Raw byte sequence payloads and RBSP trailing bits syntax	40

7.3.3	Slice header syntax	49
7.3.4	Slice data syntax	54
7.3.5	Macroblock layer syntax	55
7.4	Semantics	62
7.4.1	NAL unit semantics	62
7.4.2	Raw byte sequence payloads and RBSP trailing bits semantics	71
7.4.3	Slice header semantics	85
7.4.4	Slice data semantics	97
7.4.5	Macroblock layer semantics	97
8	Decoding process.....	110
8.1	NAL unit decoding process	111
8.2	Slice decoding process.....	112
8.2.1	Decoding process for picture order count	112
8.2.2	Decoding process for macroblock to slice group map	116
8.2.3	Decoding process for slice data partitions	120
8.2.4	Decoding process for reference picture lists construction.....	120
8.2.5	Decoded reference picture marking process	127
8.3	Intra prediction process.....	132
8.3.1	Intra_4x4 prediction process for luma samples.....	132
8.3.2	Intra_8x8 prediction process for luma samples.....	139
8.3.3	Intra_16x16 prediction process for luma samples	147
8.3.4	Intra prediction process for chroma samples.....	149
8.3.5	Sample construction process for I_PCM macroblocks	154
8.4	Inter prediction process.....	154
8.4.1	Derivation process for motion vector components and reference indices	157
8.4.2	Decoding process for Inter prediction samples	169
8.4.3	Derivation process for prediction weights	179
8.5	Transform coefficient decoding process and picture construction process prior to deblocking filter process..	181
8.5.1	Specification of transform decoding process for 4x4 luma residual blocks	182
8.5.2	Specification of transform decoding process for luma samples of Intra_16x16 macroblock prediction mode	182
8.5.3	Specification of transform decoding process for 8x8 luma residual blocks	183
8.5.4	Specification of transform decoding process for chroma samples	184
8.5.5	Specification of transform decoding process for chroma samples with ChromaArrayType equal to 3	186
8.5.6	Inverse scanning process for 4x4 transform coefficients and scaling lists	186
8.5.7	Inverse scanning process for 8x8 transform coefficients and scaling lists	187
8.5.8	Derivation process for chroma quantisation parameters	189
8.5.9	Derivation process for scaling functions	189
8.5.10	Scaling and transformation process for DC transform coefficients for Intra_16x16 macroblock type	191
8.5.11	Scaling and transformation process for chroma DC transform coefficients	191
8.5.12	Scaling and transformation process for residual 4x4 blocks	193
8.5.13	Scaling and transformation process for residual 8x8 blocks	196
8.5.14	Picture construction process prior to deblocking filter process	200
8.5.15	Intra residual transform-bypass decoding process	201
8.6	Decoding process for P macroblocks in SP slices or SI macroblocks	202
8.6.1	SP decoding process for non-switching pictures	202
8.6.2	SP and SI slice decoding process for switching pictures	205
8.7	Deblocking filter process	207
8.7.1	Filtering process for block edges	211
8.7.2	Filtering process for a set of samples across a horizontal or vertical block edge.....	213
9	Parsing process	219
9.1	Parsing process for Exp-Golomb codes	219
9.1.1	Mapping process for signed Exp-Golomb codes	221
9.1.2	Mapping process for coded block pattern	221
9.2	CAVLC parsing process for transform coefficient levels	224
9.2.1	Parsing process for total number of transform coefficient levels and trailing ones	225
9.2.2	Parsing process for level information	229
9.2.3	Parsing process for run information	230
9.2.4	Combining level and run information	234

9.3	CABAC parsing process for slice data	234
9.3.1	Initialisation process	236
9.3.2	Binarization process	260
9.3.3	Decoding process flow	269
9.3.4	Arithmetic encoding process (informative)	291
Annex A	Profiles and levels.....	299
A.1	Requirements on video decoder capability.....	299
A.2	Profiles	299
A.2.1	Baseline profile.....	299
A.2.2	Main profile	300
A.2.3	Extended profile	300
A.2.4	High profile	301
A.2.5	High 10 profile	301
A.2.6	High 4:2:2 profile	302
A.2.7	High 4:4:4 Predictive profile	302
A.2.8	High 10 Intra profile.....	303
A.2.9	High 4:2:2 Intra profile.....	303
A.2.10	High 4:4:4 Intra profile.....	304
A.2.11	CAVLC 4:4:4 Intra profile	304
A.3	Levels	305
A.3.1	Level limits common to the Baseline, Constrained Baseline, Main, and Extended profiles	305
A.3.2	Level limits common to the High, High 10, High 4:2:2, High 4:4:4 Predictive, High 10 Intra, High 4:2:2 Intra, High 4:4:4 Intra, and CAVLC 4:4:4 Intra profiles.....	307
A.3.3	Profile-specific level limits.....	309
A.3.4	Effect of level limits on frame rate (informative)	314
A.3.5	Effect of level limits on maximum DPB size in units of frames (informative)	317
Annex B	Byte stream format.....	319
B.1	Byte stream NAL unit syntax and semantics.....	319
B.1.1	Byte stream NAL unit syntax	319
B.1.2	Byte stream NAL unit semantics	319
B.2	Byte stream NAL unit decoding process.....	320
B.3	Decoder byte-alignment recovery (informative)	320
Annex C	Hypothetical reference decoder.....	322
C.1	Operation of coded picture buffer (CPB)	326
C.1.1	Timing of bitstream arrival.....	326
C.1.2	Timing of coded picture removal	327
C.2	Operation of the decoded picture buffer (DPB)	328
C.2.1	Decoding of gaps in frame_num and storage of "non-existing" frames	328
C.2.2	Picture decoding and output	329
C.2.3	Removal of pictures from the DPB before possible insertion of the current picture	329
C.2.4	Current decoded picture marking and storage	330
C.3	Bitstream conformance.....	331
C.4	Decoder conformance.....	332
C.4.1	Operation of the output order DPB.....	333
C.4.2	Decoding of gaps in frame_num and storage of "non-existing" pictures	333
C.4.3	Picture decoding	334
C.4.4	Removal of pictures from the DPB before possible insertion of the current picture	334
C.4.5	Current decoded picture marking and storage	335
Annex D	Supplemental enhancement information	338
D.1	SEI payload syntax	339
D.1.1	Buffering period SEI message syntax	341
D.1.2	Picture timing SEI message syntax	342
D.1.3	Pan-scan rectangle SEI message syntax	343
D.1.4	Filler payload SEI message syntax	343
D.1.5	User data registered by ITU-T Rec. T.35 SEI message syntax	343
D.1.6	User data unregistered SEI message syntax	344
D.1.7	Recovery point SEI message syntax	344
D.1.8	Decoded reference picture marking repetition SEI message syntax	344
D.1.9	Spare picture SEI message syntax	345

D.1.10	Scene information SEI message syntax	345
D.1.11	Sub-sequence information SEI message syntax.....	346
D.1.12	Sub-sequence layer characteristics SEI message syntax.....	346
D.1.13	Sub-sequence characteristics SEI message syntax.....	347
D.1.14	Full-frame freeze SEI message syntax	347
D.1.15	Full-frame freeze release SEI message syntax	347
D.1.16	Full-frame snapshot SEI message syntax.....	347
D.1.17	Progressive refinement segment start SEI message syntax.....	348
D.1.18	Progressive refinement segment end SEI message syntax.....	348
D.1.19	Motion-constrained slice group set SEI message syntax	348
D.1.20	Film grain characteristics SEI message syntax	349
D.1.21	Deblocking filter display preference SEI message syntax	349
D.1.22	Stereo video information SEI message syntax.....	350
D.1.23	Post-filter hint SEI message syntax.....	350
D.1.24	Tone mapping information SEI message syntax	351
D.1.25	Frame packing arrangement SEI message syntax	352
D.1.26	Reserved SEI message syntax	352
D.2	SEI payload semantics	352
D.2.1	Buffering period SEI message semantics.....	352
D.2.2	Picture timing SEI message semantics.....	353
D.2.3	Pan-scan rectangle SEI message semantics	358
D.2.4	Filler payload SEI message semantics	359
D.2.5	User data registered by ITU-T Rec. T.35 SEI message semantics.....	359
D.2.6	User data unregistered SEI message semantics.....	360
D.2.7	Recovery point SEI message semantics	360
D.2.8	Decoded reference picture marking repetition SEI message semantics	362
D.2.9	Spare picture SEI message semantics	362
D.2.10	Scene information SEI message semantics	364
D.2.11	Sub-sequence information SEI message semantics	366
D.2.12	Sub-sequence layer characteristics SEI message semantics	367
D.2.13	Sub-sequence characteristics SEI message semantics	368
D.2.14	Full-frame freeze SEI message semantics	370
D.2.15	Full-frame freeze release SEI message semantics	370
D.2.16	Full-frame snapshot SEI message semantics	370
D.2.17	Progressive refinement segment start SEI message semantics	370
D.2.18	Progressive refinement segment end SEI message semantics	371
D.2.19	Motion-constrained slice group set SEI message semantics	371
D.2.20	Film grain characteristics SEI message semantics	372
D.2.21	Deblocking filter display preference SEI message semantics	378
D.2.22	Stereo video information SEI message semantics	380
D.2.23	Post-filter hint SEI message semantics	380
D.2.24	Tone mapping information SEI message semantics	381
D.2.25	Frame packing arrangement SEI message semantics	383
D.2.26	Reserved SEI message semantics	391
Annex E	Video usability information.....	392
E.1	VUI syntax	393
E.1.1	VUI parameters syntax	393
E.1.2	HRD parameters syntax	394
E.2	VUI semantics	394
E.2.1	VUI parameters semantics	394
E.2.2	HRD parameters semantics	407
Annex F	Patent Rights	409
Annex G	Scalable video coding	411
G.1	Scope	411
G.2	Normative references	411
G.3	Definitions	411
G.4	Abbreviations	415
G.5	Conventions	415

G.6	Source, coded, decoded and output data formats, scanning processes, neighbouring and reference layer relationships	415
G.6.1	Derivation process for reference layer macroblocks	415
G.6.2	Derivation process for reference layer partitions.....	418
G.6.3	Derivation process for reference layer sample locations in resampling	419
G.6.4	SVC derivation process for macroblock and sub-macroblock partition indices.....	421
G.7	Syntax and semantics	421
G.7.1	Method of specifying syntax in tabular form	421
G.7.2	Specification of syntax functions, categories, and descriptors	421
G.7.3	Syntax in tabular form.....	421
G.7.4	Semantics	433
G.7.4.1	NAL unit semantics.....	434
G.8	SVC decoding process.....	466
G.8.1	SVC initialisation and decoding processes	468
G.8.2	SVC reference picture lists construction and decoded reference picture marking process	487
G.8.3	SVC intra decoding processes	498
G.8.4	SVC Inter prediction process.....	508
G.8.5	SVC transform coefficient decoding and sample array construction processes	521
G.8.6	Resampling processes for prediction data, intra samples, and residual samples	538
G.8.7	SVC deblocking filter processes.....	568
G.8.8	Specification of bitstream subsets	580
G.9	Parsing process	581
G.9.1	Alternative parsing process for coded block pattern	582
G.9.2	Alternative CAVLC parsing process for transform coefficient levels	583
G.9.3	Alternative CABAC parsing process for slice data in scalable extension	587
G.10	Profiles and levels	590
G.10.1	Profiles	590
G.10.2	Levels	593
G.11	Byte stream format	598
G.12	Hypothetical reference decoder	598
G.13	Supplemental enhancement information	598
G.13.1	SEI payload syntax	599
G.13.2	SEI payload semantics	605
G.14	Video usability information	633
G.14.1	SVC VUI parameters extension syntax	634
G.14.2	SVC VUI parameters extension semantics	634
Annex H Multiview video coding.....	637	
H.1	Scope	637
H.2	Normative references	637
H.3	Definitions	637
H.4	Abbreviations	639
H.5	Conventions	639
H.6	Source, coded, decoded and output data formats, scanning processes, and neighbouring relationships	639
H.7	Syntax and semantics	639
H.7.1	Method of specifying syntax in tabular form	639
H.7.2	Specification of syntax functions, categories, and descriptors	640
H.7.3	Syntax in tabular form.....	640
H.7.4	Semantics	644
H.8	MVC decoding process	657
H.8.1	MVC decoding process for picture order count	658
H.8.2	MVC decoding process for reference picture lists construction	658
H.8.3	MVC decoded reference picture marking process.....	663
H.8.4	MVC inter prediction and inter-view prediction process	663
H.8.5	Specification of bitstream subsets	663
H.9	Parsing process	667
H.10	Profiles and levels	667
H.10.1	Profiles	667
H.10.2	Levels	669
H.11	Byte stream format	672
H.12	MVC hypothetical reference decoder.....	672

H.13	MVC SEI messages	672
H.13.1	SEI message syntax.....	672
H.13.2	SEI message semantics	678
H.14	Video usability information	690
H.14.1	MVC VUI parameters extension syntax	691
H.14.2	MVC VUI parameters extension semantics	691

LIST OF FIGURES

Figure 6-1 – Nominal vertical and horizontal locations of 4:2:0 luma and chroma samples in a frame.....	18
Figure 6-2 – Nominal vertical and horizontal sampling locations of 4:2:0 samples in top and bottom fields.....	19
Figure 6-3 – Nominal vertical and horizontal locations of 4:2:2 luma and chroma samples in a frame.....	19
Figure 6-4 – Nominal vertical and horizontal sampling locations of 4:2:2 samples top and bottom fields.....	20
Figure 6-5 – Nominal vertical and horizontal locations of 4:4:4 luma and chroma samples in a frame.....	20
Figure 6-6 – Nominal vertical and horizontal sampling locations of 4:4:4 samples top and bottom fields.....	21
Figure 6-7 – A picture with 11 by 9 macroblocks that is partitioned into two slices.....	22
Figure 6-8 – Partitioning of the decoded frame into macroblock pairs	22
Figure 6-9 – Macroblock partitions, sub-macroblock partitions, macroblock partition scans, and sub-macroblock partition scans	24
Figure 6-10 – Scan for 4x4 luma blocks.....	25
Figure 6-11 – Scan for 8x8 luma blocks.....	25
Figure 6-12 – Neighbouring macroblocks for a given macroblock	26
Figure 6-13 – Neighbouring macroblocks for a given macroblock in MB AFF frames.....	27
Figure 6-14 – Determination of the neighbouring macroblock, blocks, and partitions (informative)	28
Figure 7-1 – Structure of an access unit not containing any NAL units with nal_unit_type equal to 0, 7, 8, or in the range of 12 to 18, inclusive, or in the range of 20 to 31, inclusive.....	69
Figure 8-1 – Intra_4x4 prediction mode directions (informative)	134
Figure 8-2 – Example for temporal direct-mode motion vector inference (informative)	166
Figure 8-3 – Directional segmentation prediction (informative)	167
Figure 8-4 – Integer samples (shaded blocks with upper-case letters) and fractional sample positions (un-shaded blocks with lower-case letters) for quarter sample luma interpolation	174
Figure 8-5 – Fractional sample position dependent variables in chroma interpolation and surrounding integer position samples A, B, C, and D	176
Figure 8-6 – Assignment of the indices of dcY to luma4x4BlkIdx	183
Figure 8-7 – Assignment of the indices of dcC to chroma4x4BlkIdx: (a) ChromaArrayType equal to 1, (b) ChromaArrayType equal to 2	185
Figure 8-8 – 4x4 block scans. (a) Zig-zag scan. (b) Field scan (informative)	187
Figure 8-9 – 8x8 block scans. (a) 8x8 zig-zag scan. (b) 8x8 field scan (informative)	188
Figure 8-10 – Boundaries in a macroblock to be filtered	208
Figure 8-11 – Convention for describing samples across a 4x4 block horizontal or vertical boundary	212
Figure 9-1 – Illustration of CABAC parsing process for a syntax element SE (informative)	236
Figure 9-2 – Overview of the arithmetic decoding process for a single bin (informative)	285

Figure 9-3 – Flowchart for decoding a decision.....	286
Figure 9-4 – Flowchart of renormalization	289
Figure 9-5 – Flowchart of bypass decoding process	290
Figure 9-6 – Flowchart of decoding a decision before termination	291
Figure 9-7 – Flowchart for encoding a decision.....	293
Figure 9-8 – Flowchart of renormalization in the encoder.....	294
Figure 9-9 – Flowchart of PutBit(B).....	295
Figure 9-10 – Flowchart of encoding bypass	296
Figure 9-11 – Flowchart of encoding a decision before termination	297
Figure 9-12 – Flowchart of flushing at termination	297
Figure C-1 – Structure of byte streams and NAL unit streams for HRD conformance checks.....	323
Figure C-2 – HRD buffer model	325
Figure D-1 – Rearrangement and upconversion of checkerboard interleaving (frame_packing_arrangement_type equal to 0).....	389
Figure D-2 – Rearrangement and upconversion of column interleaving (frame_packing_arrangement_type equal to 1 with quincunx_sampling_flag equal to 0).....	389
Figure D-3 – Rearrangement and upconversion of row interleaving (frame_packing_arrangement_type equal to 2 with quincunx_sampling_flag equal to 0).....	390
Figure D-4 – Rearrangement and upconversion of side-by-side packing arrangement (frame_packing_arrangement_type equal to 3 with quincunx_sampling_flag equal to 0)	390
Figure D-5 – Rearrangement and upconversion of top-bottom packing arrangement (frame_packing_arrangement_type equal to 4 with quincunx_sampling_flag equal to 0)	391
Figure D-6 – Rearrangement and upconversion of side-by-side packing arrangement with quincunx sampling (frame_packing_arrangement_type equal to 3 with quincunx_sampling_flag equal to 1).....	391
Figure D-7 – Rearrangement of a temporal interleaving frame arrangement (frame_packing_arrangement_type equal to 5)	392
Figure E-1 – Location of chroma samples for top and bottom fields for chroma_format_idc equal to 1 (4:2:0 chroma format) as a function of chroma_sample_loc_type_top_field and chroma_sample_loc_type_bottom_field	404

LIST OF TABLES

Table 5-1 – Operation precedence from highest (at top of table) to lowest (at bottom of table)	13
Table 6-1 – SubWidthC, and SubHeightC values derived from chroma_format_idc and separate_colour_plane_flag	17
Table 6-2 – Specification of input and output assignments for subclauses 6.4.10.1 to 6.4.10.7	28
Table 6-3 – Specification of mbAddrN.....	33
Table 6-4 – Specification of mbAddrN and yM.....	35
Table 7-1 – NAL unit type codes, syntax element categories, and NAL unit type classes	63
Table 7-2 – Assignment of mnemonic names to scaling list indices and specification of fall-back rule	74
Table 7-3 – Specification of default scaling lists Default_4x4_Intra and Default_4x4_Inter	74
Table 7-4 – Specification of default scaling lists Default_8x8_Intra and Default_8x8_Inter	75
Table 7-5 – Meaning of primary_pic_type	83
Table 7-6 – Name association to slice_type	86

Table 7-7 – modification_of_pic_nums_idc operations for modification of reference picture lists	92
Table 7-8 – Interpretation of adaptive_ref_pic_marking_mode_flag	94
Table 7-9 – Memory management control operation (memory_management_control_operation) values	95
Table 7-10 – Allowed collective macroblock types for slice_type	98
Table 7-11 – Macroblock types for I slices	99
Table 7-12 – Macroblock type with value 0 for SI slices	100
Table 7-13 – Macroblock type values 0 to 4 for P and SP slices	101
Table 7-14 – Macroblock type values 0 to 22 for B slices	102
Table 7-15 – Specification of CodedBlockPatternChroma values	104
Table 7-16 – Relationship between intra_chroma_pred_mode and spatial prediction modes	105
Table 7-17 – Sub-macroblock types in P macroblocks	106
Table 7-18 – Sub-macroblock types in B macroblocks	107
Table 8-1 – Refined slice group map type	117
Table 8-2 – Specification of Intra4x4PredMode[luma4x4BlkIdx] and associated names	133
Table 8-3 – Specification of Intra8x8PredMode[luma8x8BlkIdx] and associated names	140
Table 8-4 – Specification of Intra16x16PredMode and associated names	147
Table 8-5 – Specification of Intra chroma prediction modes and associated names	150
Table 8-6 – Specification of the variable colPic	159
Table 8-7 – Specification of PicCodingStruct(X)	159
Table 8-8 – Specification of mbAddrCol, yM, and vertMvScale	161
Table 8-9 – Assignment of prediction utilization flags	163
Table 8-10 – Derivation of the vertical component of the chroma vector in field coding mode	169
Table 8-11 – Differential full-sample luma locations	175
Table 8-12 – Assignment of the luma prediction sample predPartLX _L [x _L , y _L]	176
Table 8-13 – Specification of mapping of idx to c _{ij} for zig-zag and field scan	187
Table 8-14 – Specification of mapping of idx to c _{ij} for 8x8 zig-zag and 8x8 field scan	188
Table 8-15 – Specification of QP _C as a function of qP _I	189
Table 8-16 – Derivation of offset dependent threshold variables α' and β' from indexA and indexB	216
Table 8-17 – Value of variable t' _{C0} as a function of indexA and bS	217
Table 9-1 – Bit strings with "prefix" and "suffix" bits and assignment to codeNum ranges (informative)	220
Table 9-2 – Exp-Golomb bit strings and codeNum in explicit form and used as ue(v) (informative)	220
Table 9-3 – Assignment of syntax element to codeNum for signed Exp-Golomb coded syntax elements se(v)	221
Table 9-4 – Assignment of codeNum to values of coded_block_pattern for macroblock prediction modes	221
Table 9-5 – coeff_token mapping to TotalCoeff(coeff_token) and TrailingOnes(coeff_token)	227
Table 9-6 – Codeword table for level_prefix (informative)	230
Table 9-7 – total_zeros tables for 4x4 blocks with tzVlcIndex 1 to 7	232
Table 9-8 – total_zeros tables for 4x4 blocks with tzVlcIndex 8 to 15	232
Table 9-9 – total_zeros tables for chroma DC 2x2 and 2x4 blocks	233

Table 9-10 – Tables for run_before.....	234
Table 9-11 – Association of ctxIdx and syntax elements for each slice type in the initialisation process	237
Table 9-12 – Values of variables m and n for ctxIdx from 0 to 10	238
Table 9-13 – Values of variables m and n for ctxIdx from 11 to 23	239
Table 9-14 – Values of variables m and n for ctxIdx from 24 to 39	239
Table 9-15 – Values of variables m and n for ctxIdx from 40 to 53	239
Table 9-16 – Values of variables m and n for ctxIdx from 54 to 59, and 399 to 401.....	240
Table 9-17 – Values of variables m and n for ctxIdx from 60 to 69	240
Table 9-18 – Values of variables m and n for ctxIdx from 70 to 104	241
Table 9-19 – Values of variables m and n for ctxIdx from 105 to 165	242
Table 9-20 – Values of variables m and n for ctxIdx from 166 to 226	243
Table 9-21 – Values of variables m and n for ctxIdx from 227 to 275	244
Table 9-22 – Values of variables m and n for ctxIdx from 277 to 337	245
Table 9-23 – Values of variables m and n for ctxIdx from 338 to 398	246
Table 9-24 – Values of variables m and n for ctxIdx from 402 to 459	247
Table 9-25 – Values of variables m and n for ctxIdx from 460 to 483	248
Table 9-26 – Values of variables m and n for ctxIdx from 484 to 571	249
Table 9-27 – Values of variables m and n for ctxIdx from 572 to 659	251
Table 9-28 – Values of variables m and n for ctxIdx from 660 to 717	253
Table 9-29 – Values of variables m and n for ctxIdx from 718 to 775	254
Table 9-30 – Values of variables m and n for ctxIdx from 776 to 863	255
Table 9-31 – Values of variables m and n for ctxIdx from 864 to 951	257
Table 9-32 – Values of variables m and n for ctxIdx from 952 to 1011	259
Table 9-33 – Values of variables m and n for ctxIdx from 1012 to 1023	260
Table 9-34 – Syntax elements and associated types of binarization, maxBinIdxCtx, and ctxIdxOffset	262
Table 9-35 – Bin string of the unary binarization (informative)	265
Table 9-36 – Binarization for macroblock types in I slices.....	267
Table 9-37 – Binarization for macroblock types in P, SP, and B slices	268
Table 9-38 – Binarization for sub-macroblock types in P, SP, and B slices	269
Table 9-39 – Assignment of ctxIdxInc to binIdx for all ctxIdxOffset values except those related to the syntax elements coded_block_flag, significant_coeff_flag, last_significant_coeff_flag, and coeff_abs_level_minus1	271
Table 9-40 – Assignment of ctxIdxBlockCatOffset to ctxBlockCat for syntax elements coded_block_flag, significant_coeff_flag, last_significant_coeff_flag, and coeff_abs_level_minus1	272
Table 9-41 – Specification of ctxIdxInc for specific values of ctxIdxOffset and binIdx	281
Table 9-42 – Specification of ctxBlockCat for the different blocks.....	282
Table 9-43 – Mapping of scanning position to ctxIdxInc for ctxBlockCat == 5, 9, or 13	283
Table 9-44 – Specification of rangeTabLPS depending on pStateIdx and qCodIRangeIdx	287
Table 9-45 – State transition table	288
Table A-1 – Level limits	308

Table A-2 – Specification of cpbBrVclFactor and cpbBrNalFactor.....	311
Table A-3 – Baseline and Constrained Baseline profile level limits	312
Table A-4 – Main, High, High 10, High 4:2:2, High 4:4:4 Predictive, High 10 Intra, High 4:2:2 Intra, High 4:4:4 Intra, and CAVLC 4:4:4 Intra profile level limits	313
Table A-5 – Extended profile level limits	314
Table A-6 – Maximum frame rates (frames per second) for some example frame sizes.....	315
Table A-7 – Maximum DPB size (frames) for some example frame sizes.....	318
Table D-1 – Interpretation of pic_struct	356
Table D-2 – Mapping of ct_type to source picture scan	357
Table D-3 – Definition of counting_type values	358
Table D-4 – scene_transition_type values	366
Table D-5 – model_id values.....	374
Table D-6 – blending_mode_id values	375
Table D-7 – filter_hint_type values	382
Table D-8 – Definition of frame_packing_arrangement_type.....	385
Table D-9 – Definition of content_interpretation_type	386
Table E-1 – Meaning of sample aspect ratio indicator	396
Table E-2 – Meaning of video_format	397
Table E-3 – Colour primaries	398
Table E-4 – Transfer characteristics	399
Table E-5 – Matrix coefficients	402
Table E-6 – Divisor for computation of $\Delta t_{fi,dpb}(n)$	405
Table F-1 – Organisations providing patent rights licensing notices.....	410
Table G-1 – Name association to slice_type for NAL units with nal_unit_type equal to 20.....	452
Table G-2 – Interpretation of adaptive_ref_base_pic_marking_mode_flag	462
Table G-3 – Memory management base control operation (memory_management_base_control_operation) values	462
Table G-4 – Allowed collective macroblock types for slice_type	466
Table G-5 – Inferred macroblock type I_BL for EI slices.....	466
Table G-6 – Scale values cS for transform coefficient level scaling	531
Table G-7 – Macroblock type predictors mbTypeILPred.....	549
Table G-8 – Sub-macroblock type predictors subMbTypeILPred[mbPartIdx]	549
Table G-9 – 16-phase luma interpolation filter for resampling in Intra_Base prediction.....	559
Table G-10 – Mapping of (nX, nY) to coeffTokenIdx and vice versa.....	586
Table G-11 – Association of ctxIdx and syntax elements for each slice type in the initialisation process.....	590
Table G-12 – Values of variables m and n for ctxIdx from 1024 to 1026.....	590
Table G-13 – Values of variables m and n for ctxIdx from 1027 to 1030.....	590
Table G-14 – Syntax elements and associated types of binarization, maxBinIdxCtx, and ctxIdxOffset.....	591
Table G-15 – Assignment of ctxIdxInc to binIdx for the ctxIdxOffset values related to the syntax elements base_mode_flag and residual_prediction_flag	591

Table G-16 – Scalable Baseline profile level limits	600
Table G-17 – Specification of cpbBrVclFactor and cpbBrNalFactor	600
Table H-1 – modification_of_pic_nums_idc operations for modification of reference picture lists.....	658
Table H-2 – Association between camera parameter variables and syntax elements.	690

Withdrawn

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 14496-10 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information* in collaboration with ITU-T.


This part of ISO/IEC 14496 is technically aligned with ITU-T Rec. H.264 but is not published as identical text.

This sixth edition cancels and replaces the fifth edition (ISO/IEC 14496-10:2009) which has been technically revised.

ISO/IEC 14496 consists of the following parts, under the general title *Information technology — Coding of audio-visual objects*:

- *Part 1: Systems*
- *Part 2: Visual*
- *Part 3: Audio*
- *Part 4: Conformance testing*
- *Part 5: Reference software*
- *Part 6: Delivery Multimedia Integration Framework (DMIF)*
- *Part 7: Optimized reference software for coding of audio-visual objects [Technical Report]*
- *Part 8: Carriage of ISO/IEC 14496 contents over IP networks*
- *Part 9: Reference hardware description [Technical Report]*
- *Part 10: Advanced Video Coding*
- *Part 11: Scene description and application engine*
- *Part 12: ISO base media file format*

- Part 13: Intellectual Property Management and Protection (IPMP) extensions
- Part 14: MP4 file format
- Part 15: Advanced Video Coding (AVC) file format
- Part 16: Animation Framework eXtension (AFX)
- Part 17: Streaming text format
- Part 18: Font compression and streaming
- Part 19: Synthesized texture stream
- Part 20: Lightweight Application Scene Representation (LASeR) and Simple Aggregation Format (SAF)
- Part 21: MPEG-J Graphics Framework eXtensions (GFX)
- Part 22: Open Font Format
- Part 23: Symbolic Music Representation
- Part 24: Audio and systems interaction
- Part 25: 3D Graphics Compression Model
- Part 26: Audio conformance
- Part 27: 3D Graphics conformance



0 Introduction

This clause does not form an integral part of this Recommendation | International Standard.

0.1 Prologue

This subclause does not form an integral part of this Recommendation | International Standard.

As the costs for both processing power and memory have reduced, network support for coded video data has diversified, and advances in video coding technology have progressed, the need has arisen for an industry standard for compressed video representation with substantially increased coding efficiency and enhanced robustness to network environments. Toward these ends the ITU-T Video Coding Experts Group (VCEG) and the ISO/IEC Moving Picture Experts Group (MPEG) formed a Joint Video Team (JVT) in 2001 for development of a new Recommendation | International Standard.

0.2 Purpose

This subclause does not form an integral part of this Recommendation | International Standard.

This Recommendation | International Standard was developed in response to the growing need for higher compression of moving pictures for various applications such as videoconferencing, digital storage media, television broadcasting, internet streaming, and communication. It is also designed to enable the use of the coded video representation in a flexible manner for a wide variety of network environments. The use of this Recommendation | International Standard allows motion video to be manipulated as a form of computer data and to be stored on various storage media, transmitted and received over existing and future networks and distributed on existing and future broadcasting channels.

0.3 Applications

This subclause does not form an integral part of this Recommendation | International Standard.

This Recommendation | International Standard is designed to cover a broad range of applications for video content including but not limited to the following:

CATV	Cable TV on optical networks, copper, etc.
DBS	Direct broadcast satellite video services
DSL	Digital subscriber line video services
DTTB	Digital terrestrial television broadcasting
ISM	Interactive storage media (optical disks, etc.)
MMM	Multimedia mailing
MSPN	Multimedia services over packet networks
RTC	Real-time conversational services (videoconferencing, videophone, etc.)
RVS	Remote video surveillance
SSM	Serial storage media (digital VTR, etc.)

0.4 Publication and versions of this Specification

This subclause does not form an integral part of this Recommendation | International Standard.

This specification has been jointly developed by ITU-T Video Coding Experts Group (VCEG) and the ISO/IEC Moving Picture Experts Group. It is published as technically-aligned twin text in both organizations ITU-T and ISO/IEC.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 1 refers to the first approved version of this Recommendation | International Standard.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 2 refers to the integrated text containing the corrections specified in the first technical corrigendum.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 3 refers to the integrated text containing both the first technical corrigendum (2004) and the first amendment, which is referred to as the "Fidelity range extensions".

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 4 refers to the integrated text containing the first technical corrigendum (2004), the first amendment (the "Fidelity range extensions"), and an additional technical corrigendum (2005).

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 5 refers to the integrated version 4 text with its specification of the High 4:4:4 profile removed.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 6 refers to the integrated version 5 text after its amendment to support additional colour space indicators.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 7 refers to the integrated version 6 text after its amendment to define five new profiles intended primarily for professional applications (the High 10 Intra, High 4:2:2 Intra, High 4:4:4 Intra, CAVLC 4:4:4 Intra, and High 4:4:4 Predictive profiles) and two new types of supplemental enhancement information (SEI) messages (the post-filter hint SEI message and the tone mapping information SEI message).

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 8 refers to the integrated version 7 text after its amendment to specify scalable video coding in three profiles (Scalable Baseline, Scalable High, and Scalable High Intra profiles).

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 9 refers to the integrated version 8 text after applying the corrections specified in a third technical corrigendum.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 10 refers to the integrated version 9 text after its amendment to specify a profile for multiview video coding (the Multiview High profile) and to define additional SEI messages.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 11 refers to the integrated version 10 text after its amendment to define a new profile (the Constrained Baseline profile) intended primarily to enable implementation of decoders supporting only the common subset of capabilities supported in various previously-specified profiles.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 12 refers to the integrated version 11 text after its amendment to define a new profile (the Stereo High profile) for two-view video coding with support of interlaced coding tools and to specify an additional SEI message specified as the frame packing arrangement SEI message. The changes for versions 11 and 12 were processed as a single amendment in the ISO/IEC approval process.

ITU-T Rec. H.264 | ISO/IEC 14496-10 version 13 (the current Specification) refers to the integrated version 12 text with various minor corrections and clarifications.

0.5 Profiles and levels

This subclause does not form an integral part of this Recommendation | International Standard.

This Recommendation | International Standard is designed to be generic in the sense that it serves a wide range of applications, bit rates, resolutions, qualities, and services. Applications should cover, among other things, digital storage media, television broadcasting and real-time communications. In the course of creating this Specification, various requirements from typical applications have been considered, necessary algorithmic elements have been developed, and these have been integrated into a single syntax. Hence, this Specification will facilitate video data interchange among different applications.

Considering the practicality of implementing the full syntax of this Specification, however, a limited number of subsets of the syntax are also stipulated by means of "profiles" and "levels". These and other related terms are formally defined in clause 3.

A "profile" is a subset of the entire bitstream syntax that is specified by this Recommendation | International Standard. Within the bounds imposed by the syntax of a given profile it is still possible to require a very large variation in the performance of encoders and decoders depending upon the values taken by syntax elements in the bitstream such as the specified size of the decoded pictures. In many applications, it is currently neither practical nor economic to implement a decoder capable of dealing with all hypothetical uses of the syntax within a particular profile.

In order to deal with this problem, "levels" are specified within each profile. A level is a specified set of constraints imposed on values of the syntax elements in the bitstream. These constraints may be simple limits on values. Alternatively they may take the form of constraints on arithmetic combinations of values (e.g., picture width multiplied by picture height multiplied by number of pictures decoded per second).

Coded video content conforming to this Recommendation | International Standard uses a common syntax. In order to achieve a subset of the complete syntax, flags, parameters, and other syntax elements are included in the bitstream that signal the presence or absence of syntactic elements that occur later in the bitstream.

0.6 Overview of the design characteristics

This subclause does not form an integral part of this Recommendation | International Standard.

The coded representation specified in the syntax is designed to enable a high compression capability for a desired image quality. With the exception of the transform bypass mode of operation for lossless coding in the High 4:4:4 Intra, CAVLC 4:4:4 Intra, and High 4:4:4 Predictive profiles, and the I_PCM mode of operation in all profiles, the algorithm is typically not lossless, as the exact source sample values are typically not preserved through the encoding and decoding processes. A number of techniques may be used to achieve highly efficient compression. Encoding algorithms (not specified in this Recommendation | International Standard) may select between inter and intra coding for block-shaped regions of each picture. Inter coding uses motion vectors for block-based inter prediction to exploit temporal statistical dependencies between different pictures. Intra coding uses various spatial prediction modes to exploit spatial statistical dependencies in the source signal for a single picture. Motion vectors and intra prediction modes may be specified for a variety of block sizes in the picture. The prediction residual is then further compressed using a transform to remove spatial correlation inside the transform block before it is quantised, producing an irreversible process that typically discards less important visual information while forming a close approximation to the source samples. Finally, the motion vectors or intra prediction modes are combined with the quantised transform coefficient information and encoded using either variable length coding or arithmetic coding.

Scalable video coding is specified in Annex G allowing the construction of bitstreams that contain sub-bitstreams that conform to this Specification. For temporal bitstream scalability, i.e., the presence of a sub-bitstream with a smaller temporal sampling rate than the bitstream, complete access units are removed from the bitstream when deriving the sub-bitstream. In this case, high-level syntax and inter prediction reference pictures in the bitstream are constructed accordingly. For spatial and quality bitstream scalability, i.e., the presence of a sub-bitstream with lower spatial resolution or quality than the bitstream, NAL units are removed from the bitstream when deriving the sub-bitstream. In this case, inter-layer prediction, i.e., the prediction of the higher spatial resolution or quality signal by data of the lower spatial resolution or quality signal, is typically used for efficient coding. Otherwise, the coding algorithm as described in the previous paragraph is used.

Multiview video coding is specified in Annex H allowing the construction of bitstreams that represent multiple views. Similar to scalable video coding, bitstreams that represent multiple views may also contain sub-bitstreams that conform to this Specification. For temporal bitstream scalability, i.e., the presence of a sub-bitstream with a smaller temporal sampling rate than the bitstream, complete access units are removed from the bitstream when deriving the sub-bitstream. In this case, high-level syntax and inter prediction reference pictures in the bitstream are constructed accordingly. For view bitstream scalability, i.e. the presence of a sub-bitstream with fewer views than the bitstream, NAL units are removed from the bitstream when deriving the sub-bitstream. In this case, inter-view prediction, i.e., the prediction of one view signal by data of another view signal, is typically used for efficient coding. Otherwise, the coding algorithm as described in the previous paragraph is used.

0.6.1 Predictive coding

This subclause does not form an integral part of this Recommendation | International Standard.

Because of the conflicting requirements of random access and highly efficient compression, two main coding types are specified. Intra coding is done without reference to other pictures. Intra coding may provide access points to the coded sequence where decoding can begin and continue correctly, but typically also shows only moderate compression efficiency. Inter coding (predictive or bi-predictive) is more efficient using inter prediction of each block of sample values from some previously decoded picture selected by the encoder. In contrast to some other video coding standards, pictures coded using bi-predictive inter prediction may also be used as references for inter coding of other pictures.

The application of the three coding types to pictures in a sequence is flexible, and the order of the decoding process is generally not the same as the order of the source picture capture process in the encoder or the output order from the decoder for display. The choice is left to the encoder and will depend on the requirements of the application. The decoding order is specified such that the decoding of pictures that use inter-picture prediction follows later in decoding order than other pictures that are referenced in the decoding process.

0.6.2 Coding of progressive and interlaced video

This subclause does not form an integral part of this Recommendation | International Standard.

This Recommendation | International Standard specifies a syntax and decoding process for video that originated in either progressive-scan or interlaced-scan form, which may be mixed together in the same sequence. The two fields of an interlaced frame are separated in capture time while the two fields of a progressive frame share the same capture time. Each field may be coded separately or the two fields may be coded together as a frame. Progressive frames are typically coded as a frame. For interlaced video, the encoder can choose between frame coding and field coding. Frame coding or field coding can be adaptively selected on a picture-by-picture basis and also on a more localized basis within a coded frame. Frame coding is typically preferred when the video scene contains significant detail with limited motion. Field coding typically works better when there is fast picture-to-picture motion.

0.6.3 Picture partitioning into macroblocks and smaller partitions

This subclause does not form an integral part of this Recommendation | International Standard.

As in previous video coding Recommendations and International Standards, a macroblock, consisting of a 16x16 block of luma samples and two corresponding blocks of chroma samples, is used as the basic processing unit of the video decoding process.

A macroblock can be further partitioned for inter prediction. The selection of the size of inter prediction partitions is a result of a trade-off between the coding gain provided by using motion compensation with smaller blocks and the quantity of data needed to represent the data for motion compensation. In this Recommendation | International Standard the inter prediction process can form segmentations for motion representation as small as 4x4 luma samples in size, using motion vector accuracy of one-quarter of the luma sample grid spacing displacement. The process for inter prediction of a sample block can also involve the selection of the picture to be used as the reference picture from a number of stored previously-decoded pictures. Motion vectors are encoded differentially with respect to predicted values formed from nearby encoded motion vectors.

Typically, the encoder calculates appropriate motion vectors and other data elements represented in the video data stream. This motion estimation process in the encoder and the selection of whether to use inter prediction for the representation of each region of the video content is not specified in this Recommendation | International Standard.

0.6.4 Spatial redundancy reduction

This subclause does not form an integral part of this Recommendation | International Standard.

Both source pictures and prediction residuals have high spatial redundancy. This Recommendation | International Standard is based on the use of a block-based transform method for spatial redundancy removal. After inter prediction from previously-decoded samples in other pictures or spatial-based prediction from previously-decoded samples within the current picture, the resulting prediction residual is split into 4x4 blocks. These are converted into the transform domain where they are quantised. After quantisation many of the transform coefficients are zero or have low amplitude and can thus be represented with a small amount of encoded data. The processes of transformation and quantisation in the encoder are not specified in this Recommendation | International Standard.

0.7 How to read this Specification

This subclause does not form an integral part of this Recommendation | International Standard.

It is suggested that the reader starts with clause 1 (Scope) and moves on to clause 3 (Definitions). Clause 6 should be read for the geometrical relationship of the source, input, and output of the decoder. Clause 7 (Syntax and semantics) specifies the order to parse syntax elements from the bitstream. See subclauses 7.1-7.3 for syntactical order and see subclause 7.4 for semantics; i.e., the scope, restrictions, and conditions that are imposed on the syntax elements. The actual parsing for most syntax elements is specified in clause 9 (Parsing process). Finally, clause 8 (Decoding process) specifies how the syntax elements are mapped into decoded samples. Throughout reading this Specification, the reader should refer to clauses 2 (Normative references), 4 (Abbreviations), and 5 (Conventions) as needed. Annexes A through E, G, and H also form an integral part of this Recommendation | International Standard.


Annex A specifies twelve profiles (Baseline, Constrained Baseline, Main, Extended, High, High 10, High 4:2:2, High 4:4:4 Predictive, High 10 Intra, High 4:2:2 Intra, High 4:4:4 Intra, and CAVLC 4:4:4 Intra), each being tailored to certain application domains, and defines the so-called levels of the profiles. Annex B specifies syntax and semantics of a byte stream format for delivery of coded video as an ordered stream of bytes. Annex C specifies the hypothetical reference decoder and its use to check bitstream and decoder conformance. Annex D specifies syntax and semantics for supplemental enhancement information message payloads. Annex E specifies syntax and semantics of the video usability information parameters of the sequence parameter set.

Annex F specifies patent information.

Annex G specifies scalable video coding (SVC). The reader is referred to Annex G for the entire decoding process for SVC, which is specified there with references being made to clauses 2-9 and Annexes A-E. Subclause G.10 specifies three profiles for SVC (Scalable Baseline, Scalable High, and Scalable High Intra).

Annex H specifies multiview video coding (MVC). The reader is referred to Annex H for the entire decoding process for MVC, which is specified there with references being made to clauses 2-9 and Annexes A-E. Subclause H.10 specifies two profiles for MVC (Multiview High and Stereo High).

Throughout this Specification, statements appearing with the preamble "NOTE -" are informative and are not an integral part of this Recommendation | International Standard.



Information technology — Coding of audio-visual objects —

Part 10: Advanced Video Coding

1 Scope

This Part of ISO/IEC 14496 specifies advanced video coding for coding of audio-visual objects.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- ITU-T Recommendation T.35 (2000), *Procedure for the allocation of ITU-T defined codes for non-standard facilities*.
- ISO/IEC 11578:1996, *Information technology — Open Systems Interconnection — Remote Procedure Call (RPC)*
- ISO 11664-1, *Colorimetry — Part 1. CIE standard colorimetric observers*