
**Information technology — Scalable
compression and coding of
continuous-tone still images —**

**Part 8:
Lossless and near-lossless coding**

*Technologies de l'information — Compression échelonnée et codage
d'images plates en ton continu*

Withhold

Withdrawn



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions.....	1
3.2 Symbols.....	7
3.3 Abbreviated terms.....	7
4 Conventions	7
4.1 Conformance language.....	7
4.2 Operators.....	8
4.2.1 Arithmetic operators.....	8
4.2.2 Logical operators.....	8
4.2.3 Relational operators.....	8
4.2.4 Precedence order of operators.....	8
4.2.5 Mathematical functions.....	9
5 General	9
5.1 General definitions.....	9
5.2 Overview of ISO/IEC 18477-8.....	9
5.3 Profiles.....	11
5.4 Encoder requirements.....	11
5.5 Decoder requirements.....	12
Annex A (normative) Encoding and decoding process	13
Annex B (normative) Boxes	18
Annex C (normative) Multi-component decorrelation transformation	26
Annex D (normative) Entropy coding of residual data in the DCT-bypass and large range mode	30
Annex E (normative) Discrete cosine transformation	41
Annex F (normative) Component upsampling	54
Annex G (normative) Quantization and noise shaping for the DCT-bypass process	56
Annex H (normative) Profiles	59
Bibliography	60

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/IEC JTC 1, *Information technology, SC29, Coding of audio, picture, multimedia and hypermedia information*.

A list of all parts in the ISO 18477 series, published under the general title *Information technology — Scalable compression and coding of continuous-tone still images*, can be found on the ISO website.

Introduction

This document specifies a coded codestream format for storage of continuous-tone high and low dynamic range photographic content. JPEG XT part 8 is a scalable lossy to lossless image coding system supporting multiple component images consisting of integer samples between 8- and 16-bit resolution, or floating point samples of 16-bit resolution. It is by itself an extension of ISO/IEC 18477-6 and ISO/IEC 18477-7, which specify intermediate range and high-dynamic range image decoding algorithms. Both of these are based on the box-based file format specified in ISO/IEC 18477-3, which is again an extension of ISO/IEC 18477-1; the codestream is composed in such a way that legacy applications conforming to Rec. ITU-T T.81 | ISO/IEC 10918-1 are able to reconstruct a lossy, low dynamic range, 8 bits per sample version of the image.

Today, the most widely used digital photography format, a minimal implementation of JPEG (specified in Rec. ITU-T T.81 | ISO/IEC 10918-1), uses a bit depth of 8; each of the three channels that together compose an image pixel is represented by 8 bits, providing 256 representable values per channel. For more demanding applications, it is not uncommon to use a bit depth of 16, providing 65 536 representable values to describe each channel within a pixel, resulting in over 2.8×10^{14} representable colour values. In some less common scenarios, even greater bit depths are used, requiring a floating-point sample representation.

Most common photo and image formats use an 8-bit or 16-bit unsigned integer value to represent some function of the intensity of each colour channel. While it might be theoretically possible to agree on one method for assigning specific numerical values to real world colours, doing so is not practical. Since any specific device has its own limited range for colour reproduction, the device's range may be a small portion of the agreed-upon universal colour range. As a result, such an approach is an extremely inefficient use of the available numerical values, especially when using only 8 bits (or 256 unique values) per channel. To represent pixel values as efficiently as possible, devices use a numeric encoding optimized for their own range of possible colours or gamut.

This part of JPEG XT is primarily designed to encode intermediate or high dynamic image sample values **without loss**, or with a precisely controllable bounded loss using the tools defined in ISO/IEC 18477-1 and some minimal extensions of those tools. The goal is to provide a backwards compatible coding specification that allows legacy applications and existing toolchains to continue to operate on codestreams conforming to this document.

JPEG XT has been designed to be backwards compatible to legacy applications while at the same time having a small coding complexity; JPEG XT uses, whenever possible, functional blocks of Rec. ITU-T T.81 | ISO/IEC 10918-1 to extend the functionality of the legacy JPEG Coding System. It is optimized for storage and transmission of intermediate and high dynamic range and wide colour gamut 8- to 16-bit integer or 16-bit floating point images while also enabling low-complexity encoder and decoder implementations.

This document is an extension of ISO/IEC 18477-1, a compression system for continuous tone digital still images which is backwards compatible with Rec. ITU-T T.81 | ISO/IEC 10918-1. That is, legacy applications conforming to Rec. ITU-T T.81 | ISO/IEC 10918-1 will be able to reconstruct streams generated by an encoder conforming to this document, though will possibly not be able to reconstruct such streams in full dynamic range, full quality or without loss.

This document is itself based on ISO/IEC 18477-3 that defines a box-based file format similar to other JPEG standards. It also contains elements of ISO/IEC 18477-6 and ISO/IEC 18477-7. The aim of this document is to provide a migration path for legacy applications to support lossless coding of intermediate and high dynamic range images, that is images that are either represented by sample values requiring 8- to 16-bit precision, or even using 16-bit floating point sample resolution. While Rec. ITU-T T.81 | ISO/IEC 10918-1 already defines a lossless mode for integer samples, images encoded in this mode cannot be decoded by applications only supporting the lossy 8-bit-mode; the coding engine for lossless coding in Rec. ITU-T T.81 | ISO/IEC 10918-1 is completely different from the lossy coding mode. Unlike the legacy standard, this document defines a lossless scalable coding engine supporting all bit depths between 8 and 16 bits per sample, including 16-bit floating point samples, while also staying compatible with legacy applications. Such applications will continue to work, but will only able

to reconstruct a lossy 8-bit standard low dynamic range (LDR) version of the full image contained in the codestream. The parts of ISO/IEC 18477 specify a coded file format, referred to as JPEG XT, which is designed primarily for storage and interchange of continuous-tone photographic content.

Withdrawn

Information technology — Scalable compression and coding of continuous-tone still images —

Part 8: Lossless and near-lossless coding

1 Scope

This document specifies a coding format, referred to as JPEG XT, which is designed primarily for continuous-tone photographic content.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 18477-1:2015, *Information technology — Scalable compression and coding of continuous-tone still images — Part 1: Scalable compression and coding of continuous-tone still images*

ISO/IEC 18477-3:2015, *Information technology — Scalable compression and coding of continuous-tone still images — Part 3: Box file format*

ISO/IEC 18477-6:2016, *Information technology — Scalable compression and coding of continuous-tone still images — Part 6: IDR Integer Coding*

ISO/IEC 18477-7:2016, *Information technology — Scalable compression and coding of continuous-tone still images — Part 7: HDR Floating-Point Coding*

ITU-T T.81 | ISO/IEC 10918-1, *Information technology — Digital compression and coding of continuous tone still images — Requirements and guidelines*

ITU-T BT.601, *Studio encoding parameters of digital television for standard 4:3 and wide screen 16:9 aspect ratios*