
**Information technology — Digitally
recorded media for information
interchange and storage — 120 mm
Single Layer (25,0 Gbytes per disk) and
Dual Layer (50,0 Gbytes per disk) BD
Rewritable disk**

*Technologies de l'information — Supports pour l'échange d'informations
et le stockage enregistrés numériquement — Disques BD réinscriptibles
de 120 mm simple couche (25,0 Go par disque) et double couche (50,0
Go par disque)*

Withdrawn



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	x
Introduction.....	xi
1 Scope	1
2 Conformance	2
2.1 Optical Disk	2
2.2 Generating system	2
2.3 Receiving system	2
2.4 Compatibility statement	2
3 Normative references	2
4 Terms and definitions	3
5 Conventions and notations	7
5.1 Terminology	7
5.1.1 Meaning of words	7
5.1.2 Levels of grouping	7
5.2 Representation of numbers	7
5.3 Integer calculus	8
5.4 Names	8
6 List of acronyms	9
7 General descriptions of disk	11
8 General requirements	13
8.1 Environments	13
8.1.1 Test environment	13
8.1.2 Operating environment	13
8.1.3 Storage environment	14
8.1.4 Transportation	15
8.2 Safety requirements	15
8.3 Flammability	15
9 Reference drive	16
9.1 General	16
9.2 Environmental conditions	16
9.3 Optical system	16
9.4 Optical beam	17
9.5 HF read channel	17
9.6 Radial PP read channel	18
9.7 Disk Clamping	18
9.8 Rotation of the disk and Measurement Velocity	18
9.9 Normalized servo transfer function	19
9.10 Measurement Velocity and Reference servo for axial tracking	20
9.11 Measurement Velocity and Reference servo for radial tracking	21
10 Dimensional characteristics	23
10.1 General	23
10.2 Disk reference planes and reference axis	23
10.3 Overall dimensions	25
10.4 First transition Area	25
10.5 Protection ring	25
10.6 Clamping Zone	25
10.7 Second transition Area	26

10.8	Information Area	26
10.8.1	General.....	26
10.8.2	Subdivisions of Information Zone on SL disk	27
10.8.3	Subdivisions of Information Zone on DL disks	27
10.9	Rim Area	28
11	Mechanical characteristics	29
11.1	Mass	29
11.2	Moment of inertia	29
11.3	Dynamic imbalance	29
11.4	Axial runout	29
11.4.1	General.....	29
11.4.2	Residual axial tracking error	29
11.5	Radial runout.....	30
11.5.1	General.....	30
11.5.2	Residual radial tracking error on SL disks	30
11.5.3	Residual radial tracking error on DL disks	30
11.6	Durability of Cover Layer	31
11.6.1	Impact resistance of Cover Layer	31
11.6.2	Scratch resistance of Cover Layer.....	31
11.6.3	Repulsion of fingerprints by Cover Layer	31
12	Optical characteristics in Information Area	32
12.1	General.....	32
12.2	Refractive index of Transmission Stacks (TS)	32
12.3	Thickness of Transmission Stack(s)	32
12.3.1	Thickness of Transmission Stack of SL disks	32
12.3.2	Thickness of Transmission Stack of DL disks	32
12.4	Reflectivity	33
12.4.1	Reflectivity of Recording Layer of SL disks	33
12.4.2	Reflectivity of Recording Layer of DL disks	34
12.5	Birefringence.....	34
12.6	Angular deviation.....	34
13	Data format	35
13.1	General.....	35
13.2	Data Frames	37
13.3	Error-Detection Code (EDC)	37
13.4	Scrambled Data Frame.....	38
13.5	Data Block	39
13.6	LDC Block.....	39
13.7	LDC Code words	40
13.8	LDC Cluster	41
13.8.1	General.....	41
13.8.2	First interleave step	41
13.8.3	Second interleaving step	41
13.9	Addressing and Control Data	43
13.9.1	General.....	43
13.9.2	Address Units.....	43
13.9.3	User-Control Data	46
13.9.4	Byte/Bit assignments for User-Control Data	47
13.10	Access Block.....	47
13.11	BIS Block	49
13.12	BIS Code words	49
13.13	BIS Cluster.....	50
13.14	ECC Cluster	54
13.15	Recording Frames	55
13.16	Physical Cluster	55
13.17	17PP Modulation for Recordable data	55
13.17.1	General.....	55
13.17.2	Bit conversion rules	56

13.17.3	dc-control procedure	56
13.17.4	Frame Sync	56
13.18	Modulation and NRZI conversion	58
14	Physical Data Allocation and Linking	59
14.1	General	59
14.2	Recording-Unit Block (RUB)	59
14.2.1	General	59
14.2.2	Data Run-in	60
14.2.3	Data Run-out	61
14.2.4	Guard_3 field	62
14.3	Locating data relative to wobble addresses	62
14.3.1	General	62
14.3.2	Start-Position Shift (SPS)	62
15	Track format	65
15.1	General	65
15.2	Track shape	65
15.3	Track Path	66
15.4	Track Pitch	67
15.4.1	Track Pitch in BCA Zone	67
15.4.2	Track Pitch in Embossed HFM Areas	67
15.4.3	Track Pitch in Rewritable Areas	67
15.4.4	Track Pitch between Embossed HFM Area and Rewritable Area	67
15.5	Track layout of HFM Groove	67
15.5.1	General	67
15.5.2	Data Format	68
15.5.3	Addressing and Control Data	69
15.5.4	Recording Frames	72
15.6	Track layout of Wobbled Groove(s)	74
15.6.1	General	74
15.6.2	Modulation of wobbles	75
15.7	ADIP Information	76
15.7.1	General	76
15.7.2	ADIP-Unit Types	76
15.7.3	ADIP Word structure	78
15.7.4	ADIP Data structure	79
15.7.5	ADIP Error Correction	81
15.8	Disk Information in ADIP Aux Frame	83
15.8.1	General	83
15.8.2	Error protection for Disk-Information Aux Frames	83
15.8.3	Disk-Information Data structure	84
16	General description of Information Zone	115
16.1	General	115
16.2	Format of Information Zone on Single-Layer disk	115
16.3	Format of Information Zone on Dual-Layer disk	115
17	Layout of Rewritable Area of Information Zone	115
18	Inner Zone	119
18.1	General	119
18.2	Permanent Information & Control data (PIC) Zone	121
18.2.1	General	121
18.2.2	Content of PIC Zone	121
18.2.3	Emergency Brake	122
18.3	Rewritable Area of Inner Zone(s)	124
18.3.1	Protection-Zone 2	124
18.3.2	INFO 2 / Reserved 8	124
18.3.3	INFO 2 / Reserved 7	124
18.3.4	INFO 2 / Reserved 6	125
18.3.5	INFO 2 / Reserved 5	125

18.3.6	INFO 2 / PAC 2.....	125
18.3.7	INFO 2 / DMA 2.....	125
18.3.8	INFO 2 / Control Data 2.....	125
18.3.9	INFO 2 / Buffer 2.....	125
18.3.10	OPC / Test Zone.....	125
18.3.11	Reserved.....	125
18.3.12	INFO1 / Buffer 1.....	125
18.3.13	INFO 1 / Drive Area (optional).....	126
18.3.14	INFO 1 / Reserved 3.....	127
18.3.15	INFO 1 / Reserved 2.....	127
18.3.16	INFO 1 / Reserved 1.....	127
18.3.17	INFO 1 / DMA 1.....	127
18.3.18	INFO1 / Control Data 1.....	127
18.3.19	INFO1 / PAC 1.....	127
19	Data Zone.....	127
20	Outer Zone(s).....	128
20.1	General.....	128
20.2	INFO 3 / Buffer 4.....	129
20.3	INFO 3 / DMA 3.....	129
20.4	INFO 3 / Control Data 4.....	129
20.5	Angular buffer.....	129
20.6	INFO 4 / DMA 4.....	129
20.7	INFO 4 / Control Data 4.....	129
20.8	INFO 4 / Buffer 6.....	129
20.9	Protection-Zone 3.....	129
21	Physical-Access Control Clusters.....	130
21.1	General.....	130
21.2	Layout of PAC Zones.....	130
21.3	General structure of PAC Clusters.....	131
21.4	Primary PAC Cluster (mandatory).....	134
21.5	Disk Write-Protect PAC Cluster (optional).....	137
21.6	IS1 and IS2 PAC Clusters.....	141
22	Disk Management.....	142
22.1	General.....	142
22.2	Disk-Management Structure (DMS).....	142
22.2.1	General.....	142
22.2.2	Disk-Definition Structure (DDS).....	143
22.2.3	Defect List (DFL).....	147
22.2.4	Defect-List Header.....	147
22.2.5	List of Defects.....	148
22.2.6	DFL Entries.....	150
23	Assignment of Logical-Sector Numbers (LSNs).....	151
24	Characteristics of Grooved Areas.....	152
25	Method of testing for Grooved Area.....	153
25.1	General.....	153
25.2	Environment.....	153
25.3	Reference drive.....	153
25.3.1	General.....	153
25.3.2	Read power.....	153
25.3.3	Read channels.....	153
25.3.4	Tracking requirements.....	153
25.3.5	Scanning velocity.....	153
25.4	Definitions of signals.....	153
26	Signals from HFM Grooves.....	155
26.1	Push-Pull signal.....	155
26.2	HFM Wobble signal.....	155

26.3	Jitter of HFM signal	155
27	Signals from Wobbled Groove(s)	156
27.1	Phase depth	156
27.2	Push-Pull signal.....	156
27.3	Wobble signal	156
27.3.1	General	156
27.3.2	Measurement of NWS.....	156
27.3.3	Measurement of wobble CNR.....	157
27.3.4	Measurement of harmonic distortion requirements	157
28	Characteristics of Recording Layer.....	157
29	Method of testing for Recording Layer	158
29.1	General	158
29.2	Environment.....	158
29.3	Reference drive.....	158
29.3.1	General	158
29.3.2	Read power	158
29.3.3	Read channels	158
29.3.4	Tracking requirements.....	158
29.3.5	Scanning velocities	158
29.4	Write conditions	158
29.4.1	Write-pulse waveform	158
29.4.2	Write powers	159
29.4.3	Write conditions for jitter measurement	159
29.4.4	Write conditions for cross-erase measurement.....	159
29.4.5	Write conditions for inter-velocity overwrite measurements	160
29.5	Definition of signals	160
30	Signals from Recorded Areas	161
30.1	HF signals	161
30.2	Modulated amplitude.....	161
30.3	Reflectivity-Modulation product	162
30.4	Asymmetry	162
30.5	Jitter	162
30.6	Cross-erase.....	163
30.7	Inter-velocity overwrite	164
30.8	Read stability	165
31	Local defects.....	166
32	Characteristics of User Data	166
33	Method of testing for User Data.....	167
33.1	General	167
33.2	Environment.....	167
33.3	Reference drive.....	167
33.3.1	General	167
33.3.2	Read power	167
33.3.3	Read channels	167
33.3.4	Error Correction.....	167
33.3.5	Tracking requirements.....	167
33.3.6	Scanning velocities	167
33.4	Definition of signals	168
34	Minimum quality of recorded information	169
34.1	Random Symbol Error Rate	169
34.2	Maximum burst errors.....	169
34.3	User-written Data.....	169
35	BCA.....	170
Annex A (normative)	Thickness of Transmission Stacks in case of multiple layers	171
A.1	General	171

A.2	Refractive Index n_i of all layers in Cover Layer and Spacer Layer	171
A.3	Thickness variation of the Transmission Stack	171
A.4	Example of thickness calculation for SL.....	171
Annex B	(normative) Measurement of reflectivity	172
B.1	General.....	172
B.2	Calibration method	172
B.3	Measuring method	173
Annex C	(normative) Measurement of scratch resistance of Cover Layer.....	175
C.1	General.....	175
C.2	Taber Abrasion test	175
Annex D	(normative) Measurement of repulsion of grime by Cover Layer	177
D.1	General.....	177
D.2	Specifications of stamp	177
D.3	Preparation of ink	178
D.4	Preparation of ink pad.....	178
D.5	Using ink pad and stamp	179
Annex E	(normative) Measurement of wobble amplitude.....	180
E.1	Measurement methods.....	180
E.2	Calibration of filters	184
Annex F	(normative) Write-pulse waveform for testing.....	185
F.1	General write-pulse waveform.....	185
F.2	N-1 write strategy A	186
F.3	N-1 write strategy B	188
F.4	N/2 write strategy	190
F.5	Definition of pulse widths and rise and fall times	194
Annex G	(normative) Optimum Power Control (OPC) procedure for media.....	195
G.1	General.....	195
G.2	Mathematical model for modulation versus power function	195
G.3	Procedure for determination of OPC parameters for media	197
G.4	Write-power window	197
Annex H	(normative) HF signal pre-processing for jitter measurements	198
H.1	General.....	198
H.2	General implementation of equalizer.....	198
H.3	Conventional Equalizer circuit	199
H.4	Limit Equalizer circuit.....	200
H.5	Specifications of supporting circuits	201
H.5.1	Amplifiers and filters.....	201
H.5.2	Open-loop transfer function for PLL.....	202
H.5.3	Slicer	203
H.6	Condition for measurement.....	203
H.7	Jitter measurement.....	204
Annex I	(normative) Measurement procedure	205
I.1	General.....	205
I.2	Initial adjustments of Reference drive.....	205
I.3	Jitter measurement.....	206
I.4	Modulated amplitude measurements	206
I.5	Measurements of Resolution I_{2pp} / I_{8pp} and I_{3pp} / I_{8pp}	206
I.5.1	Method for measuring I_{2pp} and I_{8pp}	206
I.5.2	I_{3pp} / I_{8pp} , I_{8pp} / I_{8H} and asymmetry measurement procedure.....	208
I.6	Tracking-error signal measurements (PP_{norm} measurement procedure).....	208
I.7	Residual error of axial tracking measurement procedure.....	209
I.8	Residual error of radial tracking measurement procedure	210
I.9	Random SER measurement.....	210
Annex J	(informative) Measurement of birefringence	211
J.1	Principle of measurement.....	211

J.2	Measurements conditions	211
J.3	Example of measurement procedure	212
J.4	Interchangeability of measuring results	212
	Annex K (informative) Measurement of thickness of Cover Layer and Spacer Layer	213
K.1	Focusing method.....	213
K.2	Interferometer method	214
	Annex L (informative) Measurement of impact resistance of Cover Layer.....	216
L.1	General	216
L.2	Recommendation for drives	216
L.3	Measurements of impact resistance of Cover Layer	216
	Annex M (informative) Groove deviation and wobble amplitude	218
M.1	Relation between normalized wobble signal and wobble amplitude	218
M.2	Tolerance of normalized wobble signal	218
	Bibliography.....	220

Withdrawn

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 30192 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digitally recorded media for information interchange and storage*.

Withdrawn

Introduction

In March 2002, 9 companies known as the Blu-ray Disc Founders, or BDF, came together to create optical-disk formats with the large capacity and high-speed transfer rates, that would be needed for recording and reproducing of high-definition video content. This joint effort turned out to be fruitful, and the BDF issued the first version of its Blu-ray Disc™ Rewritable Format Part1 Version 1.0, in June of 2002.

Then, in October 2004, more than 100 companies joined and the BDF became an open forum called the Blu-ray Disc Association (BDA). The BDA issued Version 2.1 of the Blu-ray Disc™ Rewritable Format Part1 in October 2005 and Version 3.0 in June of 2010.

By the end of 2010, over 100 million of Blu-ray Disc™ had already been shipped, and the Blu-ray™ devices such as players, recorders, game consoles and PC drives were in use all over the world.

The BDA also conducts verification activities for both disks and devices and has established more than 10 Testing Centres in Asia, Europe and the USA.

The BDA gave consumer applications the highest priority in the first few years. But it was known, of course, that International Standardization would be required before many government entities and their contractors would be allowed to use Blu-ray Disc™. In February and January of 2011, ISO/IEC JTC 1/SC 23 and JIIMA (Japan Image & Information Management Association) formally requested the BDA to consider International Standardization. The reason for this was to enable the inclusion of writable BDs, along with DVDs and CDs, in an International Standard specifying test methods for the estimation of lifetime of optical storage media for long-term data storage. In October 2011, the president of the BDA responded that his organization had decided to pursue International Standards of the basic physical formats for the Recordable and Rewritable Blu-ray Disc™.

In December 2011 BDA sent project proposals for the International standardization of 4 formats to ISO/IEC JTC 1/SC 23 via the Japan national body. They are 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disks, 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Rewritable disks, 120 mm Triple Layer (100,0 Gbytes per disk) and Quadruple Layer (128,0 Gbytes per disk) BD Recordable disks and 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk.

This International Standard specifies the mechanical, physical and optical characteristics of a 120 mm rewritable optical disk with a capacity of 25,0 Gbytes or 50,0 Gbytes.

A few additional specifications are required in order to write and read video recording applications, such as the BDMV and BDAV formats, which have been specified by the BDA for use on BD Recordable disks. These specifications, which are related to the Application, the file system and the Content-protection system, are required for the disk, the generating system and the receiving system. For more information of the Application, the Content-protection system and the additional requirements for the Blu-ray™ Format specifications, see <http://www.blu-raydisc.info>.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of patents.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of holders of these patent rights are registered with ISO and IEC. Information may be obtained from:

Hitachi Consumer Electronics Co., Ltd.
Intellectual Property Management
292 Yoshida-cho, Totsuka-ku, Yokohama 244-0817 Japan

Hitachi, Ltd.,
IT Platform R&D Management Division Patent Strategy
322-2 Nakazato, Odawara-shi, Kanagawa-Ken 250-0872 Japan

Panasonic Corporation
Intellectual Property Center
OBP Panasonic Tower 8th Floor, 2-1-61, Shiromi, Chuoh-ku, Osaka, 540-6208, Japan

Pioneer Corporation
Intellectual Property Division, Legal & Intellectual Property Division,
1-1, Shin-Ogura, Saiwai-ku, Kawasaki-Shi, Kanagawa, 212-0031, Japan

Sony Corporation
IP Asset Management Department, Intellectual Property Division,
1-7-1, Konan, Minato-ku, Tokyo, 108-0075, Japan

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (<http://patents.iec.ch>) maintain on-line databases of patents relevant to their standards. Users are encouraged to consult the databases for the most up to date information concerning patents.

NOTE Blu-ray™, Blu-ray Disc™ and the logos are trademarks of the Blu-ray Disc Association.

Information technology — Digitally recorded media for information interchange and storage — 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Rewritable disk

1 Scope

This International Standard specifies the mechanical, physical and optical characteristics of a 120 mm rewritable optical disk with a capacity of 25,0 Gbytes or 50,0 Gbytes. It specifies the quality of the recorded and unrecorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. User data can be written, read and overwritten many times using a reversible method. A conforming disk is identified as a BD Rewritable disk.

This International Standard specifies

- two related but different Types of this disk,
- the conditions for conformance,
- the environments in which the disk is to be operated and stored,
- the mechanical and physical characteristics of the disk, which allow mechanical interchange between data processing systems,
- the format of the information on the disk, including the physical disposition of the Tracks and Sectors,
- the error-correcting codes and the coding method used,
- the characteristics of the signals recorded on the disk, which enable data processing systems to read data from the disk.

This International Standard provides for interchange of disks between drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical Disk

A claim of conformance with this International Standard shall specify the Type implemented. An optical disk shall be in conformance with this International Standard if it meets all mandatory requirements specified for its Type.

2.2 Generating system

A generating system shall be in conformance with this International Standard if the optical disk it generates is in accordance with 2.1.

2.3 Receiving system

A receiving system shall be in conformance with this International Standard if it is able to handle both Types of optical disks according to 2.1.

2.4 Compatibility statement

A claim of conformance by a Generating or Receiving system with this International Standard shall include a statement listing any other standards supported. This statement shall specify the numbers of the standards, the optical disk Types supported (where appropriate) and whether support includes reading only or both reading and writing.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 646:1991, *Information technology — ISO 7-bit coded character set for information interchange*

ISO 9352:1995, *Plastics — Determination of resistance to wear by abrasive wheels*

IEC 60068-2-2:1974, *Environment testing — Part 2-2: Tests — Test B: Dry heat*

IEC 60068-2-30:2005, *Environment testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 h + 12 h cycle)*

IEC 60950-1:2005, *Information technology equipment — Safety — Part 1: General requirements*