



## TECHNICAL REPORT



**Information technology – Generic cabling systems for customer premises –  
Part 9903: Matrix modelling of channels and links**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 35.200

ISBN 978-2-8322-2923-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions and abbreviations .....	8
3.1 Terms and definitions.....	8
3.2 Abbreviations.....	9
4 Matrix model.....	9
5 Matrix definition.....	10
5.1 Quadriports.....	10
5.2 Matrix port definition for a two pair system representative for modelling purposes.....	10
5.3 Operational scattering matrix .....	10
5.4 General naming convention.....	11
5.5 S-Matrix.....	11
5.6 Passivity.....	12
5.7 Operational reflexion loss matrix.....	12
5.8 Transmission matrix (T-matrix).....	13
5.9 S-matrix of cabling.....	13
6 Calculation with matrices using limit lines.....	13
7 Extracting limit lines.....	14
7.1 General.....	14
7.2 Equations to extract the cabling limit lines .....	14
7.2.1 Operational attenuation.....	14
7.2.2 Near end crosstalk.....	15
7.2.3 Attenuation to far end crosstalk ratio .....	15
7.2.4 Reflection.....	15
8 Component values to be used as input to the model.....	15
8.1 General.....	15
8.2 Cable.....	16
8.2.1 General.....	16
8.2.2 Wave attenuation.....	16
8.2.3 Near end crosstalk.....	16
8.2.4 Far end crosstalk.....	16
8.2.5 Reflection .....	16
8.3 Connections.....	17
8.3.1 General .....	17
8.3.2 As point source of disturbance.....	17
8.3.3 As a transmission line.....	18
Annex A (informative) S to T and T to S-matrix conversion formulas .....	19
A.1 Overview.....	19
A.2 Formulas.....	19
Annex B (informative) Calculation examples .....	20
B.1 Overview.....	20
B.2 Component assumptions for modelling purposes.....	20

B.2.1	Cables .....	20
B.2.2	Connections .....	21
B.3	Model results .....	21
B.3.1	General .....	21
B.3.2	Insertion loss .....	21
B.3.3	NEXT .....	22
B.3.4	ACR-F .....	22
B.3.5	Return loss .....	22
Annex C (informative)	Terms and definitions .....	23
C.1	Comparison of namings .....	23
C.2	General.....	24
C.3	Background of terms and definitions .....	24
C.3.1	Operational attenuation .....	24
C.3.2	Operational transfer function ( $T_B$ ).....	26
C.3.3	Image or wave transfer function ( $T$ ) .....	26
C.3.4	Insertion transfers function of a two-port ( $T_{B }$ ).....	26
C.3.5	Insertion transfer function ( $T_{B }$ ) measured with a NWA.....	26
C.3.6	Operational reflection loss transfer function ( $T_{ref} = S_{ref}$ ) of a junction.....	26
Bibliography.....		28
Figure 1 – Link configurations of ISO/IEC 11801:2002 .....		6
Figure 2 – Matrix definition of a 4 port 2 twisted pair system .....		10
Figure 3 – Operational scattering parameters example from port 2 .....		11
Figure 4 – All 4 ports operational scattering parameter definition .....		11
Figure 5 – $S$ -Matrix definition showing corresponding $S$ parameters.....		11
Figure 6 – Equal $S$ parameters for real components .....		12
Figure 7 – Final operational scattering matrix for real components.....		12
Figure 8 – Definition of the operational reflection loss matrix with unitarity included (see C.3.6).....		13
Figure 9 – Transmission matrix concatenation showing an example of a 2 connector permanent link.....		13
Figure 10 – Graphical example of a $NEXT-L$ calculation showing statistical results (red) and final calculation (blue).....		14
Figure 11 – 100 m cable return loss without reflection at both ends .....		17
Figure 12 – 100 m cable return loss with a reflection of 0,03 at both ends (6 $\Omega$ mismatch, ~23 dB return loss at 1 MHz).....		17
Figure C.1 – Defining the operational attenuation and the operational transfer functions of a two-port .....		25
Figure C.2 – Defining the reflection transfer functions and the return loss of a junction.....		27
Table B.1 – Modelling assumptions for cable transmission parameters .....		20
Table B.2 – Modelling assumptions for connection transmission parameters.....		21
Table B.3 – Insertion loss .....		21
Table B.4 – NEXT .....		22
Table B.5 – ACR-F.....		22
Table B.6 – Return loss .....		22
Table C.1 – Comparison of naming in ISO/IEC 11081:2002 and this technical report .....		23

## INFORMATION TECHNOLOGY – GENERIC CABLING SYSTEMS FOR CUSTOMER PREMISES –

### Part 9903: Matrix modelling of channels and links

#### FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 11801-9903, which is a technical report, has been prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology – Generic cabling for customer premises*, can be found on the IEC web site.

This Technical Report has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

Withdrawn


## INTRODUCTION

The pass/fail limits for defined channel and permanent link cabling configurations have an implicit impact on the component limits for the cabling components used. The channel configurations are described in Clause 5, the link configurations in Clause 6 of ISO/IEC 11801:2002 with its amendments 1:2008 and 2:2010.

The permanent link configurations, which represent the fixed portion of the cabling, have two possible topologies:

A connection plus a segment of cable plus a connection (2 connector topology).

A connection plus a segment of cable plus a connection plus another segment of cable plus another connection (3 connector topology).



PP = patch panel; C = connection; CP = consolidation point;

TO = telecommunications outlet

**Figure 1 – Link configurations of ISO/IEC 11801:2002**

This Technical Report includes models and assumptions, which support pass/fail limits for the channel and permanent link test configurations in this standard. These are based on the performance requirements of cable and connecting hardware as specified in IEC standards.

This Technical Report provides reasonable assurance that a channel created by adding compliant patch cords to a previously certified permanent link will meet the applicable channel performance limits.

Over the years the frequencies of the classes increased, but the theory for calculating the limits stayed the same. Especially the higher order effects had to be considered and at the end only by doing a Monte Carlo calculation, assuming that not all components would be at the limit at the same time, allowed to prove compliance.

The model uses 2 pairs for all calculations. The limits are equal for pairs or pair combinations but in reality measured values could be different. If results are required that need more pairs to be considered, then this calculation can be done based on the results from multiple 2 pair calculations with appropriate inputs (worst case). An example of such a calculation is the power sum and average limit lines for 4 pairs.

Symmetry and additional contributions that result from unbalanced signals and differential-to-common and common-to-differential mode coupling are not included in this Technical Report but can be added easily in a next step by increasing the matrix size.

For details on the naming of transmission parameters, see definitions and Clause C.1.

Withdrawn

## INFORMATION TECHNOLOGY – GENERIC CABLING SYSTEMS FOR CUSTOMER PREMISES –

### Part 9903: Matrix modelling of channels and links

#### 1 Scope

This part of ISO/IEC 11801 establishes a matrix-model for formulating limits for differential mode parameters for return loss, insertion loss, and near and far end crosstalk, within and between two pairs of balanced cabling. This is for the purpose of supporting new, improved balanced cabling channel and link specifications, which are expected to be included in the next edition of ISO/IEC 11801<sup>1</sup>.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11801:2002, *Information technology – Generic cabling for customer premises*  
Amendment 1:2008  
Amendment 2:2010<sup>2</sup>

---

<sup>1</sup> A new edition of ISO/IEC 11801 is under consideration and is planned as ISO/IEC 11801-1 (first edition).  
<sup>2</sup> A consolidated version of this publication exists, comprising ISO/IEC 11801:2002, ISO/IEC 11801:2002/AMD 1:2008 and ISO/IEC 11801:2002/AMD 2:2010.