



INTERNATIONAL STANDARD



Lead-acid starter batteries – Part 2: Dimensions of batteries and dimensions and marking of terminals

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.220.20; 43.040.10

ISBN 978-2-8323-0000-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 General requirements	8
4.1 General.....	8
4.2 Marking.....	8
4.2.1 Safety labelling.....	8
4.2.2 Marking of the polarity of terminals	8
4.3 Recycling	9
4.3.1 Recycling of lead	9
4.3.2 Recycling of plastic material	9
4.4 Dimensions and design	9
4.5 Dimensions of tapered battery terminals	9
5 Recommended types used in Europe (EU).....	10
5.1 General.....	10
5.2 Main dimensions of batteries.....	10
5.3 Handles	14
5.3.1 General	14
5.3.2 Mounting of handles	14
5.4 Mounting of batteries	15
5.4.1 General	15
5.4.2 Dimensions and arrangement of ledges and notches	15
5.5 Terminals.....	16
5.5.1 Position of terminals	16
5.5.2 Dimensions of battery terminals.....	16
5.5.3 Marking of polarity	16
5.6 Special features of the battery lid.....	17
5.6.1 General	17
5.6.2 Semi bloc lid.....	17
5.6.3 Central degassing.....	17
5.6.4 Recessed holes	17
5.6.5 Removable cell plugs.....	18
5.6.6 Position of sensor openings.....	18
5.7 Handling of starter batteries by robot-equipment.....	19
5.8 Bulging and reinforcement of battery side walls	21
6 Other battery types used in Europe (EU)	22
6.1 General.....	22
6.2 Main dimensions of batteries.....	23
6.3 Handles	28
6.4 Mounting of batteries	28
6.4.1 General	28
6.4.2 Dimensions and arrangement of ledges and notches	28
6.5 Terminals.....	28
6.5.1 Position of terminals	28
6.5.2 Dimensions of battery terminals.....	28

6.5.3	Marking of polarity	28
6.6	Handling of starter batteries by robot-equipment	28
7	Recommended types used in North America (AM)	31
7.1	General.....	31
7.2	Terminals and terminal configuration	31
7.2.1	Tapered terminals.....	31
7.2.2	Side terminals.....	31
7.2.3	Terminal configuration	32
7.3	Standard fastening on the bottom	32
7.3.1	General	32
7.3.2	Design of ledges.....	32
7.3.3	Design of recesses	33
7.4	Main dimensions of the battery group sizes AM.....	37
8	Recommended types used in East Asia (AS)	42
8.1	General.....	42
8.2	Terminals and terminal configuration	42
8.2.1	Design of terminals.....	42
8.2.2	Dimensions and classification of terminals.....	42
8.2.3	Configuration of terminals.....	42
8.3	Main dimensions of the battery group sizes AS	42
Figure 1	– Marking of polarity	8
Figure 2	– Marking of polypropylene-polyethylene copolymer battery components	9
Figure 3	– Dimensions of positive (on the right) and negative (on the left) terminal	10
Figure 4	– Main dimensions of batteries of standard series LN and LBN – Top view	11
Figure 5	– Details of Figure 4.....	12
Figure 6	– Main dimensions of batteries of standard series LN – Front view	13
Figure 7	– Main dimensions of batteries of standard series LN – Side view	14
Figure 8	– Details of ledges of Figure 6 and Figure 7	16
Figure 9	– Detail X – Notch on ledge.....	16
Figure 10	– Degassing outlet	17
Figure 11	– Recessed holes "M" for optional terminal protection	18
Figure 12	– Removable cell plugs and sensor positions	19
Figure 13	– Grips for handling by robot equipment.....	20
Figure 14	– Section P-P of Figure 13 and Figure 22.....	20
Figure 15	– Detail U of Figure 13 and Figure 22.....	21
Figure 16	– Maximum allowed bulging on short sides.....	21
Figure 17	– Reinforcement by thicker walls on short sides	22
Figure 18	– Reinforcement by additional ribs on short sides.....	22
Figure 19	– Main dimensions of batteries of series L, LB, E, EB	26
Figure 20	– Main dimensions of batteries of series LS, LBS, ES, EBS	27
Figure 21	– Details of Figure 19 and Figure 20	27
Figure 22	– Grips for handling by robot equipment for LBN series.....	29
Figure 23	– Grips for handling by robot equipment for L and LS series	29
Figure 24	– Detail V of Figure 23	30

Figure 25 – Grips for handling by robot equipment for LB and LBS series – Option 1	30
Figure 26 – Grips for handling by robot equipment for LB and LBS series – Option 2	30
Figure 27 – Detail Y of Figure 25 and Figure 26	31
Figure 28 – Side terminal groove description	32
Figure 29 – Side terminal groove dimensions in mm and (in)	32
Figure 30 – Design for batteries with ledges on long sides for hold-down-devices in mm and (in)	33
Figure 31 – Design for batteries with recesses on long sides for hold-down-devices in mm and (in)	34
Figure 32 – Design for batteries with recesses on sides for hold-down-devices in mm and (in)	35
Figure 33 – Design for batteries with recesses on sides for hold-down-devices in mm and (in)	36
Figure 34 – Design for batteries with recesses on sides for hold-down-devices in mm and (in)	37
Figure 35 – Main dimensions of batteries of group sizes 24R, 26R, 34R, 35, 51R, 85	39
Figure 36 – Main dimensions of batteries of group size 24, 25, 26, 27, 34, 51, 86	39
Figure 37 – Main dimensions of batteries of group size 36R	40
Figure 38 – Main dimensions of batteries of group sizes 59, 65	40
Figure 39 – Main dimensions of batteries of group size 75, 78,100 with positive terminal on the right	41
Figure 40 – Main dimensions of batteries of group size 75, 78,100 with positive terminal on the left	41
Figure 41 – Main dimensions of battery group sizes AS	43
Table 1 – Main dimensions of batteries of standard series LN	11
Table 2 – Main dimensions of batteries of other series LBN	23
Table 3 – Main dimensions of other series L, LS, LB and LBS	24
Table 4 – Main dimensions of other series E, ES, EB and EBS	25
Table 5 – Battery group sizes AM	38
Table 6 – Dimensions and classification of terminals	42
Table 7 – Dimensions of group sizes AS	43

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LEAD-ACID STARTER BATTERIES –

Part 2: Dimensions of batteries and dimensions and marking of terminals

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60095-2 has been prepared by IEC technical committee 21: Secondary cells and batteries.

This fifth edition cancels and replaces the fourth edition published in 2009. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) update of the dimensions of batteries:
 - in Europe according to the last version of the European standard;
 - in USA with figures updated;
 - in Asia with one type of Japanese battery removed.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
21/1086/FDIS	21/1092/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60095 series, published under the general title *Lead-acid starter batteries*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

LEAD-ACID STARTER BATTERIES –

Part 2: Dimensions of batteries and dimensions and marking of terminals

1 Scope

This part of IEC 60095 is applicable to lead-acid batteries used for starting, lighting and ignition of passenger cars and light vehicles with a nominal voltage of 12 V.

All batteries in accordance with this document can be fastened to the vehicle either by means of the ledges around the container or by means of a hold-down device engaging with the lid.

This document specifies dimensions of battery for Europe, East Asia and North America.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482, *International Electrotechnical Vocabulary – Part 482: Primary and secondary cells and batteries*

IEC 60095-1:2018, *Lead-acid starter batteries – Part 1: General requirements and methods of test*

IEC 60417:2002, *Graphical symbols for use on equipment*

ISO/IEC 10646, *Information technology – Universal coded character set (UCS)*

ISO 1043-1, *Plastics – Symbols and abbreviated terms – Part 1: Basic polymers and their special characteristics*

ISO 11469, *Plastics – Generic identification and marking of plastics products*