

INTERNATIONAL STANDARD

IEC 60268-3

Third edition
2000-08

Sound system equipment –

Part 3: Amplifiers

Equipements pour systèmes électroacoustiques –

*Partie 3:
Amplificateurs*

© IEC 2000 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission
Telefax: +41 22 919 0300

3, rue de Varembé Geneva, Switzerland
e-mail: inmail@iec.ch

IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XA**

For price, see current catalogue

CONTENTS

	Page
FOREWORD	5
Clause	
1 Scope	7
2 Normative references	7
3 Conditions	8
3.1 Rated conditions and standard measuring conditions	8
3.1.1 Introduction	8
3.1.2 Rated conditions	8
3.1.3 Standard measuring conditions	9
3.2 Other conditions	9
4 Classes of operation	9
5 Interchangeable parts	10
6 Automatic controls	10
7 Power supply	10
8 Position of the volume controls	10
9 Pre-conditioning for measurements	10
10 Series of measurements	11
11 Variable consumption apparatus	11
12 Marking	11
13 Operating environment	12
14 Characteristics to be specified, and their methods of measurement	12
14.1 Power supply characteristics	12
14.1.1 Characteristics to be specified	12
14.1.2 Method of measurement	12
14.2 Tolerance of (long-term) power supply voltage variations	12
14.2.1 Characteristic to be specified	12
14.2.2 Methods of measurement	13
14.3 Tolerance of power supply frequency variations	14
14.3.1 Characteristics to be specified	14
14.3.2 Methods of measurement	14
14.4 Tolerance of power supply harmonics and ripple	14
14.4.1 Characteristics to be specified	14
14.4.2 Methods of measurement	15
14.5 Input characteristics	15
14.5.1 Rated source impedance, characteristic to be specified	15
14.5.2 Input impedance	15
14.5.3 Rated source e.m.f., characteristic to be specified	17
14.5.4 Minimum source e.m.f. for rated distortion-limited output voltage	17
14.6 Output characteristics	17
14.6.1 Rated load impedance, characteristic to be specified	17
14.6.2 Output source impedance	18
14.6.3 Output voltage and power (distortion-limited)	18

Clause	Page
14.6.4 Regulation	20
14.6.5 Overload restoring time.....	20
14.7 Limiting characteristics	20
14.7.1 Overload source e.m.f.....	20
14.7.2 Short-term maximum output voltage and power.....	21
14.7.3 Long-term maximum output voltage and power	22
14.7.4 Temperature-limited output power.....	23
14.8 Characteristics of protection circuits	23
14.8.1 Introduction.....	23
14.8.2 Protection against potentially damaging combinations of output voltage and current	24
14.8.3 Characteristics of d.c. offset protection circuits	25
14.9 Sustaining-time for rated (distortion-limited) output voltage or power	26
14.9.1 Introduction.....	26
14.9.2 Characteristic to be specified	27
14.9.3 Method of measurement.....	27
14.10 Gain.....	28
14.10.1 Voltage gain and e.m.f. gain	28
14.10.2 Maximum e.m.f. gain.....	28
14.10.3 Attenuation characteristic of the volume control	28
14.10.4 Attenuation characteristic of balance controls for multi-channel equipment.....	29
14.11 Response.....	29
14.11.1 Gain-frequency response.....	29
14.11.2 Gain-limited effective frequency range.....	30
14.11.3 Distortion-limited effective frequency range	30
14.11.4 Phase-frequency response	30
14.12 Amplitude non-linearity.....	31
14.12.1 Introduction	31
14.12.2 Rated total harmonic distortion	31
14.12.3 Total harmonic distortion under standard measuring conditions	31
14.12.4 Total harmonic distortion as a function of amplitude and frequency.....	32
14.12.5 Harmonic distortion of the <i>n</i> th order under standard measuring conditions	32
14.12.6 Harmonic distortion of the <i>n</i> th order as a function of amplitude and frequency.....	33
14.12.7 Modulation distortion of the <i>n</i> th order.....	34
14.12.8 Difference-frequency distortion of the <i>n</i> th order	35
14.12.9 Dynamic intermodulation distortion (DIM).....	37
14.12.10 Total difference frequency distortion	38
14.12.11 Weighted total harmonic distortion	40
14.13 Noise	40
14.13.1 Characteristic to be specified.....	40
14.13.2 Method of measurement	41
14.14 Hum	41
14.14.1 Introduction	41
14.14.2 Characteristics to be specified	41
14.14.3 Method of measurement	42

Clause	Page
14.15	42
14.15.1	42
14.15.2	43
14.15.3	44
14.16	45
14.16.1	45
14.16.2	45
14.17	46
14.17.1	46
14.17.2	47
14.18	47
Annex A (informative)	53
Bibliography	54
Figure 1 – Arrangements for measuring input impedance	48
Figure 2 – Oscillogram when measuring overload restoring time	49
Figure 3 – Protection against potentially damaging combinations of output voltage and current	50
Figure 4 – Arrangement for combining two input signals	51
Figure 5 – Frequency spectrum below 30 kHz of the signal for measuring dynamic intermodulation distortion	51
Figure 6 – Arrangement for measuring the balance of a balanced input	52
Figure 7 – Arrangement for measuring the internal impedance balance of a balanced output	52
Figure 8 – Arrangement for measuring the voltage symmetry of a balanced output	52
Table 1 – Different rated total harmonic distortion and rated distortion-limited output power specifications for the same amplifier	27
Table 2 – Distortion components due to dynamic intermodulation distortion falling in the frequency range up to 20 kHz	37

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SOUND SYSTEM EQUIPMENT –

Part 3: Amplifiers

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60268-3 has been prepared by subcommittee 100C: Audio, video and multimedia subsystems and equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This third edition cancels and replaces the second edition published in 1988, amendment 1 (1990) and amendment 2 (1991), and constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
100C/147/FDIS	100C/165/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

This part of IEC 60268 shall be used in conjunction with IEC 60268-1 (1985) and IEC 60268-2 (1987).

Annex A is for information only.

The committee has decided that the contents of this publication will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

Withdrawn

SOUND SYSTEM EQUIPMENT –

Part 3: Amplifiers

1 Scope

This part of IEC 60268 applies to analogue amplifiers, and the analogue parts of analogue/digital amplifiers, which form part of a sound system for professional or household applications. It specifies the characteristics which should be included in specifications of amplifiers and the corresponding methods of measurement.

NOTE The methods of measurement for digital amplifiers and similar equipment are given in IEC 61606. [6] ¹⁾

In general, the specified methods of measurement are those which are seen to be most directly related to the characteristics. This does not exclude the use of other methods which give equivalent results.

In general, the methods are based on the simplest measuring equipment which can provide useful results. This does not exclude the use of more complex equipment which can give higher accuracy and/or allow automatic measurement and recording of results.

Rated conditions and standard measuring conditions are specified in order to allow measurements to be reliably repeated.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 60268. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 60268 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60065:1998, *Audio, video and similar electronic apparatus – Safety requirements*

IEC 60268-1:1985, *Sound system equipment – Part 1: General*

IEC 60268-2:1987, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*
Amendment 1 (1991)

IEC 60417-1:1998, *Graphical symbols for use on equipment – Part 1: Overview and application*

IEC 61000-4-17:1999, *Electromagnetic Compatibility (EMC) – Part 4-17: Testing and measurement techniques – Ripple on d.c. input power port immunity test – Basic EMC Publication*

IEC 61000-4-29, *Electromagnetic Compatibility (EMC) – Part 4-29: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations on d.c. input power ports, immunity tests – Basic EMC Publication ²⁾*

¹⁾ Numbers in square brackets refer to the bibliography.

²⁾ To be published.

IEC 61938:1996, *Audio, video and audiovisual systems – Interconnections and matching values – Preferred matching values of analogue signals*

Withdrawn