

IEC 60317-12

Edition 4.1 2024-05 CONSOLIDATED VERSION

INTERNATIONAL STANDARD



Specifications for particular types of winding wires – Part 12: Polyvinyl acetal enamelled round copper wire, class 120

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.060.10

ISBN 978-2-8322-9004-0

Warning! Make sure that you obtained this publication from an authorized distributor.

REDLINE VERSION

- 2 - IEC 60317-12:2020+AMD1:2024 CSV © IEC 2024

CONTENTS

FOF	REWORD	.3
INT	RODUCTION	.5
1	Scope	.6
2	Normative references	.6
3	Terms, definitions, general notes and appearance	.6
3	3.1 Terms and definitions	.6
3	3.2 General notes	
	3.2.1 Methods of test	
	3.2.2 Winding wire	
	3.3 Appearance	
4	Dimensions	
5	Electrical resistance	
6 7	Elongation	
7	Springiness	
8	Flexibility and adherence	
9	Heat shock	
	0.1 Nominal conductor diameters up to and including 1,600 mm	
ء 10	0.2 Nominal conductor diameters over 1,600 mm Cut-through	
10	Gut-tillough	.0
11	Resistance to abrasion (nominal conductor diameters from 0.250 mm up to and	
11	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm)	.8
11 12		
	including 2,500 mm)	.9
12	including 2,500 mm) Resistance to solvents	.9 .9
12 13	including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation	.9 .9 .9
12 13 14	including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index	.9 .9 .9 .9
12 13 14 15	including 2,500 mm) Resistance to solvents. Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants.	.9 .9 .9 .9 .9
12 13 14 15 16	including 2,500 mm) Resistance to solvents. Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants. Solderability	.9 .9 .9 .9 .9 .9
12 13 14 15 16 17 18	including 2,500 mm) Resistance to solvents. Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants. Solderability Heat or solvent bonding.	.9 .9 .9 .9 .9 .9
12 13 14 15 16 17 18 19	including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor	.9 .9 .9 .9 .9 .9 10
12 13 14 15 16 17 18 19 20	including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil	.9 .9 .9 .9 .9 10 10
12 13 14 15 16 17 18 19 20 21	including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil Loss of mass	.9 .9 .9 .9 .9 10 10 10
12 13 14 15 16 17 18 19 20 21 23	including 2,500 mm)	.9 .9 .9 .9 .9 10 10 10
12 13 14 15 16 17 18 19 20 21 23 30	including 2,500 mm)	.9 .9 .9 .9 .9 10 10 10 10
12 13 14 15 16 17 18 19 20 21 23 30	including 2,500 mm)	.9 .9 .9 .9 .9 10 10 10 10
12 13 14 15 16 17 18 19 20 21 23 30 Bibl	including 2,500 mm)	.9 .9 .9 .9 10 10 10 10 10

REDLINE VERSION

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES -

Part 12: Polyvinyl acetal enamelled round copper wire, class 120

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60317-12 edition 4.1 contains the fourth edition (2020-06) [documents 55/1841/FDIS and 55/1854/RVD] and its amendment 1 (2024-05) [documents 55/1982/CDV and 55/2018/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

- 3 -

REDLINE VERSION

- 4 - IEC 60317-12:2020+AMD1:2024 CSV © IEC 2024

International Standard IEC 60317-12 has been prepared by IEC technical committee 55: Winding wires.

This fourth edition of IEC 60317-12 cancels and replaces the third edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) modification of the Scope;
- b) addition of reference to transformer oil resistance test method in Clause 20.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be used in conjunction with IEC 60317-0-1:2013 and its Amendment 1:2019.

A list of all parts in the IEC 60317 series, published under the general title *Specifications for particular types of winding wires*, can be found on the IEC website.

The numbering of clauses in this document is not continuous from Clauses 21 through 30 in order to reserve space for possible future wire requirements prior to those for wire packaging.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

REDLINE VERSION

INTRODUCTION

- 5 -

This Part of IEC 60317 forms an element of a series of standards which deals with insulated wires used for windings in electrical equipment. It is composed of the following series:

- 1) Winding wires Test methods (IEC 60851 series);
- 2) Specifications for particular types of winding wires (IEC 60317 series);
- 3) Packaging of winding wires (IEC 60264 series).

- 6 -

REDLINE VERSION

IEC 60317-12:2020+AMD1:2024 CSV © IEC 2024

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 12: Polyvinyl acetal enamelled round copper wire, class 120

1 Scope

This part of IEC 60317 specifies the requirements of enamelled round copper winding wires of class 120 with a sole coating based on polyvinyl acetal or polyvinyl formal resin, which can be modified provided it retains the chemical identity of the original resin and meets all specified wire requirements.

NOTE 1 A modified resin is a resin that has undergone a chemical change, or contains one or more additives to enhance certain performance or application characteristics.

NOTE 2 Polyvinyl acetal is a general name for a family of thermoplastic vinyl resins produced by the condensation of polyvinyl alcohol with an aldehyde. Examples are polyvinyl acetal, polyvinyl formal and polyvinyl butyral.

The range of nominal conductor diameters covered by this document is:

- Grade 1: 0,040 mm up to and including 2,500 mm;
- Grade 2: 0,040 mm up to and including 5,000 mm;
- Grade 3: 0,080 mm up to and including 5,000 mm.

The nominal conductor diameters are specified in Clause 4 of IEC 60317-0-1:2013.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60317-0-1:2013, Specifications for particular types of winding wires – Part 0-1: General requirements – Enamelled round copper wire IEC 60317-0-1:2013/AMD1:2019

FINAL VERSION

IEC 60317-12:2020+AMD1:2024 CSV © IEC 2024

CONTENTS

– 2 –

FOF	REWORD	3
INT	RODUCTION	5
1	Scope	6
2	Normative references	.6
3	Terms, definitions, general notes and appearance	6
3	3.1 Terms and definitions	6
3	3.2 General notes	6
	3.2.1 Methods of test	6
	3.2.2 Winding wire	7
3	3.3 Appearance	
4	Dimensions	
5	Electrical resistance	
6	Elongation	7
7	Springiness	.7
8	Flexibility and adherence	7
9	Heat shock	7
ç	0.1 Nominal conductor diameters up to and including 1,600 mm	7
ç	0.2 Nominal conductor diameters over 1,600 mm	8
10	Cut-through	. 8
11	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm)	
	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and	8
11	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents	8 9
11 12	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage	8 9 9
11 12 13	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation	8 9 9
11 12 13 14 15	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index	8 9 9 9
11 12 13 14 15 16	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants.	8 9 9 9 9
11 12 13 14 15 16 17	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents. Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants. Solderability	8 9 9 9 9 9
11 12 13 14 15 16 17 18	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants. Solderability Heat or solvent bonding.	8 9 9 9 9 9
 11 12 13 14 15 16 17 18 19 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents. Breakdown voltage Continuity of insulation . Temperature index Resistance to refrigerants. Solderability Heat or solvent bonding.	8 9 9 9 9 9 10
 11 12 13 14 15 16 17 18 19 20 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil	8 9 9 9 9 10 10
 11 12 13 14 15 16 17 18 19 20 21 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil Loss of mass	8 9 9 9 9 10 10 10
 11 12 13 14 15 16 17 18 19 20 21 23 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil Loss of mass Pin hole test	8 9 9 9 9 10 10 10
 11 12 13 14 15 16 17 18 19 20 21 23 30 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil Loss of mass Pin hole test Packaging	8 9 9 9 9 10 10 10 10
 11 12 13 14 15 16 17 18 19 20 21 23 30 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil Loss of mass Pin hole test	8 9 9 9 9 10 10 10 10
 11 12 13 14 15 16 17 18 19 20 21 23 30 Bibl 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents. Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding. Dielectric dissipation factor Resistance to transformer oil Loss of mass Pin hole test Packaging iography.	8 9 9 9 9 10 10 10 10 10
 11 12 13 14 15 16 17 18 19 20 21 23 30 Bibl Tab 	Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,500 mm) Resistance to solvents Breakdown voltage Continuity of insulation Temperature index Resistance to refrigerants Solderability Heat or solvent bonding Dielectric dissipation factor Resistance to transformer oil Loss of mass Pin hole test Packaging	8 9 9 9 10 10 10 10 10 10

FINAL VERSION

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES -

Part 12: Polyvinyl acetal enamelled round copper wire, class 120

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60317-12 edition 4.1 contains the fourth edition (2020-06) [documents 55/1841/FDIS and 55/1854/RVD] and its amendment 1 (2024-05) [documents 55/1982/CDV and 55/2018/RVC].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

- 3 -

FINAL VERSION

- 4 - IEC 60317-12:2020+AMD1:2024 CSV © IEC 2024

International Standard IEC 60317-12 has been prepared by IEC technical committee 55: Winding wires.

This fourth edition of IEC 60317-12 cancels and replaces the third edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) modification of the Scope;
- b) addition of reference to transformer oil resistance test method in Clause 20.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be used in conjunction with IEC 60317-0-1:2013 and its Amendment 1:2019.

A list of all parts in the IEC 60317 series, published under the general title *Specifications for particular types of winding wires*, can be found on the IEC website.

The numbering of clauses in this document is not continuous from Clauses 21 through 30 in order to reserve space for possible future wire requirements prior to those for wire packaging.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

FINAL VERSION

INTRODUCTION

- 5 -

This Part of IEC 60317 forms an element of a series of standards which deals with insulated wires used for windings in electrical equipment. It is composed of the following series:

- 1) Winding wires Test methods (IEC 60851 series);
- 2) Specifications for particular types of winding wires (IEC 60317 series);
- 3) Packaging of winding wires (IEC 60264 series).

- 6 -

FINAL VERSION

IEC 60317-12:2020+AMD1:2024 CSV © IEC 2024

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 12: Polyvinyl acetal enamelled round copper wire, class 120

1 Scope

This part of IEC 60317 specifies the requirements of enamelled round copper winding wires of class 120 with a sole coating based on polyvinyl acetal or polyvinyl formal resin, which can be modified provided it retains the chemical identity of the original resin and meets all specified wire requirements.

NOTE 1 A modified resin is a resin that has undergone a chemical change, or contains one or more additives to enhance certain performance or application characteristics.

NOTE 2 Polyvinyl acetal is a general name for a family of thermoplastic vinyl resins produced by the condensation of polyvinyl alcohol with an aldehyde. Examples are polyvinyl acetal, polyvinyl formal and polyvinyl butyral.

The range of nominal conductor diameters covered by this document is:

- Grade 1: 0,040 mm up to and including 2,500 mm;
- Grade 2: 0,040 mm up to and including 5,000 mm;
- Grade 3: 0,080 mm up to and including 5,000 mm.

The nominal conductor diameters are specified in Clause 4 of IEC 60317-0-1:2013.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60317-0-1:2013, Specifications for particular types of winding wires – Part 0-1: General requirements – Enamelled round copper wire IEC 60317-0-1:2013/AMD1:2019