



INTERNATIONAL STANDARD

QC 440000

**Thermistors – Directly heated positive temperature coefficient –
Part 1: Generic specification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.040.30

ISBN 978-2-88910-269-3

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
4 Units and symbols	16
5 Preferred values	17
5.1 Climatic categories	17
5.2 Marking	17
5.3 Spacings	18
6 Quality assessment procedures	18
6.1 General	18
6.2 Primary stage of manufacture.....	19
6.3 Subcontracting	19
6.4 Structurally similar components.....	19
6.5 Qualification approval procedures	20
6.6 Rework and repair	27
6.7 Release for delivery	27
6.8 Certified test records of released lots	28
6.9 Delayed delivery.....	28
6.10 Alternative test methods	28
6.11 Manufacture outside the geographical limits of IECQ NSIs	28
6.12 Unchecked parameters.....	28
7 Test and measurement procedures.....	28
7.1 General	28
7.2 Standard conditions for testing	29
7.3 Drying and recovery	29
7.4 Visual examination and check of dimensions.....	30
7.5 Zero-power resistance.....	30
7.6 Temperature coefficient of resistance	31
7.7 Insulation resistance (for insulated types only)	31
7.8 Voltage proof (for insulated types only)	32
7.9 Resistance/temperature characteristic.....	32
7.10 Dissipation factor at $U_{\max}(\delta)$	33
7.11 Response time by ambient temperature change (t_a).....	34
7.12 Response time by power change (t_p).....	34
7.13 Thermal time constant by ambient temperature change (τ_a).....	35
7.14 Thermal time constant by cooling (τ_c).....	35
7.15 Robustness of terminations	37
7.16 Solderability	38
7.17 Resistance to soldering heat	39
7.18 Rapid change of temperature	40
7.19 Vibration.....	40
7.20 Bump	40
7.21 Shock.....	41

7.22 Climatic sequence	41
7.23 Damp heat, steady state	42
7.24 Endurance	43
7.25 Tripping current and tripping time	47
7.26 Non-tripping current	47
7.27 Residual current	47
7.28 Surface temperature	48
7.29 Inrush current	49
7.30 Mounting (for surface mount thermistors only)	49
7.31 Shear (adhesion) test	50
7.32 Substrate bending test	51
Annex A (normative) Interpretation of sampling plans and procedures as described in IEC 60410 for use within the IEC quality assessment system for electronic components (IECQ)	52
Annex B (informative) Mounting for electrical measurements (except surface mount types)	53
Annex C (informative) Mounting for temperature measurements	56
Figure 1 – Typical resistance-temperature characteristic and definitions for PTC thermistors (at zero power)	10
Figure 2 – Typical R-TNF characteristic for PTC thermistors in sensor applications	11
Figure 3 – Typical current/voltage characteristic for PTC thermistors	11
Figure 4 – I_{in} against t at U_{dc}	14
Figure 5 – I_{in} against t at U_{rms}	15
Figure 6 – Dissipation factor test circuit	33
Figure 7 – Temperature gradient	34
Figure 8 – Circuit for measurement of thermal time constant by cooling	36
Figure 9 – Circuit for endurance at maximum operating temperature and maximum voltage	45
Figure 10 – Circuit for surface temperature measurement	48
Figure 11 – Measuring circuit	49
Figure B.1 – Example of a preferred mounting method for thermistors without wire terminations	53
Figure B.2 – Example of a preferred mounting method for thermistors with wire terminations	54
Figure B.3 – Example of a preferred mounting method for surface mount thermistors	55
Figure C.1 – Example of a preferred mounting method for temperature measurement on cylindrical heating elements	56
Table 1 – Creepage distances and clearances	18
Table 2 – Fixed sample size test schedule for qualification approval of thermistors for current limitation – Assessment level EZ	22
Table 3 – Fixed sample size test schedule for qualification approval of thermistors for use as heating elements – Assessment level EZ	23
Table 4 – Fixed sample size test schedule for qualification approval of thermistors for inrush current application – Assessment level EZ	24
Table 5 – Fixed sample size test schedule for qualification approval of thermistors for use as temperature sensing elements, Assessment level EZ	25

Table 6 – Quality conformance inspection for lot-by-lot inspection	26
Table 7 – Quality conformance inspection for periodic testing	27
Table 8 – Tensile force	37
Table 9 – Number of cycles per climatic category	42

INTERNATIONAL ELECTROTECHNICAL COMMISSION

THERMISTORS – DIRECTLY HEATED POSITIVE TEMPERATURE COEFFICIENT –

Part 1: Generic specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60738-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This consolidated version of IEC 60738-1 consists of the third edition (2006) [documents 40/1651/FDIS and 40/1730/RVD] and its amendment 1 (2009) [documents 40/1940/CDV and 40/1999/RVC].

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience.

It bears the edition number 3.1.

A vertical line in the margin shows where the base publication has been modified by amendment 1.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The QC number that appears on the front cover of this publication is the specification number in the IEC Quality Assessment System for Electronic Components (IECQ).

IEC 60738 consists of the following parts, under the general title *Thermistors – Directly heated positive step-function coefficient*:

Part 1: Generic specification

Part 1-1: Blank detail specification – Current limiting application – Assessment level EZ

Part 1-2: Blank detail specification – Heating element application – Assessment level EZ

Part 1-3: Blank detail specification – Inrush current application – Assessment level EZ

Part 1-4: Blank detail specification – Sensing application – Assessment level EZ

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

THERMISTORS – DIRECTLY HEATED POSITIVE TEMPERATURE COEFFICIENT –

Part 1: Generic specification

1 Scope

This part of IEC 60738 describes terms and methods of test for positive step-function temperature coefficient thermistors, insulated and non-insulated types typically made from ferro-electric semi-conductor materials.

It establishes standard terms, inspection procedures and methods of test for use in detail specifications for Qualification Approval and for Quality Assessment Systems for electronic components.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027 (all parts), *Letter symbols to be used in electrical technology*

IEC 60050 (all parts), *International Electrotechnical Vocabulary (IEV)*

IEC 60062, *Marking codes for resistors and capacitors*

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*
Amendment 1 (1992)

IEC 60068-2-1:1990, *Environmental testing – Part 2: Tests – Tests A: Cold*
Amendment 1 (1993)
Amendment 2 (1994)

IEC 60068-2-2:1974, *Environmental testing – Part 2: Tests – Tests B: Dry heat*
Amendment 1 (1993)

IEC 60068-2-6, *Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-11, *Environmental testing – Part 2: Tests – Test Ka: Salt mist*

IEC 60068-2-13, *Environmental testing – Part 2: Tests – Test M: Low air pressure*

IEC 60068-2-14:1984, *Environmental testing – Part 2: Tests – Test N: Change of temperature*
Amendment 1 (1986)

IEC 60068-2-20:1979, *Environmental testing – Part 2: Tests – Test T: Soldering*
Amendment 2 (1987)

IEC 60068-2-21, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-27, *Environmental testing – Part 2: Tests – Test Ea and guidance: Shock*

IEC 60068-2-29, *Environmental testing – Part 2: Tests – Test Eb and guidance: Bump*

IEC 60068-2-30:2005, *Environmental testing – Part 2: Tests – Test Db: Damp heat, cyclic (12 h + 12-hour cycle)*

IEC 60068-2-45:1980, *Environmental testing – Part 2: Tests – Test XA and guidance – Immersion in cleaning solvents*

IEC 60068-2-58, *Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60068-2-78, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60294, *Measurement of the dimensions of a cylindrical component having two axial terminations*

IEC 60410, *Sampling plans and procedures for inspection by attributes*

IEC 60617 (all parts) [DB]¹: *Graphical symbols for diagrams*

IEC 60717, *Method for determination of the space required by capacitors and resistors with unidirectional terminations*

IEC 61249-2-7, *Materials for printed boards and other interconnecting structures – Part 2-7: Reinforced base materials clad and unclad – Epoxide woven E-glass laminated sheet of defined flammability (vertical burning test), copper-clad*

IEC 61760-1, *Surface mounting technology – Part 1: Standard method for the specification of surface mounting components (SMDs)*

IEC QC 001002-3, *Rules of Procedure of the IEC Quality Assessment System for Electronic Components (IECQ) – Part 3: Approval procedures*

ISO 1000, *SI units and recommendations for the use of their multiples and of certain other units*

¹ “DB” refers to the IEC on-line database.