



INTERNATIONAL STANDARD



**Connectors for electrical and electronic equipment – Product requirements –
Part 3-104: Detail specification for 8-way, shielded free and fixed connectors for
data transmissions with frequencies up to 2 000 MHz**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.10

ISBN 978-2-8322-4362-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references	11
3 Technical information	13
3.1 Terms and definitions.....	13
3.2 Levels of compatibility.....	14
3.2.1 Interchangeability level	14
3.2.2 Intermateabilty.....	14
3.2.3 Interoperability.....	14
3.3 Groups of related connectors	14
3.4 Classification into climate categories	15
3.5 Clearance and creepage distances	15
3.6 Current carrying capacity	15
3.7 Marking.....	15
3.7.1 General	15
3.7.2 Performance marking.....	15
4 Dimensional information	15
4.1 General.....	15
4.2 Isometric views and common features.....	16
4.2.1 General	16
4.2.2 Fixed connector variant 01 (cable outlet)	17
4.2.3 Fixed connector variant 02, (printed circuit board outlet).....	20
4.2.4 Free connector variant 03 (4-pair plug)	21
4.2.5 Free connector variant 04 (2-pair plug).....	25
4.2.6 Free connector variant 05 (1-pair plug).....	27
4.3 Terminations	30
4.3.1 General	30
4.3.2 Referenced solderless termination types	30
4.3.3 Non-referenced termination types	31
4.3.4 Solder terminations.....	31
4.4 Mounting information	31
4.4.1 General	31
4.4.2 Mounting information for fixed connectors.....	31
4.4.3 Mounting information for free connectors	31
4.5 Gauges	31
4.5.1 Sizing gauges and retention force gauges; mechanical function, engaging/separating/insertion/withdrawal force.....	31
4.6 Mechanical function, engaging/separating/insertion/withdrawal force gauges.....	38
4.7 Test panels	38
5 Characteristics	39
5.1 General.....	39
5.2 Pin and pair grouping assignment	39
5.3 Climatic categories	39
5.4 Electrical characteristics	40
5.4.1 Creepage and clearance distances	40
5.4.2 Voltage proof.....	40

5.4.3	Current carrying capacity	40
5.4.4	Initial contact and shield resistance	41
5.4.5	Input to output resistance	41
5.4.6	Input to output resistance unbalance	41
5.4.7	Insulation resistance	42
5.5	Transmission characteristics	42
5.5.1	General	42
5.5.2	Insertion loss	42
5.5.3	Return loss	42
5.5.4	Propagation delay	43
5.5.5	Delay skew	43
5.5.6	NEXT loss	43
5.5.7	Power sum NEXT loss (for information only)	43
5.5.8	FEXT loss	44
5.5.9	Power sum FEXT loss (for information only)	44
5.5.10	Transverse conversion loss	45
5.5.11	Transverse conversion transfer loss	45
5.5.12	Power sum alien (exogenous) NEXT loss	46
5.5.13	Power sum alien (exogenous) FEXT loss	46
5.5.14	Coupling attenuation	47
5.5.15	Transfer impedance	47
5.6	Mechanical characteristics	47
6	Test schedule	48
6.1	General	48
6.2	Test procedures and measuring methods	48
6.3	Preconditioning	48
6.4	Wiring and mounting of specimens	48
6.4.1	Wiring	48
6.4.2	Mounting	48
6.4.3	Arrangement for contact resistance measurement and procedure	49
6.4.4	Arrangement for dynamic stress tests (test phase CP1)	49
6.5	Test schedules	50
6.5.1	General	50
6.5.2	Basic (minimum) test schedule	50
6.5.3	Full test schedule	50
Annex A (normative)	Gauging procedure	59
A.1	Fixed connectors	59
A.2	Free connectors	59
Annex B (normative)	Locking device mechanical operation – test procedure and requirements	60
B.1	Object	60
B.2	Preparation of the specimens	60
B.3	Test method	60
B.4	Final measurements	60
Annex C (normative)	Plug and outlet interoperability qualification	61
C.1	Object	61
C.2	Test equipment	61
C.3	Test procedure	62
Annex D (normative)	General requirements for the measurement set-up	63

D.1	Test instrumentation	63
D.2	Coaxial cables and test leads for network analysers	63
D.3	Measurement precautions	63
D.4	Balun requirements	64
D.5	Reference components for calibration	65
D.5.1	Reference loads for calibration	65
D.5.2	Reference cables for calibration	65
D.6	Termination loads for termination of conductor pairs	65
D.7	Termination of screens	66
D.8	Test specimen and reference planes	67
Annex E (normative)	Insertion loss	68
E.1	Object	68
E.2	Test method	68
E.3	Test set up	68
E.4	Procedure	68
E.4.1	Calibration	68
E.4.2	Measurement	68
E.5	Test report	69
E.6	Accuracy	69
Annex F (normative)	Return loss	70
F.1	Object	70
F.2	Test method	70
F.3	Test set-up	70
F.4	Procedure	70
F.4.1	Calibration	70
F.4.2	Measurement	70
F.5	Test report	70
F.6	Accuracy	70
Annex G (normative)	Near end cross talk (NEXT)	72
G.1	Object	72
G.2	Test method	72
G.3	Test set-up	72
G.4	Procedure	73
G.4.1	Calibration	73
G.4.2	Establishment of noise floor	73
G.4.3	Measurement	73
G.5	Test report	74
G.6	Accuracy	74
Annex H (normative)	Far end cross talk (FEXT)	75
H.1	Object	75
H.2	Test method	75
H.3	Test set-up	75
H.4	Procedure	76
H.4.1	Calibration	76
H.4.2	Establishment of noise floor	76
H.5	Measurement	76
H.6	Test report	77
H.7	Accuracy	77

Annex I (normative) Transverse Conversion Loss (<i>TCL</i>) and Transverse Conversion Transfer Loss (<i>TCTL</i>).....	78
I.1 Object.....	78
I.2 Test method.....	78
I.3 Test set-up	78
I.4 Procedure	79
I.4.1 Calibration.....	79
I.4.2 Noise floor	79
I.4.3 Measurement.....	80
I.5 Test report	80
I.6 Accuracy.....	80
Annex J (normative) Termination of balun	81
J.1 Termination of balun with low return loss for common mode.....	81
J.2 Centre tap connected to ground	81
J.3 Centre tap open	81
Bibliography.....	83
Figure 1 – Isometric view of cable and PCB fixed connectors.....	16
Figure 2 – Isometric view showing free connector for 4, 2 and 1 pair	16
Figure 3 – Variant 01 drawing 1	17
Figure 4 – Variant 01 drawing 2	19
Figure 5 – Variant 02 drawing	20
Figure 6 – Variant 03 drawing 1	21
Figure 7 – Variant 03 drawing 2	22
Figure 8 – Variant 03 drawing 3	24
Figure 9 – Variant 04 drawing 1	25
Figure 10 – Variant 04 drawing 2	26
Figure 11 – Variant 05 drawing 1	27
Figure 12 – Variant 05 drawing 2	28
Figure 13 – Variant 05 drawing 3	29
Figure 14 – Fixed connector location "Go" gauge.....	32
Figure 15 – Fixed connector location "No-Go" gauge	32
Figure 16 – Fixed connector size "Go" gauge.....	33
Figure 17 – Fixed connector size "No-Go" gauge	34
Figure 18 – Free connector location "Go" gauge	35
Figure 19 – Free connector location "No-Go" gauge.....	36
Figure 20 – Free connector size "Go" gauge	37
Figure 21 – Free connector size "No-Go" gauge	38
Figure 22 – Fixed connector panel	39
Figure 23 – Schematic diagram of fixed connector	39
Figure 24 – Connector de-rating curve	41
Figure 25 – Arrangement for contact resistance measurement	49
Figure 26 – Arrangement for dynamic stress	50
Figure C.1 – Precision test fixtures (covers).....	61
Figure D.1 – 180° hybrid used as a balun	64

Figure D.2 – Calibration of reference loads	65
Figure D.3 – Resistor load	66
Figure D.4 – Definition of reference planes	67
Figure E.1 – Calibration	68
Figure E.2 – Measuring set-up	69
Figure G.1 – NEXT measurement differential mode only terminations	72
Figure G.2 – NEXT measurement differential and common mode terminations.....	73
Figure H.1 – FEXT measurement differential mode only terminations.....	75
Figure H.2 – FEXT measurement differential and common mode terminations	76
Figure I.1 – <i>TCL</i> measurement.....	78
Figure I.2 – <i>TCTL</i> measurement.....	79
Figure J.1 – Balanced attenuator for balun centre tap grounded	81
Figure J.2 – Balanced attenuator for balun centre tap open	82
Table 1 – Variant 01 drawing 1 dimensions	18
Table 2 – Variant 01 drawing 2 dimensions	19
Table 3 – Variant 02 drawing dimensions	20
Table 4 – Variant 03 drawing 1 dimensions	22
Table 5 – Variant 03 drawing 2 dimensions	23
Table 6 – Variant 03 drawing 3 dimensions	24
Table 7 – Variant 04 drawing 1 dimensions	25
Table 8 – Variant 04 drawing 2 dimensions	26
Table 9 – Variant 05 drawing 1 dimensions	27
Table 10 – Variant 05 drawing 2 dimensions	28
Table 11 – Variant 05 drawing 3 dimensions	29
Table 12 – Climatic categories – Selected values	40
Table 13 – minimum creepage and clearance distances.....	40
Table 14 – Insertion loss.....	42
Table 15 – Return loss	43
Table 16 – NEXT loss	43
Table 17 – Power sum NEXT loss	44
Table 18 – FEXT loss	44
Table 19 – Power sum FEXT loss	45
Table 20 – Transverse conversion loss	45
Table 21 – Transverse conversion transfer loss	45
Table 22 – Power sum alien (exogenous) NEXT loss	46
Table 23 – Power sum alien (exogenous) FEXT loss.....	46
Table 24 – Coupling attenuation	47
Table 25 – Transfer impedance.....	47
Table 26 – Test group P	51
Table 27 – Test group AP	52
Table 28 – Test group BP	54
Table 29 – Test group CP	55

Table 30 – Test group DP	56
Table 31 – Test group EP	57
Table 32 – Test group FP	58
Table 33 – Test group GP	58
Table D.1 – Test balun performance characteristics.....	64
Table F.1 – Uncertainty band of return loss measurement at frequencies below 100 MHz	71

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 3-104: Detail specification for 8-way, shielded free and fixed connectors for data transmissions with frequencies up to 2 000 MHz

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61076-3-104 has been prepared by subcommittee 48B: Electrical connectors, of IEC technical committee 48: Electrical connectors and mechanical structures for electrical and electronic equipment.

This third edition of IEC 61076-3-104 cancels and replaces the second edition, published in 2006, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the title has been changed to incorporate transmissions with frequencies up to 2 000 MHz;
- b) the drawings of some styles have been corrected for clarification;
- c) Figures 23 and 24 have been updated;

- d) Figure 3 has been updated to include reference dimensions and dimensional format changes;
- e) the dimensions of Figure 7 have been updated;
- f) the type designation and ordering information has been removed for consistency with the most updated sectional specification;
- g) the test schedule was updated to include appropriate IEC 60512 Test Nos;
- h) the electrical performance requirements have been revised for 2 GHz level;
- i) interchangeability information has been added for performance categories.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
48B/2560/FDIS	48B/2565/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61076 series, published under the general title *Connectors for electronic equipment – Product requirements*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning connectors given in 4.2.2 and 4.2.4.

The IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he is willing to give free licences with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with the IEC.

Information may be obtained from:

The Siemon Company
Siemon Business Park
101 Siemon Company Drive
Watertown, CT 06795-0400
USA

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 3-104: Detail specification for 8-way, shielded free and fixed connectors for data transmissions with frequencies up to 2 000 MHz

1 Scope

This part of IEC 61076 establishes uniform specifications, type testing requirements for 8-way, shielded free and fixed connectors for data transmissions with frequencies up to 2 000 MHz, and used as category 7_A connectors in class F_A cabling systems specified in ISO/IEC 11801-1. It contains all test methods and sequences, severity and preferred values for dimensions and characteristics.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-581, *International Electrotechnical Vocabulary – Part 581: Electromechanical components for electronic equipment*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60169-15, *Radio-frequency connectors – Part 15: R.F. coaxial connectors with inner diameter of outer conductor 4.13 mm (0.163 in) with screw coupling – Character impedance 50 ohms (Type SMA)*

IEC 60352-2, *Solderless connections – Part 2: Crimped connections – General requirements, test methods and practical guidance*

IEC 60352-3, *Solderless connections – Part 3: Solderless accessible insulation displacement connections – General requirements, test methods and practical guidance*

IEC 60352-4, *Solderless connections – Part 4: Solderless non-accessible insulation displacement connections – General requirements, test methods and practical guidance*

IEC 60352-5, *Solderless connections – Part 5: Press-in connections – General requirements, test methods and practical guidance*

IEC 60352-6, *Solderless connections – Part 6: Insulation piercing connections – General requirements, test methods and practical guidance*

IEC 60352-7, *Solderless connections – Part 7: Spring clamp connections – General requirements, test methods and practical guidance*

IEC 60512-1-1, *Connectors for electronic equipment – Tests and measurements – Part 1-1: General examination – Test 1a: Visual examination*

IEC 60512-1-2, *Connectors for electronic equipment – Tests and measurements – Part 1-2: General examination – Test 1b: Examination of dimension and mass*

IEC 60512-2-1, *Connectors for electronic equipment – Tests and measurements – Part 2-1: Electrical continuity and contact resistance tests – Test 2a: Contact resistance – Millivolt level method*

IEC 60512-2-5, *Connectors for electronic equipment – Tests and measurements – Part 2-5: Electrical continuity and contact resistance tests – Test 2e: Contact disturbance*

IEC 60512-3-1, *Connectors for electronic equipment – Tests and measurements – Part 3-1: Insulation tests – Test 3a: Insulation resistance*

IEC 60512-4-1, *Connectors for electronic equipment – Tests and measurements – Part 4-1: Voltage stress tests – Test 4a: Voltage proof*

IEC 60512-6-4, *Connectors for electronic equipment – Tests and measurements – Part 6-4: Dynamic stress tests – Test 6d: Vibration (sinusoidal)*

IEC 60512-9-1, *Connectors for electronic equipment – Tests and measurements – Part 9-1: Endurance tests – Test 9a: Mechanical operation*

IEC 60512-9-2, *Connectors for electronic equipment – Tests and measurements – Part 9-2: Endurance tests – Test 9b: Electrical load and temperature*

IEC 60512-11-4, *Connectors for electronic equipment – Tests and measurements – Part 11-4: Climatic tests – Test 11d: Rapid change of temperature*

IEC 60512-11-7, *Connectors for electronic equipment – Tests and measurements – Part 11-7: Climatic tests – Test 11g: Flowing mixed gas corrosion test*

IEC 60512-13-2, *Connectors for electronic equipment – Tests and measurements – Part 13-2: Mechanical operation tests – Test 13b: Insertion and withdrawal forces*

IEC 60512-15-6, *Connectors for electronic equipment – Tests and measurements – Part 15-6: Connector tests (mechanical) – Test 15f: Effectiveness of connector coupling devices*

IEC 60512-26-100, *Connectors for electronic equipment – Tests and measurements – Part 26–100: measurement setup, test and reference arrangements and measurements for connectors according to IEC 60603-7 – Test 26a to 26g*

IEC 60512-28-100, *Connectors for electronic equipment – Tests and measurements – Part 28-100: Signal integrity tests up to 1 000 MHz on IEC 60603-7 and IEC 61076-3 series connectors – Test 28a to 28g*

IEC 61076-1:2006, *Connectors for electronic equipment – Product requirements – Part 1: Generic specification*

IEC 61076-3:2008, *Connectors for electronic equipment – Product requirements – Part 3: Rectangular connectors – Sectional specification*

IEC 61156 (all parts), *Multicore and symmetrical pair/quad cables for digital communications*

IEC 61156-2, *Multicore and symmetrical pair/quad cables for digital communications – Part 2: Symmetrical pair/quad cables with transmission characteristics up to 100 MHz – Horizontal floor wiring – Sectional specification*

IEC 61156-3, *Multicore and symmetrical pair/quad cables for digital communications – Part 3: Work area cable – Sectional specification*

IEC 61156-4, *Multicore and symmetrical pair/quad cables for digital communications – Part 4: Riser cables – Sectional specification*

IEC 61156-5, *Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification*

IEC 61156-6, *Multicore and symmetrical pair/quad cables for digital communications – Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification*

IEC 61156-7, *Multicore and symmetrical pair/quad cables for digital communications – Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analog communication cables*

IEC 61156-9, *Multicore and symmetrical pair/quad cables for digital communications – Part 9: Cables for channels with transmission characteristics up to 2 GHz – Sectional specification*

IEC 61156-10, *Multicore and symmetrical pair/quad cables for digital communications – Part 10: Cables for cords with transmission characteristics up to 2 GHz – Sectional specification*

IEC 62153-4-12, *Metallic communication cable test methods – Part 4-12: Electromagnetic compatibility (EMC) – Coupling attenuation or screening attenuation of connecting hardware – Absorbing clamp method*

ISO/IEC 11801-11, *Information technology – Generic cabling for customer premises – Part 1: General requirements*

ISO 1302, *Geometrical Product Specifications (GPS) – Indication of surface texture in technical product documentation*

Recommendation ITU-T K.44:2012, *Resistibility test for telecommunication equipment exposed to overvoltages and overcurrents – Basic recommendation*

EN 50289-1-14, *Communication cables – Specifications for test methods – Part 1-14: Electrical test methods – Coupling attenuation or screening attenuation of connecting hardware*

¹ To be published.