

This is a preview - click here to buy the full publication



IEC 61156-2

Edition 3.0 2010-04

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 2: Symmetrical pair/quad cables with transmission characteristics up to
100 MHz – Horizontal floor wiring – Sectional specification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

P

ICS 33.120.20

ISBN 978-2-88910-419-2

CONTENTS

FOREWORD	4
1 General	6
1.1 Scope and object	6
1.2 Normative references	6
1.3 Installation considerations	6
2 Definitions and requirements	7
2.1 Definitions	7
2.2 Materials and cable construction	7
2.2.1 General remarks	7
2.2.2 Cable construction	7
2.2.3 Conductor	7
2.2.4 Insulation	7
2.2.5 Colour code of insulation	7
2.2.6 Cable element	7
2.2.7 Screening of the cable element	8
2.2.8 Cable make-up	8
2.2.9 Screening of the cable core	8
2.2.10 Sheath	8
2.2.11 Colour of sheath	8
2.2.12 Identification	8
2.2.13 Finished cable	8
3 Characteristics and requirements	9
3.1 General remarks	9
3.2 Electrical characteristics	9
3.2.1 Conductor resistance	9
3.2.2 Resistance unbalance	9
3.2.3 Dielectric strength	9
3.2.4 Insulation resistance	9
3.2.5 Mutual capacitance	9
3.2.6 Capacitance unbalance	9
3.2.7 Transfer impedance	10
3.3 Transmission characteristics	10
3.3.1 Velocity of propagation (phase velocity)	10
3.3.2 Attenuation	11
3.3.3 Unbalance attenuation	11
3.3.4 Near-end crosstalk (<i>NEXT</i>)	11
3.3.5 Far-end crosstalk	11
3.3.6 Characteristic impedance	12
3.3.7 Structural return loss (<i>SRL</i>)	12
3.4 Mechanical and dimensional characteristics and requirements	13
3.4.1 Dimensional requirements	13
3.4.2 Elongation at break of the conductors	13
3.4.3 Elongation at break of the insulation	13
3.4.4 Elongation at break of the sheath	13
3.4.5 Tensile strength of the sheath	13
3.4.6 Crush test of the cable	13
3.4.7 Impact test of the cable	13

3.4.8	Bending under tension	13
3.4.9	Tensile performance of the cable	13
3.5	Environmental characteristics	13
3.5.1	Shrinkage of insulation.....	13
3.5.2	Wrapping test of insulation after thermal ageing	13
3.5.3	Bending test of insulation at low temperature	14
3.5.4	Elongation at break of the sheath after ageing.....	14
3.5.5	Tensile strength of the sheath after ageing.....	14
3.5.6	Sheath pressure test at high temperature	14
3.5.7	Cold bend test of the cable	14
3.5.8	Heat shock test.....	14
3.5.9	Flame propagation characteristics of a single cable.....	14
3.5.10	Flame propagation characteristics of bunched cables	14
3.5.11	Acid gas evolution.....	14
3.5.12	Smoke generation.....	14
3.5.13	Toxic gas emission	14
3.5.14	Combined flame and smoke test for cables in environmental air handling space	15
4	Introduction to the blank detail specification	15
	Bibliography	16
	Table 1 – Constants	11
	Table 2 – <i>NEXT</i> constants.....	11
	Table 3 – Input impedance values	12
	Table 4 – Function fitted impedance	12
	Table 5 – Structural return loss (dB min)	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 2: Symmetrical pair/quad cables with transmission characteristics up to 100 MHz – Horizontal floor wiring – Sectional specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-2 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This third edition cancels and replaces the second edition published in 2003 and constitutes a technical revision. This new edition includes category 3 and 5 cables.

This standard is to be read in conjunction with IEC 61156-1:2002.

The text of this standard is based on the following documents:

FDIS	Report on voting
46C/911/FDIS	46C/914/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 61156 series, under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 2: Symmetrical pair/quad cables with transmission characteristics up to 100 MHz – Horizontal floor wiring – Sectional specification

1 General

1.1 Scope and object

This sectional specification relates to IEC 61156-1:2002. The cables are specifically intended for horizontal floor wiring as defined in ISO/IEC 11801:1995.

This specification defines individually screened or unscreened pair/quad cables, with or without overall common screen for horizontal floor wiring. These cables are suitable for the various communication systems for which the reference is given in the relevant detail specification.

The cables covered by this sectional specification are intended to operate with voltages and currents normally adopted for communication systems. These cables should not be connected to low impedance sources, for example, the public mains electricity supply.

The normal operating temperature range is –40 °C to +60 °C.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1:2002¹⁾, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-2-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 2-1: Horizontal floor wiring – Blank detail specification*

¹⁾ A more recent version of this standard exists (2007), but as not all of the tests cited herein are addressed by the newer edition, it has been decided that the 2002 edition is to be used.