

This is a preview - click here to buy the full publication



IEC 61158-4-8

Edition 1.0 2007-12

INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –
Part 4-8: Data-link layer protocol specification – Type 8 elements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

XF

ICS 35.100.20; 25.040.40

ISBN 2-8318-9435-2

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
1.1 General.....	10
1.2 Specifications.....	10
1.3 Procedures.....	10
1.4 Applicability.....	10
1.5 Conformance.....	11
2 Normative references.....	11
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Reference model terms and definitions.....	11
3.2 Service convention terms and definitions.....	12
3.3 Common terms and definitions.....	13
3.4 Additional Type 8 definitions.....	14
3.5 Symbols and abbreviations.....	15
4 DL-protocol.....	18
4.1 Overview.....	18
4.2 DL-service Interface (DLI).....	18
4.3 Peripherals data link (PDL).....	22
4.4 Basic Link Layer (BLL).....	58
4.5 Medium Access Control (MAC).....	74
4.6 Peripherals network management for layer 2 (PNM2).....	108
4.7 Parameters and monitoring times of the DLL.....	116
Annex A (informative) – Implementation possibilities of definite PNM2 functions.....	122
A.1 Acquiring the current configuration.....	122
A.2 Comparing the acquired and stored configurations prior to a DL-subnetwork error.....	126
Bibliography.....	132
Figure 1 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses.....	13
Figure 2 – Data Link Layer Entity.....	18
Figure 3 – Location of the DLI in the DLL.....	18
Figure 4 – State transition diagram of DLI.....	20
Figure 5 – Location of the PDL in the DLL.....	22
Figure 6 – PDL connection between slave and master.....	23
Figure 7 – Interface between PDL-user (DLI) and PDL in the layer model.....	24
Figure 8 – Overview of the PDL services.....	24
Figure 9 – PDL_Data_Ack service between master and only one slave.....	26
Figure 10 – Parallel processing of PDL_Data_Ack services.....	26
Figure 11 – PSM and GSM service for buffer access.....	26
Figure 12 – Buffer_Received service to indicate successful data transfer.....	27
Figure 13 – Data flow between PDL-user, PDL and BLL of a PDL_Data_Ack service.....	30
Figure 14 – Interface between PDL and PNM2 in the layer model.....	30
Figure 15 – Reset, Set Value and Get Value PDL services.....	32

Figure 16 – Event PDL service.....	32
Figure 17 – Transmit and receive FCBs on the master and slave sides.....	35
Figure 18 – Data transmission master → slave with SWA Message	36
Figure 19 – Time sequence of the data transmission master → slave with SWA Message	36
Figure 20 – Data transmission slave → master with SWA/RWA Message.....	37
Figure 21 – Time sequence of the data transmission slave → master with SWA/RWA Message	37
Figure 22 – Allocation of actions of the PDL protocol machines and data cycles	38
Figure 23 – Message transmission: master → slave.....	39
Figure 24 – Message transmission: slave → master.....	39
Figure 25 – Code octet of a PDL PDU.....	40
Figure 26 – Structure of a message with a size of one word.....	41
Figure 27 – Structure of a SPA Message	41
Figure 28 – Structure of a SVA Message	42
Figure 29 – Structure of a FCB_SET Message.....	42
Figure 30 – Structure of a RWA Message	42
Figure 31 – Structure of a SWA Message	43
Figure 32 – Structure of a confirmation for SPA or SVA Messages.....	43
Figure 33 – Structure of a FCB_SET as confirmation	43
Figure 34 – Structure of the data octet for FCB_SET as requests and confirmations.....	43
Figure 35 – Structure of a message with a size of more than one word	44
Figure 36 – PDL base protocol machine.....	45
Figure 37 – Locations of the PDL and the PDL protocol machines in the master and slaves	48
Figure 38 – PDL protocol machine	49
Figure 39 – TRANSMIT protocol machine	52
Figure 40 – RECEIVE protocol machine.....	55
Figure 41 – Location of the BLL in the DLL	58
Figure 42 – Interface between PDL and BLL in the layer model	59
Figure 43 – BLL_Data service.....	60
Figure 44 – Interface between PNM2 and BLL in the layer model.....	62
Figure 45 – Reset, Set Value and Get Value BLL services	64
Figure 46 – Event BLL service	64
Figure 47 – BLL operating protocol machine of the master.....	68
Figure 48 – BLL-BAC protocol machine	70
Figure 49 – BLL operating protocol machine of the slave	73
Figure 50 – Location of the MAC in the DLL.....	74
Figure 51 – Model details of layers 1 and 2.....	75
Figure 52 – DLPDU cycle of a data sequence without errors.....	76
Figure 53 – DLPDU cycle of a data sequence with errors.....	76
Figure 54 – Data sequence DLPDU transmitted by the master	77
Figure 55 – Data sequence DLPDU received by the master	77
Figure 56 – Check sequence DLPDU	77

Figure 57 – Loopback word (LBW)	77
Figure 58 – Checksum status generated by the master	80
Figure 59 – Checksum status received by the master	80
Figure 60 – MAC protocol machine of a master: transmission of a message	81
Figure 61 – MAC protocol machine of a master: receipt of a message	84
Figure 62 – MAC sublayer of a master: data sequence identification.....	88
Figure 63 – Data sequence DLPDU received by a slave.....	91
Figure 64 – Data sequence DLPDU transmitted by a slave	91
Figure 65 – Checksum status received by the slave.....	91
Figure 66 – Checksum status generated by the slave	92
Figure 67 – State transitions of the MAC sublayer of a slave: data sequence.....	93
Figure 68 – State transitions of the MAC sublayer of a slave: check sequence	94
Figure 69 – Interface between MAC-user and MAC in the layer model	99
Figure 70 – Interactions at the MAC-user interface (master)	100
Figure 71 – Interactions at the MAC-user interface (slave).....	101
Figure 72 – Interface between MAC and PNM2 in the layer model	104
Figure 73 – Reset, Set Value and Get Value MAC services.....	106
Figure 74 – Event MAC service.....	106
Figure 75 – Location of the PNM2 in the DLL.....	108
Figure 76 – Interface between PNM2-user and PNM2 in the layer model	109
Figure 77 – Reset, Set Value, Get Value and Get Active Configuration services	111
Figure 78 – Event PNM2 service	111
Figure 79 – Set Active Configuration, Get Current Configuration service.....	111
Figure 80 – The active_configuration parameter	115
Figure 81 – Device code structure	118
Figure 82 – Relations between data width, process data channel and parameter channel	120
Figure 83 – Structure of the control code	121
Figure A.1 – DL-subnetwork configuration in the form of a tree structure	122
Figure A.2 – State machine for the acquisition of the current configuration	124
Figure A.3 – State machine for comparing two configurations	128
Figure A.4 – State machine for comparing one line of two configuration matrices.....	130
Table 1 – Primitives issued by DLS-/DLMS-user to DLI.....	19
Table 2 – Primitives issued by DLI to DLS-/DLMS-user	19
Table 3 – DLI state table – sender transactions	20
Table 4 – DLI state table – receiver transactions	21
Table 5 – Function GetOffset	22
Table 6 – Function GetLength.....	22
Table 7 – Function GetRemAdd	22
Table 8 – Function GetDisUserId	22
Table 9 – PDL_Data_Ack.....	27
Table 10 – PDL_Data_Ack L_status values.....	27

Table 11 – PSM	28
Table 12 – GSM.....	28
Table 13 – PDL_Reset.....	32
Table 14 – PDL_Set_Value.....	32
Table 15 – PDL variables.....	33
Table 16 – PDL_Get_Value.....	33
Table 17 – PDL_Event.....	34
Table 18 – Events.....	34
Table 19 – Encoding of the L_status	40
Table 20 – FCT code (PDL PDU-Types)	40
Table 21 – State transitions of the PDL base protocol machine.....	46
Table 22 – Counters of the PDL protocol machines.....	48
Table 23 – Meaning of the "connection" flag	49
Table 24 – State transitions of the PDL protocol machine	50
Table 25 – State transitions of the TRANSMIT protocol machine	53
Table 26 – State transitions of the RECEIVE protocol machine	55
Table 27 – BLL_Data	61
Table 28 – BLL_Data	64
Table 29 – BLL_Reset	65
Table 30 – BLL_Set_Value	65
Table 31 – BLL variables	66
Table 32 – BLL_Get_Value	66
Table 33 – BLL_Event.....	66
Table 34 – BLL_Event.....	67
Table 35 – State transitions of the BLL operating protocol machine of the master.....	69
Table 36 – State transitions of the BLL-BAC protocol machine.....	71
Table 37 – State transitions of the BLL operating protocol machine of the slave	73
Table 38 – FCS length and polynomial.....	78
Table 39 – MAC_Reset.....	106
Table 40 – MAC_Set_Value	106
Table 41 – MAC variables.....	107
Table 42 – MAC_Get_Value.....	107
Table 43 – MAC_Event	107
Table 44 – MAC_Event	108
Table 45 – PNM2_Reset.....	112
Table 46 – M_status values of the PNM2_Reset	112
Table 47 – PNM2_Set_Value	112
Table 48 – M_status values of the PNM2_Set_Value	113
Table 49 – PNM2_Get_Value.....	113
Table 50 – M_status values of the PNM2_Get_Value.....	113
Table 51 – PNM2_Event	114
Table 52 – MAC Events	114
Table 53 – PNM2_Get_Current_Configuration	114

Table 54 – PNM2_Get_Active_Configuration	115
Table 55 – PNM2_Set_Active_Configuration.....	116
Table 56 – Data direction.....	118
Table 57 – Number of the occupied octets in the parameter channel.....	119
Table 58 – Device class.....	119
Table 59 – Control data	119
Table 60 – Data width	120
Table 61 – Medium control.....	121
Table A.1 – DL-subnetwork configuration in the form of a matrix.....	123
Table A.2 – Acquire_Configuration.....	123
Table A.3 – State transitions of the state machine for the acquisition of the current configuration	125
Table A.4 – Check_Configuration.....	126
Table A.5 – Compare_Slave	127
Table A.6 – State transitions of the state machine for comparing two configurations.....	129
Table A.7 – State transitions of the state machine for comparing one line of two configuration matrixes	131

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-8: Data-link layer protocol specification – Type 8 elements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

IEC draws attention to the fact that it is claimed that compliance with this standard may involve the use of patents as follows, where the [xx] notation indicates the holder of the patent right:

Type 8 and possibly other Types:

DE 41 00 629 C1 [PxC] Steuer- und Datenübertragungsanlage

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights are registered with IEC. Information may be obtained from:

[PxC]: Phoenix Contact GmbH & Co. KG
Referat Patente / Patent Department
Postfach 1341
D-32819 Blomberg
Germany

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61158-4-8 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-4 subseries cancel and replace IEC 61158-4:2003. This edition of this part constitutes an editorial revision.

This edition of IEC 61158-4 includes the following significant changes from the previous edition:

- a) deletion of the former Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data link layer, for lack of market relevance;
- b) addition of new types of fieldbuses;
- c) division of this part into multiple parts numbered -4-1, -4-2, ..., -4-19.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/474/FDIS	65C/485/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-8: Data-link layer protocol specification – Type 8 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides a highly-optimized means of interchanging fixed-length input/output data and variable-length segmented messages between a single master device and a set of slave devices interconnected in a loop (ring) topology. The exchange of input/output data is totally synchronous by configuration, and is unaffected by the messaging traffic.

Devices are addressed implicitly by their position on the loop. The determination of the number, identity and characteristics of each device can be configured, or can be detected automatically at start-up.

1.2 Specifications

This standard specifies

- a) procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed data-link service provider;
- b) the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-2 (Ed.4.0), *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-8, *Digital data communications for measurement and control – Fieldbus for use in industrial control systems – Part 3-8: Data link service definition – Type 8 elements*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*