

This is a preview - click here to buy the full publication



IEC 61169-52

Edition 1.0 2015-06

INTERNATIONAL STANDARD



Radio-frequency connectors – Part 52: Sectional specification for series MMCX RF coaxial connectors

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.30

ISBN 978-2-8322-2735-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	6
3 Mating face and gauge information.....	6
3.1 Dimensions – General connectors – Grade 2	6
3.1.1 Connector with pin centre contact.....	6
3.1.2 Connector with socket centre contact	7
3.2 Gauges.....	8
3.2.1 Gauge pin for socket centre contact	8
3.2.2 Gauge for outer contact.....	9
3.3 Dimensions – Standard test connectors – Grade 0	11
3.3.1 Connector with pin centre contact.....	11
3.3.2 Connector with socket centre contact	12
4 Quality assessment procedure	13
4.1 General.....	13
4.2 Rating and characteristics (see Clause 5 of IEC 61169-1:2013).....	13
4.3 Test schedule and inspection requirements.....	15
4.3.1 Acceptance tests.....	15
4.3.2 Periodic tests.....	16
4.4 Procedures for the qualification approval	18
4.4.1 Quality conformance inspection.....	18
4.4.2 Qualification approval and its maintenance	18
5 Instructions for preparation of detail specifications (DS)	18
5.1 General.....	18
5.2 Identification of the component.....	18
5.3 Performances.....	19
5.4 Marking, ordering information and related matters.....	19
5.5 Selection of tests, test conditions and severities	19
5.6 Blank detail specification pro-forma for type MMCX connector.....	20
6 Marking	24
6.1 Marking of component.....	24
6.2 Marking and contents of package	24
Figure 1 – Connector with pin centre contact.....	7
Figure 2 – Connector with socket centre contact.....	8
Figure 3 – Gauge pin for socket centre contact.....	9
Figure 4 – Gauge for outer contact.....	10
Figure 5 – Connector with pin centre contact.....	11
Figure 6 – Connector with socket centre contact.....	12
Table 1 – Dimensions of connector with pin centre contact	7
Table 2 – Dimensions of connector with socket centre contact	8
Table 3 – Dimensions of gauge pin for socket centre contact	9
Table 4 – Dimensions of gauge for outer contact	10
Table 5 – Dimensions of connector with pin centre contact	11

Table 6 – Dimensions of connector with socket centre contact	12
Table 7 – Preferred climatic categories (see IEC 60068-1).....	13
Table 8 – Rating and characteristics.....	13
Table 9 – Acceptance tests	16
Table 10 – Periodic tests	16

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RADIO-FREQUENCY CONNECTORS –

Part 52: Sectional specification for series MMCX RF coaxial connectors

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61169-52 has been prepared by subcommittee 46F: R.F. and microwave passive components, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories

The text of this standard is based on the following documents:

FDIS	Report on voting
46F/314/FDIS	46F/320/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61169 series, under the general title: *Radio-frequency connectors*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

RADIO-FREQUENCY CONNECTORS –

Part 52: Sectional specification for series MMCX RF coaxial connectors

1 Scope

This part of IEC 61169, which is a sectional specification (SS), provides information and rules for the preparation of detail specifications (DS) for RF coaxial connectors with snap-on coupling, typically for use in 50 Ω cable networks (MMCX).

It prescribes mating face dimensions for general purpose connectors – grade 2, dimensional details of standard test connectors-grade 0, gauging information and tests selected from IEC 61169-1, applicable to all detail specifications relating to series MMCX RF connectors.

This specification indicates recommended performance characteristics to be considered when writing a detail specification and it covers test schedules and inspection requirements for assessment levels M and H.

The MMCX miniature snap-on coupling structure series R.F. coaxial connector with the characteristic of normative impedance 50 Ω are used with various kinds of R.F cables and strips. The operating frequency limit is up to 6 GHz.

NOTE Metric dimension are original dimensions. All undimensioned pictorial configurations are for reference purpose only.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61169-1:2013, *Radio frequency connectors – Part 1: Generic specification – General requirements and measuring methods*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 62037 (all parts), *Passive RF and microwave devices, intermodulation level measurement*