

This is a preview - click here to buy the full publication



IEC TR 61282-12

Edition 1.0 2016-02

# TECHNICAL REPORT

---

**Fibre optic communication system design guides –  
Part 12: In-band optical signal-to-noise ratio (OSNR)**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.180.01

ISBN 978-2-8322-3171-5

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions .....	6
4 Background .....	8
4.1 General.....	8
4.2 Higher spectral density of signals .....	9
4.3 Spectral filtering in wavelength-routing elements.....	10
4.4 Transmission of signals with multiple subcarriers .....	11
5 In-band OSNR measurement with spectrally shaped noise.....	12
5.1 Measurement of in-band ASE noise .....	12
5.2 In-band OSNR definitions .....	13
5.2.1 Background .....	13
5.2.2 Spectrally integrated in-band OSNR .....	13
5.2.3 In-band OSNR from averaged noise power spectral density .....	14
5.2.4 In-band OSNR from maximal noise power spectral density.....	14
5.2.5 In-band OSNR for individual optical subcarriers .....	15
5.3 Spectral shaping of ASE noise.....	15
5.3.1 General .....	15
5.3.2 Case (a): ASE noise shaped outside of the signal spectrum .....	15
5.3.3 Case (b): ASE noise shaped within the signal spectrum .....	16
5.3.4 Case (c): ASE noise shaping in a ROADM network .....	17
6 Guidelines for using the definitions .....	19
6.1 General.....	19
6.2 Wavelength integration range .....	20
6.3 Spectral resolution .....	22
7 In-band OSNR penalties of filtered signals .....	25
7.1 Scope of simulations .....	25
7.2 Results for 43 Gbit/s RZ-DQPSK .....	26
7.3 Results for 128 Gbit/s PM NRZ-QPSK .....	31
7.4 Results for 10 Gbit/s NRZ-OOK .....	31
7.5 Observations.....	31
Bibliography .....	33
Figure 1 – Optical power spectrum composed of a modulated signal and ASE noise.....	9
Figure 2 – Optical power spectrum of 50-GHz spaced 40 Gbit/s RZ-DQPSK signals with significant spectral overlap.....	10
Figure 3 – Optical power spectrum of 50-GHz spaced 10 Gbit/s NRZ-OOK signals after spectral filtering in ROADMs .....	11
Figure 4 – Optical power spectrum of a 400 Gbit/s optical "superchannel" comprised of four very densely spaced 100 Gbit/s PM-QPSK signals.....	11
Figure 5 – Power spectral density of a 10 Gbit/s signal with ASE noise that has been shaped by a relatively broad optical filter.....	16
Figure 6 – Power spectral densities of a broadband 40 Gbit/s signal and ASE noise which have been shaped by the same filter .....	17

Figure 7 – Variation of the in-band OSNR values $R_{\text{int}}$ , $R_{\text{avg}}$ and $R_{\text{max}}$ versus filter bandwidth for the signal shown in Figure 6 .....	17
Figure 8 – Optical power density spectra of signal and ASE noise after filtering in a ROADM network with intermediate amplification .....	18
Figure 9 – Variation of the in-band OSNR values $R_{\text{int}}$ , $R_{\text{avg}}$ and $R_{\text{max}}$ versus number of filters for the signal shown in Figure 8 .....	19
Figure 10 – Impact of integration range on $R_{\text{int}}$ for 43 Gbit/s RZ-DPSK signals in a ROADM network .....	21
Figure 11 – Impact of instrument noise on $s(\nu)/\rho(\nu)$ for strongly filtered 10 Gbit/s NRZ-OOK signals .....	21
Figure 12 – Dependence of in-band OSNR on spectral resolution for 43 Gbit/s RZ-DQPSK signals .....	23
Figure 13 – Dependence of in-band OSNR on spectral resolution for 10 Gbit/s NRZ-OOK signals .....	24
Figure 14 – ROADM filter arrangements for OSNR penalty simulations .....	26
Figure 15 – In-band OSNR penalties for filtered 43 Gbit/s RZ-DQPSK signals .....	28
Figure 16 – In-band OSNR penalties for filtered 128 Gbit/s PM NRZ-QPSK signals .....	29
Figure 17 – In-band OSNR penalties for filtered 10 Gbit/s NRZ-OOK signals .....	30

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

#### Part 12: In-band optical signal-to-noise ratio (OSNR)

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 61282-12, which is a technical report, has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86C/1341/DTR	86C/1364/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61282 series, published under the general title *Fibre optic communication system design guides*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

### Part 12: In-band optical signal-to-noise ratio (OSNR)

#### 1 Scope

The purpose of this part of IEC 61282, which is a Technical Report, is to provide a definition for in-band optical signal-to-noise ratio (OSNR) that is applicable to situations where the spectral noise power density is not independent of the optical frequency, as assumed in the OSNR definition of IEC 61280-2-9, but is significantly shaped across the optical bandwidth of the signal. Considering the development of multiple measurement methods for different use cases, as detailed below, it is desirable to establish a definition of in-band OSNR that is independent of the method used and, furthermore, is consistent with the OSNR definition of IEC 61280-2-9 in the case of frequency-independent noise power density.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61280-2-9:2009, *Fibre optic communication subsystem test procedures – Part 2-9: Digital systems – Optical signal-to-noise ratio measurement for dense wavelength-division multiplexed systems*