

TECHNICAL REPORT

IEC TR 61282-3

Second edition
2006-10

Fibre optic communication system design guides – Part 3: Calculation of link polarization mode dispersion

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

V

For price, see current catalogue

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Basic design models for total system <i>PMD</i> performance.....	6
2.1 Notation.....	6
2.2 Calculation of system <i>PMD</i>	7
3 Calculation of cabled fibre <i>PMD</i>	9
3.1 General.....	9
3.2 Method 1: Calculating PMD_Q , the <i>PMD</i> link design value.....	11
3.3 Method 2: Calculating the probability of exceeding DGD_{max}	14
3.4 Equivalence of methods.....	18
4 Calculation of optical component <i>PMD</i>	20
5 Summary of acronyms and symbols.....	20
Annex A (informative) <i>PMD</i> concatenation fundamentals.....	22
Annex B (informative) Combining Maxwell extrema from two populations.....	26
Annex C (informative) Worked example.....	30
Annex D (informative) Relationship of probability to system performance.....	31
Annex E (informative) Concatenation experiment.....	32
Bibliography.....	34
Figure 1 – Various passing distributions.....	15
Figure 2 – Worst case approach assumption.....	17
Figure 3 – Convolution of two Diracs.....	17
Figure 4 – Equivalence envelopes for method 1/2 defaults.....	19
Figure A.1 – Sum of randomly rotated elements.....	25
Figure A.2 – Sum of randomly rotated elements.....	25
Table 1 – Probability based on wavelength average.....	9
Table 2 – Acronyms and definitions.....	21
Table 3 – Symbols and clause of definition.....	21
Table E.1 – Concatenation math verification.....	33

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

Part 3: Calculation of link polarization mode dispersion

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 61282-3, which is a technical report, has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

This second edition cancels and replaces the first edition published in 2002. It is a technical revision that includes the following significant changes:

- a) the title has been changed to better reflect its applicability to links;
- b) Equations (1) and (2) were simplified in order to align with agreements in the ITU-T.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86C/701/DTR	86C/720/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61282 series, published under the general title *Fibre optic communication system design guides*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Polarization mode dispersion (*PMD*) is usually described in terms of a differential group delay (*DGD*), which is the time difference between the principal states of polarization of an optical signal at a particular wavelength and time. *PMD* in cabled fibres and optical components causes an optical pulse to spread in the time domain, which may impair the performance of a fibre optic telecommunication system, as defined in IEC 61281-1.

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

Part 3: Calculation of link polarization mode dispersion

1 Scope

This part of IEC 61282 provides guidelines for the calculation of polarization mode dispersion (*PMD*) in fibre optic systems to accommodate the statistical variation of *PMD* and differential group delay (*DGD*) in optical fibre cables and components.

This technical report describes methods for calculating *PMD* due to optical fibre cables and optical components in an optical link. The calculations are compatible with those documented in the outdoor optical fibre cable specification IEC 60794-3. Example calculations are given to illustrate the methods for calculating total optical link *PMD* from typical cable and optical component data. The calculations include the statistics of concatenating individual optical fibre cables drawn from a specified distribution. The calculations assume that all components have *PMD* equal to the maximum specified value.

The calculations described cover first order *PMD* only. The following subject areas are currently beyond the scope of this technical report, but remain under study:

- calculation of second and higher order *PMD*;
- accommodation of components with polarization dependent loss (PDL) – if it is assumed that PDL is negligible in optical fibre cables;
- system impairments (power penalty) due to *PMD*;
- interaction with chromatic dispersion and other nonlinear effects.

Measurement of *PMD* is beyond the scope of this technical report. Methods of measurement of *PMD* of optical fibre and cable are given in IEC 60793-1-48. The measurement of optical amplifier *PMD* is in IEC 61290-11-1. The measurement of component *PMD* is in IEC 61300-3-32. Measurement of link *PMD* is given in 61280-4-4. A general theory and guidance on measurements is given in 61282-9.