

This is a preview - click here to buy the full publication



IEC TR 62048

Edition 3.0 2014-01

TECHNICAL REPORT



**Optical fibres –
Reliability – Power law theory**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XB**

ICS 33.180.10

ISBN 978-2-8322-1369-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Symbols	8
4 General approach.....	10
5 Formula types.....	10
6 Measuring parameters for fibre reliability.....	11
6.1 Overview.....	11
6.2 Length and equivalent length	11
6.3 Reliability parameters	12
6.3.1 Overview	12
6.3.2 Proof-testing.....	12
6.3.3 Static fatigue	12
6.3.4 Dynamic fatigue.....	13
6.4 Parameters for the low-strength region	13
6.4.1 Overview	13
6.4.2 Variable proof test stress	13
6.4.3 Dynamic fatigue.....	14
6.5 Measured numerical values.....	17
7 Examples of numerical calculations	17
7.1 Overview.....	17
7.2 Failure rate calculations	18
7.2.1 FIT rate formulae.....	18
7.2.2 Long lengths in tension.....	18
7.2.3 Short lengths in uniform bending	20
7.3 Lifetime calculations	22
7.3.1 Lifetime formulae.....	22
7.3.2 Long lengths in tension.....	22
7.3.3 Short lengths in uniform bending	23
7.3.4 Short lengths with uniform bending and tension.....	25
8 Fibre weakening and failure.....	26
8.1 Crack growth and weakening	26
8.2 Crack fracture	28
8.3 Features of the general results	29
8.4 Stress and strain.....	30
9 Fatigue testing.....	30
9.1 Overview.....	30
9.2 Static fatigue.....	30
9.3 Dynamic fatigue	32
9.3.1 Overview	32
9.3.2 Fatigue to breakage.....	32
9.3.3 Fatigue to a maximum stress	34
9.4 Comparisons of static and dynamic fatigue	34
9.4.1 Intercepts and parameters obtained.....	34
9.4.2 Time duration	34

9.4.3	Dynamic and inert strengths	35
9.4.4	Plot non-linearities	36
9.4.5	Environments	36
10	Proof-testing	37
10.1	Overview	37
10.2	The proof test cycle	37
10.3	Crack weakening during proof-testing	38
10.4	Minimum strength after proof-testing	39
10.4.1	Overview	39
10.4.2	Fast unloading	39
10.4.3	Slow unloading	40
10.4.4	Boundary condition	41
10.5	Varying the proof test stress	41
11	Statistical description of strength by Weibull probability models	41
11.1	Overview	41
11.2	Strength statistics in uniform tension	41
11.2.1	Unimodal probability distribution	41
11.2.2	Bimodal probability distribution	43
11.3	Strength statistics in other geometries	43
11.3.1	Stress non-uniformity	43
11.3.2	Uniform bending	44
11.3.3	Two-point bending	45
11.4	Weibull analysis for static fatigue before proof-testing	45
11.5	Weibull analysis for dynamic fatigue before proof-testing	47
11.6	Weibull distribution after proof-testing	49
11.7	Weibull analysis for static fatigue after proof-testing	51
11.8	Weibull analysis for dynamic fatigue after proof-testing	53
12	Reliability prediction	54
12.1	Reliability under general stress and constant stress	54
12.2	Lifetime and failure rate from fatigue testing	55
12.3	Certain survivability after proof-testing	56
12.4	Failures in time	57
13	<i>B</i> -value: elimination from formulae, and measurements	58
13.1	Overview	58
13.2	Approximate Weibull distribution after proof-testing	58
13.2.1	Overview	58
13.2.2	"Risky region" during proof-testing	58
13.2.3	Other approximations	59
13.3	Approximate lifetime and failure rate	61
13.4	Estimation of the <i>B</i> -value	62
13.4.1	Overview	62
13.4.2	Fatigue intercepts	62
13.4.3	Dynamic fatigue failure stress	62
13.4.4	Obtaining the strength	62
13.4.5	Stress pulse measurement	63
13.4.6	Flaw growth measurement	63

Annex A (informative) Statistical strength degradation map.....	64
Bibliography.....	65
Figure 1 – Weibull dynamic fatigue plot near the proof test stress level.....	16
Figure 2 – Instantaneous FIT rates of 1 km fibre versus time for applied stress/proof test stress percentages (bottom to top): 10 %, 15 %, 20 %, 25 %, 30 %.....	19
Figure 3 – Averaged FIT rates of 1 km fibre versus time for applied stress/proof test stress percentages (bottom to top): 10 %, 15 %, 20 %, 25 %, 30 %	19
Figure 4 – Instantaneous FIT rates of bent fibre with 1 m effective length versus time	21
Figure 5 – Averaged FIT rates of bent fibre with 1 m effective length versus time for bend diameters (top to bottom): 10 mm, 20 mm, 30 mm, 40 mm, 50 mm.....	21
Figure 6 – 1 km lifetime versus failure probability for applied stress/proof test stress percentages (top to bottom): 10 %, 15 %, 20 %, 25 %, 30 %.....	23
Figure 7 – Lifetimes of bent fibre with 1 m effective length versus failure probability for bend diameters (bottom-right to top-left): 10 mm, 20 mm, 30 mm, 40 mm, 50 mm.....	24
Figure 8 – Static fatigue – Applied stress versus time for a particular applied stress	31
Figure 9 – Static fatigue – Schematic data of failure time versus applied stress	32
Figure 10 – Dynamic fatigue – Applied stress versus time for a particular applied stress rate	32
Figure 11 – Dynamic fatigue – Schematic data of failure time versus applied stress rate	34
Figure 12 – Proof-testing – Applied stress versus time.....	38
Figure 13 – Static fatigue schematic Weibull plot	47
Figure 14 – Dynamic fatigue schematic Weibull plot.....	48
Figure A.1 – Schematic diagram of the statistical strength degradation map	64
Table 1 – Symbols	8
Table 2 –FIT rates of 1 km fibre in Figures 2 and 3 at various times.....	20
Table 3 – FIT rates of 1 metre effective length bent fibre in Figures 4 and 5 at various times	22
Table 4 – FIT rates of Table 3 neglecting stress versus strain non-linearity.....	22
Table 5 – 1 km lifetimes in years of Figure 6 for various failure probabilities	23
Table 6 – Lifetimes of bent fibre with 1 metre effective length in years of Figure 7 for various failure probabilities	24
Table 7 – Lifetimes in years of Table 6 neglecting stress versus strain non-linearity	245
Table 8 – Calculated results in case of bend plus 30 % of proof test tension for 30 years	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL FIBRES –

Reliability – Power law theory

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC/TR 62048, which is a technical report, has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This third edition cancels and replaces the second edition published in 2011, and constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- correction to the unit of failure rates in Table 1;

- correction to the FIT equation for instantaneous failure rate [19]¹ in addition to all call-outs and derivations;
- insertion of a new note about fibre length dependency of failure rates;
- addition of informative Annex A and relevant reference;
- editorial corrections of inconsistencies.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
86A/1537/DTR	86A/1554/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

¹ Numbers in square brackets refer to the Bibliography.

INTRODUCTION

Reliability is expressed as an expected lifetime or as an expected failure rate. The results cannot be used for specifications or for the comparison of the quality of different fibres. This technical report develops the theory behind the experimental principles used in measuring the fibre parameters needed in the reliability formulae. Much of the theory is taken from the referenced literature and is presented here in a unified manner. The primary results are formulae for lifetime or for failure rate, given in terms of the measurable parameters. Conversely, an allowed maximum service stress or extreme value of another parameter may be calculated for an acceptable lifetime or failure rate.

For readers interested only in the final results of this technical report – a summary of the formulae used and numerical examples in the calculation of fibre reliability – Clauses 6 and 7 – are sufficient and self-contained. Readers wanting a detailed background with algebraic derivations will find this in Clauses 8 to 12. An attempt is made to unify the approach and the notation to make it easier for the reader to follow the theory. Also, it should ensure that the notation is consistent in all test procedures. The Bibliography has a limited set of mostly theoretical references, but it is not necessary to read them to follow the analytical development in this technical report. Annex A introduces a statistical strength degradation (SSD) map which gives intuitive understanding of the physical meaning of the formulae appearing in Clauses 10 and 11.

NOTE Clauses 8 to 12 reference the B -value, and this is done for theoretical completeness only. There are as yet no agreed methods for measuring B , so the Bibliography gives only a brief analytical outline of some proposed methods and furthermore develops theoretical results for the special case in which B can be neglected.

OPTICAL FIBRES – Reliability – Power law theory

1 Scope

This technical report is a guideline that gives formulae to estimate the reliability of fibre under a constant service stress based on a power law for crack growth.

NOTE Power law is derived empirically, but there are other laws which have a more physical basis (for example, the exponential law). All these laws generally fit short-term experimental data well but lead to different long-term predictions. The power law has been selected as a most reasonable representation of fatigue behaviour by the experts of several standard-formulating bodies.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-1-30, *Optical fibres – Part 1-30: Measurement methods and test procedures – Fibre proof test*

IEC 60793-1-31, *Optical fibres – Part 1-31: Measurement methods and test procedures – Tensile strength*