

This is a preview - click here to buy the full publication



IEC 62365

Edition 2.0 2009-05

# INTERNATIONAL STANDARD

---

**Digital audio – Digital input-output interfacing – Transmission of digital audio over asynchronous transfer mode (ATM) networks**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

U

---

ICS 35.200, 33.160

ISBN 978-2-88910-683-7

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references.....	8
3 Terms and definitions.....	8
4 Format of audio data in ATM cells.....	10
4.1 Format of audio samples.....	10
4.1.1 Subframes.....	10
4.1.2 Audio sample word.....	10
4.1.3 Ancillary data.....	10
4.1.4 Protocol overhead.....	10
4.2 Packing of sample data into cells.....	12
4.2.1 Packing schemes.....	12
4.2.2 Temporal grouping.....	12
4.2.3 Multi-channel.....	12
4.2.4 Grouping by channel.....	13
4.3 Formats.....	13
4.4 ATM adaptation layer.....	13
4.5 ATM-user-to-ATM-user indication.....	13
5 Switched virtual circuits.....	14
5.1 Addresses.....	14
5.2 Audio call connection: SETUP and ADD PARTY messages.....	14
5.2.1 Restrictions on connection requests.....	14
5.2.2 Information elements in the SETUP and ADD PARTY messages.....	14
5.2.3 Destination response to SETUP and ADD PARTY messages.....	15
5.3 Call disconnection.....	16
6 Coding of audio formats.....	16
6.1 Qualifying information.....	16
6.2 Subframe format.....	17
6.3 Packing of subframes into cells.....	17
6.4 Sampling frequency.....	18
7 Permanent virtual circuits.....	18
8 Management interface.....	19
8.1 Call connection: SETUP messages.....	19
8.1.1 Restrictions on connection requests.....	19
8.1.2 Information elements in the SETUP message.....	19
8.1.3 Destination response to SETUP message.....	20
8.2 Message encapsulation.....	20
8.3 Message format and action to be taken by recipient.....	20
8.4 Message types.....	21
8.4.1 Messages sent from the controlling entity.....	21
8.4.2 Messages sent to the controlling entity.....	23
8.4.3 Vendor-specific messages.....	25
Annex A (informative) Data protection.....	26
Annex B (informative) Application identifier values.....	28

Bibliography.....	29
Table 1 – Fields contained in a subframe.....	10
Table 2 – Default port number and packing for certain VCIs.....	19
Table 3 – Status enquiry message .....	21
Table 4 – Audio connection request message .....	22
Table 5 – Audio disconnection request message.....	22
Table 6 – Input port status message .....	23
Table 7 – Output port status message.....	24
Table 8 – Other status messages.....	25
Table 9 – Vendor-specific messages.....	25
Table A.1 – Sequence number protection field values .....	26
Table B.1 – Application identifier (octets 9 to 12) values in the BHLI IE .....	28

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**DIGITAL AUDIO –  
DIGITAL INPUT-OUTPUT INTERFACING –  
TRANSMISSION OF DIGITAL AUDIO OVER  
ASYNCHRONOUS TRANSFER MODE (ATM) NETWORKS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62365 has been prepared by technical area 4: Digital systems interfaces and protocols, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/1517/FDIS	100/1550/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The main changes with respect to the previous edition (2004) are listed below.

- Second, third, and fourth required formats in 4.3 removed.
- 4.3 reformatted, eliminating Table 2, and subsequent Tables renumbered.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

This International Standard describes means for the transmission of professional audio across digital networks, including metropolitan- and wide-area networks, to provide the best performance with regard to latency, jitter, and other relevant factors.

Current-generation wide-area communications are based on two very similar systems, synchronous optical network (SONET) and synchronous digital hierarchy (SDH), SONET being used in the United States and SDH in Europe. On top of them are run integrated services digital network (ISDN), asynchronous transfer mode (ATM), and Internet protocol (IP).

ISDN provides telephone call connections of a fixed capacity that carry one 8-bit value per 125  $\mu$ s; when a call is set up, its route through the system is chosen, and the switches that route the data are configured accordingly. Each link, between switches or between switch and end equipment, is formatted into frames that take 125  $\mu$ s to transmit, and each data byte is identified by its position in the frame.

ATM, also called broadband ISDN, provides a service similar to ISDN, but with the capacity of each call being specified by the caller. Links are formatted into cells, which consist of a header and 48 data bytes; the header is typically 5 bytes long, and most of it is taken up with the virtual channel identifier (VCI) that shows to which call the cell belongs. Call set-up, routing, and switching are done in the same way as in ISDN, but with calls not being restricted to 1 byte every 125  $\mu$ s.

IP provides a very different service, not designed for continuous media such as audio and video. There is no call set-up, and each packet contains enough information within itself to allow it to be routed to its destination. This means that the header is much larger than in the case of ATM, typically 74 bytes, and packets will also typically be much larger, if only because otherwise the overheads would be excessive. Each packet is liable to be routed separately, so two packets that are part of the same flow may well take different routes. This can mean that the one that was sent first does not arrive first.

For many professional audio applications, a round-trip time from the microphone through the mixing desk and back to the headphones of no more than 3 ms is required. Allowing 0,5 ms each for conversion from analog to digital and back again, it follows that the network connections to and from the mixing desk must have a latency of less than 1 ms each. For distances of more than about 200 km, the transmission delay alone will exceed 1 ms, but within a metropolitan area the transmission delay should be no more than 0,25 ms (equivalent to about 50 km), leaving 0,75 ms for packetization, queuing within switches, and resynchronization within the receiving equipment.

Packetization delays are proportional to the size of the transmission unit (frame, cell, or packet), and resynchronization delays depend on how evenly spaced the transmission units are when they arrive at their destination. Both classes of delay are thus small for ISDN and large for IP. Using the format specified in this standard to carry dual-channel IEC 60958-4 audio with a 48 kHz sampling frequency over ATM results in an inter-cell time of 125  $\mu$ s, at which ATM will have similar delays to ISDN. A higher sampling frequency or a larger number of channels would reduce the inter-cell time and hence also the delays.

The queuing time within each ISDN switch is likely to be around one frame time or 125  $\mu$ s. The ATM documents limit the queuing time in an ATM switch to approximately the inter-cell time for the call, which, as with the other delays, translates into performance similar to that of ISDN for dual-channel 48 kHz IEC 60958-4 audio and better for higher sampling frequencies or larger numbers of channels.

The queuing time within an IP router for normal, best effort, Internet traffic is unbounded, and if the router is congested, packets may simply be thrown away. Resource reservation protocol (RSVP) (see Annex A) allows capacity to be reserved for a particular traffic flow, but it does

not guarantee that the packets will actually be routed over the links on which the capacity has been reserved; if the flow is re-routed, it will only get a best effort service until a reservation has been made on the new route, and it may not even be possible to make a reservation on the new route at all.

ATM has therefore been chosen as providing a more convenient service than ISDN and significantly better performance than IP, even when RSVP is used.

This standard does not specify a physical interface to the network because one of the features of ATM is its ability to make a seamless connection between interfaces operating at a wide variety of data rates and with different ways of encoding the ATM cells. Commonly used interfaces provide 25,6 Mbit/s over category 3 structured wiring and 155,52 Mbit/s over category-5 structured wiring or fibre-optic cable.

The physical layer section description and unique ATM abbreviations can be found in ATM forum approved specifications. See the Bibliography.

# **DIGITAL AUDIO – DIGITAL INPUT-OUTPUT INTERFACING – TRANSMISSION OF DIGITAL AUDIO OVER ASYNCHRONOUS TRANSFER MODE (ATM) NETWORKS**

## **1 Scope**

This International Standard specifies a means to carry multiple channels of audio in linear PCM or IEC 60958-4 format over an ATM layer service conforming to ITU-T Recommendation I.150. It includes a means to convey, between parties, information concerning the digital audio signal when setting up audio calls across the ATM network.

It does not specify the physical interface to the network.

## **2 Normative references**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60958-1, *Digital audio interface – Part 1: General*

IEC 60958-4, *Digital audio interface – Part 4: Professional applications (TA4)*

ITU-T Recommendation I.150: *B-ISDN asynchronous transfer mode functional characteristics*

ITU-T Recommendation I.363.5, *B-ISDN ATM Adaptation Layer specification: Type 5 AAL*

ITU-T Recommendation Q.2931: *Digital Subscriber Signalling System No. 2 – User-Network Interface (UNI) layer 3 specification for basic call/connection control*