

This is a preview - click here to buy the full publication



IEC 62388

Edition 2.0 2013-06

INTERNATIONAL STANDARD



**Maritime navigation and radiocommunication equipment and systems –
Shipborne radar – Performance requirements, methods of testing and required
test results**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

ICS 33.060; 47.020.70

ISBN 978-2-8322-0890-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	11
1 Scope.....	14
2 Normative references.....	14
3 Terms and definitions.....	15
4 General.....	27
4.1 Overview.....	27
4.2 Purpose.....	28
4.3 Application of these standards.....	28
4.4 Equipment categories.....	28
4.5 Establishing equipment type and status.....	29
4.6 Conditions of measurement and related definitions.....	30
4.7 Quality requirements.....	30
5 Tests.....	30
5.1 Test sites and simulation.....	30
5.1.1 Environmental and RF testing.....	30
5.1.2 Over-sea radar performance tests.....	30
5.1.3 Test targets and target simulation for performance tests.....	31
5.2 Test terminology and format.....	31
5.2.1 General.....	31
5.2.2 Test requirement terminology.....	31
5.2.3 Testing method terminology.....	32
6 Radar performance.....	32
6.1 General.....	32
6.2 Transmission and interference.....	32
6.2.1 Transmission frequency.....	32
6.2.2 Interference.....	33
6.3 Performance optimisation and monitoring.....	33
6.3.1 General.....	33
6.3.2 Optimum performance.....	33
6.4 Gain and anti-clutter functions.....	34
6.4.1 General.....	34
6.4.2 Gain function.....	34
6.4.3 Manual and automatic sea anti-clutter.....	34
6.4.4 Rain anti-clutter.....	35
6.5 Signal processing.....	35
6.5.1 General.....	35
6.5.2 Target enhancement.....	35
6.5.3 Radar signal correlation.....	36
6.5.4 Signal processing and radar image latency.....	36
6.5.5 Second-time-around echoes.....	36
6.5.6 Transmission format.....	37
6.5.7 Picture update.....	37
6.5.8 Additional processing.....	37
6.5.9 Signal processing description.....	37
6.6 Operation with SARTs, target enhancers (RTEs) and beacons.....	38
6.6.1 General.....	38

6.6.2	Radar beacons, SARTs and enhancers	38
6.7	Minimum range and range compensation.....	38
6.7.1	General.....	38
6.7.2	Range compensation.....	39
6.7.3	Minimum range	39
6.8	Range and bearing discrimination	40
6.8.1	General.....	40
6.8.2	Measurement conditions	40
6.8.3	Range discrimination	40
6.8.4	Bearing discrimination	40
6.8.5	Fundamental radar accuracy	41
6.9	Target detection performance assessment.....	41
6.9.1	General.....	41
6.9.2	Range of first detection in minimal clutter	42
6.9.3	Assessment of target detection with clutter	44
6.9.4	Radar performance documentation.....	49
6.10	Radar antenna (including pitch and roll)	50
6.10.1	General.....	50
6.10.2	Vertical radiation pattern/pitch and roll	50
6.10.3	Antenna horizontal pattern	51
6.10.4	Antenna side lobes.....	51
6.11	Radar availability – Standby and transmit	52
6.11.1	Requirements	52
6.11.2	Methods of test and required results	52
7	Display presentation	53
7.1	General.....	53
7.1.1	Requirements	53
7.1.2	Methods of test and required results	53
7.2	Linearity and index delay	53
7.2.1	Requirements	53
7.2.2	Methods of test and required results	53
7.3	Use and discrimination of colour.....	53
7.3.1	Requirements	53
7.3.2	Methods of test and required results	53
8	CCRP and own ship.....	54
8.1	Consistent common reference point (CCRP).....	54
8.1.1	CCRP	54
8.1.2	CCRP position	54
8.1.3	Measurements	54
8.1.4	Antenna offset	55
8.2	Own ship.....	55
8.2.1	General.....	55
8.2.2	Own ship's outline and minimised symbol	55
8.2.3	Heading line	55
8.2.4	Stern line	56
9	Navigation tools.....	56
9.1	General.....	56
9.2	Units of measurement.....	56
9.2.1	Requirements	56

9.2.2	Methods of test and required results	57
9.3	Presentation	57
9.3.1	Requirements	57
9.3.2	Methods of test and required results	57
9.4	Display range scales	57
9.4.1	Mandatory range scales	57
9.5	Variable range marker (VRM)	58
9.5.1	General	58
9.5.2	VRM measurements	58
9.6	Electronic bearing line (EBL)	59
9.6.1	General	59
9.6.2	EBL measurements	59
9.6.3	EBL origin position	60
9.7	Cursor	60
9.7.1	General	60
9.7.2	Cursor measurement	60
9.7.3	Selection by cursor	61
9.8	Offset measurement of range and bearing	61
9.8.1	General	61
9.8.2	Electronic range and bearing line (ERBL)	61
9.9	Parallel index lines (PI)	62
9.9.1	General	62
9.9.2	PI lines and positioning	62
9.10	Bearing scale	63
9.10.1	General	63
9.10.2	Bearing scale presentation	63
9.11	Range rings	64
9.11.1	General	64
9.11.2	Range ring presentation and measurement	64
9.12	Radar maps	65
9.12.1	General	65
9.12.2	Map functions and display simple user-defined maps	65
9.12.3	Map memory and transfer	65
9.12.4	Map presentation properties	66
9.13	Navigation routes	66
9.13.1	General	66
9.13.2	Route display and monitoring	67
10	Orientation, motion and stabilisation	67
10.1	General	67
10.2	Azimuth orientation	67
10.2.1	Accuracy of alignment	67
10.2.2	Heading readout and reference	68
10.2.3	Azimuth stabilisation update	69
10.3	Motion and orientation modes	69
10.3.1	General	69
10.3.2	True and relative motion	69
10.4	Off-centring	70
10.4.1	General	70
10.4.2	Manual and automatic off-centring	70

10.4.3	Automatic reset	70
10.4.4	Display orientation	71
10.5	Ground and sea stabilisation	72
10.5.1	Mode and source	72
10.5.2	Ground stabilisation	72
10.5.3	Sea stabilisation	73
11	Aids for collision avoidance	73
11.1	General.....	73
11.2	Target trails and past positions.....	73
11.2.1	General.....	73
11.2.2	Time and plot requirements.....	74
11.2.3	Trails/past position availability.....	74
11.3	Target tracking (TT)	75
11.3.1	General.....	75
11.3.2	Presentation of targets	75
11.3.3	Tracking calculations.....	76
11.3.4	Target tracking availability	76
11.3.5	Classification and tracked target capacity.....	77
11.3.6	Manual acquisition	78
11.3.7	Automatic acquisition	78
11.3.8	Motion trend	78
11.3.9	Visibility of 50 %	79
11.3.10	Tracking algorithm	79
11.3.11	Target swap	79
11.3.12	Cease tracking.....	79
11.3.13	Target tracking scenarios.....	79
11.3.14	Target motion and tracking accuracy.....	80
11.3.15	Tracker range and bearing accuracy	88
11.3.16	Reference target.....	89
11.4	Tracking limitations	89
11.4.1	Tracking warnings.....	89
11.4.2	Documentation.....	90
11.4.3	Requirements	90
11.4.4	Methods of test and required results	90
11.5	Automatic identification system.....	90
11.5.1	General.....	90
11.5.2	AIS targets and data report capacity	90
11.5.3	AIS target filtering	92
11.5.4	Activation and deactivation of AIS targets.....	92
11.5.5	AIS functionality and presentation.....	93
11.6	Radar and AIS target data.....	95
11.6.1	Requirements	95
11.6.2	Methods of test and required results	95
11.6.3	Bow crossing range and time (BCR/BCT).....	96
11.7	Operational target alerts	96
11.7.1	CPA and TCPA	96
11.7.2	New target warning	97
11.7.3	Lost tracked radar target.....	97
11.7.4	Lost AIS target criteria.....	98

11.8	Target association.....	99
11.8.1	General.....	99
11.8.2	Association and priority.....	99
11.9	Trial manoeuvre.....	103
11.9.1	General.....	103
11.9.2	Trial functions.....	103
12	Chart radar (optional classification).....	104
12.1	General requirements.....	104
12.1.1	General.....	104
12.1.2	Chart operation and source.....	104
12.1.3	Chart elements and availability.....	105
12.1.4	Chart reference.....	106
12.1.5	Primary chart information set.....	106
12.1.6	Chart stabilisation and chart redraw.....	107
12.1.7	Chart position and latency.....	108
12.1.8	Matching and adjustment.....	108
12.1.9	Chart symbols, colours, and size.....	109
12.1.10	Chart display size.....	110
12.1.11	Chart alerts and indications.....	110
12.1.12	Chart malfunction.....	111
12.1.13	Chart radar malfunction.....	111
12.2	Additional requirements for standalone radar with chart facilities.....	111
12.2.1	General.....	111
12.2.2	Provision and updating of chart information.....	111
12.2.3	Content and structure of chart data.....	112
12.3	Additional requirements for ECDIS back-up (optional).....	112
12.3.1	General.....	112
12.3.2	Requirements.....	112
12.3.3	Test Methods and required results.....	112
13	Ergonomic criteria (control functions and display).....	112
13.1	General.....	112
13.2	Operational controls.....	112
13.2.1	Requirements.....	112
13.2.2	Methods of test and required results.....	113
13.3	Primary controls.....	113
13.3.1	Requirements.....	113
13.3.2	Methods of test and required results.....	113
13.4	Control properties.....	114
13.4.1	Requirements.....	114
13.4.2	Methods of test and required results.....	114
13.5	Default control setting and saved user control settings.....	114
13.5.1	Requirements.....	114
13.5.2	Test methods and required results.....	115
14	Interfacing.....	116
14.1	General.....	116
14.2	Input interfacing.....	116
14.2.1	Input data.....	116
14.2.2	Input quality, integrity and latency.....	117
14.3	Output interfacing.....	117

14.3.1	Output format	117
14.3.2	Output target data	117
14.3.3	VDR interface	118
15	Design, servicing and installation	119
15.1	General.....	119
15.2	Fault diagnosis and servicing	119
15.2.1	Requirements	119
15.2.2	Methods of test and required results	120
15.3	Display design	120
15.3.1	Requirements	120
15.3.2	Methods of test and required results	120
15.4	Transceiver design.....	120
15.4.1	General.....	120
15.4.2	Sector blanking.....	121
15.5	Antenna design.....	121
15.5.1	Requirements	121
15.5.2	Methods of test and required results	121
15.6	Inter-switched and multiple radars	122
15.6.1	General.....	122
15.6.2	System safeguards.....	122
15.6.3	Combining radar	122
15.6.4	Multiple radar system status.....	123
15.7	Multiple operational displays	123
15.7.1	Additional information and conformity.....	123
15.7.2	Requirements	123
15.7.3	Methods of test and required results	124
15.8	Safety – antenna and radiation	124
15.8.1	General.....	124
15.8.2	Antenna radiation and rotation.....	124
15.8.3	Microwave radiation levels	124
16	Alerts and failures.....	125
16.1	General.....	125
16.1.1	Priority of alerts	125
16.1.2	Alerts and indications	125
16.1.3	Alarm contact outputs.....	125
16.1.4	Alert management interface.....	125
16.1.5	Unacknowledged warnings.....	126
16.1.6	Unacknowledged alarms	127
16.1.7	Remote acknowledgement and silencing of alerts.....	127
16.1.8	Picture freeze	128
16.1.9	Sensor failure alert.....	128
16.2	Backup and fallback arrangements	128
16.2.1	Requirements	128
16.2.2	Failure of heading information (azimuth stabilisation).....	128
16.2.3	Failure of speed through the water information.....	129
16.2.4	Failure of course and speed over ground information	129
16.2.5	Failure of position input information	129
16.2.6	Failure of radar video input information	130
16.2.7	Failure of AIS input information.....	130

16.2.8	Failure of an integrated or networked system	130
17	Environmental testing	130
17.1	General.....	130
17.2	Testing to IEC 60945.....	131
17.2.1	Requirements	131
17.2.2	Methods of test and required results	131
17.3	Additional environmental tests.....	131
17.3.1	General.....	131
17.3.2	Antenna shock test.....	132
18	Equipment familiarisation and documentation	132
18.1	Familiarisation simulator	132
18.1.1	General.....	132
18.1.2	Requirements	132
18.1.3	Methods of test and required results	132
18.2	Instructions and documentation	133
18.2.1	General.....	133
18.2.2	Documentation.....	133
18.2.3	Operating instructions.....	133
18.3	Radar system installation.....	134
18.3.1	Requirements	134
18.3.2	Methods of test and required results	134
18.4	Maintenance information for equipment update	135
18.4.1	Requirements	135
18.4.2	Methods of test and required results	135
Annex A (informative)	Guidelines for radar functionality on navigation displays.....	136
Annex B (normative)	Unwanted emissions of radar systems.....	137
Annex C (informative)	Radar target size (RCS) and detection range calculations	142
Annex D (informative)	Factors that influence target detection.....	146
Annex E (normative)	Sensor errors.....	155
Annex F (informative)	Target scenario simulator/reported target simulator.....	157
Annex G (informative)	Tracked and reported target states	158
Annex H (normative)	IEC 61162 sentence formats	159
Annex I (normative)	Radar control function/indication grouping	168
Annex J (informative)	Interference to shipborne radar from emissions in adjacent frequency bands.....	172
Bibliography	175
Figure 1	– Reduction of range to first detection due to rain at S-band	45
Figure 2	– Reduction of range to first detection due to rain at X-band	45
Figure 3	– TT scenario 1	82
Figure 4	– TT scenario 2	83
Figure 5	– TT scenario 3	84
Figure 6	– TT scenario 4	85
Figure 7	– TT scenario 5	86
Figure B.1	– B ₄₀ falls within the allocated band	140
Figure B.2	– B ₄₀ falls outside the allocated band.....	141

Figure C.1 – Enhancement by reflection (dB) over free-space (9,41 GHz)	145
Figure C.2 – Enhancement by reflection (dB) over free-space (3,05 GHz)	145
Figure D.1 – Effect of sea spikes on target detection.....	148
Figure D.2 – Multi-path plots for S-band.....	150
Figure D.3 – Multi-path plot for X-band	150
Figure G.1 – Tracked target states	158
Figure G.2 – AIS target state	158
Table 1 – Performance requirements for categories of ship/craft for SOLAS V	29
Table 2 – Range of first detection in clutter-free conditions	42
Table 3 – X-band pass/fail assessment criteria	48
Table 4 – S-band pass/fail assessment criteria	48
Table 5 – Pass/fail assessment.....	49
Table 6 – Douglas sea state parameters	49
Table 7 – Main horizontal beam pattern	51
Table 8 – Effective side-lobes.....	52
Table 9 – Features and colours to be used for radar maps.....	66
Table 10 – Tracked target capacity (subset of Table 1).....	77
Table 11 – Typical tracked target accuracy (95 % probability figures)	80
Table 12 – TT scenario 1, with sensor errors applied	81
Table 13 – TT scenario 1, times of measurement task.....	81
Table 14 – TT scenario 1, accuracies after 1 min and 3 min (all values)	82
Table 15 – TT scenario 2, own ship turning through 180°	83
Table 16 – TT scenario 3, initial target data.....	84
Table 17 – TT scenario 4, initial target data for fast targets (standard speed ships).....	84
Table 18 – TT scenario 4, initial target data for fast targets (HSC).....	85
Table 19 – TT scenario 5: initial target data for standard craft.....	86
Table 20 – TT scenario 5: initial target data for collision scenario for HSC.....	86
Table 21 – Measurement points and results at 3 min and 6 min for HSC	87
Table 22 – Measurement points and results at 11 min and 14 min for HSC.....	87
Table 23 – Measurement points and results at 3 min and 6 min for standard craft	87
Table 24 – Measurement points and results at 11 min and 14 min for standard craft.....	88
Table 25 – Measurement of tracked target accuracy.....	88
Table 26 – AIS display capacity (subset of Table 1)	91
Table 27 – AIS reporting rates	98
Table 28 – Association scenario 1, initial TT and AIS target position and data	100
Table 29 – Association scenario 1, AIS target data for diverging and converging tracks	101
Table 30 – Association scenario 2, initial TT and AIS target position and data	101
Table 31 – Association scenario 2, AIS target data for changing speed	102
Table 32 – Association scenario 3, TT and AIS target start position and data.....	102
Table 33 – Association scenario 4, initial TT and AIS target position and data	103
Table 34 – Association scenario 4, TT and AIS target with the same course and speed	103
Table 35 – Control settings configured in response to ‘Default’ selection.....	115

Table 36 – Antenna shock test severity (half sine pulse).....	132
Table B.1 – Measurement frequency ranges.....	138
Table D.1 – Spread of RCS values for typical ships.....	147
Table D.2 – S-band performance predictions for ranges of 0,2, 0,4, 0,7 NM.....	149
Table D.3 – X-band performance predictions for ranges of 0,2, 0,7 NM	149
Table D.4 – Parameters for attenuation in uniform rain conditions	151
Table D.5 – Typical values for attenuation and backscatter in uniform rain conditions.....	151
Table D.6 – Additional radar system parameters (X/S-band)	151
Table D.7 – Target size, height and RCS values	152
Table D.8 – S-band radar parameters (LP).....	153
Table D.9 – X-band radar parameters (LP).....	154
Table H.1 – Mandatory IEC 61162-1 sentences	159
Table H.2 – Optional IEC 61162-3 messages	160
Table H.3 – Description of terms	161
Table H.4 – Header format (1 of 2).....	162
Table H.5 – Package data format	164
Table I.1 – Top-level grouping of data and control functions for radar applications	168
Table I.2 – Icons for common function controls (1 of 2).....	169

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Shipborne radar – Performance requirements, methods of testing and required test results

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62388 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

The main changes with respect to the previous edition are:

- in 6.2 (Transmission and interference) reference is now made to a revised Annex B (Unwanted emissions) where the mask has been tightened from 20 dB/decade to 30 dB/decade in line with ITU requirements and a new informative Annex J has been added concerning interference from emissions in adjacent frequency bands;
- Clause 7 (Display presentation) has been simplified (and the previous Annexes J and K deleted) with reference made instead to IEC 62288 with associated changes throughout the standard;
- in 9.9.2 (PI lines and positioning) the requirements for parallel index lines have been revised;
- in 10.4.4 (Display orientation) a new mode of display orientation “head-up stabilised” has been added;
- in 11.5 (Automatic identification system) new requirements and tests have been added for types of AIS targets, AIS repeater stations and filtering of AIS targets;
- in Clause 12 (Chart radar) a new subclause 12.3 has been added for ECDIS backup requirements;
- in Clause 13 (Ergonomic criteria) a new subclause 13.5 has been added giving requirements for default control settings;
- 14.3 (Output interfacing) has been revised together with the associated Annex H to update the requirements particularly with regard to interfaces to the VDR;
- Clause 16 (Alerts and failures) has been revised to update the requirements to align with bridge alert management and new requirements added for an alert management interface with associated changes throughout the standard;
- in Clause 18 (Equipment familiarisation and documentation) a new subclause 18.3 has been added for maintenance information and equipment update.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/696/FDIS	80/705/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

All the text in this standard with wording identical to that in IMO resolutions is printed in italics. Reference to MSC.192(79) is by the relevant requirement clause as indicated in brackets, for example (MSC.192/4.2.3). Some clauses from Resolution MSC.192(79) may be split and the requirements in this case are addressed separately.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of February 2014 have been included in this copy.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Shipborne radar – Performance requirements, methods of testing and required test results

1 Scope

This International Standard specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards not inferior to those adopted by the IMO in Resolution MSC.192(79).

(MSC.192/2) The radar installation, in addition to meeting the general requirements as set out in resolution A.694(17) and the related standard IEC 60945, should comply with the performance standards of MSC.192(79). When a requirement of this standard is different from IEC 60945, the requirement in this standard takes precedence.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information systems (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61924-2:2012, *Maritime navigation and radiocommunication equipment and systems – Part 2 Modular Structure for INS - Operational and performance requirements, methods of testing and required test results*

IEC 61996-1:2012, *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR) – Part 1: Voyage data recorder (VDR) - Performance requirements – Methods of testing and required test results*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required results*

ITU-R Recommendation M.628, *Technical characteristics for search and rescue radar transponders*

ITU-R Recommendation M.824, *Technical parameters of radar beacons (racons)*

ITU-R Recommendation M.1176, *Technical parameters of radar target enhancers*

IHO S-52, *Specifications for chart content and display aspects of ECDIS*

IHO S-52 Annex A, *IHO ECDIS Presentation Library*

IMO Resolution A.424(XI), *Performance standards for Gyro-compasses*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.821(19), *Performance standards for Gyro-compasses for High-Speed Craft*

IMO Resolution MSC.96(72), *Amendments to IMO Resolution A.824(19), Performance standards for devices to indicate speed and distance*

IMO Resolution MSC.116(73), *Performance standards for marine transmitting heading devices (THDs)*

IMO Resolution MSC.191(79), *Performance standards for the presentation of navigation-related information on shipborne navigational displays*

IMO Resolution MSC.192(79), *Revised performance standards for radar equipment*

IMO Resolution MSC.232(82), *Revised performance standards for electronic chart display and information systems (ECDIS)*

IMO Resolution MSC.302(87), *Performance standards for bridge alert management*

IMO MSC.1/Circ.1389, *Guidance on procedures for updating shipborne navigation and communication equipment*

VESA-2007-5:2007, *Industry standards and guidelines for computer display monitor timing (DMT)*

DDWG DVI:1999, *Digital Visual Interface (DVI) Revision 1.0, Digital Display Working Group (DDWG)*