



INTERNATIONAL STANDARD

**Electronic components – Long-term storage of electronic semiconductor devices –
Part 4: Storage**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.020

ISBN 978-2-8322-5768-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	8
4 Purpose of storage (facility).....	10
4.1 General.....	10
4.2 Cost of ownership	10
4.3 Security	10
4.4 Location and ambient environment.....	10
4.5 Incorrect control of reliability during storage.....	10
5 Storage	10
5.1 General.....	10
5.2 Type of environment	11
5.3 Storage identification – traceability	11
5.4 Initial packaging.....	11
5.5 Storage conditions	12
5.5.1 General	12
5.5.2 Storage area.....	12
5.6 Maintaining storage conditions.....	13
6 Periodic check of the components	13
6.1 Objectives.....	13
6.2 Periodicity.....	13
6.3 Tests during periodic check	14
7 Removal from storage	14
7.1 Precautions.....	14
7.2 Electrostatic discharges	14
8 Materials used in storage regimes	14
8.1 General.....	14
8.2 Moisture barrier bags (MBB)	14
8.3 Desiccant.....	15
8.4 Humidity indicator card (HIC).....	15
8.5 Dry nitrogen atmosphere.....	15
8.6 High purity dry air atmosphere	15
8.7 Storage containers.....	16
8.8 Foams, packing material and protective cushioning	16
9 General storage environment.....	16
10 LTS methods	16
10.1 General.....	16
10.2 Dry cabinet storage.....	17
10.2.1 General	17
10.2.2 Humidity controlled storage	17
10.2.3 Oxygen (O ₂)-controlled storage	17
10.2.4 Outgassing-controlled storage	17
10.3 MBB storage	17
10.3.1 General	17

10.3.2	Humidity-controlled storage	17
10.3.3	Oxygen (O ₂)-voided storage	17
10.3.4	Outgassing controlled storage	18
10.3.5	Nitrogen (N ₂) positive-pressure MBB storage	18
11	LTS double containment redundancy	18
Annex A (normative)	Example checklist for long-term storage facilities	19
Bibliography	20
Table A.1	– Example checklist for storage facilities	19

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRONIC COMPONENTS – LONG-TERM STORAGE OF ELECTRONIC SEMICONDUCTOR DEVICES –

Part 4: Storage

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62435-4 has been prepared by IEC technical committee 47: Semiconductor devices.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
47/2469/FDIS	47/2486/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62435 series, published under the general title *Electronic components – Long-term storage of electronic semiconductor devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This standard applies to the long-term storage of electronic components.

This is a standard for long-term storage (LTS) of electronic devices drawing on the best long-term storage practices currently known. For the purposes of this document, LTS is defined as any device storage whose duration may be more than 12 months for products scheduled for long duration storage. While intended to address the storage of unpackaged semiconductors and packaged electronic devices, nothing in this document precludes the storage of other items under the storage levels defined herein.

Although it has always existed to some extent, obsolescence of electronic components and particularly of integrated circuits, has become increasingly intense over the last few years.

Indeed, with the existing technological boom, the commercial life of a component has become very short compared with the life of industrial equipment such as that encountered in the aeronautical field, the railway industry or the energy sector.

The many solutions enabling obsolescence to be resolved are now identified. However, selection of one of these solutions should be preceded by a case-by-case technical and economic feasibility study, depending on whether storage is envisaged for field service or production, for example:

- remedial storage as soon as components are no longer marketed;
- preventative storage anticipating declaration of obsolescence.

Taking into account the expected life of some installations, sometimes covering several decades, the qualification times and the unavailability costs, which can also be very high, the solution to be adopted to resolve obsolescence should often be rapidly implemented. This is why the solution retained in most cases consists in systematically storing components which are in the process of becoming obsolescent.

The technical risks of this solution are, a priori, fairly low. However, it requires perfect mastery of the implemented process and especially of the storage environment, although this mastery becomes critical when it comes to long-term storage.

All handling, protection, storage and test operations are recommended to be performed according to the state of the art.

The application of the approach proposed in this document in no way guarantees that the stored components are in perfect operating condition at the end of this storage. It only comprises a means of minimizing potential and probable degradation factors.

Some electronic device users have the need to store electronic devices for long periods of time. Lifetime buys are commonly made to support production runs of assemblies that will exceed the production timeframe of their individual parts. This puts the user in a situation requiring careful and adequate storage of such parts to maintain the as-received solderability and to minimize any degradation effects to the part over time. Major degradation concerns are moisture, electrostatic fields, ultra-violet light, large variations in temperature, air-borne contaminants and outgassing.

Warranties and sparring also present a challenge for the user or repair agency, as some systems have been designated to be used for long periods of time, in some cases for up to 40 years or more. Some of the devices needed for repair of these systems will not be available from the original supplier for the lifetime of the system, or the spare assembly can be built with the original production run but then require long-term storage. This document was developed to provide a standard for storing electronic devices for long periods of time.

The storage of devices that are moisture sensitive but that do not need to be stored for long periods of time is dealt with in IEC TR 62258-3.

Long-term storage assumes that the device is going to be placed in uninterrupted storage for a number of years. It is essential that it be useable after storage. It is important that storage media and the local environment are considered together.

These guidelines do not imply any warranty of product or guarantee of operation beyond the storage time given by the manufacturer.

The IEC 62435 series is intended to ensure that adequate reliability is achieved for devices in user applications after long-term storage. Users are encouraged to request data from suppliers to applicable specifications to demonstrate a successful storage life as requested by the user. These standards are not intended to address built-in failure mechanisms that would take place regardless of storage conditions.

These standards are intended to give practical guidance on methods of long-duration storage of electronic components, where this is intentional or involves planned storage of a product for a number of years. Storage regimes for work-in-progress production are managed according to company internal process requirements and are not detailed in this series of standards.

The overall standard series is split into a number of parts. Parts 1 to 4 apply to any long-term storage and contain general requirements and guidance, whereas Parts 5 to 9 are specific to the type of product being stored.

Electronic components requiring different storage conditions are covered separately starting with Part 5.

The structure of the IEC 62435 series as currently planned consists of the following:

Part 1 – General

Part 2 – Deterioration mechanisms

Part 3 – Data

Part 4 – Storage

Part 5 – Die and wafer devices

Part 6 – Packaged or finished devices

Part 7 – MEMS

Part 8 – Passive electronic devices

Part 9 – Special cases

ELECTRONIC COMPONENTS – LONG-TERM STORAGE OF ELECTRONIC SEMICONDUCTOR DEVICES –

Part 4: Storage

1 Scope

This part of IEC 62435 specifies long-term storage methods and recommended conditions for long-term storage of electronic components including logistics, controls and security related to the storage facility. Long-term storage refers to a duration that may be more than 12 months for products scheduled for long duration storage. The philosophy of such storage, good working practices and general means to facilitate the successful long-term storage of electronic components are also addressed.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60749-20-1, *Semiconductor devices – Mechanical and climatic test methods – Part 20-1: Handling, packing, labelling and shipping of surface-mount devices sensitive to the combined effect of moisture and soldering heat*

IEC TR 62258-3, *Semiconductor die products – Part 3: Recommendations for good practice in handling, packing and storage*

IEC 61340-5-2, *Electrostatics – Part 5-2: Protection of electronic devices from electrostatic phenomena – User guide*

JEDEC J-STD-033, *Standard for handling, packing, shipping, and use of moisture/reflow sensitive surface mount devices*

MIL-PRF-27401, *Propellant pressurizing agent nitrogen*

MIL-PRF-81705, *ESD Materials, Bags and Performance Specification*