

This is a preview - click here to buy the full publication



IEC 62458

Edition 1.0 2010-01

INTERNATIONAL STANDARD



**Sound system equipment – Electroacoustical transducers – Measurement of
large signal parameters**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

T

ICS 33.160.50

ISBN 978-2-88910-733-9

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions.....	7
4 Test signals.....	9
4.1 General.....	9
4.2 Large d.c. signal.....	9
4.3 Large d.c. signal and small a.c. signal.....	9
4.4 Broadband noise signal.....	9
4.5 Music.....	9
5 Mounting condition.....	10
5.1 Drive units.....	10
5.2 Loudspeaker systems.....	10
6 Climatic conditions.....	10
7 Acoustical environment.....	10
8 Preconditioning.....	10
9 Time-varying properties of the loudspeaker.....	11
10 Methods of measurement.....	11
10.1 General.....	11
10.2 Static or quasi-static method.....	11
10.3 Point-by-point dynamic method.....	12
10.4 Full dynamic method.....	14
11 Nonlinear force factor.....	15
11.1 Force factor curve $Bl(x)$	15
11.2 Force-factor limited displacement, X_{Bl}	16
11.3 Symmetry point, $x_{\text{sym}}(x_{\text{ac}})$	17
11.4 Voice coil offset, x_{offset}	18
12 Nonlinear stiffness.....	18
12.1 Nonlinear stiffness curve $K_{\text{ms}}(x)$	18
12.2 Compliance-limited displacement x_c	19
12.3 Stiffness asymmetry $A_K(x_{\text{peak}})$	19
13 Displacement-dependent inductance, $L_e(x)$	20
13.1 Inductance curve $L_e(x)$	20
13.2 Inductance-limited displacement, x_L	21
14 Current -dependent inductance, $L_e(i)$	21
14.1 Characteristic to be specified.....	21
14.2 Method of measurement.....	21
15 Parameters derived from geometry and performance.....	22
15.1 Maximal peak displacement, x_{MAXd}	22
15.2 Method of measurement.....	22
Bibliography.....	23
Figure 1 – Electro-dynamical transducer.....	7

Figure 2 –Static and quasi-static measurement setup	12
Figure 3 – Setup for measurement of large signal parameters by using the point-by-point dynamic method	13
Figure 4 – Setup for dynamic measurement of large signal parameters.....	14
Figure 5 – Reading the maximal peak displacement x_B limited by force factor only	16
Figure 6 – Reading the voice coil offset from the symmetry point $x_{\text{sym}}(x_{\text{ac}})$ curve	17
Figure 7 – Definition of the symmetry point x_{sym} in the nonlinear force factor characteristic $Bl(x)$	18
Figure 8 – Reading the stiffness asymmetry from the $K_{\text{ms}}(x)$ curve	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SOUND SYSTEM EQUIPMENT – ELECTROACOUSTICAL TRANSDUCERS – MEASUREMENT OF LARGE SIGNAL PARAMETERS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62458 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition cancels and replaces IEC/PAS 62458 published in 2006. It constitutes a technical revision. The main changes are listed below:

- descriptions of the methods of measurement are adjusted to the state of the technology;
- addition of Clauses 4 to 15;
- integration of Annex A in the main body of the standard;
- overall textual review.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/1624/FDIS	100/1647/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

INTRODUCTION

Electro-mechanical-acoustical transducers such as loudspeaker drive units, loudspeaker systems, headphones, micro-speakers, shakers, and other actuators behave in a nonlinear manner at higher amplitudes. This limits the acoustical output and generates nonlinear signal distortion. Linear models fail in describing the large signal behaviour of such transducers and extended models have been developed which consider dominant nonlinearities in the motor and suspension. The free parameters of the large signal model have to be measured on the particular transducer by using static or dynamic methods. The large signal parameters show the physical cause of the signal distortion directly and are very important for the objective assessment of sound quality and failure diagnostics in development and manufacturing. Furthermore, the model and parameters identified for a particular transducer are the basis for predicting the maximum output and signal distortion for any input signal. The close relationship between causes and symptoms simplifies the interpretation of the harmonic and intermodulation distortion measured according to IEC 60268-5. Large signal parameters are valuable input data for the synthesis of loudspeaker systems and the development of electrical control systems dedicated to loudspeakers.

SOUND SYSTEM EQUIPMENT – ELECTROACOUSTICAL TRANSDUCERS – MEASUREMENT OF LARGE SIGNAL PARAMETERS

1 Scope

This International Standard applies to transducers such as loudspeaker drive units, loudspeaker systems, headphones, micro-speakers, shakers and other actuators using either an electro-dynamical or electro-magnetic motor coupled with a mechanical suspension. The large signal behaviour of the transducer is modelled by a lumped parameter model considering dominant nonlinearities such as force factor, stiffness and inductance as shown in Figure 1. The standard defines the basic terms and parameters of the model, the methods of measurements and the way the results should be reported.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60268-1, *Sound system equipment – Part 1: General*

IEC 60268-5:2003, *Sound system equipment – Part 5: Loudspeakers*
Amendment 1 (2007)