

This is a preview - click here to buy the full publication



IEC/TR 62543

Edition 1.0 2011-03

TECHNICAL REPORT



High-voltage direct current (HVDC) power transmission using voltage sourced converters (VSC)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XC**

ICS 29.200; 29.240.99

ISBN 978-2-88912-424-4

CONTENTS

FOREWORD.....	6
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	8
3.1 General	8
3.2 Letter symbols.....	9
3.3 Power semiconductor terms	9
3.4 VSC topologies	10
submodule d.c. capacitor.....	12
3.5 VSC transmission.....	12
3.6 Operating states.....	14
3.7 Type tests	15
3.8 Production tests	15
3.9 Sample tests	15
3.10 Insulation co-ordination terms	16
3.11 Power losses.....	16
4 VSC transmission overview	17
4.1 Basic operating principles of VSC transmission.....	17
4.1.1 The voltage sourced converter as a black box	17
4.1.2 The principles of active and reactive power control.....	18
4.1.3 Operating principles of a VSC transmission scheme.....	19
4.1.4 Applications of VSC transmission	20
4.2 Design life	20
4.3 VSC transmission configurations	20
4.3.1 General	20
4.3.2 D.C. circuit configurations.....	21
4.3.3 Monopole configuration	21
4.3.4 Bipolar configuration.....	22
4.3.5 Parallel connection of two converters	22
4.3.6 Series connection of two converters	23
4.3.7 Parallel and series connection of more than two converters.....	23
4.4 Semiconductors for VSC transmission.....	23
5 VSC transmission converter topologies	25
5.1 General	25
5.2 Converter topologies with VSC valves of “switch” type	25
5.2.1 General	25
5.2.2 Operating principle	26
5.2.3 Topologies.....	26
5.3 Converter topologies with VSC valves of the “controllable voltage source” type.....	29
5.3.1 General	29
5.3.2 MMC topology with VSC levels in half-bridge topology.....	30
5.3.3 MMC topology with VSC levels in full-bridge topology.....	31
5.4 VSC valve design considerations	32
5.4.1 Reliability and failure mode	32
5.4.2 Current rating	33

5.4.3	Transient current and voltage requirements	33
5.4.4	Diode requirements	33
5.4.5	Additional design details	34
5.5	Other converter topologies	34
5.6	Other equipment for VSC transmission schemes	35
5.6.1	General	35
5.6.2	Power components of a VSC transmission scheme	35
5.6.3	VSC substation circuit breaker	35
5.6.4	A.C. system side harmonic filters	35
5.6.5	Radio frequency interference filters	36
5.6.6	Interface transformers and phase reactors	36
5.6.7	Valve reactor	37
5.6.8	D.C. capacitors	37
5.6.9	D.C. reactor	39
5.6.10	Common mode blocking reactor	39
5.6.11	D.C. filter	39
6	Overview of VSC controls	39
6.1	General	39
6.2	Operational modes and operational options	40
6.3	Power transfer	41
6.3.1	General	41
6.3.2	Telecommunication between converter stations	42
6.4	Reactive power and a.c. voltage control	42
6.4.1	A.C. voltage control	42
6.4.2	Reactive power control	42
6.5	Black start capability	43
6.6	Supply from a wind farm	43
7	Steady state operation	44
7.1	Steady state capability	44
7.2	Converter power losses	45
8	Dynamic performance	45
8.1	A.C. system disturbances	45
8.2	D.C. system disturbances	46
8.2.1	D.C. cable fault	46
8.2.2	D.C. overhead line fault	46
8.3	Internal faults	46
9	HVDC performance requirements	47
9.1	Harmonic performance	47
9.2	Wave distortion	48
9.3	Fundamental and harmonics	48
9.3.1	Three-phase 2-level VSC	48
9.3.2	Selective harmonic elimination modulation	50
9.3.3	Multi-pulse and multi-level converters	51
9.4	Harmonic voltages on power systems due to VSC operation	51
9.5	Design considerations for harmonic filters (a.c. side)	52
9.6	D.C. side filtering	52
10	Environmental impact	52
10.1	General	52

10.2 Audible noise	52
10.3 Electric and magnetic fields (EMF)	53
10.4 Electromagnetic compatibility (EMC)	53
11 Testing and commissioning	54
11.1 General	54
11.2 Factory tests	54
11.2.1 Component tests	54
11.2.2 Control system tests	54
11.3 Commissioning tests / System tests	55
11.3.1 General	55
11.3.2 Precommissioning tests	55
11.3.3 Subsystem tests	55
11.3.4 System tests.....	56
Annex A (informative) Functional specification requirements for VSC transmission systems	60
Annex B (informative) Determination of VSC valve power losses	68
Bibliography.....	77
Figure 1 – Major components that may be found in a VSC substation	9
Figure 2 – Diagram of a generic voltage source converter (a.c. filters not shown)	17
Figure 3 – The principle of active power control	18
Figure 4 – The principle of reactive power control	19
Figure 5 – A point-to-point VSC transmission scheme.....	19
Figure 6 – VSC transmission with a symmetrical monopole.....	21
Figure 7 – VSC transmission with an asymmetrical monopole with metallic return.....	22
Figure 8 – VSC transmission with an asymmetrical monopole with earth return.....	22
Figure 9 – VSC transmission in bipolar configuration	22
Figure 10 – Parallel connection of two converter units	23
Figure 11 – Symbol of a controllable switch and associated free-wheeling diode	24
Figure 12 – Symbol of an IGBT	24
Figure 13 – Diagram of a three-phase 2-level converter and associated a.c. waveform for one phase.....	26
Figure 14 – Single-phase a.c. output for 2-level converter with PWM switching at 21 times fundamental frequency	27
Figure 15 – Diagram of a three-phase 3-level NPC converter and associated a.c. waveform for one phase.....	28
Figure 16 – Single-phase a.c. output for 3-level NPC converter with PWM switching at 21 times fundamental frequency	29
Figure 17 – Electrical equivalent for a converter with VSC valves acting like a controllable voltage source	30
Figure 18 – VSC valve level arrangement and equivalent circuit in MMC topology in half-bridge topology	30
Figure 19 – Converter block arrangement with MMC topology in half-bridge topology	31
Figure 20 – VSC valve level arrangement and equivalent circuit in MMC topology with full-bridge topology	32
Figure 21 – Typical SSOA for the IGBT.....	33
Figure 22 – A 2-level VSC bridge with the IGBTs turned off	33

Figure 23 – Representing a VSC unit as an a.c. voltage of magnitude U and phase angle δ behind reactance.....	40
Figure 24 – Concept of vector control	41
Figure 25 – VSC power controller	41
Figure 26 – A.C. voltage controller.....	42
Figure 27 – A typical simplified PQ diagram.....	44
Figure 28 – Protection concept of a VSC substation.....	47
Figure 29 – Waveforms for three-phase 2-level VSC.....	49
Figure 30 – Voltage harmonics spectra of a 2-level VSC with carrier frequency at 21st harmonic.....	50
Figure 31 – Phase output voltage for selective harmonic elimination modulation (SHEM).....	50
Figure 32 – Equivalent circuit at the PCC of the VSC.....	51
Figure B.1 – On state voltage of an IGBT or free-wheeling diode	69
Figure B.2 – Piecewise-linear representation of IGBT or FWD on-state voltage	70
Figure B.3 – IGBT switching losses as a function of collector current.....	73
Figure B.4 – Free-wheeling diode recovery loss as a function of current	74

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE DIRECT CURRENT (HVDC) POWER TRANSMISSION USING VOLTAGE SOURCED CONVERTERS (VSC)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC/TR 62543, which is a technical report, has been prepared by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment.

The present technical report cancels and replaces IEC/PAS 62543:2008 (Ed.1) which was published by IEC and CIGRÉ jointly, and combined with engineering experience.

The present IEC/TR 62543 bears the edition number 1.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
22F/230/DTR	22F/239A/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

A bilingual version of this publication may be issued at a later date.

HIGH-VOLTAGE DIRECT CURRENT (HVDC) POWER TRANSMISSION USING VOLTAGE SOURCED CONVERTERS (VSC)

1 Scope

This technical report gives general guidance on the subject of voltage-sourced converters used for transmission of power by high voltage direct current (HVDC). It describes converters that are not only voltage-sourced (containing a capacitive energy storage medium and where the polarity of d.c. voltage remains fixed) but also self-commutated, using semiconductor devices which can both be turned on and turned off by control action. The scope includes 2-level and 3-level converters with pulse-width modulation (PWM), along with multi-level converters, but excludes 2-level and 3-level converters operated without PWM, in square-wave output mode.

HVDC power transmission using voltage sourced converters is known as “VSC transmission”.

The various types of circuit that can be used for VSC transmission are described in the report, along with their principal operational characteristics and typical applications. The overall aim is to provide a guide for purchasers to assist with the task of specifying a VSC transmission scheme.

Line-commutated and current-sourced converters are specifically excluded from this report.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60633, *Terminology for high-voltage direct-current (HVDC) transmission*

IEC 61975, *High-voltage direct current (HVDC) installations – System tests*