



INTERNATIONAL STANDARD



**Surface acoustic wave (SAW) and bulk acoustic wave (BAW) duplexers of
assessed quality –
Part 2: Guidelines for the use**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.140

ISBN 978-2-8322-5081-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	7
4 Technical considerations	7
5 Fundamentals of SAW and BAW duplexers.....	7
5.1 Basic function	7
5.1.1 General	7
5.1.2 TX filter response (filter response from TX port to antenna port).....	8
5.1.3 RX filter response (filter response from antenna port to RX port).....	9
5.1.4 Isolation (isolation from TX port to RX port)	9
5.2 Basic structure.....	10
5.3 Principle of operation.....	10
5.4 Diplexer	14
6 SAW and BAW duplexer characteristics.....	14
6.1 General conditions for SAW and BAW duplexers	14
6.2 Typical characteristics of SAW and BAW duplexers	16
6.2.1 UMTS duplexer.....	16
6.2.2 US CDMA duplexer.....	17
6.2.3 PCS CDMA duplexer	17
7 Application guidelines.....	21
7.1 Power durability	21
7.2 Harmonics and inter-modulation distortion	21
7.3 Measurement method for the duplexer	21
7.4 Electrostatic voltage protection	23
Bibliography.....	24
Figure 1 – Basic duplexer configuration	8
Figure 2 – Basic TX filter response example of SAW and BAW duplexers	9
Figure 3 – Basic RX filter response example of SAW and BAW duplexers.....	9
Figure 4 – Basic isolation characteristics example of SAW and BAW duplexers	10
Figure 5 – The block diagram of a duplexer	11
Figure 6 – Demanded condition of TX part for duplexers.....	12
Figure 7 – Phase rotation in TX part	13
Figure 8 – Demanded condition of RX part for duplexers	13
Figure 9 – Basic duplexer configuration	14
Figure 10 – Typical wide range frequency response of TX filter	15
Figure 11 – Typical wide range frequency response of RX filter for upper local system.....	15
Figure 12 – Phase shifter by microstrip line on the surface of a ceramic package	16
Figure 13 – Lumped element phase shifter	16
Figure 14 – Duplexer configuration	16
Figure 15 – Frequency characteristics of SAW duplexer for UMTS Band 1 system.....	18
Figure 16 – Frequency characteristics of a SAW duplexer for US CDMA system.....	19
Figure 17 – Frequency characteristics of BAW duplexer for PCS CDMA system)	20

Figure 18 – Four-port-type network analyzer for duplexer measurement	22
Figure 19 – Four-port-type network analyzer for measurement of a balanced RX port duplexer.....	23
Table 1 – Frequency allocation for typical LTE frequency division duplex (FDD) bands.....	8

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SURFACE ACOUSTIC WAVE (SAW) AND BULK ACOUSTIC WAVE (BAW) DUPLEXERS OF ASSESSED QUALITY –

Part 2: Guidelines for the use

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62604-2 has been prepared by IEC technical committee 49: Piezoelectric, dielectric and electrostatic devices and associated materials for frequency control, selection and detection.

This second edition cancels and replaces the first edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- duplexers are described;
- duplexers with a balanced RX port are considered in the measurement method subclause (7.3).

NOTE In this standard, SAW and BAW duplexers are treated simultaneously because both duplexers are used in the same manner especially in mobile phone systems and have same requirements of characteristics, test method and so on.

The text of this International Standard is based on the following documents:

CDV	Report on voting
49/1217/CDV	49/1251/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62604 series, published under the general title *Surface acoustic wave (SAW) and bulk acoustic wave (BAW) duplexers of assessed quality*, can be found on the IEC website.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SURFACE ACOUSTIC WAVE (SAW) AND BULK ACOUSTIC WAVE (BAW) DUPLEXERS OF ASSESSED QUALITY –

Part 2: Guidelines for the use

1 Scope

This part of IEC 62604 concerns duplexers which can separate receiving signals from transmitting signals and are key components for two-way radio communications, and which are generally used in mobile phone systems compliant with CDMA systems such as N-CDMA in second generation mobile telecommunication systems (2G), W-CDMA / UMTS (3G) or LTE (4G). While in 2G systems mainly dielectric duplexers have been used, the ongoing miniaturization in 3G and 4G mobile communication systems promoted the development and application of acoustic wave duplexers due to their small size, light weight and good electrical performance. While standard surface acoustic wave (SAW) duplexers have been employed for applications with moderate requirements regarding the steepness of individual filters, applications with narrow duplex gap (e.g. Bands 2, 3, 8, 25), i.e. the frequency gap between receiving and transmitting bands, require the application of temperature-compensated (TC) SAW or bulk acoustic wave (BAW) technology, because of their better temperature characteristics and resonator Q-factors.

It is neither the aim of these guidelines to explain theory, nor to attempt to cover all the eventualities which may arise in practical circumstances. These guidelines draw attention to some of the more fundamental questions, which should be considered by the user before he places an order for SAW and BAW duplexers for a new application. Such a procedure will be the user's insurance against unsatisfactory performance. Because SAW and BAW duplexers have very similar performance for the usage, it is useful and convenient for users that both duplexers are described in one standard.

Standard specifications, such as those of IEC, of which these guidelines form a part, and national specifications or detail specifications issued by manufacturers will define the available combinations of centre frequency, pass bandwidth and insertion attenuation for each sort of transmitting and receiving filters and the isolation level between transmitter and receiver ports, etc. These specifications are compiled to include a wide range of SAW and BAW duplexers with standardized performances. It cannot be over-emphasized that the user should, wherever possible, select his duplexers from these specifications, when available, even if it may lead to making small modifications to his circuit to enable the use of standard duplexers. This applies particularly to the selection of the nominal frequency band.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60862-1:2015, *Surface acoustic wave (SAW) filters of assessed quality – Part 1: Generic specification*

IEC 62575-1:2015, *Radio frequency (RF) bulk acoustic wave (BAW) filters of assessed quality – Part 1: Generic specification*