



TECHNICAL SPECIFICATION



**Nanomanufacturing – Key control characteristics –
Part 4-3: Nano-enabled electrical energy storage – Contact and coating
resistivity measurements for nanomaterials**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 07.030

ISBN 978-2-8322-2851-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms, definitions, acronyms and abbreviations	7
3.1 Terms and definitions	7
3.2 Acronyms and abbreviations.....	8
4 Sample preparation methods	8
4.1 General.....	8
4.2 Reagents	9
4.2.1 Casting slurry.....	9
4.2.2 Isolator substrates	9
4.2.3 Metal collector strips and sample layout	9
4.3 Preparation of the electrode nanomaterial test samples	9
5 Measurement of electric properties	10
5.1 General.....	10
5.2 Coating resistivity.....	10
5.2.1 Demarcation of method	10
5.2.2 Measurement of the sample thickness	10
5.2.3 Experimental procedures and measurement conditions	10
5.3 Contact resistivity.....	11
5.3.1 Demarcation of method	11
5.3.2 Experimental procedures and measurement conditions	11
6 Data analysis / interpretation of results	11
6.1 Coating resistivity.....	11
6.2 Contact resistivity.....	12
Annex A (informative) Case study	13
A.1 Sample preparation	13
A.2 Results for a supercap EDLC-electrode and a lithium-ion battery NCM-cathode.....	15
A.2.1 Linear correlation between current and voltage of the electrode coating resistance of a supercap electrode (ohmic behaviour).....	15
A.2.2 Results for coating resistivity.....	16
A.2.3 Results of measurement of contact resistivity	17
Bibliography	18
Figure 1 – Layout of the coating (left) and contact (right) resistivity measurement	9
Figure A.1 – Sample preparation	13
Figure A.2 – Construction steps	15
Figure A.3 – Correlation between current and voltage of the coating resistance of various supercap EDLC-electrodes (variation in amount of carbon black additive in the electrode recipe).....	15
Figure A.4 – Coating resistivity of supercap electrodes with variation in the amount of carbon black in the electrode composite recipe and sample thickness.....	16
Figure A.5 – Coating resistivity of NCM-based lithium-ion battery cathode with variation in the amount of NCM, binder to carbon black value and sample thickness.....	16

Figure A.6 – Contact resistivity of a supercap electrode in the state “as cast” and “densified”	17
Figure A.7 – Contact resistivity of a NCM-based lithium-ion battery cathode (81,3 vol.-% NCM) in the state “as cast” and “as densified”	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 4-3: Nano-enabled electrical energy storage – Contact and coating resistivity measurements for nanomaterials

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 62607-4-3, which is a Technical Specification, has been prepared by IEC technical committee 113: Nanotechnology standardization for electrical and electronic products and systems.

The text of this Technical Specification is based on the following documents:

Enquiry draft	Report on voting
113/239/DTS	113/263A/RVC

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62607 series, published under the general title *Nanomanufacturing – Key control characteristics*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International Standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The future utilization of renewable energy technologies including e-mobility for individual transportation significantly depends on the development of efficient systems for energy storage. From today's perspective, lithium-ion batteries, supercapacitors and their derivative concepts are regarded as the most promising innovative candidates.

A high energy density for the desired power and a long life time (recharge characteristics) are the two most important criteria for electrode materials. Because many electrochemically active materials such as metal oxides show an inherently lower and insufficient conductivity for the electron transport, composite materials with carbon nanomaterial content are used for optimization of the current flow in the electrodes of a battery. The electrochemical reactions and the ensuing energy density of the battery cells are influenced by the movement of electrons in a composite. Furthermore, the electronic contact resistivity between the electrode material and the metal collector is important to realize a low ohmic internal resistance of the battery or capacitor device.

This part of IEC 62607 provides standard methods to measure coating and contact resistivity of nano-enabled electrode materials and to evaluate the best combinations of the composite material recipes and fabrication technologies for carbon containing coatings of such nano-enabled electrodes. Following this method will allow comparison of the results of different research groups.

This standardized method is intended for comparing the contact and coating resistivity of composite materials with carbon nanomaterial content in the study stage, not for evaluating the electrode in end products.

The method is applicable for nano-enabled materials exhibiting function or performance only possible with nanotechnology, intentionally added to composite materials for measurable and significant improvement of the current flow in the electrodes of electrical energy storage devices.

In this context it is important to note that the percentage content of nanomaterial of the device in question has no direct relation to the applicability of this part of IEC 62607, because minute quantities of nanomaterial are frequently sufficient to improve the performance significantly.

The fraction of nanomaterials in electrodes, electrode coatings, separators or electrolyte is not of relevance for using this method.

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 4-3: Nano-enabled electrical energy storage – Contact and coating resistivity measurements for nanomaterials

1 Scope

This part of IEC 62607 provides a standardized test method for the measurement of contact and coating resistivity of nano-enabled electrode materials. This method will enable a customer to:

- a) decide whether or not a coating composite material is usable, and
- b) select best combinations of coating composite material with fabrication technologies suitable for their application.

This part of IEC 62607 includes:

- definitions of terminology used in this part of IEC 62607,
- recommendations for sample preparation,
- outlines of the experimental procedures used to measure and calculate the contact and coating resistivity,
- methods of interpretation of results and discussion of data analysis, and
- a case study.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 80004-1, *Nanotechnologies – Vocabulary – Part 1: Core terms*