



INTERNATIONAL STANDARD

**Plugs, socket-outlets and ship couplers for high-voltage shore connection
(HVSC) systems –
Part 1: General requirements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.120.30

ISBN 978-2-8322-7005-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	5
INTRODUCTION	7
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	9
4 General.....	15
4.1 General requirements.....	15
4.2 General notes on tests	15
5 Standard ratings.....	16
6 Classification.....	16
7 Marking.....	16
8 Dimensions.....	19
9 Protection against electric shock.....	19
10 Provisions for protective earthing	21
11 Terminals and terminations.....	22
11.1 Common requirements for terminals and terminations	22
11.2 Type of terminals	23
11.2.1 Conductor terminals.....	23
11.2.2 Conductors.....	23
11.2.3 Screw type terminals.....	26
11.2.4 Contact pressure.....	26
11.2.5 Clamping screws.....	26
11.3 Mechanical tests on terminals	26
12 Locking devices and interlocks	29
13 Resistance to ageing of rubber and thermoplastic material	30
14 General construction.....	30
15 Construction of socket-outlets and ship inlets.....	32
16 Construction of ship connectors	32
17 Construction of plugs	32
18 Degrees of protection.....	33
19 Insulation resistance, dielectric withstand and partial discharge tests.....	34
19.1 Insulation resistance and dielectric strength.....	34
19.2 Pilot contacts	34
19.3 Measurements.....	34
19.4 Dielectric withstand test for low voltage (LV) pilot contacts	35
19.5 Partial discharge test for high voltage (HV) power contacts	35
19.6 AC withstand test for HV power contacts.....	35
19.7 Subsequent tests	36
19.8 Verifications.....	36
20 Normal operation.....	37
21 Temperature rise.....	37
21.1 Permissible temperature rise.....	37
21.2 Surface temperature	38

22	Flexible cables and their connection.....	39
22.1	Means for cable clamping.....	39
22.2	Requirements for plugs and ship connectors.....	39
23	Mechanical strength.....	42
23.1	Impact resistance.....	42
23.2	Drop test.....	42
24	Screws, current-carrying parts and connections.....	43
25	Resistance to heat, to fire and to tracking.....	46
26	Corrosion and resistance to rusting.....	47
27	Conditional short-circuit current withstand test.....	48
27.1	General.....	48
27.2	Ratings and test conditions.....	48
27.3	Test circuit.....	48
27.4	Calibration.....	49
27.5	Test procedure.....	49
27.6	Behaviour of the accessory under test.....	49
27.7	Acceptance conditions.....	49
28	Electromagnetic compatibility.....	51
28.1	Immunity.....	51
28.2	Emission.....	51
	Bibliography.....	52
	Figure 1 – Diagram showing the use of the accessories.....	10
	Figure 2 – Pillar terminals.....	12
	Figure 3 – Screw terminals.....	12
	Figure 4 – Stud terminals.....	12
	Figure 5 – Saddle terminals.....	13
	Figure 6 – Lug terminals.....	13
	Figure 7 – Mantle terminals.....	14
	Figure 8 – Standard test finger.....	21
	Figure 9 – Gauges for testing insertability of round unprepared conductors having the maximum specified cross-section.....	25
	Figure 10 – Test apparatus for checking damage to conductors.....	27
	Figure 11 – Apparatus for testing the cable anchorage.....	40
	Figure 12 – Arrangement for mechanical strength test for plugs and ship connectors.....	43
	Figure 13 – Diagram of the test circuit for the verification of short-circuit current withstand of a three-phase accessory.....	50
	Figure 14 – Diagram of the test circuit for the verification of short-circuit current withstand of a three-phase and separate neutral accessory.....	51
	Table 1 – Size for connectable conductors.....	24
	Table 2 – Test values for flexing tests for copper conductors.....	28
	Table 3 – Test values for pull-out tests for copper conductors.....	29
	Table 4 – Test voltage for dielectric strength test of pilot contacts.....	35
	Table 5 – Dielectric withstand test voltage.....	36

Table 6 – Test current and conductor cross-section for temperature rise	38
Table 7 – Maximum surface temperatures	38
Table 8 – Flexible cable types and dimensions, including conductor sizes and wire type41	
Table 9 – Cable secureness test values	41
Table 10 – Screw sizes and torque test values	44

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PLUGS, SOCKET-OUTLETS AND SHIP COUPLERS FOR HIGH-VOLTAGE SHORE CONNECTION (HVSC) SYSTEMS –

Part 1: General requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62613-1 has been prepared by subcommittee 23H: Plugs, socket-outlets and couplers for industrial and similar applications, and for electric vehicles, of IEC technical committee 23: Electrical accessories.

This second edition cancels and replaces the first edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) extension of the scope to an unlimited number of pilot contacts (previously limited to 3);
- b) update of the Figures and deletion of their embedded texts;
- c) insertion of tables of keys whenever required by the Figures.

The text of this International Standard is based on the following documents:

CDV	Report on voting
23H/411/CDV	23H/442A/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types are used:

- requirements proper: in roman type;
- *test specifications: in italic type;*
- notes: in smaller roman type.

A list of all the parts in the IEC 62613 series, under the general title *Plugs, socket-outlets and ship couplers for high-voltage shore connection (HVSC) systems*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This part of IEC 62613 has been primarily written to address the needs of IEC/IEEE 80005-1 in terms of plugs, socket-outlets, ship connectors and ship inlets (hereafter referred to as "accessories"), to deliver electrical power to ships in ports. The purpose of IEC/IEEE 80005-1 is to define requirements that allow compliant ships to connect to compliant high-voltage shore power supplies through a compatible shore-to-ship connection.

These ships are described in IEC/IEEE 80005-1.

Ships that do not require connecting with standardized high-voltage shore power supplies as above may use accessories that are not covered by the standard sheets of IEC 62613-2, but they may find it impossible to connect to these shore supplies.

Low-voltage plugs, socket-outlets, ship connectors and ship inlets used for the connection of certain ship types to low-voltage shore power supplies can be found in IEC 60309 (all parts).

PLUGS, SOCKET-OUTLETS AND SHIP COUPLERS FOR HIGH-VOLTAGE SHORE CONNECTION (HVSC) SYSTEMS –

Part 1: General requirements

1 Scope

This part of IEC 62613 applies to accessories with

- three phases and earth with pilot contacts,
- one pole for neutral.

These accessories have rated currents not exceeding 500 A and rated operating voltages not exceeding 12 kV 50/60 Hz.

NOTE 1 In some countries, the term "ground" is used instead of "earth".

These accessories are primarily intended for use outdoors, in a seawater environment, for the shore supply of ships (ship-to-shore connection), in an ambient temperature within the range of -25 °C to $+45\text{ °C}$.

NOTE 2 In some countries, other ambient temperatures prevail and are considered.

These accessories are not intended for use in hazardous areas. In such locations where special conditions prevail, additional requirements can be necessary.

These accessories are intended to be connected to cables of copper or copper alloy only.

Socket-outlets or ship inlets incorporated in or fixed to electrical equipment are within the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-75, *Environmental testing – Part 2-75: Tests – Test Eh: Hammer tests*

IEC 60092 (all parts), *Electrical installations in ships*

IEC 60092-354, *Electrical installations in ships – Part 354: Single- and three-core power cables with extruded solid insulation for rated voltages 6 kV ($U_m = 7,2\text{ kV}$) up to 30 kV ($U_m = 36\text{ kV}$)*

IEC 60112, *Method for the determination of the proof and the comparative tracking indices of solid insulating materials*

IEC 60228, *Conductors of insulated cables*

IEC 60269-1, *Low-voltage fuses – Part 1: General requirements*

IEC 60269-2, *Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Examples of standardized systems of fuses A to K*

IEC 60502-4:2010, *Power cables with extruded insulation and their accessories for rated voltages from 1 kV ($U_m = 1,2$ kV) up to 30 kV ($U_m = 36$ kV) – Part 4: Test requirements on accessories for cables with rated voltages from 6 kV ($U_m = 7,2$ kV) up to 30 kV ($U_m = 36$ kV)*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60664-1, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests*

IEC 60695-2-11, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products (GWEPT)*

IEC 60695-10-2, *Fire hazard testing – Part 10-2: Abnormal heat – Ball pressure test method*

IEC 62262, *Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK code)*

IEC 62271-1, *High-voltage switchgear and controlgear – Part 1: Common specifications for alternating current switchgear and controlgear*

ASTM B117-1985, *Standard practice for operating salt spray (fog) apparatus*

IEEE 1580, *IEEE Recommended Practice for Marine Cable for Use on Shipboard and Fixed or Floating Facilities*