



INTERNATIONAL STANDARD



Fibre optics – Multimode launch conditions – Part 1: Launch condition requirements for measuring multimode attenuation

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.180.01

ISBN 978-2-8322-8398-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	5
4 Background on multimode launch conditions	6
5 Test source launch	7
5.1 General.....	7
5.2 Encircled flux	7
5.3 Encircled flux template illustration.....	7
5.4 Encircled flux target for attenuation measurement.....	8
5.5 Harmonization of multimode launch conditions to eliminate wavelength bias.....	9
5.6 Uncertainties expectations	10
5.7 Encircled flux limits	10
5.8 Practical limitations of multimode launch conditions	11
Bibliography.....	12
Figure 1 – EF template illustration for 50 µm core fibre cabling at 850 nm	8
Figure 2 – Wavelength comparison	9
Table 1 – EF target for 50 µm core fibre at 850 nm	8
Table 2 – EF target for 50 µm core fibre at 1 300 nm	8
Table 3 – EF target for 62,5 µm fibre at 850 nm	9
Table 4 – EF target for 62,5 µm fibre at 1 300 nm	9
Table 5 – Attenuation, threshold tolerance and confidence level	10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTICS – MULTIMODE LAUNCH CONDITIONS –

Part 1: Launch condition requirements for measuring multimode attenuation

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62614-1 has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

This first edition cancels and replaces IEC 62614, published in 2010, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62614:

- a) increase of the value of the uncertainty attenuation variation coefficient Y for 50 μm core fibre at 1 300 nm, due to launch conditions, to twice the previous value;
- b) changes to 3.4, 5.6, including Table 5, and some references to remain consistent with IEC 61280-4-1:2019;
- c) changes to multimode fibre references to be consistent with IEC 60793-2-10:2019.

The text of this International Standard is based on the following documents:

CDV	Report on voting
86C/1625/CDV	86C/1654A/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62614 series, published under the general title *Fibre optics – Multimode launch conditions*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

FIBRE OPTICS – MULTIMODE LAUNCH CONDITIONS –

Part 1: Launch condition requirements for measuring multimode attenuation

1 Scope

This part of IEC 62614 describes the launch condition requirements used for measuring multimode attenuation in passive components and in installed cable plants.

In this document, the fibre types that are addressed include category A1-OM_x, where $x = 2, 3, 4$ and 5 ($50\ \mu\text{m}/125\ \mu\text{m}$), and A1-OM₁ ($62,5\ \mu\text{m}/125\ \mu\text{m}$) multimode fibres, as specified in IEC 60793-2-10. The nominal test wavelengths detailed are 850 nm and 1 300 nm. This document can be suitable for multimode attenuation measurements for other multimode categories and/or other wavelengths, but the source condition for other categories and wavelengths are not defined here.

The purpose of these requirements is as follows:

- to ensure consistency of field measurements when different types of test equipment are used;
- to ensure consistency of factory measurements when different types of test equipment are used;
- to ensure consistency of field measurements when compared with factory measurements.

This document describes launch condition requirements for optical attenuation using sources with a controlled encircled flux (EF).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61280-1-4, *Fibre optic communication subsystem test procedures – Part 1-4: General communication subsystems – Light source encircled flux measurement method*