

This is a preview - click here to buy the full publication



**IEC 62616**

Edition 1.0 2010-02

# **INTERNATIONAL STANDARD**

---

**Maritime navigation and radiocommunication equipment and systems – Bridge  
navigational watch alarm system (BNWAS)**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

**Q**

---

ICS 47.020.70

ISBN 978-2-88910-774-2

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references .....	6
3 Performance requirements .....	7
3.1 Functionality.....	7
3.1.1 Operational modes .....	7
3.1.2 Operational sequence of indications and alarms .....	7
3.1.3 Reset function .....	8
3.1.4 Emergency call facility and transfer of alarms .....	9
3.2 Accuracy .....	9
3.3 Security.....	9
3.4 Malfunctions, alarms and indications .....	10
4 Ergonomic criteria requirements .....	10
4.1 Operational controls .....	10
4.2 Presentation of information.....	10
4.2.1 Operational mode .....	10
4.2.2 Visual indications .....	10
4.2.3 First stage bridge audible alarm.....	10
4.2.4 Second and third stage remote audible alarm .....	10
5 Design and installation requirements .....	11
5.1 General.....	11
5.2 Specific requirements .....	11
5.2.1 System physical integrity .....	11
5.2.2 Reset devices.....	11
5.3 Power supply.....	11
5.4 Installation documentation.....	11
6 Interfacing requirements .....	11
6.1 Inputs.....	11
6.2 Outputs .....	12
7 Methods of testing and required test results .....	12
7.1 General.....	12
7.2 General requirements.....	12
7.3 Display of information.....	13
7.4 Operational tests.....	13
7.4.1 Operational modes .....	13
7.4.2 Dormant period.....	13
7.4.3 Alarms.....	13
7.4.4 Alarm alternatives.....	13
7.4.5 Description of reset function .....	13
7.4.6 Initiation of reset function .....	13
7.4.7 Continuous activation .....	14
7.4.8 Emergency call facility and transfer of alarms .....	14
7.4.9 Accuracy .....	14
7.4.10 Security.....	14
7.4.11 Malfunction.....	14
7.4.12 Operational controls .....	14

7.4.13	Operational mode .....	14
7.4.14	Visual indications .....	15
7.4.15	First stage bridge audible alarm.....	15
7.4.16	Second and third stage remote audible alarm .....	15
7.4.17	Design and installation general.....	15
7.4.18	System physical integrity .....	15
7.4.19	Reset devices.....	15
7.4.20	Power supply.....	15
7.4.21	Installation documentation .....	15
7.4.22	Interfacing .....	15
Annex A (normative)	Installation considerations.....	16
Bibliography	.....	17
Figure 1	– Alarm sequence without acknowledgements.....	7

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – BRIDGE NAVIGATIONAL WATCH ALARM SYSTEM (BNWAS)

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62616 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/577/FDIS	80/588/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this document may be issued at a later date.

The contents of the corrigendum of July 2012 have been included in this copy.

## MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – BRIDGE NAVIGATIONAL WATCH ALARM SYSTEM (BNWAS)

### 1 Scope

This International Standard specifies the minimum performance requirements, technical characteristics and methods of testing, and required test results, for a bridge navigational watch alarm system (BNWAS) as required by Chapter V of the International Convention for the Safety of Life at Sea (SOLAS), as amended. It takes account of the general requirements given in IMO resolution A.694(17) and is associated with IEC 60945. When a requirement in this International Standard is different from IEC 60945, the requirement in this standard takes precedence.

This standard incorporates the parts of the performance standards included in IMO resolution MSC.128(75).

NOTE 1 All text of this standard, whose wording is identical to that of IMO resolution MSC.128(75), is printed in italics, and the resolution and associated performance standard paragraph numbers are indicated in brackets.

*(128/A1) The purpose of a bridge navigational watch alarm system (BNWAS) is to monitor bridge activity and detect operator disability which could lead to marine accidents. The system monitors the awareness of the Officer of the Watch (OOW) and automatically alerts the Master or another qualified OOW if for any reason the OOW becomes incapable of performing the OOW's duties. This purpose is achieved by a series of indications and alarms to alert first the OOW and, if he is not responding, then to alert the Master or another qualified OOW. Additionally, the BNWAS may provide the OOW with a means of calling for immediate assistance, if required. The BNWAS should be operational whenever the ship is underway at sea (SOLAS V/19.2.2.3).*

NOTE 2 BNWAS may not, in practice, be realised as a stand alone equipment. It may be integrated in other equipment such as radar, ECDIS, etc.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements – Methods of testing and required results*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the Global maritime distress and safety system and for electronic navigational aids*

IMO Resolution A.813(19), *General requirements for electromagnetic compatibility (EMC) for all electrical and electronic ship's equipment*

IMO Resolution A.830(19), *Code on alarms and indicators*

IMO Resolution MSC.128(75), *Recommendation on performance standards for a bridge navigational watch alarm system (BNWAS)*

IMO MSC/Circ.982, *Guidelines on Ergonomic Criteria for Bridge equipment and Layout*