



INTERNATIONAL STANDARD



**3D display devices –
Part 13-1: Visual inspection methods for stereoscopic displays using glasses –
Ghost image**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-4867-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Standard visual inspection conditions	6
4.1 Environmental conditions	6
4.2 Setup conditions	7
4.2.1 Standard visual inspection distance and standard observing point	7
4.2.2 Setup conditions of stereoscopic display	7
4.2.3 Warm-up conditions of display modules and glasses	7
4.3 Lighting conditions	7
4.4 Inspector conditions	8
4.5 Input signals	8
4.5.1 Signal format and field frequency of input video signal	8
4.5.2 Input signal pattern	8
5 Visual inspection methods	12
5.1 Purpose	12
5.2 Visual inspection equipment.....	12
5.3 Visual inspection conditions	12
5.4 Visual inspection procedure	13
5.4.1 Warm-up.....	13
5.4.2 Inspection of 2D artefact.....	13
5.4.3 Inspection of 3D ghost.....	13
5.5 Report.....	15
Annex A (informative) Measurement with two-dimensional light measuring device (LMD)	16
A.1 General.....	16
A.2 Measuring conditions	16
A.3 Measuring layout	16
A.4 Measuring method	16
A.5 Report.....	17
Annex B (informative) Signal format.....	18
Bibliography.....	19
Figure 1 – Top view of standard visual inspection layout.....	7
Figure 2 – Nine positions for the box patterns	8
Figure 3 – Example of box pattern at G_1 and G_2	9
Figure 4 – Example of input signal for the visual inspection of ghost at G_2 and G_1	11
Figure 5 – Example of input signal for 2D image comparison	12
Figure 6 – Example of ghost artefact.....	13
Figure 7 – Comparison of ghost artefact and bar of the different grey levels G_b in the box pattern	14
Figure A.1 – Top view of standard measuring layout using a two-dimensional LMD	16
Figure B.1 – Signal formats for stereoscopic display using glasses	18

Table 1 – Value of grey levels G_1 and G_2 for an 8-bit grey scale display.....	10
Table 2 – Example of visual inspection report at nine positions for grey levels $G_1 = 255$ and $G_2 = 0$	15
Table A.1 – Example of measurement report, using the input signal of nine-box pattern, grey levels $G_1 = 255$ and $G_2 = 0$	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

3D DISPLAY DEVICES –

Part 13-1: Visual inspection methods for stereoscopic displays using glasses – Ghost image

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62629-13-1 has been prepared by IEC technical committee 110: Electronic display devices.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
110/896/FDIS	110/912/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62629 series, published under the general title *3D display devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

3D DISPLAY DEVICES –

Part 13-1: Visual inspection methods for stereoscopic displays using glasses – Ghost image

1 Scope

This part of IEC 62629 specifies the visual inspection methods of ghost image. This document is applicable to stereoscopic displays using glasses.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61747-30-1:2012, *Liquid crystal display devices – Part 30-1: Measuring methods for liquid crystal displays modules – Transmissive type*

IEC 61988-2-1:2012, *Plasma display panels – Part 2-1: Measuring methods – Optical and optoelectrical*

IEC 62341-6-3:2012, *Organic light emitting diode (OLED) displays – Part 6-3: Measuring methods of image quality*

IEC 62629-1-2, *3D display devices – Part 1-2: Terminology and letter symbols*