

This is a preview - click here to buy the full publication



IEC 62629-22-1

Edition 2.0 2016-10

INTERNATIONAL STANDARD

**3D display devices –
Part 22-1: Measuring methods for autostereoscopic displays – Optical**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-3688-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	5
1 Scope	7
2 Normative references	7
3 Terms, definitions and abbreviated terms	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
4 Standard measuring conditions.....	8
4.1 Standard environmental conditions	8
4.1.1 Temperature, humidity and pressure conditions	8
4.1.2 Illumination conditions	8
4.2 Light measuring device	8
4.2.1 General	8
4.2.2 Aperture size	9
4.3 Measuring setup	9
4.3.1 Designed viewing distance	9
4.3.2 Measurement area.....	10
4.3.3 Measuring layout	10
4.4 Test signal	12
4.5 Standard measuring points	13
5 Measuring method for two-view and multi-view displays	14
5.1 Maximum luminance direction	14
5.1.1 General	14
5.1.2 Measuring equipment	14
5.1.3 Measuring conditions.....	15
5.1.4 Measuring procedure	15
5.1.5 Measurement report	15
5.2 Lobe angle and lobe angle variation on screen	16
5.2.1 General	16
5.2.2 Measuring equipment	16
5.2.3 Measuring conditions.....	16
5.2.4 Measuring procedure	17
5.2.5 Measurement report	17
5.3 Luminance, screen luminance uniformity, and angular luminance variation	18
5.3.1 Luminance and screen luminance uniformity.....	18
5.3.2 Angular luminance variation.....	19
5.4 White chromaticity, white chromaticity uniformity on screen, and white chromaticity variation in angle.....	20
5.4.1 White chromaticity and white chromaticity uniformity on screen	20
5.4.2 White chromaticity angular variation	22
6 Standard measuring method for integral imaging displays (1D/2D)	23
6.1 General.....	23
6.2 Lobe angle and lobe angle variation on screen	24
6.3 Luminance, screen luminance uniformity, and angular luminance variation	24
6.3.1 Luminance and screen luminance uniformity.....	24
6.3.2 Angular luminance variation.....	24

6.4	White chromaticity, white chromaticity uniformity on screen, and white chromaticity variation in angle.....	24
6.4.1	White chromaticity and white chromaticity uniformity on screen	24
6.4.2	White chromaticity variation in angle.....	24
7	Measuring method for 3D crosstalk related property	24
7.1	3D crosstalk (luminance components ratio), 3D crosstalk variation on screen, and 3D crosstalk variation in angle for two-view and multi-view displays.....	24
7.1.1	3D crosstalk (luminance components ratio) and 3D crosstalk variation on screen	24
7.1.2	3D crosstalk angular variation.....	27
7.2	3D crosstalk related property for multi-view display.....	28
7.2.1	General	28
7.2.2	Offset crosstalk	28
7.2.3	3D pixel crosstalk	30
Annex A (informative)	Principle of autostereoscopic display.....	35
A.1	General.....	35
A.2	Two-view display	35
A.3	Multi-view display	36
A.4	Integral imaging display	37
Annex B (informative)	Angular profile of luminance	39
Annex C (informative)	3D crosstalk based on one inter-pupil distance	40
C.1	General.....	40
C.2	Measuring equipment.....	41
C.3	Measuring conditions	41
C.4	Measuring procedure	41
C.5	Measuring report.....	41
Annex D (informative)	View density for motion parallax smoothness	44
D.1	General.....	44
D.2	Measuring equipment.....	44
D.3	Measuring conditions	44
D.4	Measuring procedure	44
D.5	Measuring report.....	44
Bibliography.....		46
Figure 1 – Measuring system		9
Figure 2 – Measuring layout for centre point measurement		10
Figure 3 – Measuring layout for multi-point measurement (side view).....		11
Figure 4 – Other measuring layout for multi-point measurement (side view).....		11
Figure 5 – Measuring layout for horizontal viewing direction dependency.....		12
Figure 6 – Measuring layout for vertical viewing direction dependency.....		12
Figure 7 – Two examples of the relation between pixel and lenslet in multi-view display		13
Figure 8 – Measuring points for the centre and multi-point measurement.....		14
Figure 9 – Example of n by m measuring points		14
Figure 10 – Example of measurement results for angular luminance profile		16
Figure 11 – Example of lobe angle measurement.....		17
Figure 12 – Example of 3D crosstalk variation on screen		25
Figure 13 – Example of acquired images in multi-view display		25

Figure 14 – Spatial luminance data acquisition (left) and example of calculated spatial crosstalk graph (right).....	26
Figure 15 – Example of minimum luminance and maximum luminance for offset crosstalk.....	29
Figure 16 – Example of adjacent overlap.....	30
Figure 17 – Example of slanted lens configuration where 4,688 sub-pixels in a row are covered in one lens pitch.....	31
Figure 18 – Measuring layout example for 3D pixel crosstalk for multi-view displays having dozens of perspective output images.....	32
Figure 19 – Example of luminance angular profile for a multi-view display having 28 views (perspective images).....	33
Figure A.1 – Structure of two-view display.....	35
Figure A.2 – Basic principle of two-view display.....	36
Figure A.3 – Structure of multi-view display.....	36
Figure A.4 – Basic principle of multi-view display.....	37
Figure A.5 – Basic principle of integral imaging display.....	37
Figure B.1 – Example of angular profile of luminance.....	39
Figure C.1 – Example image of a traditional multi-view display.....	40
Figure C.2 – Example image of the multi-view display having at least one view within one IPD.....	40
Figure C.3 – Example of luminance angular profile for a multi-view display having at least one view within one IPD (at designed viewing distance = 3,878 m).....	42
Table 1 – Example of reported specification of two-dimensional LMD.....	9
Table 2 – Example of measurement results for maximum luminance direction.....	16
Table 3 – Example of measurement results for lobe angle variation on screen.....	18
Table 4 – Example of measurement results for luminance and screen luminance non-uniformity.....	19
Table 5 – Example of measurement results for angular luminance variation.....	20
Table 6 – Example of measurement results for white chromaticity and white chromaticity uniformity on screen.....	22
Table 7 – Example of measurement results for white chromaticity variation in angle.....	23
Table 8 – Example of measurement results for 3D crosstalk variation on screen.....	27
Table 9 – Example of measurement results for 3D crosstalk angular variation.....	28
Table 10 – Example of measurement results for offset crosstalk.....	30
Table 11 – Example of 3D pixel crosstalk calculation results.....	34
Table B.1 – Example of measurement results.....	39
Table C.1 – Example of measurement results for 3D crosstalk based on one IPD.....	43
Table D.1 – Example of measurement results for motion parallax smoothness.....	45

INTERNATIONAL ELECTROTECHNICAL COMMISSION

3D DISPLAY DEVICES –

Part 22-1: Measuring methods for autostereoscopic displays – Optical

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62629-22-1 has been prepared by IEC technical committee 110: Electronic display devices.

This second edition cancels and replaces the first edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of offset crosstalk and 3D pixel crosstalk as 3D crosstalk related property.

The text of this standard is based on the following documents:

FDIS	Report on voting
110/784/FDIS	110/797/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62629 series, under the general title *3D display devices*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

3D DISPLAY DEVICES –

Part 22-1: Measuring methods for autostereoscopic displays – Optical

1 Scope

This part of IEC 62629-22 specifies optical measuring methods for autostereoscopic display devices. It defines general measuring procedures for optical characteristics of two-view and multi-view displays and integral imaging displays.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62629-1-2, *3D display devices – Part 1-2: Generic – Terminology and letter symbols*

ISO/CIE 19476, *Characterization of the performance of illuminance meters and luminance meters*

CIE 15:2004, *Colorimetry*