

This is a preview - click here to buy the full publication



IEC/TR 62730

Edition 1.0 2012-03

TECHNICAL REPORT

**HV polymeric insulators for indoor and outdoor use tracking and erosion testing
by wheel test and 5 000h test**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

R

ICS 29.080.10

ISBN 978-2-8322-0070-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|--|----|
| FOREWORD..... | 3 |
| INTRODUCTION..... | 5 |
| 1 Scope and object..... | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions | 6 |
| 4 Background to the tracking and erosion tests | 8 |
| 4.1 Difference between the tracking and erosion and accelerated ageing tests on polymeric insulators | 8 |
| 4.2 The wheel test..... | 8 |
| 4.3 The 5 000h multiple stress test..... | 9 |
| 5 Classification of tests | 10 |
| 6 General requirements for insulator test specimens | 10 |
| 7 The tests | 10 |
| 7.1 Wheel test..... | 10 |
| 7.1.1 Test specimens | 10 |
| 7.1.2 Procedure..... | 10 |
| 7.1.3 Test conditions | 12 |
| 7.1.4 Acceptance criteria..... | 12 |
| 7.2 5 000 hour test (test at multiple stresses)..... | 12 |
| 7.2.1 Test specimen | 12 |
| 7.2.2 Procedure..... | 12 |
| 7.2.3 Test conditions | 13 |
| 7.2.4 Voltage..... | 15 |
| 7.2.5 Solar simulation..... | 15 |
| 7.2.6 Artificial rain | 15 |
| 7.2.7 Dry heat | 16 |
| 7.2.8 Humidity | 16 |
| 7.2.9 Pollution | 16 |
| 7.2.10 Salt fog calibration..... | 16 |
| 7.2.11 Acceptance criteria..... | 18 |
| Bibliography..... | 19 |
| Figure 1 – Test arrangement of the tracking wheel test..... | 11 |
| Figure 2 – Typical layout of the test specimens in the chamber and main dimensions of the chamber..... | 13 |
| Figure 3 – Multiple stress cycle..... | 14 |
| Figure 4 – Typical layout of the rain and salt fog spray systems and the xenon lamp | 14 |
| Figure 5 – Spectrum of xenon arc lamp and solar spectrum | 15 |
| Figure 6 – Reference porcelain insulator..... | 17 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HV POLYMERIC INSULATORS FOR INDOOR AND OUTDOOR USE TRACKING AND EROSION TESTING BY WHEEL TEST AND 5 000H TEST

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62730, which is a technical report, has been prepared by IEC technical committee 36: Insulators.

The text of this technical report is based on the following documents:

| | |
|---------------|------------------|
| Enquiry draft | Report on voting |
| 36/305/DTR | 36/316A/RVC |

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

IEC 62217 [1]¹ included three different tracking and erosion tests. One, the 1 000 hour salt-fog test, was included in the main text as a default test and two others, the 5 000 hour test and the tracking wheel test, were given in annexes as alternative tests.

Following a decision by TC 36 it was decided that it was desirable to have a single standardised test in IEC 62217; hence a study of the usage and effectiveness of all three tests was undertaken by Working Group 12 of TC 36. The results of this study indicated that, while the 5 000h and the tracking wheel tests each had their advantages, only the 1 000 hour salt fog test was adapted to all insulator types and was more economical to perform.

It was decided by TC 36 to adopt the 1 000 hour salt-fog test as the only standardised test. It was also decided to draft this Technical Report to reproduce the 5 000 hour and the tracking wheel test procedures in order to keep the information on the test methods and parameters available for those wishing to use those tests for research or other purposes.

The tracking and erosion tests given in this technical report are considered as screening tests intended to reject materials or designs which are inadequate. These tests are not intended to predict long-term performance for insulator designs under cumulative service stresses.

Composite insulators are used in both a.c. and d.c. applications. In spite of this fact a specific tracking and erosion test procedure for d.c. applications as a design test has not yet been defined and accepted.

IEC Guide 111 has been followed during preparation of this technical report wherever possible.

¹ Numbers in square brackets refer to the Bibliography.

HV POLYMERIC INSULATORS FOR INDOOR AND OUTDOOR USE TRACKING AND EROSION TESTING BY WHEEL TEST AND 5 000H TEST

1 Scope and object

This technical report is applicable to polymeric insulators whose insulating body consists of one or various organic materials. Polymeric insulators covered by this technical report include both solid core and hollow insulators. They are intended for use on overhead lines and in indoor and outdoor equipment with a rated voltage greater than 1 000 V.

The object of this technical report is:

- to define the common terms used;
- to give the background behind the development and use of the 5 000 h multiple stress test and the tracking wheel test;
- to describe the test methods for the 5 000 h multiple stress test and the tracking wheel tests on polymeric insulators;
- to describe possible acceptance or failure criteria, if applicable;

These tests, criteria and recommendations are intended to give a common basis for the 5 000h multiple stress test and the tracking wheel test when they are used for research or required as a supplementary design test. These tests are not mandatory and their use is subject to prior agreement between the interested parties.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-47:2007, *International Electrotechnical Vocabulary – Part 471: Insulators*

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements.*

IEC 60507, *Artificial pollution tests on high-voltage insulators to be used on a.c. systems*

IEC 60815-2, *Selection and dimensioning of high-voltage insulators intended for use in polluted conditions – Part 2: Ceramic and glass insulators for a.c. systems*