

This is a preview - click here to buy the full publication



IEC 62746-10-1

Edition 1.0 2018-11

INTERNATIONAL STANDARD



**Systems interface between customer energy management system and the
power management system –
Part 10-1: Open automated demand response**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.200

ISBN 978-2-8322-6228-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	10
3.1 Terms and definitions.....	10
3.2 Abbreviated terms.....	11
4 Overview	12
4.1 General.....	12
4.2 Node and device types.....	13
4.3 IEC 62746-10-1 services.....	14
4.4 Assumptions	15
5 IEC 62746-10-1 features.....	15
5.1 General.....	15
5.2 Supported services	15
5.3 Report Only VENs.....	15
5.4 Transport mechanism	15
5.5 Security	15
6 Services and data model extensions.....	15
6.1 Event service	15
6.1.1 Event interactions.....	15
6.1.2 oadrEvent mechanism	19
6.2 Report service	23
6.2.1 General	23
6.2.2 Core reporting operations	25
6.3 Registration service	30
6.3.1 Service operations.....	30
6.3.2 Registration information.....	33
6.4 Opt service	34
6.4.1 Service operations.....	34
6.4.2 Detail requirements	35
6.5 Poll service	36
6.6 Application error codes	39
7 Transport protocol	40
7.1 General.....	40
7.2 Simple HTTP	40
7.2.1 General	40
7.2.2 PUSH and PULL implementation	40
7.2.3 Service endpoint URIs	41
7.2.4 HTTP methods.....	41
7.2.5 Failure conditions	41
7.2.6 HTTP response codes	41
7.2.7 Message timeouts.....	42
7.2.8 Message retry/quiesce behaviour	42
7.2.9 PULL timing.....	42
7.2.10 HTTP headers	43

7.3	Transport-specific security	44
7.3.1	General	44
7.3.2	TLS client certificate	44
7.4	XMPP	44
7.4.1	General	44
7.4.2	Exchange model implementation	44
7.4.3	Service endpoints	44
7.4.4	Service execution	45
7.4.5	Implementation of XMPP features	45
7.4.6	Security considerations	48
8	Cyber security	49
8.1	General	49
8.2	Architecture and certificate types	49
8.3	Certificate authorities	50
8.4	Certificate revocation	50
8.5	TLS and cipher suites	50
8.6	System registration process	50
8.6.1	General	50
8.6.2	Certificate fingerprints	50
8.7	Implementing XML signatures for message payloads	51
8.7.1	XML signature	51
8.7.2	Components of XML signatures	51
8.7.3	Creating XML signatures	52
8.7.4	Verifying XML signatures	53
9	Conformance	53
9.1	Conformance statement	53
9.2	Conformance rules	53
9.2.1	EiEvent	53
9.2.2	EiEvent – Additional 2.0b conformance rules	61
9.2.3	EiOpt	63
9.2.4	EiReport	65
9.2.5	EiRegisterParty	71
9.2.6	General conformance rules	73
9.3	Cardinality	76
Annex A (normative)	Detailed report description	77
Annex B (normative)	Profile extensions	78
B.1	Overview	78
B.2	Report extension	78
B.3	Event extension	78
B.4	Other extensions	78
Annex C (normative)	oadrPoll scenarios	79
C.1	Overview	79
C.2	Scenarios	79
Annex D (normative)	Definition of VEN, VTN, resource, and party	81
Annex E (normative)	IEC 62746-10-1 Schema	82
Bibliography	206

Figure 1 – Possible relationships of VTN and VEN	14
--	----

Figure 2 – EiEvent PUSH pattern	16
Figure 3 – EiEvent PULL pattern	17
Figure 4 – Time intervals of an event	19
Figure 5 – Report type	24
Figure 6 – Interaction diagram: Register reporting capabilities	26
Figure 7 – Interaction diagram: Request reports	27
Figure 8 – Interaction diagram: Send reports	29
Figure 9 – Interaction diagram: Cancel reports.....	30
Figure 10 – Interaction diagram: Query registration	31
Figure 11 – Interaction diagram: Create registration	31
Figure 12 – Interaction diagram: Request reregistration	32
Figure 13 – Interaction diagram: Cancel registration	32
Figure 14 – Interaction diagram: Create opt.....	35
Figure 15 – Interaction diagram: Cancel opt.....	35
Figure 16 – Interaction diagram: oadrPoll (nothing in queue)	37
Figure 17 – Interaction diagram: oadrPoll (oadrDistributeEvent reply).....	38
Figure 18 – Interaction diagram: oadrPoll (oadrCreateReport reply).....	38
Figure 19 – Interaction diagram: oadrPoll (request reregistration reply)	39
Figure 20 – XML signature example	52
Table 1 – IEC 62746-10-1 services support	13
Table 2 – Signals	21
Table 3 – EiRegisterParty payloads	30
Table 4 – VEN information in oadrCreatePartyRegistration payload	33
Table 5 – VTN information oadrCreatedPartyRegistration payload	34
Table 6 – EiOpt payloads	34
Table 7 – Conformance rules	54
Table 8 – Additional conformance rules	61
Table 9 – EiOpt conformance rules	63
Table 10 – EiReport conformance rules	65
Table 11 – EiRegisterParty conformance rules.....	71
Table 12 – General conformance rules.....	73
Table 13 – Cardinalities	76

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SYSTEMS INTERFACE BETWEEN CUSTOMER ENERGY
MANAGEMENT SYSTEM AND THE POWER MANAGEMENT SYSTEM –**

Part 10-1: Open automated demand response

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62746-10-1 has been prepared by IEC project committee 118: Smart grid user interface.

The text of this International Standard is based on the following documents:

CDV	Report on voting
118/91/CDV	118/96B/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62746 series, published under the general title *Systems interface between customer energy management system and the power management system*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Development of the demand response (DR) market has resulted in a transition from manual DR to OpenADR (this document) in automated DR programs. DR is defined as an action taken to reduce electricity demand in response to price, monetary incentives, or utility directives so as to maintain reliable electric service or avoid high electricity prices. This document was developed to support common auto-DR programs and energy policy objectives to move toward dynamic markets to improve the economics and reliability of the electricity grid. The recent developments have expanded the use of this document to meet diverse market needs, such as ancillary services, dynamic prices, intermittent renewable resources, supplement grid-scale storage, electric vehicles, and load as generation. For example, with real-time price information, an automated client within the customer facility can be designed to continuously monitor these prices and translate this information into continuous automated control and response strategies.

This document's communication has the following defining features:

- Continuous, secure, and reliable – Provides continuous, secure, and reliable two-way communications where the endpoints at the end-use site receive and acknowledge the receipt of DR signals from the energy service providers.
- Translation – Translates DR event information to internet signals to facilitate DR automation. These signals are designed to interoperate with energy management and control systems, lighting, or other end-use controls.
- Automation – Receipt of the external signal is designed to initiate automation through the use of pre-programmed demand response strategies determined and controlled by the end-use participant.
- Opt-out – Provides opt-out or override function to any participants for a DR event if the event comes at a time when changes in end-use services are not desirable.
- Complete data model – Describes a rich data model and architecture to communicate price, reliability, and other DR activation signals.
- Scalable architecture – Provides scalable communications architecture to different forms of DR programs, end-use buildings, and dynamic pricing.
- Open standards – Open standards-based technology such as internet protocol (IP) and web services form the basis of the communications model.

This document is a communications data model, along with transport and security mechanisms, which facilitate information exchange between two end-points: the electricity service provider or DR program operator, and a customer-side resource. It is not a protocol that specifies "bit-structures" as some communications protocols do, but instead relies upon existing open standards such as Extensible Markup Language (XML) and internet protocol (IP) as the framework for exchanging DR signals. In some references, the term "system," "technology," or "service" is used to refer to the features of this document.

IEC 62746-10-1 is designed to facilitate automation of DR actions at the customer location, whether it involves electric load decreases, load increases, or load shifting for various demand response markets. Many emergency or reliability DR events occur at specific times when the electricity grid is strained. The communications are designed to coordinate such signals with facility control systems (commercial, industrial, and residential). This document is also designed to provide continuous dynamic price signals, such as hourly, day-ahead, or day-of real-time pricing. With such price information, an automated client can be configured to continuously monitor these prices and translate this information into continuous automated control and response within a facility. Several reports present the history of this document and the involved research. This document covers the signalling data models for price and reliability signals to both wholesale and retail markets, and can act as a complementary standard to a CIM-based grid control system.

This document provides the following benefits:

- Open specification – Provides a standardized DR communications and signalling infrastructure using open, non-proprietary, industry-approved data models that can be implemented for both dynamic prices and DR emergency or reliability events.
- Flexibility – Provides open communications interfaces and protocols that are flexible, platform-independent, interoperable, and transparent to end-to-end technologies and software systems.
- Innovation and interoperability – Encourages open innovation and interoperability, and allows controls and communications within a facility or enterprise to build on existing strategies to reduce technology operation and maintenance costs, stranded assets, and obsolescence in technology.
- Ease of integration – Facilitates integration of common energy management and control systems (EMCS), centralised lighting, and other end-use devices that can receive internet signals (such as XML).
- Supports a wide range of information complexity – Can express the information in the DR signals in a variety of ways to allow for systems ranging from simple end devices (e.g. thermostats) to sophisticated intermediaries (e.g. aggregators) to receive the DR information that is best suited for its operations.

This document's purpose is to manage the growing demand for demand-side flexibility – the ability to modify the load profile of the consumers over time. This low-cost communications infrastructure is used to improve the reliability, repeatability, robustness, and cost-effectiveness of DR.

This technology has been field tested for over a decade and deployed in a number of DR programs worldwide. While the scope of this document focuses on signals for DR events and prices, significant supporting research work has been done to study DR strategies and techniques to automate DR within facilities. This document interacts with facility control systems that are pre-programmed to take action based on a DR signal, enabling a response to a DR event or a price to be fully automated, with no manual intervention.

SYSTEMS INTERFACE BETWEEN CUSTOMER ENERGY MANAGEMENT SYSTEM AND THE POWER MANAGEMENT SYSTEM –

Part 10-1: Open automated demand response

1 Scope

This part of IEC 62746-10, OpenADR 2.0 (this document), specifies a minimal data model and services for demand response (DR), pricing, and distributed energy resource (DER) communications. This document can be leveraged to manage customer energy resources, including load, generation, and storage, via signals provided by grid and/or market operators. These resources can be identified and managed as individual resources with specific capabilities, or as virtual resources with an aggregated set of capabilities.

This document specifies how to implement a two-way signaling system to facilitate information exchange between electricity service providers, aggregators, and end users. The DR signalling system is described in terms of servers (virtual top nodes or VTNs), which publish information to automated clients (virtual end nodes, or VENs), which in turn subscribe to the information.

This document provides application-level service communication that can be used to incentivise a response from a customer-owned DER. Price and DR signals over the internet allow indirect control of customer-owned devices that otherwise would not be available.

This document's services are independent of transport mechanisms. For the purposes of interoperability, this document provides basic transport mechanisms and their relevant interaction patterns to address different stakeholder needs. In addition, this document specifies cyber security mechanisms required for data confidentiality, integrity, authentication and message-level security, in order to provide non-repudiation and mitigation of cyber security risks.

The services make no assumption of specific DR electric load control strategies that can be used within a DR resource or of any market-specific contractual or business agreements between electricity service providers and their customers.

This document provides a clear set of mandatory and optional attributes within each of the services to meet broader interoperability, testing and certification requirements. All necessary XML schema are included in Annex E.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

INTERNET ENGINEERING TASK FORCE (IETF). RFC 2616: *Hypertext Transfer Protocol – HTTP/1.1* [online]. Edited by R. Fielding et al. June 1999 [viewed 2018-08-02]. available at: <http://www.ietf.org/rfc/rfc2616.txt>

INTERNET ENGINEERING TASK FORCE (IETF). RFC 3986: *Uniform Resource Identifier (URI): Generic Syntax* [online]. Edited by T. Berners-Lee et al. January 2005 [viewed 2018-08-02]. available at:
<http://www.ietf.org/rfc/rfc3986.txt>

INTERNET ENGINEERING TASK FORCE (IETF). RFC 5246: *The Transport Layer Security (TLS) Protocol Version 1.2* [online]. Edited by T. Dierks et al. August 2008 [viewed 2018-08-02]. available at
<https://tools.ietf.org/html/rfc5246>

INTERNET ENGINEERING TASK FORCE (IETF). RFC 6120: *Extensible Messaging and Presence Protocol (XMPP): Core* [online]. Edited by P. Saint-Andre. March 2011 [viewed 2018-08-02]. available at:
<http://www.ietf.org/rfc/rfc6120.txt>

INTERNET ENGINEERING TASK FORCE (IETF). RFC 6121: *Extensible Messaging and Presence Protocol (XMPP): Instant Messaging and Presence* [online]. Edited by P. Saint-Andre. March 2011 [viewed 2018-08-02]. available at:
<http://www.ietf.org/rfc/rfc6121.txt>

XMPP Standards Foundation. *XEP-0030: Service Discovery* [online]. Edited by J. Hildebrand et al. October 2017 [viewed 2018-08-02]. available at:
<http://xmpp.org/extensions/xep-0030.html>