



INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Semiconductor devices – Semiconductor interface for human body
communication –
Part 4: Capsule endoscope**

**Dispositifs à semiconducteurs – Interface à semiconducteurs
pour les communications via le corps humain –
Partie 4: Capsule endoscopique**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.080.01

ISBN 978-2-8322-7804-8

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and letter symbols.....	6
3.1 General terms	6
3.2 Rating and characteristics.....	8
3.2.1 Capsule endoscope characteristics.....	8
3.2.2 Receiving device characteristics	8
3.2.3 Transfer characteristics	8
3.3 Letter symbols	10
4 General requirements	10
4.1 General specifications.....	10
4.1.1 General	10
4.1.2 Function	10
4.1.3 Implementation types.....	12
4.2 Constructional specifications.....	12
4.3 Electrical specifications.....	12
4.3.1 General	12
4.3.2 Power supply characteristics	12
4.3.3 Power supply type	13
4.3.4 Dynamic characteristics of driver in capsule endoscope.....	13
4.3.5 Dynamic characteristics of analog front end.....	13
4.3.6 CDR circuit interface.....	14
4.3.7 Modem interface.....	14
4.3.8 Limiting values.....	14
4.3.9 Temperatures	15
4.4 Operating specifications.....	15
4.4.1 Main application	15
4.4.2 Compatibility.....	15
Annex A (informative) General description of capsule endoscope using human body communication.....	16
Figure 1 – Definition of cut-off frequency and bandwidth.....	9
Figure 2 – Typical example of semiconductor interface structure for capsule endoscope using galvanic coupling human body communication.....	11
Figure 3 – Typical example of data recovery circuit (DRC).....	12
Figure A.1 – Capsule endoscope application.....	17
Table 1 – Letter symbols.....	10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SEMICONDUCTOR DEVICES –
SEMICONDUCTOR INTERFACE FOR HUMAN BODY COMMUNICATION –**

Part 4: Capsule endoscope

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62779-4 has been prepared by IEC technical committee 47: Semiconductor devices.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
47/2600/FDIS	47/2611/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62779 series, published under the general title *Semiconductor devices – Semiconductor interface for human body communication*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 62779-1, IEC 62779-2 and IEC 62779-3 define the general requirements, measurement method and functional type of a semiconductor interface for human body communication. They include the general and functional specifications of the interface, the electrical performances of an electrode, and the operational conditions of the interface. However, an in-body to on-body channel for a capsule endoscope using galvanic coupling human body communication (HBC) is different from the channel that is described in IEC 62779-1, IEC 62779-2 and IEC 62779-3 using capacitive coupling human body communication (i.e. channel properties, such as signal loss and signal propagation mechanism, are different). Therefore, the semiconductor interface covered by IEC 62779-1, IEC 62779-2 and IEC 62779-3 cannot be used for the capsule endoscope using galvanic coupling human body communication. A common interface for a capsule endoscope using human body communication should be defined to secure communication compatibility between various capsule endoscope devices and receiving devices that are implemented on or inside the human body.

SEMICONDUCTOR DEVICES – SEMICONDUCTOR INTERFACE FOR HUMAN BODY COMMUNICATION –

Part 4: Capsule endoscope

1 Scope

This part of IEC 62779 defines general requirements on the electrical performances of a semiconductor interface for capsule endoscope using galvanic coupling human body communication. It includes general and functional specifications of the interface. The semiconductor interface that is covered in this document is the interface to handle or deliver an electrical signal between the capsule endoscope inside the human body and the HBC modem in the receiving device outside the human body.

NOTE Additional information on capsule endoscope using the human body communication is provided in Annex A.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEEE 802.15.6:2012, *IEEE Standard for Local and Metropolitan area networks – Part 15.6: Wireless Body Area Networks*