



TECHNICAL SPECIFICATION



**Industrial electroheating and electromagnetic processing equipment –
Requirements on touch currents, voltages and electric fields from 1 kHz
to 6 MHz**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 25.180.10

ISBN 978-2-8322-4798-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	9
2 Normative references	9
3 Terms and definitions	9
4 Organization and use of this document.....	11
5 Prospective source voltage limits.....	12
6 Assessment of the source impedance.....	12
7 Touching and access considerations	13
7.1 General.....	13
7.2 Primary contact areas	13
7.3 Special protective gloves, footwear and clothing	13
7.4 External metallic objects and tools	14
7.5 Considerations for the secondary contact area assessment	14
8 Impedances of parts of the body, and touch current densities.....	14
8.1 General.....	14
8.2 The equivalent circuit of skin and parts of the body.....	15
8.3 Touch current density consideration for large contact areas.....	16
9 Capacitively coupled currents in the body due to an external electric field or insulated live part	16
9.1 General and measurement frequency.....	16
9.2 Determination of the capacitance	16
9.3 Assessment of the electric field and use of reference level data.....	17
9.4 Measurement methods and limiting values	17
9.4.1 Simplified measurement of the prospective current in the parts of the body	17
9.4.2 More accurate method for determination of currents in the parts of the body	17
9.4.3 Limiting touch current values	17
10 Electric shock – immediate nerve and muscle reactions.....	17
10.1 General.....	17
10.2 Touch current limits – immediate nerve and muscle reactions.....	17
11 Electric shock – local overheating and burns of parts of the body	18
11.1 General and initial thermal conditions	18
11.2 Awareness, perception and withdrawal	19
11.2.2 Heat sensing nerves exist only in the skin region, and thus not in the interior of for example fingers. Conditions where such interior heating occurs while the skin sensing is insufficient for perception are dealt with in 11.3.	19
11.2.3 The perception conditions for hazard calculations are skin temperature rises of at least 3 K over 5 s to 10 s and 5 K over 20 s or less. These times then include the time for withdrawal. The high alternative value 10 s applies if the touching part of the body is large and less easy to withdraw (i.e. the upper arm, leg or torso) than a hand or finger for which 5 s applies.	19
11.3 Long-term tissue overheating.....	19
12 Requirements and risk group classification.....	20
12.1 General.....	20

12.2	Conditions for the touch current limits up to 100 kHz	20
12.3	Requirements related to skin temperature rises and times of awareness, perception and withdrawal	21
12.3.1	Skin heat capacity considerations	21
12.3.2	Skin temperature considerations	21
12.4	Risk level categorisation as function of the prospective contact voltage	22
12.5	Additional protection: residual current protective devices (RCDs).....	22
13	Non-sinusoidal touch currents	22
14	Warning marking and risk group classifications.....	23
Annex A (informative)	Examples of calculations	24
A.1	General.....	24
A.2	Skin heating.....	24
A.3	Examples of tissue heating conditions.....	29
A.3.1	With 1 500 mm ² fingerskin area, i.e. gripping	29
A.3.2	With the maximal fingerskin area 230 mm ²	29
Annex B (informative)	Rationales, references and volunteer studies in the non-thermal case.....	31
B.1	Background and observations	31
B.2	Discussion of Figure B.1	31
B.3	A volunteer study at 11 kHz sinusoidal conditions	33
B.3.1	Experimental setup and data	33
B.3.2	Discussion and analysis of the experimental data	33
B.4	Contact/touch current data from standards and other published documents	34
B.5	Reference levels for the external electric field.....	35
B.6	Prospective touch voltage limits	35
B.7	Perception and pain in relation to risk levels	35
B.8	Remarks on the slope of the curves for frequencies higher than 10 kHz.....	36
B.9	Remarks on the touch current levels above 100 kHz in ICNIRP and IEEE specifications.....	36
Annex C (informative)	Additional information and rationales – skin data and impedances of parts of the body	37
C.1	Skin anatomy	37
C.2	Comparative calculation procedure for wet skin impedances.....	38
C.3	Some data for dry skin	38
C.4	Frequency dependence of the body tissue electrical conductivities	39
C.5	Calculations for Table 1	39
Bibliography	41
Figure 1	– Complex impedances of various parts of the body, 1 kHz to 6 MHz.....	15
Figure 2	– Maximum allowed touch and touch currents, 1 kHz to 100 kHz, immediate nerve and muscle electric shock	18
Figure 3	– Warning markings	23
Figure B.1	– Maximum allowed touch and touch currents in various standards, 1 kHz to 100 kHz, immediate nerve and muscle electric shock.....	32
Figure B.2	– Setup for touch current and voltage measurements with index and middle fingers on 50 mm ² flat conductors	33
Figure B.3	– Current measuring circuit for unweighed touch current, from IEC 60990:2016.....	35
Figure C.1	– Human skin anatomy (from Wikipedia).....	37

Figure C.2 – Average electrical conductivities for homogeneous body modelling from 10 Hz to 10 MHz (from EN 50444:2008)..... 39

Table 1 – Maximally allowed skin power density per surface area, under various conditions of withdrawal..... 22

Table A.1 – Comparison of impedances of parts of the body, using the equivalent circuits in IEC 60990:2016 and in this document 25

Table A.2 – Moist skin, finger and overall heating rate at 50 V overall effective voltage, using equivalent circuits in IEC 60990:2016 and this document 25

Table A.3 – Wet skin, finger and overall heating rate at 50 V overall effective voltage, using this document, with halved skin impedances compared with Table A.2 26

Table A.4 – Effective contact voltage limits for the moist skin examples in Table A.2 27

Table A.5 – Effective contact voltage limits for the wet skin examples in Table A.3 28

Table C.1 – Comparison of complex impedances of moist and wet fingers 39

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL ELECTROHEATING AND ELECTROMAGNETIC PROCESSING EQUIPMENT – REQUIREMENTS ON TOUCH CURRENTS, VOLTAGES AND ELECTRIC FIELDS FROM 1 kHz TO 6 MHz

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62996, which is a technical specification, has been prepared by IEC technical committee 27: Industrial electroheating and electromagnetic processing.

The text of this document is based on the following documents:

Draft TS	Report on voting
27/1005/DTS	27/1010/RVDTS

Full information on the voting for the approval of this document can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this document, the following print types are used:

- terms defined in Clause 3: in bold type.
- in Table A.4 and Table A.5, the resulting voltage limits are bolded, for clarity.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Touch and touch currents and voltages constitute a very important category of electrical safety issues particularly for electroheating (EH) equipment and equipment for electro-magnetic processing of materials (EPM). The equipment manufacturer is mandated to adequately reduce any hazard from touching live equipment parts. For being able to do so, assessments and verifications are necessary for determination of hazards.

During the drafting of IEC 60519-1:2015, it became apparent that there was a need for a technical specification providing an overview, a guidance and requirements for users of that standard, and dealing with the nearest higher frequency interval above that of IEC 61140 and IEC 60204 (all parts). A revised IEC 61140:2016 covers issues up to 1 kHz (up to 200 Hz in earlier editions). Thus, this document deals with touch and touch currents and voltages in the frequency range from 1 kHz to 6 MHz. This range was adopted due to deviating frequency dependence of skin impedances below 1 kHz.

In principle, cases with strong external electric fields where the person is not touching the live insulated or bare live conductor are closely related to cases where the person is actually touching an insulated live conductor. These cases of currents in parts of the body by capacitive coupling are therefore included in this document.

NOTE A parallel IEC technical specification IEC TS 62997:2017 is developed by TC 27, dealing with the magnetic nearfields from 1 Hz to 6 MHz.

The upper frequency limit 6 MHz is chosen due to

- higher frequencies not being expected in internal frequency converters for DC voltage transformation in equipment,
- the free space wavelength of 6 MHz being 50 m, which results in wave phenomena that essentially not exist with or at objects with less than 10 % spatial dimensions of this,
- the fact that the power penetration depth limitation by the equivalent complex permittivity of body tissues has not yet set in at 6 MHz, so currents can be considered to be the same across the two touch areas and their patterns are as with low frequencies, and
- industrial processing frequencies below this limit are typically low impedance; higher impedance dielectric heating has its lowest ISM frequency at 6,8 MHz and is dealt with in IEC 60519-9.

Separation of electric shock (by a current between two parts of the body, creating an internal electric field by the tissue impedance) and induced electric shock (by an internally induced electric field caused by an external alternating magnetic field) is generally possible in the frequency interval considered in this document, since the latter requires a very high current in the conductor generating the magnetic field and conductor resistive losses are low by design. However, touching of such a conductor can occur and both mechanisms will then have to be assessed.

Impedance considerations for skin and other parts of the body are usually not included in sufficient detail in most existing standards, technical specifications and guidelines. With the exception of IEC 60601 (all parts) for medical equipment, no IEC standards provide reasonably complete touch current and voltage specifications. Equivalent test circuits tend to be too general and in some instances even contradictory to established literature data. This specification includes references to relevant IEC, IEEE, ICNIRP, EN and scientific literature data. Additional inputs are from numerical calculations with model situations, and volunteer studies.

Local overheating of particularly skin regions can be the dominating hazard at frequencies higher than some tens of kilohertz. Hazard limits are then to be based on skin impedances, thermal properties and touch as well as current path cross section area considerations. In addition, awareness, perception and withdrawal considerations become crucial. All these factors are dealt with in this document, in a more detailed way than in any other IEC publication.

Even if the scope of IEC TC 27 is limited to industrial electroheating and electromagnetic processing of materials, this document can fill an important gap, with its generally applicable and detailed specifications for higher frequencies than alternating current. It is therefore expected to be of more general use. It should, however, be observed that in particular skin impedances behave non-linearly for frequencies below about 1 kHz.

INDUSTRIAL ELECTROHEATING AND ELECTROMAGNETIC PROCESSING EQUIPMENT – REQUIREMENTS ON TOUCH CURRENTS, VOLTAGES AND ELECTRIC FIELDS FROM 1 kHz TO 6 MHz

1 Scope

This document addresses the safety assessments in the frequency range between 1 kHz and 6 MHz and provides limits for touch and touch currents for industrial installations or equipment for electroheating (EH) and electromagnetic processing of materials (EPM). Indirect contact by capacitive currents to parts of an earthed human body in an open space are also included, since the current is then distributed analogously in the part of the body and differs from cases of induced electric shock.

NOTE 1 Induced electric shock phenomena are caused by the alternating magnetic field external to a current-carrying conductor, inducing an electric field in a part of the body in the vicinity of or directly contacting it. The causes are thus different from those causing electric shock phenomena and are dealt with in IEC TS 62997 on magnetic nearfield safety, developed by TC 27.

The overall safety requirements for the various types of EH or EPM equipment and installations in general result from the joint application of the general requirements specified in IEC 60519-1:2015 and related particular requirements covering specific types of installations or equipment. This document complements IEC 60519-1:2015.

NOTE 2 This document complements Annex B in IEC 60519-1:2015.

On contacting, this document is based primarily on a movement of the primary contact area in relation to the live part, resulting in a contact or **touch current**. The awareness, perception and reaction times differ in comparison with a situation where a person is, for example, leaning towards or holding a conductor which subsequently becomes live, or a similar fault condition. Different considerations are then applicable and are dealt with in a detailed way in this document.

Since high impedances for dry skin will result in the lowest **touch current** and the dryness is typically variable, data for only moist and wet skin are used in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60417, *Graphical symbols for use on equipment* (available at <http://www.graphical-symbols.info/equipment>)

IEC 60519-1:2015, *Safety in installations for electroheating and electromagnetic processing – Part 1: General requirements*