

PRE-RELEASE VERSION (FDIS)

**Insulators for overhead lines with a nominal voltage above 1000 V –
Ceramic insulators for AC systems – Characteristics of insulator units of the
long rod type**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.080.10; 29.240.20

Warning! Make sure that you obtained this publication from an authorized distributor.



FINAL DRAFT INTERNATIONAL STANDARD (FDIS)

PROJECT NUMBER: IEC 60433 ED4	
DATE OF CIRCULATION: 2020-10-09	CLOSING DATE FOR VOTING: 2020-11-20
SUPERSEDES DOCUMENTS: 36/472/CDV, 36/495/RVC	

IEC TC 36 : INSULATORS	
SECRETARIAT: Sweden	SECRETARY: Mr Dan Windmar
OF INTEREST TO THE FOLLOWING COMMITTEES:	HORIZONTAL STANDARD: <input type="checkbox"/>
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input checked="" type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Final Draft International Standard (FDIS) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE: Insulators for overhead lines with a nominal voltage above 1000 V – Ceramic insulators for A.C. systems – Characteristics of insulator units of the long rod type
--

PROPOSED STABILITY DATE: 2024

NOTE FROM TC/SC OFFICERS:

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Characteristics, dimensions and type of long rod insulators	6
5 Designation and marking	6
Bibliography	11
Figure 1 – Long rod insulator with clevis couplings, type C	10
Figure 2 – Long rod insulator with socket couplings, type B	10
Table 1 – Specified values for long rod insulators	8

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INSULATORS FOR OVERHEAD LINES WITH A NOMINAL VOLTAGE ABOVE 1 000 V – CERAMIC INSULATORS FOR AC SYSTEMS – CHARACTERISTICS OF INSULATOR UNITS OF THE LONG ROD TYPE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60433 has been prepared by IEC technical committee 36: Insulators.

This fourth edition cancels and replaces the third edition published in 1998. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) wording in Scope changed from "should" to "are intended to";
- b) new normative references added;
- c) title of Clause 4 amended, new Note 4 added;
- d) Table 1 expanded to include more specified mechanical failing loads.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
36/XX/FDIS	36/XX/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INSULATORS FOR OVERHEAD LINES WITH A NOMINAL VOLTAGE ABOVE 1 000 V – CERAMIC INSULATORS FOR AC SYSTEMS – CHARACTERISTICS OF INSULATOR UNITS OF THE LONG ROD TYPE

1 Scope

This International Standard is applicable to string insulator units of the long rod type with insulating parts of ceramic material intended for use in AC overhead power lines with a nominal voltage greater than 1 000 V and a frequency not greater than 100 Hz. It is also applicable to insulators of similar design, used in substations.

This document is applicable to ceramic string insulator units of the long rod type, either with a clevis end fitting at both ends for coupling with a tongue, or with a socket end fitting at both ends for coupling with a pin ball.

The object of this document is to prescribe specified values for electrical and mechanical characteristics, and for the principal dimensions of ceramic string insulator units of the long rod type.

This document is applicable to string insulator units for use on overhead lines situated in lightly polluted areas, and the creepage distances given in Table 1 have been established accordingly, using the IEC TS 60815-2 recommendation of 27,8 mm/kV for SPS class. However, shorter creepage distances are applicable for use in some non-polluted areas. If specific operating conditions require or allow non-standard (longer or shorter) creepage distances, the mechanical characteristics as well as the lengths L (see Clause 4) of this document are intended to be used unless the need for exceptionally long creepage distances requires values of L greater than those given in Table 1. In the case of special requirements, e.g. very heavy polluted areas and for other particular or extreme environmental conditions, it may be necessary for certain dimensions to be changed.

As far as reasonably applicable, this document is also applicable to be applied to similar insulator units outside the scope of this standard, such as insulators for electric traction lines. This document does not include tests on insulators and dimensions of end fittings.

Ball and socket couplings are covered by IEC 60120, clevis and tongue couplings by IEC 60471.

NOTE 1 For the definition of site pollution severity, see applicable part of IEC TS 60815.

NOTE 2 The term "ceramic" is used in this document to refer to porcelain materials and, contrary to North American practice, does not include glass.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60383-1, *Insulators for overhead lines with a nominal voltage above 1 000 V – Part 1: Ceramic or glass insulator units for AC systems – Definitions, test methods and acceptance criteria*