

# PRE-RELEASE VERSION (FDIS)



---

**Maritime navigation and radiocommunication equipment and systems – Digital interfaces –  
Part 1: Single talker and multiple listeners**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 47.020.70

**Warning! Make sure that you obtained this publication from an authorized distributor.**



This is a preview - click here to buy the full publication

# 80/1093/FDIS

## FINAL DRAFT INTERNATIONAL STANDARD (FDIS)

PROJECT NUMBER: <b>IEC 61162-1 ED6</b>	
DATE OF CIRCULATION: <b>2023-09-15</b>	CLOSING DATE FOR VOTING: <b>2023-10-27</b>
SUPERSEDES DOCUMENTS: <b>80/1064/CDV, 80/1082/RVC</b>	

IEC TC 80 : MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS	
SECRETARIAT: United Kingdom	SECRETARY: Mr Kim Fisher
OF INTEREST TO THE FOLLOWING COMMITTEES:	HORIZONTAL STANDARD: <input type="checkbox"/>
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING <b>Attention IEC-CENELEC parallel voting</b> The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Final Draft International Standard (FDIS) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to consider for future work to include relevant "In Some Countries" clauses. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (See [AC/22/2007](#) or NEW [GUIDANCE DOC](#)).

TITLE: <b>Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners</b>
---

PROPOSED STABILITY DATE: 2028
-------------------------------

NOTE FROM TC/SC OFFICERS:
---------------------------

Copyright © 2023 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

## CONTENTS

FOREWORD .....	8
INTRODUCTION .....	10
1 Scope .....	11
2 Normative references .....	11
3 Terms and definitions .....	11
4 Manufacturer's documentation .....	12
5 Hardware specification .....	12
5.1 General .....	12
5.2 Interconnecting wire .....	12
5.3 Conductor definitions .....	12
5.4 Electrical connections/shield requirements .....	13
5.5 Connector .....	13
5.6 Electrical signal characteristics .....	13
5.6.1 General .....	13
5.6.2 Signal state definitions .....	13
5.6.3 Talker drive circuits .....	13
5.6.4 Listener receive circuits .....	13
5.6.5 Electrical isolation .....	14
5.6.6 Maximum voltage on bus .....	14
6 Data transmission .....	14
7 Data format protocol .....	15
7.1 Characters .....	15
7.1.1 General .....	15
7.1.2 Reserved characters .....	15
7.1.3 Valid characters .....	15
7.1.4 Undefined characters .....	15
7.1.5 Character symbols .....	15
7.1.6 Manufacturer's mnemonic code .....	15
7.2 Fields .....	16
7.2.1 String .....	16
7.2.2 Address field .....	16
7.2.3 Data fields .....	17
7.2.4 Checksum field .....	18
7.2.5 Sequential message identifier field .....	18
7.3 Sentences .....	18
7.3.1 General structure .....	18
7.3.2 Description of approved sentences .....	18
7.3.3 Parametric sentences .....	19
7.3.4 Encapsulation sentences .....	20
7.3.5 Query sentences .....	22
7.3.6 Proprietary sentences .....	23
7.3.7 Command sentences .....	23
7.3.8 Valid sentences .....	24
7.3.9 Multi-sentence messages .....	24
7.3.10 Sentence transmission timing .....	24

7.3.11	Additions to approved sentences.....	25
7.3.12	Message reception timeout for multi-sentence method.....	25
7.4	Error detection and handling .....	25
7.5	Handling of deprecated sentences .....	25
8	Data content .....	25
8.1	Character definitions.....	25
8.2	Field definitions .....	28
8.3	Approved sentences .....	31
8.3.1	General format .....	31
8.3.2	AAM – Waypoint arrival alarm .....	31
8.3.3	ABK – AIS addressed and binary broadcast acknowledgement .....	32
8.3.4	ABM – AIS addressed binary and safety related message.....	33
8.3.5	ACA – AIS channel assignment message .....	34
8.3.6	ACK – Acknowledge alarm.....	35
8.3.7	ACN – Alert command .....	35
8.3.8	ACS – AIS channel management information source .....	36
8.3.9	AGL – Alert group list .....	37
8.3.10	AIR – AIS interrogation request.....	37
8.3.11	AKD – Acknowledge detail alarm condition .....	39
8.3.12	ALA – Report detailed alarm condition.....	39
8.3.13	ALC – Cyclic alert list .....	40
8.3.14	ALF – Alert sentence .....	41
8.3.15	ALR – Set alarm state.....	44
8.3.16	APB – Heading/track controller (autopilot) sentence B .....	44
8.3.17	ARC – Alert command refused .....	45
8.3.18	BBM – AIS broadcast binary message.....	45
8.3.19	BEC – Bearing and distance to waypoint – Dead reckoning.....	46
8.3.20	BOD – Bearing origin to destination .....	47
8.3.21	BWC – Bearing and distance to waypoint – Great circle .....	47
8.3.22	BWR – Bearing and distance to waypoint – Rhumb line .....	47
8.3.23	BWW – Bearing waypoint to waypoint .....	47
8.3.24	CUR – Water current layer – Multi-layer water current data.....	48
8.3.25	DBT – Depth below transducer.....	48
8.3.26	DDC – Display dimming control.....	48
8.3.27	DOR – Door status detection .....	51
8.3.28	DPT – Depth .....	53
8.3.29	DSC – Digital selective calling information.....	53
8.3.30	DSE – Expanded digital selective calling .....	54
8.3.31	DTM – Datum reference.....	54
8.3.32	EPM – Command or report long equipment property value .....	55
8.3.33	EPV – Command or report equipment property value.....	56
8.3.34	ETL – Engine telegraph operation status .....	58
8.3.35	EVE – General event message.....	59
8.3.36	FIR – Fire detection.....	59
8.3.37	FSI – Frequency set information .....	60
8.3.38	GBS – GNSS satellite fault detection.....	61
8.3.39	GDC – GNSS differential correction .....	64
8.3.40	GEN – Generic binary information .....	67
8.3.41	GFA – GNSS fix accuracy and integrity .....	68

8.3.42	GGA – Global positioning system (GPS) fix data.....	69
8.3.43	GLL – Geographic position – Latitude/longitude.....	69
8.3.44	GNS – GNSS fix data .....	70
8.3.45	GRS – GNSS range residuals .....	72
8.3.46	GSA – GNSS DOP and active satellites.....	75
8.3.47	GST – GNSS pseudorange error statistics.....	78
8.3.48	GSV – GNSS satellites in view.....	78
8.3.49	HBT – Heartbeat supervision sentence.....	81
8.3.50	HCR – Heading correction report .....	81
8.3.51	HDG – Heading, deviation and variation .....	82
8.3.52	HDT – Heading true.....	82
8.3.53	HMR – Heading monitor receive.....	82
8.3.54	HMS – Heading monitor set .....	83
8.3.55	HRM – Heel angle, roll period and roll amplitude measurement device .....	83
8.3.56	HSC – Heading steering command.....	85
8.3.57	HSS – Hull stress surveillance systems.....	85
8.3.58	HTC – Heading/track control command; HTD – Heading /track control data .....	85
8.3.59	LR1 – AIS long-range reply sentence 1 .....	87
8.3.60	LR2 – AIS long-range reply sentence 2 .....	87
8.3.61	LR3 – AIS long-range reply sentence 3 .....	88
8.3.62	LRF – AIS long-range function .....	88
8.3.63	LRI – AIS long-range interrogation .....	89
8.3.64	MOB – Man over board notification .....	90
8.3.65	MSK – MSK receiver interface .....	91
8.3.66	MSS – MSK receiver signal status.....	92
8.3.67	MTW – Water temperature.....	92
8.3.68	MWD – Wind direction and speed .....	92
8.3.69	MWV – Wind speed and angle .....	93
8.3.70	NAK – Negative acknowledgement.....	93
8.3.71	NLS – Navigation light status .....	94
8.3.72	NRM – NAVTEX receiver mask .....	95
8.3.73	NRX – MSI received message.....	97
8.3.74	NSR – Navigation status report.....	98
8.3.75	OSD – Own ship data .....	99
8.3.76	POS – Device position and ship dimensions report or configuration command .....	100
8.3.77	PRC – Propulsion remote control status .....	101
8.3.78	RLM – Return link message .....	102
8.3.79	RMA – Recommended minimum specific LORAN-C data.....	103
8.3.80	RMB – Recommended minimum navigation information .....	103
8.3.81	RMC – Recommended minimum specific GNSS data .....	104
8.3.82	ROR – Rudder order status.....	106
8.3.83	ROT – Rate of turn .....	106
8.3.84	RPM – Revolutions .....	106
8.3.85	RRT – Report route transfer.....	106
8.3.86	RSA – Rudder sensor angle.....	108
8.3.87	RSD – Radar system data.....	108
8.3.88	RTE – Routes.....	109

8.3.89	SEL – Selection report.....	109
8.3.90	SFI – Scanning frequency information.....	110
8.3.91	SLM – Steering location/mode.....	111
8.3.92	SM1 – SafetyNET Message, All Ships/NavArea.....	112
8.3.93	SM2 – SafetyNET Message, Coastal Warning Area.....	114
8.3.94	SM3 – SafetyNET Message, Circular Area address.....	116
8.3.95	SM4 – SafetyNET Message, Rectangular Area Address.....	118
8.3.96	SMB – IMO SafetyNET Message Body.....	121
8.3.97	SMV – SafetyNET Message, Vessel in distress information.....	122
8.3.98	SPW – Security password sentence.....	124
8.3.99	SSD – AIS ship static data.....	125
8.3.100	STN – Multiple data ID.....	126
8.3.101	THS – True heading and status.....	126
8.3.102	TLB – Target label.....	126
8.3.103	TLL – Target latitude and longitude.....	127
8.3.104	TRC – Thruster control data.....	127
8.3.105	TRD – Thruster response data.....	128
8.3.106	TRL – AIS transmitter-non-functioning log.....	128
8.3.107	TTD – Tracked target data.....	129
8.3.108	TTM – Tracked target message.....	132
8.3.109	TUT – Transmission of multi-language text.....	132
8.3.110	TXT – Text transmission.....	133
8.3.111	UID – User identification code transmission.....	134
8.3.112	VBC – Water-referenced and ground-referenced docking speed data.....	134
8.3.113	VBW – Dual ground/water speed.....	135
8.3.114	VDM – AIS VHF data-link message.....	135
8.3.115	VDO – AIS VHF data-link own-vessel report.....	136
8.3.116	VDR – Set and drift.....	137
8.3.117	VER – Version.....	137
8.3.118	VHW – Water speed and heading.....	138
8.3.119	VLW – Dual ground/water distance.....	138
8.3.120	VPW – Speed measured parallel to wind.....	138
8.3.121	VSD – AIS voyage static data.....	138
8.3.122	VTG – Course over ground and ground speed.....	140
8.3.123	WAT – Water level detection.....	140
8.3.124	WCV – Waypoint closure velocity.....	141
8.3.125	WNC – Distance waypoint to waypoint.....	142
8.3.126	WPL – Waypoint location.....	142
8.3.127	XDR – Transducer measurements.....	142
8.3.128	XTE – Cross-track error, measured.....	145
8.3.129	XTR – Cross-track error, dead reckoning.....	145
8.3.130	ZDA – Time and date.....	146
8.3.131	ZDL – Time and distance to variable point.....	146
8.3.132	ZFO – UTC and time from origin waypoint.....	146
8.3.133	ZTG – UTC and time to destination waypoint.....	147
9	Applications.....	147
9.1	Example parametric sentences.....	147
9.1.1	General.....	147
9.1.2	Example 1 – LORAN-C latitude/longitude.....	147

9.1.3	Example 2 – LORAN-C arrival alarm .....	147
9.1.4	Example 3 – Proprietary sentence.....	148
9.1.5	Example 4 – RMA examples .....	148
9.1.6	Example 5 – FSI examples .....	149
9.1.7	Example 6 – MSK/MSS examples .....	149
9.1.8	Example 7 – DSC and DSE sentences .....	150
9.1.9	Example 8 – FIR, DOR and WAT sentences .....	150
9.2	Example encapsulation sentences.....	151
9.3	Examples of receiver diagrams .....	151
Annex A	(informative) Example encapsulation sentence .....	152
A.1	Example encapsulation sentence .....	152
A.2	AIS VHF data-link message VDM sentence encapsulation example.....	152
A.3	Background discussion – Encapsulation coding .....	152
A.4	Decoding the encapsulated string.....	156
A.5	Conversion from symbols to binary bits .....	156
A.6	Organising the binary message data .....	157
A.7	Interpreting the decoded binary strings.....	157
Annex B	(normative) Guidelines for methods of testing and required test results .....	158
B.1	General.....	158
B.2	Definition of environmental conditions for the tests .....	158
B.3	Examination of the manufacturer's documentation .....	158
B.4	Test of hardware .....	159
B.4.1	Interface units .....	159
B.4.2	Input circuit test.....	159
B.4.3	Check of electrical isolation .....	159
B.4.4	Maximum input voltage test .....	159
B.4.5	Test arrangement for performance tests according to IEC 60945.....	159
B.4.6	Test under maximum interface workload.....	159
B.4.7	Test for correct parsing of sentences .....	160
B.4.8	Test under long term conditions .....	161
B.4.9	Protocol test of the interface of the EUT .....	161
Annex C	(normative) Six-bit binary field conversion.....	167
Annex D	(normative) Alarm system fields.....	170
Annex E	(informative) Example of use of FIR, DOR and WAT sentences.....	178
E.1	Example of the use of system status messages .....	178
E.2	Use of system division codes .....	178
E.3	Send complete status .....	179
E.4	Change measurement point status .....	180
E.5	Point status change during a status update .....	180
E.6	Failure in a sub-system.....	180
E.7	Status updates when a sub-system is in fault.....	181
E.8	Signal a correction of a sub-system fault .....	181
Bibliography	.....	182
Figure 1	– Listener receive circuit .....	14
Figure 2	– Data transmission format .....	14
Figure 3	– Example 1, J-FET, N channel, opto-isolator based listener circuit.....	151
Figure 4	– Example 2, NPN opto-isolator based listener circuit .....	151

Figure A.1 – Message data format .....	154
Figure A.2 – Work sheet for decoding and interpreting encapsulated string .....	155
Figure C.1 – 6-bit binary code converted to valid IEC 61162-1 character .....	168
Figure C.2 – Valid IEC 61162-1 character converted to 6-bit binary code .....	169
Figure E.1 – Example system diagram .....	179
Table 1 – Reserved characters .....	26
Table 2 – Valid characters .....	26
Table 3 – Character symbol .....	27
Table 4 – Talker identifier mnemonics .....	28
Table 5 – Field type summary .....	30
Table A.1 – Example message from ITU-R M.1371 .....	153
Table B.1 – Example – Special characters .....	160
Table B.2 – Example – Parsing .....	160
Table B.3 – Example – Future extensions .....	161
Table B.4 – Example – Data string GGA sent by the EUT to the test receiver (listener) .....	162
Table B.5 – Example – Checksum data sent .....	163
Table B.6 – Example – Data string GNS received by the EUT .....	164
Table B.7 – Example – Checksum data received .....	165
Table B.8 – Example – Break of data line .....	166
Table B.9 – Example – Receiving interval .....	166
Table B.10 – Example – Talker ID .....	166
Table C.1 – Six-bit binary field conversion table .....	167
Table D.1 – System alarm fields .....	170



## INTERNATIONAL ELECTROTECHNICAL COMMISSION

# MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

## Part 1: Single talker and multiple listeners

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61162-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

This sixth edition cancels and replaces the fifth edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) alternative hardware is given in 5.1 which may now be as specified in this document or as specified in IEC 61162-2;
- b) the data transmission rate given in Clause 6 is now configurable. The default remains as 4 800 (bits/s) but higher rates may be provided;

- c) new identifiers have been added to Table 4;
- d) new sentences AGL, EPM, GDC, NLS, SEL, SLM, SMV and VBC have been added;
- e) revisions have been made to ABK, ABM, ACN, ALC, ALF, ARC, BBM, DDC, DTM, EPV, FIR, GBS, GFA, GLL, GNS, GRS, GSA, GST, GSV, HRM, NRX, POS, RLM, ROR, RSA, TLB, TTD, VSD and XDR;
- f) the previous Annex A, Glossary, has been deleted as being of historical interest.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/XX/FDIS	80/XX/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts in the IEC 61162 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

The IEC 61162 series consists of 5 parts which specify digital interfaces for application in marine navigation, radiocommunication and system integration, as follows:

- IEC 61162-1: Single talker and multiple listeners;
- IEC 61162-2: Single talker and multiple listeners, high speed transmission;
- IEC 61162-3: Serial data instrument network;
- IEC 61162-450: Multiple talkers and multiple listeners – Ethernet interconnection;
- IEC 61162-460: Multiple talkers and multiple listeners – Ethernet interconnection – Safety and security

IEC technical committee 80 interface standards are developed with input from manufacturers, private and government organisations and equipment operators. The information is intended to meet the needs of users at the time of publication, but users should recognise that as applications and technology change, interface standards should change as well. Users of this document are advised to immediately inform the IEC of any perceived inadequacies therein.

The first edition of IEC 61162-1 was published in 1995. The second edition published in 2000 removed some sentences which were no longer in use, added some new sentences and included details of the ship equipment defined in IMO resolutions together with appropriate sentences for communication between them. This information was subsequently removed from the third edition when it became the practice to specify the sentence formatters in the individual standards for equipment.

The third edition published in 2007 introduced a re-arrangement of the text and new sentences particularly to support the automatic identification system and the voyage data recorder. The third edition also introduced a further type of start of sentence delimiter. The conventional delimiter "\$" was retained for the conventional sentences which are now called "parametric sentences". The new delimiter "!" identifies sentences that conform to special purpose encapsulation.

The fourth edition removed some sentences which were not in use, added some new sentences for new applications and made some corrections and additions. In particular, the sentences of relevance to satellite navigation receivers were expanded to facilitate the description of new satellite systems.

The fifth edition also removed some sentences which were no longer in use, added some new sentences for new applications and made some corrections and additions.

This sixth edition adds some new sentences for new applications and makes some corrections and additions.

This edition has been aligned where appropriate and possible with NMEA 0183 version 4.10.

# MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

## Part 1: Single talker and multiple listeners

### 1 Scope

This part of IEC 61162 contains the requirements for data communication between maritime electronic instruments, navigation and radiocommunication equipment when interconnected via an appropriate system.

This document is intended to support one-way serial data transmission from a single talker to one or more listeners. These data are in printable ASCII form and can include information such as position, speed, depth, frequency allocation, etc. Typical messages can be from about 11 to a maximum of 79 characters in length and generally require transmission no more rapidly than one message per second.

The electrical definitions in this document are not intended to accommodate high-bandwidth applications such as radar or video imagery, or intensive database or file transfer applications. Since there is no provision for guaranteed delivery of messages and only limited error checking capability, it is important this document is used with caution in all safety applications.

For applications where a faster transmission rate is necessary, IEC 61162-2 applies.

For applications to shore based equipment of the automatic identification system (AIS) the IEC 62320 series applies.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements - Methods of testing and required test results*

ISO/IEC 8859-1:1998, *Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No. 1*

ITU-T Recommendation X.27/V.11:1996, *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s*