

This is a preview - click here to buy the full publication



IEC 62439-3

Edition 4.0 2021-10

# PRE-RELEASE VERSION (FDIS)



---

**Industrial communication networks – High availability automation networks –  
Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless  
Redundancy (HSR)**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 25.040.40; 35.100.05

**Warning! Make sure that you obtained this publication from an authorized distributor.**



## FINAL DRAFT INTERNATIONAL STANDARD (FDIS)

PROJECT NUMBER:

**IEC 62439-3 ED4**

DATE OF CIRCULATION:

**2021-10-08**

CLOSING DATE FOR VOTING:

**2021-11-19**

SUPERSEDES DOCUMENTS:

**65C/998/CDV, 65C/1044/RVC**

IEC SC 65C : INDUSTRIAL NETWORKS	
SECRETARIAT: France	SECRETARY: Ms Valérie DEMASSIEUX
OF INTEREST TO THE FOLLOWING COMMITTEES: SC 22G,TC 57	HORIZONTAL STANDARD: <input type="checkbox"/>
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING <b>Attention IEC-CENELEC parallel voting</b> The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Final Draft International Standard (FDIS) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

**Industrial communication networks - High availability automation networks - Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless Redundancy (HSR)**

PROPOSED STABILITY DATE: 2025

NOTE FROM TC/SC OFFICERS:

## CONTENTS

FOREWORD.....	10
INTRODUCTION.....	13
0.1    General.....	13
0.2    Patent declaration.....	13
1    Scope.....	15
1.1    General.....	15
1.2    Code component distribution.....	15
2    Normative references .....	16
3    Terms, definitions, abbreviated terms, and conventions.....	17
3.1    Terms and definitions.....	17
3.2    Abbreviated terms.....	19
3.3    Conventions.....	20
4    Parallel Redundancy Protocol (PRP) .....	20
4.1    PRP principle of operation .....	20
4.1.1    PRP network topology .....	20
4.1.2    PRP LANs with linear or bus topology.....	22
4.1.3    PRP LANs with ring topology.....	22
4.1.4    DANP node structure .....	23
4.1.5    PRP attachment of singly attached nodes.....	24
4.1.6    Compatibility between singly and doubly attached nodes.....	25
4.1.7    Network management.....	25
4.1.8    Implication on application .....	25
4.1.9    Transition to a single-thread network .....	26
4.1.10    Duplicate handling .....	26
4.1.11    Network supervision .....	31
4.1.12    Redundancy management interface.....	31
4.2    PRP protocol specifications .....	32
4.2.1    Installation, configuration and repair guidelines .....	32
4.2.2    Unicast MAC addresses.....	32
4.2.3    Multicast MAC addresses .....	32
4.2.4    IP addresses .....	33
4.2.5    Node specifications .....	33
4.2.6    Duplicate Accept mode (testing only).....	33
4.2.7    Duplicate Discard mode.....	34
4.3    PRP_Supervision frame .....	38
4.3.1    PRP_Supervision frame format.....	38
4.3.2    PRP_Supervision frame contents.....	40
4.3.3    PRP_Supervision frame for RedBox .....	41
4.3.4    Bridging node (deprecated) .....	41
4.4    Constants .....	42
4.5    PRP layer management entity (LME) .....	42
5    High-availability Seamless Redundancy (HSR).....	42
5.1    HSR objectives .....	42
5.2    HSR principle of operation .....	43
5.2.1    Basic operation with a ring topology .....	43

5.2.2	HSR connection to other networks .....	45
5.2.3	DANH node structure .....	57
5.2.4	RedBox structure .....	58
5.3	HSR protocol specifications .....	59
5.3.1	HSR layout .....	59
5.3.2	HSR operation .....	59
5.3.3	DANH sending from its link layer interface .....	61
5.3.4	DANH receiving from an HSR port .....	62
5.3.5	DANH forwarding rules .....	62
5.3.6	HSR Class of Service .....	64
5.3.7	HSR clock synchronization .....	64
5.3.8	Deterministic transmission delay and jitter .....	64
5.4	HSR RedBox specifications .....	64
5.4.1	RedBox properties .....	64
5.4.2	RedBox receiving from port C (interlink) .....	65
5.4.3	RedBox receiving from port A or port B (HSR ring) .....	67
5.4.4	RedBox receiving from its link layer interface (local) .....	69
5.4.5	Redbox ProxyNodeTable handling .....	69
5.4.6	RedBox CoS .....	69
5.4.7	RedBox clock synchronization .....	69
5.4.8	RedBox medium access .....	69
5.5	QuadBox specification .....	70
5.6	Duplicate Discard method .....	70
5.7	Frame format for HSR .....	70
5.7.1	Frame format for all frames .....	70
5.7.2	HSR_Supervision frame .....	71
5.8	HSR constants .....	74
5.9	HSR layer management entity (LME) .....	75
6	Protocol Implementation Conformance Statement (PICS) .....	77
7	PRP/HSR Management Information Base (MIB) .....	79
Annex A (normative)	Synchronization of clocks over redundant paths .....	95
A.1	Overview .....	95
A.2	PRP mapping to PTP .....	95
A.2.1	Particular operation of PRP for PTP messages .....	95
A.2.2	Scenarios and device roles .....	97
A.2.3	Attachment to redundant LANs by a BC .....	99
A.2.4	Attachment to redundant LANs by doubly attached clocks .....	99
A.2.5	Specifications of DANP as DAC .....	103
A.2.6	PRP-SAN RedBoxes for PTP .....	104
A.3	HSR Mapping to PTP .....	124
A.3.1	HSR messages and other messages .....	124
A.3.2	HSR operation with PTP messages .....	124
A.3.3	HSR with redundant master clocks .....	126
A.3.4	HSR timing diagram for PTP messages .....	127
A.3.5	HSR nodes specifications .....	128
A.4	HSR RedBoxes for PTP .....	130
A.4.1	HSR-SAN RedBox .....	130
A.4.2	HSR-PRP RedBox connection by BC .....	131
A.4.3	HSR-PRP RedBox connection by TC .....	133

A.4.4	HSR to HSR connection by QuadBoxes .....	135
A.5	Doubly attached clock specification.....	136
A.5.1	State machine .....	136
A.5.2	Supervision of the port.....	139
A.5.3	BMCA for paired ports .....	140
A.5.4	Selection of the port state .....	141
A.6	PTP datasets for high availability .....	141
A.6.1	General .....	141
A.6.2	Data types .....	141
A.6.3	Datasets for OC or BC .....	142
A.6.4	Datasets for TCs.....	150
Annex B (normative)	PTP profile for Power Utility Automation (PUP) – Redundant clock attachment.....	151
B.1	Application domain.....	151
B.2	PTP profile specification .....	151
B.3	Specifications .....	151
B.4	Redundant clock attachment .....	151
Annex C (normative)	PTP industry profiles for high-availability automation networks .....	153
C.1	Application domain.....	153
C.2	PTP profile specification .....	153
C.3	Clock types .....	154
C.4	Protocol specification common.....	154
C.4.1	Base protocol .....	154
C.4.2	Version control .....	154
C.4.3	Time scale .....	155
C.4.4	BMCA.....	155
C.4.5	Time correction mechanism .....	155
C.4.6	Management.....	155
C.4.7	1 PPS support .....	155
C.4.8	Leap second transition.....	155
C.4.9	Use of port number .....	155
C.4.10	Time distribution security .....	156
C.5	Protocol specification for L3E2E industry profile .....	156
C.5.1	Base protocol .....	156
C.5.2	Multicast address.....	156
C.5.3	Delay calculation mechanism.....	156
C.5.4	Sync message padding.....	156
C.6	Protocol specification for L2P2P industry profile .....	157
C.6.1	Base protocol .....	157
C.6.2	Delay measurement mechanism .....	157
C.6.3	Consideration of media converters.....	157
C.7	Common timing requirements for L2P2P and L3E2E .....	157
C.7.1	Measurement conditions .....	157
C.7.2	Network time inaccuracy.....	157
C.7.3	Response to time step changes .....	158
C.7.4	Requirements for GCs .....	158
C.7.5	Requirements for TCs.....	160
C.7.6	Requirements for BCs.....	160
C.8	Requirements for media converters.....	163

C.9	Requirements for links .....	163
C.10	Network engineering .....	163
C.11	Default settings .....	164
C.12	Handling of doubly attached clocks .....	165
C.13	Protocol Implementation Conformance Statement (PICS) for PTP .....	166
C.13.1	PICS conventions .....	166
C.13.2	PICS for PTP .....	166
C.14	Recommendations for time representation .....	168
C.14.1	Usage of flags in TimePropertyDS .....	168
C.14.2	UTC leap second transition .....	169
C.14.3	ALTERNATE_TIME_OFFSET_INDICATOR_TLV .....	170
Annex D (informative)	Precision Time Protocol tutorial for the PTP Industrial profile .....	174
D.1	Objective .....	174
D.2	Precision and accuracy .....	174
D.3	PTP clock types .....	175
D.4	PTP main options .....	177
D.5	Layer 2 and layer 3 communication .....	178
D.6	1-step and 2-step correction .....	178
D.6.1	Time correction in TCs .....	178
D.6.2	2-step to 1-step translation .....	179
D.7	End-to-End link delay measurement .....	181
D.7.1	General method .....	181
D.7.2	End-to-end link delay measurement with 1-step clock correction .....	181
D.7.3	End-to-end link delay measurement with 2-step clock correction .....	182
D.7.4	End-to-end link delay calculation by Delay_Req – Delay_Resp .....	183
D.7.5	Consideration of media converters in end-to-end delay calculation .....	183
D.8	Peer-to-peer link delay calculation .....	184
D.8.1	Peer-to-peer link delay calculation with 1-step correction .....	184
D.8.2	Peer-to-peer link delay calculation with 2-step correction .....	185
D.8.3	Consideration of media converters in peer delay calculation .....	186
Annex E (normative)	Management Information base for singly and doubly attached clocks .....	188
Annex F (normative)	Conformance testing for PRP and HSR and handling of redundancy in PIP and PUP .....	216
F.1	General .....	216
F.2	PRP conformance test .....	216
F.2.1	PRP test set-up .....	216
F.2.2	PRP test components .....	217
F.2.3	Test for documentation and labelling .....	217
F.2.4	Test for (unicast) IP addresses .....	218
F.2.5	Test for configuration .....	218
F.2.6	Test of DANP .....	219
F.2.7	Test of PRP Redboxes .....	223
F.2.8	Test for Management .....	225
F.2.9	Test of DANP or RedBox for processing of PTP frames .....	227
F.3	HSR conformance test .....	232
F.3.1	HSR test set-up .....	232
F.3.2	HSR test components .....	233
F.3.3	Test for HSR documentation and labelling .....	233

F.3.4	Test of DANH or RedBox for IP addresses.....	234
F.3.5	Test of DANH for configuration .....	234
F.3.6	Test of DANH .....	235
F.3.7	Test of HSR RedBoxes .....	239
F.3.8	Test of DANH or RedBox for receive/transmit counters.....	241
F.3.9	Test of DANH or RedBox for processing of PTP frames in L2P2P .....	242
Bibliography.....		246
Figure 1	– PRP example of general duplicated network .....	21
Figure 2	– PRP example of duplicated network in bus topology.....	22
Figure 3	– PRP example of redundant ring with SANs and DANPs .....	23
Figure 4	– PRP with two DANPs communicating .....	24
Figure 5	– PRP RedBox, transition from single to double LAN.....	26
Figure 6	– PRP frame closed by an RCT .....	27
Figure 7	– PRP VLAN-tagged frame closed by an RCT .....	28
Figure 8	– PRP padded frame closed by an RCT .....	28
Figure 9	– Duplicate Discard algorithm boundaries .....	30
Figure 10	– HSR example of ring traffic for multicast frames .....	43
Figure 11	– HSR example of ring traffic for unicast frames.....	44
Figure 12	– HSR example of coupling two redundant PRP LANs to a ring (unicast).....	47
Figure 13	– HSR example of coupling from a ring node to PRP LANs (multicast) .....	49
Figure 14	– HSR example of coupling from a ring to two PRP LANs (multicast) .....	50
Figure 15	– HSR example of coupling three rings to one PRP LAN .....	51
Figure 16	– HSR example of peer coupling of two rings .....	52
Figure 17	– HSR example of connected rings .....	53
Figure 18	– HSR example of meshed topology.....	54
Figure 19	– HSR example of topology using two independent networks .....	55
Figure 20	– HSR example of coupling an RSTP LAN to HSR by two bridges .....	56
Figure 21	– HSR structure of a DANH .....	57
Figure 22	– HSR structure of a RedBox .....	58
Figure 23	– HSR frame without a VLAN tag .....	70
Figure 24	– HSR frame with VLAN tag .....	71
Figure 25	– HSR node with management counters.....	76
Figure 26	– HSR RedBox with management counters .....	77
Figure A.1	– Connection of a DAC master to a DAC slave over PRP.....	96
Figure A.2	– Elements of PRP time distribution networks .....	98
Figure A.3	– Doubly Attached Clock as BC (OC3A is best master).....	99
Figure A.4	– Doubly Attached Clocks OC1 and OC2 .....	101
Figure A.5	– Doubly attached clocks when OC1 has the same identity on both LANs .....	103
Figure A.6	– PRP RedBox as TWBCs .....	105
Figure A.7	– RedBox DABC clock model.....	106
Figure A.8	– PRP RedBoxes as DABC with E2E – message flow .....	108
Figure A.9	– PRP RedBoxes as DABC with E2E – timing .....	109
Figure A.10	– PRP RedBoxes as DABC with P2P on PRP – message flow .....	110

Figure A.11 – PRP RedBoxes as DABC with P2P on PRP – timing .....	111
Figure A.12 – PRP-SAN RedBox as SLTC with E2E – message flow .....	113
Figure A.13 – PRP RedBox as SLTC with E2E – timing .....	115
Figure A.14 – PRP RedBox as SLTC with P2P – message flow.....	116
Figure A.15 – PRP RedBox as SLTC with P2P – timing diagram.....	117
Figure A.16 – PRP RedBox as DATC with E2E – message flow .....	120
Figure A.17 – PRP RedBox as DATC with E2E – timing.....	121
Figure A.18 – PRP RedBox as DATC with P2P – message flow .....	122
Figure A.19 – PRP RedBox as DATC with P2P – timing.....	123
Figure A.20 – HSR with two GCs (GC1 is grandmaster, GC2 is back-up).....	126
Figure A.21 – PTP messages sent and received by an HSR node (1-step).....	127
Figure A.22 – PTP messages sent and received by an HSR node (2-step).....	128
Figure A.23 – Attachment of a GC to an HSR ring through a RedBox as TC and BC.....	130
Figure A.24 – PRP to HSR coupling by BCs.....	132
Figure A.25 – PRP to HSR coupling by DATC and SLTC .....	134
Figure A.26 – HSR coupling to two PRP and one HSR network.....	135
Figure A.27 – Port states including transitions for redundant operation .....	137
Figure A.28 – BMCA for redundant masters .....	140
Figure C.1 – Response to a time step .....	158
Figure C.2 – States of a BC .....	161
Figure D.1 – Time error as a probability distribution function.....	174
Figure D.2 – PTP principle with GC, TC and OC .....	176
Figure D.3 – PTP elements .....	177
Figure D.4 – Delays and time-stamping logic in TCs .....	178
Figure D.5 – 1-step and 2-step correction of a Sync message (peer-to-peer) .....	179
Figure D.6 – Translation from 2-step to 1-step correction in TCs.....	180
Figure D.7 – Translation from 2-step to 1-step correction – message view .....	181
Figure D.8 – End-to-end link delay measurement with 1-step correction .....	182
Figure D.9 – End-to-end delay measurement with 2-step correction.....	183
Figure D.10 – Peer-to-peer link delay measurement with 1-step correction .....	184
Figure D.11 – Peer-to-peer link delay measurement with 2-step correction .....	185
Figure D.12 – Peer delay measurement and Sync message delay with media converter .....	187
Figure F.1 – Test set-up for PRP .....	217
Figure F.2 – Test set-up for PRP and PTP with L2P2P .....	227
Figure F.3 – Test set-up for HSR (without PTP) .....	233
Figure F.4 – Test set-up for HSR with L2P2P.....	242
Table 1 – Duplicate discard cases .....	30
Table 2 – Monitoring data set.....	34
Table 3 – NodesTable attributes .....	35
Table 4 – PRP_Supervision frame with no VLAN tag.....	39
Table 5 – PRP_Supervision frame with (optional) VLAN tag.....	40
Table 6 – PRP_Supervision frame contents .....	41



Table 7 – PRP_Supervision TLV for Redbox .....	41
Table 8 – PRP constants .....	42
Table 9 – HSR_Supervision frame with no VLAN tag .....	72
Table 10 – HSR_Supervision frame with optional VLAN tag .....	73
Table 11 – HSR Constants.....	75
Table 12 – PICS .....	78
Table A.1 – States .....	138
Table A.2 – Transitions.....	139
Table A.3 – Variables .....	139
Table C.1 – ClockClass.....	159
Table C.2 – PTP attributes.....	165
Table C.3 – PICS for clocks.....	166
Table C.4 – Transitions with an inserted leap second (UTC binary and C37.118).....	170
Table C.5 – Transitions with a removed leap second (UTC binary and C37.118).....	170
Table C.6 – ATOI transition to Pacific Summer Time (spring).....	172
Table C.7 – ATOI transitions to Pacific Standard Time (autumn).....	172
Table C.8 – Transitions with an inserted leap second in Pacific Standard Time.....	173
Table C.9 – Transitions with a removed leap second in Pacific Standard Time.....	173
Table F.1 – Test for PRP documentation and labelling .....	218
Table F.2 – Test for (unicast) IP addresses.....	218
Table F.3 – Test for PRP configuration (Table 8) .....	219
Table F.4 – Test for PRP supervision frames (Table 4 and Table 5).....	219
Table F.5 – Test for PRP tagging (4.1.10.2, 4.2.7.3).....	221
Table F.6 – Test of a DANP without a NodesTable.....	222
Table F.7 – Test of a DANP with a NodesTable .....	222
Table F.8 – Test for discard over different ports.....	223
Table F.9 – Test for PRP supervision frames (Table 4 and Table 5).....	224
Table F.10 – Test of RedBox for ProxyNodeTable.....	224
Table F.11 – Test of RedBox for forwarding.....	225
Table F.12 – Test for DANP receive/transmit counters .....	226
Table F.13 – Test procedure for processing of PTP frames.....	229
Table F.14 – Test for processing of PTP frames .....	230
Table F.15 – Test for processing of PTP frames .....	231
Table F.16 – Test procedure for processing of PTP frames.....	232
Table F.17 – Test for HSR documentation.....	234
Table F.18 – Test for IP addresses .....	234
Table F.19 – Test procedure for HSR configuration (Table 11).....	235
Table F.20 – Test for HSR supervision frames (Table 9 and Table 10).....	236
Table F.21 – Test for HSR tagging.....	237
Table F.22 – Test of DANH for HSR Mode H multicast.....	238
Table F.23 – Test of DANH for HSR Mode H unicast.....	238
Table F.24 – Test of DANH for other modes than Mode H.....	239
Table F.25 – Test of RedBox for HSR supervision frames (Table 9 and Table 10).....	239

Table F.26 – Test of RedBox for ProxyNodeTable.....	240
Table F.27 – Test of RedBox for Mode H Unicast.....	240
Table F.28 – Test of DANH or RedBox for receive/transmit counters .....	241
Table F.29 – Test for processing of PTP frames (slave).....	243
Table F.30 – Test for processing of PTP frames (master) .....	244

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### **INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –**

### **Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless Redundancy (HSR)**

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62439-3 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) References to Precision Time Protocol (PTP) IEC 61588:2021 replace references to IEC 61588:2009, unless the previous version is explicitly referenced (Clause 2);
- b) References to IEC 61850-90-4:2020 replace references to IEC 61850-90-4:2013 with corresponding changes in the Logical Nodes (Clause 2);

- c) Terms and abbreviations are aligned with the next edition of IEC/IEEE 61850-9-3 (currently under preparation) (Clause 3);
- d) RSTP support in HSR is specified (5.2.2.10);
- e) RedBoxes and QuadBoxes specifications are extended to TCs (5.5);
- f) Network management (MIB) for PRP and HSR is available as a "Code Component", machine-readable separate document (Clause 7);
- g) PTP over PRP specifies a unified operation of DATC and SLTC RedBoxes (A.2.6.4);
- h) PTP over HSR specifies the operation of RedBoxes for TCs (A.4.3);
- i) PTP datasets are aligned with IEC 61588:2021 (Clause A.6);
- j) PTP industry profile is extended:
  - Sync messages padding to support media converters (C.5.4);
  - ClockClass definition aligned with IEC 61588:2021 option a) (C.7.4.3);
  - TC operation over different domains (C.7.5.3);
  - BCs behaviour in holdover and recovery (C.7.6.2);
  - PICS entries renamed and extended (C.13.2);
  - Flags semantics in TimePropertyDS actualized (C.14.1);
  - UTC events handling during a leap second specified (C.14.2);
  - UTC leap second time representation aligned with IEEE C37.118.2 (C.14.2.2);
  - Daylight saving time and leap second events recommended in the ALTERNATE\_TIME\_OFFSET\_INDICATOR TLV (C.14.3.2);
- k) Tutorial extended to explain the media converter issue (D.8.3);
- l) PTP network management MIB (Annex E) is available as a "Code Component", machine-readable separate document and considers IEC 61588:2021 objects;
- m) Conformance testing for PRP, HSR and the doubly attached PTP clocks (Annex F) has been added.
- n) Interoperability issues with previous editions of this International Standard are mentioned in a note at the end of the corresponding clause.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
65C/XX/FDIS	65C/XX/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/standardsdev/publications](http://www.iec.ch/standardsdev/publications).

This International Standard is to be read in conjunction with IEC 62439-1.

A list of all parts in the IEC 62439 series, published under the general title *Industrial communication networks – High availability automation networks*, can be found on the IEC website.

This IEC standard includes Code Components, i.e., components that are intended to be directly processed by a computer. Such content is any text found between the markers <CODE BEGINS> and <CODE ENDS>, or otherwise is clearly labeled in this standard as a Code Component.

The purchase of this IEC standard carries a copyright license for the purchaser to sell software containing Code Components from this standard directly to end users and to end users via distributors, subject to IEC software licensing conditions, which can be found at: <http://www.iec.ch/CCv1>.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.**

## INTRODUCTION

### 0.1 General

This document belongs to the IEC 62439 series “*Industrial communication networks – High availability automation networks*”. It was developed jointly with IEC TC57 WG10 as the redundancy method for demanding substation automation networks operating on layer 2 networks, in accordance with IEC 61850-8-1 and IEC 61850-9-2, and extended to encompass the needs of CPF 2 of IEC 61784-1 and IEC 61784-2 for layer 3 networks.

This document specifies two related redundancy protocols that, in the event of failure of any network element, provide seamless switchover with zero recovery time:

- PRP (Parallel Redundancy Protocol), which allows attaching nodes to two separate networks while allowing attachment of nodes to one network only; and
- HSR (High-availability Seamless Redundancy), which allows threading two-port nodes in a ring or multi-port nodes in a meshed network.

This document applies the seamless redundancy principle to clocks compliant with the Precision Time Protocol (PTP).

This document specifies a PTP Industry profile (PIP) that offers the performance needed to achieve sub-microsecond time accuracy. This profile can be applied to any industrial communication network based on Ethernet. Two variants of PIP are specified:

- L3E2E (Layer 3, end-to-end) for clocks operating on layer 3 networks with end-to-end path delay measurement such as CP 2/2 of IEC 61784-1 and IEC 61784-2; and
- L2P2P (Layer 2, peer-to-peer) for clocks operating on layer 2 with peer-to-peer link delay measurement (P2P).

Based on L2P2P, IEC TC57 WG10 and the IEEE PSRC jointly specified the Power Utility Profile (PUP) and copied it to IEC/IEEE 61850-9-3. IEC and IEEE agreed to keep the contents of this document and IEC/IEEE 61850-9-3 aligned, under the umbrella of the Dual Logo Maintenance Team (DLMT) hosted by IEEE PSCC P20.

The specifications of PRP and HSR present no backward compatibility issues as the changes are compatible extensions of the protocol. The minor version of these protocols is kept at value “1”.

The specifications of the clock profile PIP are based on IEC 61588:2021, which presents some differences compared with IEC 61588:2009. The minorVersionPTP has been increased to 1.

This document includes guidelines for conformance testing, applicable to PRP, HSR and to the PIP and PUP clock synchronization profiles.

### 0.2 Patent declaration

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this standard may involve the use of a patent. IEC takes no position concerning the evidence, validity, and scope of this patent right.

The holder of this patent right has assured IEC that s/he is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from the patent database available at <http://patents.iec.ch>.

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those in the patent database. IEC shall not be held responsible for identifying any or all such patent rights.

## **INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –**

### **Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless Redundancy (HSR)**

## **1 Scope**

### **1.1 General**

The IEC 62439 series is applicable to high-availability automation networks based on the Ethernet technology.

This document:

- specifies PRP and HSR as two related redundancy protocols designed to provide seamless recovery in case of single failure of an inter-bridge link or bridge in the network, which are based on the same scheme: parallel transmission of duplicated information;
- specifies the operation of the precision time protocol (PTP) in networks that implement the two redundancy protocols (Annex A);
- specifies PTP profiles with performance suitable for power utility automation (Annex B) and industrial automation (Annex C);
- includes for better understanding a tutorial (Annex D) on the PTP features effectively used in high-availability automation networks;
- includes a management information base for PTP (Annex E);
- defines a conformance test suite for the above protocols (Annex F).

### **1.2 Code component distribution**

This document is associated with Code components. Each Code Component is a ZIP package containing at least the electronic representation of the Code Component itself and a file describing the content of the package (IECManifest.xml).

The IECManifest contains different sections giving information on:

- the copyright notice;
- the identification of the code component;
- the publication related to the code component;
- the list of the electronic files which compose the code component;
- an optional list of history files to track changes during the evolution process of the code component.

The Code Components associated with this IEC standard are a set of SNMP MIBs. The Code Component IEC-62439-3-MIB.mib is a file containing the MIBs for PRP/HSR and PTP\_SNMP. It is available in a full version, which contains the MIBs defined in this document with the documentation associated and access is restricted to purchaser of this document.

The Code Components are freely accessible on the IEC website for download at: [https://www.iec.ch/sc65c/supportingdocuments/IEC\\_62439-3.MIB.{VersionStateInfo}.full.zip](https://www.iec.ch/sc65c/supportingdocuments/IEC_62439-3.MIB.{VersionStateInfo}.full.zip) but the usage remains under the licensing conditions.



The life cycle of a code component is not restricted to the life cycle of the related publication. The publication life cycle goes through two stages, "Version" (corresponding to an edition) and "Revision" (corresponding to an amendment). Consequently, new release(s) of the Code Component(s) may be released, which supersede(s) the previous release, and will be distributed through the IEC web site at: <https://www.iec.ch/sc65c/supportingdocuments>.

The latest version/release of the document will be found by selecting the file IEC\_62439-3.MIB.{VersionStateInfo}.full.zip for the code component with the highest value for VersionStateInfo.

In case of any differences between the downloadable code and the IEC pdf published content, the downloadable code(s) is(are) the valid one; it may be subject to updates. See history files.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-192, *International Electrotechnical Vocabulary – Part 192: Dependability*

IEC 61588:2021, *Precision Clock Synchronization Protocol for Networked Measurement and Control Systems*

IEC TR 61850-90-4:2020, *Communication networks and systems for power utility automation – Part 90-4: Network engineering guidelines*

IEC 62439-1, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation method*

ISO/IEC/IEEE 8802-3:2021, *Standard for Ethernet*

IEC/IEEE 61850-9-3:2016, *Communication networks and systems for power utility automation – Part 9-3: Precision time protocol profile for power utility automation*

IEEE 802.1Q-2018, *IEEE Standard for Local and metropolitan area networks – Bridges and Bridged Network*

NOTE IETF references are dated with the original Request for Comment (RFC). Subsequent versions receive a new RFC number. Since IETF amends or extends documents and publishes errata on-line, the valid version can be found on the internet at <https://tools.ietf.org/>.

IETF RFC 768, *User Datagram Protocol (UDP)* [online]. August 1980 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc768>

IETF RFC 791, *Internet Protocol (IP)* [online]. September 1981 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc791>

IETF RFC 792, *Internet Control Message Protocol* [online]. September 1981 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc792>

IETF RFC 793, *Transmission Control Protocol* [online]. September 1981 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc793>

IETF RFC 826, *Ethernet Address Resolution Protocol* [online]. November 1982 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc826>

IETF RFC 2578, *Structure of Management Information Version 2 (SMIv2)* [online]. April 1999 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc2578>

IETF RFC 3418, *Structure of Management Information Version 2 (SMIv2)* [online]. December 2002 [viewed 2020-05-07]. Available at <https://tools.ietf.org/html/rfc3418>