

PRE-RELEASE VERSION (FDIS)



**Laser displays –
Part 5-5: Optical measuring methods of raster-scanning retina direct projection
laser displays**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.260

Warning! Make sure that you obtained this publication from an authorized distributor.



110/1374/FDIS

FINAL DRAFT INTERNATIONAL STANDARD (FDIS)

PROJECT NUMBER: IEC 62906-5-5 ED1	
DATE OF CIRCULATION: 2021-11-12	CLOSING DATE FOR VOTING: 2021-12-24
SUPERSEDES DOCUMENTS: 110/1308/CDV, 110/1341A/RVC	

IEC TC 110 : ELECTRONIC DISPLAYS	
SECRETARIAT: Japan	SECRETARY: Mr Yoshi SHIBAHARA
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 76,TC 100	HORIZONTAL STANDARD: <input type="checkbox"/>
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING	<input checked="" type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE: Laser displays – Part 5-5: Optical measuring methods of raster-scanning retina direct projection laser displays
--

PROPOSED STABILITY DATE: 2025

NOTE FROM TC/SC OFFICERS:

CONTENTS

FOREWORD	5
1 Scope	7
2 Normative references	7
3 Terms, definitions and abbreviated terms	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	8
4 Standard measuring conditions.....	9
4.1 Standard measuring environmental conditions	9
4.2 Coordinate system	9
4.3 Standard conditions of RS-RDP laser displays and light measuring devices.....	10
4.3.1 General	10
4.3.2 Adjustment of RS-RDP laser display.....	10
4.3.3 Requirements for light measuring device	10
4.4 Laser-safety requirements for measurement	12
5 Optical measuring methods	12
5.1 General.....	12
5.2 Optical power at the primary colour wavelength	12
5.2.1 General	12
5.2.2 Measurement at exit window (measurement point 1).....	12
5.2.3 Measurement at focal point (measurement point 2).....	13
5.2.4 Elimination of the effect of other spectral powers	13
5.3 Eye-box	14
5.3.1 General	14
5.3.2 Eye-box measurement by 2D image sensor	15
5.3.3 Eye-box measurement by goniometric spectroradiometer	15
5.4 Field of view	16
5.4.1 General	16
5.4.2 FOV measurement by 2D image sensor.....	16
5.4.3 FOV measurement by goniometric spectroradiometer.....	17
5.5 Aspect ratio	17
5.6 Effective angular image resolution	18
5.6.1 General	18
5.6.2 Measuring methods of effective angular image resolution	19
5.7 Retinal free focus range.....	22
5.7.1 General	22
5.7.2 Retinal free focus range measured by direct method	23
5.7.3 Retinal free focus range measured by imaging method.....	24
5.8 Retinal white illuminance	24
5.8.1 General	24
5.8.2 Retinal white illuminance measurement using the method in 5.2.3.....	25
5.8.3 Retinal white illuminance measurement using spectral irradiance meter	25
5.9 Luminance and chromaticity of virtual image.....	25
5.9.1 General	25
5.9.2 Measurement procedure.....	25
5.10 White chromaticity nonuniformity	26

5.10.1	General	26
5.10.2	White chromaticity nonuniformity	26
5.10.3	Virtual image chromaticity nonuniformity	26
6	Report	27
Annex A (informative)	Structure of RS-RDP laser displays	28
A.1	General	28
A.2	Example of mechanical structure	28
A.3	Example of fundamental electro-optical structure of RS-RDP laser display	28
Annex B (informative)	Maxwellian view of RS-RDP laser displays	30
B.1	General	30
B.2	Maxwellian view	30
B.3	Pinhole image on the retina in the Maxwellian view	31
B.4	Laser image on the retina in the Maxwellian view	31
Annex C (informative)	Eyeball model and use of planar 2D sensor for measuring optical property	32
C.1	Human eyeball structure, its optics and modelling for practical measurement	32
C.2	Retinal sensor model	36
C.3	Optical measuring method with planar 2D image sensor	37
Annex D (informative)	Comparison of retinal illuminance with other displays	43
D.1	Projected area on retina	43
D.2	Retinal illuminance estimation for the conventional displays using natural viewing	45
D.3	Retinal illuminance estimation for RS-RDP laser display using Maxwellian viewing	46
D.4	Comparison of retinal illuminance between RS-RDP laser displays and the conventional displays	46
Bibliography	47
Figure 1	– Coordinate system and setup for planar measurements	10
Figure 2	– Two measurement points of optical power	14
Figure 3	– Measurement geometry of the eye-box	16
Figure 4	– Measurement geometry of the FOV	17
Figure 5	– Example of beam waist for Maxwellian view at the 2D image sensor plane	18
Figure 6	– Example of measurement locations for effective angular image resolution	19
Figure 7	– Setup for measuring effective angular image resolution and retinal free focus range	20
Figure 8	– Test patterns for resolution measurement	21
Figure 9	– Example of contrast modulation plot	22
Figure 10	– Example of the measured results of retinal free focus range	24
Figure 11	– Nonuniformity measurement locations and box patterns	27
Figure A.1	– Example of mechanical structure of RS-RDP laser display	28
Figure A.2	– Example of electro-optical structure of RS-RDP laser display	29
Figure B.1	– Maxwellian view (a) and normal viewing (b)	30
Figure B.2	– Pinhole (a) and laser beam (b) in the Maxwellian view	31
Figure C.1	– Cross-sectional human eyeball structure	32
Figure C.2	– Schematic of the eye with geometrical and optical information	33

Figure C.3 – Calculated refracted beam angle in the eye with respect to incident beam angle for blue (465 nm), green (520 nm) and red (640 nm)	33
Figure C.4 – Schematic eye optics	35
Figure C.5 – Example of beam spot radius calculation for the eye model as a function of incident beam diameter	36
Figure C.6 – Retinal sensor model with curved 2D image sensor	37
Figure C.7 – Geometrical relationship between point A on the retina and B on the fovea plane for the Cartesian coordinate system	38
Figure C.8 – Cross-sectional view of the plane consisting of the z -axis and the line segment OB in Figure C.7	38
Figure C.9 – Schematic diagrams of human eye	39
Figure C.10 – Geometrical relation of points A, B, C, and D	42
Figure D.1 – Projected area on the spherical retina	44
Figure D.2 – Spherical cap cut off by a circular plane, 3D-view (a) and y - z cross-section (b)	44
Figure D.3 – Strip-shaped region S_V cut off by the two spherical caps	45

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LASER DISPLAYS –

Part 5-5: Optical measuring methods of raster-scanning retina direct projection laser displays

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62906-5-5 has been prepared by IEC technical committee 110: Electronic displays. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
110/XX/FDIS	110/XX/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts of the IEC 62906 series, under the general title *Laser display devices*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

LASER DISPLAYS –

Part 5-5: Optical measuring methods of raster-scanning retina direct projection laser displays

1 Scope

This part of IEC 62906 specifies the standard measurement conditions and optical measuring methods for raster-scanning retina direct projection laser displays with light sources such as direct-emitting lasers, optionally equipped with higher-order harmonic generation devices. The hybrid light sources using both lasers and spontaneous-emission-based light sources are not considered.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TR 60825-14, *Safety of laser products – Part 14: A user's guide*

IEC 62595-2-4:2020, *Display lighting unit – Part 2-4: Electro-optical measuring methods of laser module*

IEC 63145-20-10:2019, *Eyewear displays–Part 20-10: Fundamental measurement methods – Optical properties*

IEC 63145-20-20:2019, *Eyewear displays–Part 20-20: Fundamental measurement methods – Image quality*

ISO/CIE 19476, *Characterization of the performance of illuminance and luminance meters*

CIE 233, *Calibration, Characterization and Use of Array Spectroradiometers*