

## PRE-RELEASE VERSION (FDIS)



---

### Electronic displays – Part 2-1: Measurements of optical characteristics – Fundamental measurements

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 31.120; 31.260

**Warning! Make sure that you obtained this publication from an authorized distributor.**



PROJECT NUMBER:

**IEC 62977-2-1 ED1**

DATE OF CIRCULATION:

**2020-10-23**

CLOSING DATE FOR VOTING:

**2020-12-04**

SUPERSEDES DOCUMENTS:

**110/1188/CDV, 110/1215A/RVC**

IEC TC 110 : ELECTRONIC DISPLAYS	
SECRETARIAT: Japan	SECRETARY: Mr Yoshi SHIBAHARA
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 100,TA 2	HORIZONTAL STANDARD: <input type="checkbox"/>
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING	<input checked="" type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

**Electronic displays - Part 2-1: Measurements of optical characteristics - Fundamental measurements**

PROPOSED STABILITY DATE: 2024

NOTE FROM TC/SC OFFICERS:

## CONTENTS

FOREWORD .....	6
INTRODUCTION .....	8
1 Scope .....	9
2 Normative references .....	9
3 Terms, definitions and abbreviated terms .....	10
3.1 Terms and definitions .....	10
3.2 Abbreviated terms .....	11
4 General .....	11
4.1 Measured basic quantities .....	11
4.2 Electrical driving of the display (depending on the nature of the display) .....	11
4.3 Data acquisition timing and display driving .....	12
4.3.1 Stationary measurements .....	12
4.3.2 Properties of display under test .....	12
5 Standard measuring conditions .....	12
5.1 Standard measuring environmental conditions .....	12
5.2 Standard measuring darkroom conditions .....	12
5.3 Standard setup conditions .....	12
5.3.1 General .....	12
5.3.2 Adjustment of display .....	12
5.3.3 Starting conditions of measurements .....	13
5.3.4 Conditions of measuring equipment .....	13
5.4 Location of measurement field .....	15
5.5 Standard test patterns .....	16
5.6 Viewing direction coordinate system .....	16
6 Simple box optical measurement methods .....	17
6.1 General .....	17
6.2 Test patterns .....	17
6.3 Luminance .....	18
6.3.1 Purpose .....	18
6.3.2 Measuring conditions .....	18
6.3.3 Measuring method .....	18
6.4 Darkroom contrast ratio .....	19
6.4.1 Purpose .....	19
6.4.2 Measuring conditions .....	19
6.4.3 Measuring method .....	19
6.5 Luminance uniformity .....	20
6.5.1 Purpose .....	20
6.5.2 Measuring conditions .....	20
6.5.3 Measuring method .....	20
6.6 Chromaticity .....	21
6.6.1 Purpose .....	21
6.6.2 Measuring conditions .....	21
6.6.3 Measuring method .....	22
6.7 White chromaticity and correlated colour temperature .....	22
6.7.1 Purpose .....	22

6.7.2	Measuring conditions .....	22
6.7.3	Measuring method .....	22
6.8	Chromaticity non-uniformity .....	23
6.8.1	Purpose .....	23
6.8.2	Measuring conditions .....	23
6.8.3	Measuring method .....	23
6.9	Chromaticity/colour gamut area.....	24
6.9.1	Purpose .....	24
6.9.2	Measuring conditions .....	24
6.9.3	Measuring method .....	24
6.9.4	Chromaticity/colour gamut area in CIE 1931 and CIE 1976 chromaticity diagram .....	27
6.10	Luminance and colour variation with viewing direction .....	28
6.10.1	Purpose .....	28
6.10.2	Measuring conditions .....	28
6.10.3	Measuring method .....	28
7	Display multi-colour optical measuring methods .....	30
7.1	General.....	30
7.2	Test patterns.....	30
7.3	Luminance .....	33
7.3.1	Purpose .....	33
7.3.2	Measuring conditions .....	33
7.3.3	Measuring method .....	34
7.4	Darkroom contrast ratio .....	35
7.4.1	Purpose .....	35
7.4.2	Measuring conditions .....	35
7.4.3	Measuring method .....	35
7.5	Luminance uniformity .....	35
7.6	Chromaticity, tristimulus values, and spectra .....	35
7.6.1	Purpose .....	35
7.6.2	Measuring conditions .....	36
7.6.3	Measuring method .....	36
7.7	White chromaticity and correlated colour temperature .....	36
7.7.1	Purpose .....	36
7.7.2	Measuring conditions .....	36
7.7.3	Measuring method .....	36
7.8	Chromaticity/colour gamut area.....	37
7.8.1	Purpose .....	37
7.8.2	Measuring conditions .....	37
7.8.3	Measuring method .....	37
7.8.4	Chromaticity/colour gamut area in CIE 1931 and CIE 1976 chromaticity diagram .....	37
7.9	Chromaticity non-uniformity .....	38
7.10	Luminance and colour variation with viewing direction .....	38
7.10.1	Purpose .....	38
7.10.2	Measuring conditions .....	38
7.10.3	Measuring method .....	38
8	CIELAB colour gamut volume .....	39
8.1	Purpose .....	39

8.2	Measuring conditions .....	40
8.3	Measuring method .....	40
Annex A (normative) RGB boundary colours for CIELAB colour gamut volume measurements .....		43
A.1	General.....	43
A.2	Equally-spaced 98 boundary colours on the RGB cube .....	43
A.3	Recommended 602 boundary colours on the RGB cube .....	46
Annex B (informative) Calculation method for CIELAB gamut volume.....		61
B.1	Purpose .....	61
B.2	Procedure for calculating the colour gamut volume .....	61
B.3	Number of sampled colours .....	62
B.4	RGB cube surface subdivision method for CIELAB colour gamut volume calculation .....	62
B.4.1	General .....	62
B.4.2	Assumption.....	62
B.4.3	Uniform RGB grid algorithm .....	62
B.4.4	Software example execution .....	65
Annex C (informative) Significance of Clause 0.....		74
C.1	Summary .....	74
C.2	Significance of Clause 0 during the research and development stage .....	74
C.3	Significance of Clause 0 during the manufacturing stage .....	75
C.4	Significance of Clause 0 during the evaluation of other test results .....	76
Annex D (informative) Colour-signal luminance.....		77
Annex E (informative) Gamut rings .....		78
E.1	General.....	78
E.2	Visualization method.....	79
E.3	Software example .....	80
Bibliography.....		82
Figure 1 – Layout diagram of measurement setup with terminology.....		14
Figure 2 – Example of measurement locations with nine measurement locations equally spaced in the display active area .....		16
Figure 3 – Representation of the viewing direction, or direction of measurement .....		17
Figure 4 – Example of centre box test patterns using the standard 4 % and 10 % area boxes.....		18
Figure 5 – Example of uniformity measurement locations with nine measurement locations .....		20
Figure 6 – Examples of a display with colour boundaries represented by the black triangle in two common chromaticity diagrams .....		26
Figure 7 – Top view example of configurations for measuring luminance and colour in the horizontal viewing direction .....		29
Figure 8 – Side view example of configurations for measuring luminance and colour in the vertical viewing direction .....		30
Figure 9 – Standard medium APL loading version of the colour tile test pattern with red, green, blue, and white boxes used for luminance and colour measurements .....		31
Figure 10 – Medium APL loading version of colour tile patterns illustrating the sequence of test patterns used for luminance and colour measurements .....		31
Figure 11 – Standard medium APL RGBCMY test pattern used for centre luminance and colour measurements with 25 % APL .....		33

Figure 12 – Sequence for measuring luminance at the nine display locations for all coloured tile patterns .....	34
Figure 13 – Example of range in colours produced by a given display as represented by the CIELAB colour space .....	42
Figure B.1 – Analysis flow chart for calculating the CIELAB gamut volume .....	61
Figure B.2 – Example of tessellation using a 5 x 5 grid of surface colours on the RGB cube .....	64
Figure B.3 – Example of tessellation for the RGB cube using a 3 x 3 grid .....	66
Figure B.4 – Example of tessellation for the CIELAB gamut volume using a 3 x 3 grid .....	66
Figure C.1 – Example of conceptual scheme for the supply chain of displays and the usage of the measurement methods (MM) of Clause 0 and Clause 0 .....	74
Figure C.2 – Conceptual example of the evaluation of the components .....	75
Figure C.3 – Example of a mechanical stress test .....	76
Figure E.1 – Example of transformation of the CIELAB gamut volume (top) illustrated by $L^*$ slices into the concentric areas of the gamut ring representation (bottom) .....	79
Figure E.2 – Example of calculation of gamut rings using the data from Table B.1 .....	80
Table 1 – Summary of display characteristics .....	8
Table 2 – Example of luminance of white, red, green, and blue measured at nine screen locations and the resulting average luminance .....	21
Table 3 – Example of a white colour measured at nine screen locations and the resulting chromaticity non-uniformity .....	24
Table 4 – Standard digital-equivalent input signals for rendering the white, primary and secondary colours in test patterns .....	25
Table 5 – Example of report format for CIELAB gamut volume .....	42
Table A.1 – Equally-spaced 98 RGB boundary colours used for CIELAB colour gamut volume measurements .....	43
Table A.2 – Recommended RGB boundary colours used for CIELAB colour gamut volume measurements .....	46
Table B.1 – Example data format used for CIELAB colour gamut volume measurements .....	65

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### ELECTRONIC DISPLAYS –

#### Part 2-1: Measurements of optical characteristics – Fundamental measurements

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62977-2-1 has been prepared by IEC technical committee 110: Electronic displays.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
110/XX/FDIS	110/XX/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62977 series, published under the general title *Electronic displays*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**



## INTRODUCTION

This document describes the common optical measurement methods applicable in the field of electronic display devices, which can overlap with some of the parts of existing documents developed within TC 110 (IEC 61747-30-1 [1]<sup>1</sup>, IEC 62341-6-1, IEC 61988-2-1 [1], IEC 62715-5-1 [9]), that describe the optical measurement methods of the individual technologies, such as LCD, OLED, PDP and others. This document on common optical measurement methods is intended to be used as the reference document in future documents and in revisions of existing documents (e.g. IEC 61747-30-1, IEC 62341-6-1, IEC 61988-2-1, IEC 62715-5-1). The existing documents will be revised in their maintenance time to refer to this document to the largest extent possible.

All documents in IEC TC 110 that are concerned with the measurement of optical properties of electronic displays refer to a set of methods and procedures that are similar to each other, or sometimes even identical. This document is intended to identify these methods and to describe them, together with suitable precautions and diagnostics, as a reference for forthcoming documents to make the work of the involved experts more efficient and to avoid duplication of efforts.

Introduction of the common optical measurement method (COMM) is also related to a structure where each kind of optical measurement finds its unambiguous position for identification of similarities to other methods or for clarification of distinctions. This structural classification together with a general taxonomy is supposed to make the process of document production easier, faster and thus more effective.

The above characteristics are summarized in Table 1. The display characteristics that are addressed in this part of IEC 62977 are indicated by a check mark ✓ in the table.

**Table 1 – Summary of display characteristics**

Variables	Time		Location ( <i>x, y</i> )	Direction ( <i>θ, φ</i> )	Test pattern, electrical driving, input signal	Illumination conditions	Temperature, humidity
	Fast	Slow	Slow ✓	Slow	Slow ✓		
<b>Evaluation</b>							
Results	transitions from one optical state to another state	temporal stability (uniformity)	uniformity ✓	uniformity, ✓	static pattern, ✓ characteristic function (electro-optic transfer function, EOTF) characteristic values (e.g. threshold, saturation)	darkroom, ✓ indoor, outdoor	standard environment ✓
Evaluation 1st order	turn-on, turn-off, delay (latency) time periods, temporal modulations				luminance, ✓ contrast, ✓ chromaticity, ✓ threshold, saturation values, steepness of transitions, etc.		
Evaluation 2nd order	flicker prediction, moving picture response time, etc.				EOTF from which the exponent gamma is evaluated chromaticity/ colour gamut area, ✓ colour gamut volume, ✓		

<sup>1</sup> Numbers in square brackets refer to the Bibliography.

## **ELECTRONIC DISPLAYS –**

### **Part 2-1: Measurements of optical characteristics – Fundamental measurements**

#### **1 Scope**

This part of IEC 62977 specifies standard measurement conditions and measuring methods for determining the optical characteristics of electronic display modules and systems. These methods apply to emissive and transmissive direct view displays that render real 2D images on a flat panel. This document evaluates the optical characteristics of these displays under darkroom conditions. This document applies to the testing of display performance in response to standard analogue or digital input signals that are not absolute luminance encoded. The input signal is relative RGB without metadata information that codes for real luminance, colour space or colour coordinates. These methods are limited to input signals with typical OETFs such as defined in IEC 61966-2-1, ITU BT. Rec. 601, ITU BT. Rec.709, and ITU BT. Rec.2020. The tests in this document are not approved for use with HDR input signals.

NOTE A flat panel or flat panel display is a display with a flat surface and minimal depth that emits visible light from the surface. The display is subdivided into an array of electronically driven pixels which can be light valves modulating a backlight, or self-luminous. Emissive/transmissive/reflective hybrid displays can be flat panel or flat panel displays.

#### **2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-845, *International Electrotechnical Vocabulary – Part 845: Lighting* (available at [www.electropedia.org](http://www.electropedia.org))

IEC 61966-2-1, *Multimedia systems and equipment – Colour measurement and management – Part 2-1: Colour management – Default RGB colour space – sRGB*

IEC 62341-6-1, *Organic light emitting diode (OLED) displays – Part 6-1: Measuring methods of optical and electro-optical parameters*

IEC TR 62977-2-3, *Electronic display devices – Part 2-3: Measurements of optical properties – Multi-colour test patterns*

ISO 9241-305, *Ergonomics of human-system interaction – Part 305: Optical laboratory test methods for electronic visual displays*

ISO 15076-1:2010, *Image technology colour management – Architecture, profile format and data structure – Part 1: Based on ICC.1:2010*

ISO/CIE 11664-1, *Colorimetry – Part 1: CIE standard colorimetric observers*

ISO/CIE 11664-4, *Colorimetry – Part 4: CIE 1976 L\*a\*b\* colour space*

CIE 15:2004, *Colorimetry, 3<sup>rd</sup> edition*

CIE 168:2005, *Criteria for the evaluation of extended-gamut colour encodings*

CIE 233:2019, *Calibration, characterization and use of array spectroradiometers*

ITU-R BT.601, *Studio encoding parameters of digital television for standard 4:3 and wide screen 16:9 aspect ratios*

ITU-R BT.709, *Parameters values for the HDTV standards for production and international programme exchange*

ITU-R BT.2020, *Parameters values for ultra-high definition television systems for production and international programme exchange*