

This is a preview - click here to buy the full publication



IEC 80000-6

Edition 2.0 2022-06

PRE-RELEASE VERSION (FDIS)

**Quantities and units –
Part 6: Electromagnetism**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 01.040.29; 17.220.01

Warning! Make sure that you obtained this publication from an authorized distributor.



25/732/FDIS

FINAL DRAFT INTERNATIONAL STANDARD (FDIS)

PROJECT NUMBER:

IEC 80000-6 ED2

DATE OF CIRCULATION:

2022-06-10

CLOSING DATE FOR VOTING:

2022-07-15

SUPERSEDES DOCUMENTS:

25/683/CDV, 25/712C/RVC

IEC TC 25 : QUANTITIES AND UNITS	
SECRETARIAT: Italy	SECRETARY: Mr Luca Mari
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 1,TC 77,TC 85,TC 106,CIS/D,CIS/I	HORIZONTAL STANDARD: <input type="checkbox"/>
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Final Draft International Standard (FDIS) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Quantities and units - Part 6: Electromagnetism

PROPOSED STABILITY DATE: 2027

NOTE FROM TC/SC OFFICERS:

CONTENTS

FOREWORD	3
INTRODUCTION	5
0.1 Tables of quantities	5
0.2 Units	5
0.2.1 General	5
0.2.2 Remark on units for quantities of dimension one, or dimensionless quantities	5
0.3 Numerical statements in this document	6
0.4 Special remarks	6
0.4.1 General	6
0.4.2 System of quantities	6
0.4.3 Sinusoidal quantities	7
0.4.4 Root-mean-square value, RMS value	7
1 Scope	8
2 Normative references	8
3 Names, symbols, definitions and units of quantities	8
Annex A (informative) Units in the CGS system with special names	27
Alphabetical index	28
Bibliography	34
Table 1 – Quantities and units in electromagnetism	9
Table A.1 – Deprecated units with special names taken from the CGS system	27

INTERNATIONAL ELECTROTECHNICAL COMMISSION

QUANTITIES AND UNITS –

Part 6: Electromagnetism

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 80000-6 has been prepared by IEC technical committee 25: Quantities and units, and their letter symbols in close cooperation with ISO/TC 12, Quantities and units. It is an International Standard.

This second edition of IEC 80000-6 cancels and replaces the first edition published in 2008. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) With the new definitions in SI, some previously exact values for quantities now must be determined experimentally while other quantities are given as exact values;
- b) Item 6-2.2, elementary charge added;
- c) Item 6-11.4, induced voltage, added;
- d) Index of entries added;
- e) Editorial alignment to other parts of the IEC and ISO 80000 series.

The text of this International Standard is based on the following documents:

Draft	Report on voting
25/XX/FDIS	25/XX/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

IEC 80000 consists of the following parts, under the general title *Quantities and units*:

- 1) *Part 6: Electromagnetism*
- 2) *Part 13: Information science and technology*
- 3) *Part 15: Logarithmic and related quantities, and their units*
- 4) *Part 16: Printing and writing rules*
- 5) *Part 17: Time dependency*

The following parts are published by ISO:

- 1) *Part 1: General*
- 2) *Part 2: Mathematical signs and symbols to be used in the natural sciences and technology*
- 3) *Part 3: Space and time*
- 4) *Part 4: Mechanics*
- 5) *Part 5: Thermodynamics*
- 6) *Part 7: Light*
- 7) *Part 8: Acoustics*
- 8) *Part 9: Physical chemistry and molecular physics*
- 9) *Part 10: Atomic and nuclear physics*
- 10) *Part 11: Characteristic numbers*
- 11) *Part 12: Condensed matter physics*

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

0.1 Tables of quantities

The names in English of the most important quantities within the field of this document are given together with their symbols and, in most cases, their definitions. The definitions are given for identification of the quantities in the International System of Quantities (ISQ), listed in Table 1; they are not intended to be complete.

The scalar, vectorial or tensorial character of quantities is pointed out, especially when this is needed for the definitions.

In most cases, only one name and only one symbol for the quantity are given; where two or more names or two or more symbols are given for one quantity and no special distinction is made, they are on an equal footing. When two types of italic letters exist (for example as with ϑ and θ ; φ and ϕ ; a and α ; g and g) only one of these is given. This does not mean that the other is not equally acceptable. It is recommended that such variants should not be given different meanings. A symbol within parenthesis implies that it is an alternative symbol, to be used when, in a particular context, the main symbol is in use with a different meaning.

0.2 Units

0.2.1 General

The names of units for the corresponding quantities are given together with the international symbols and the definitions. These unit names are language-dependent, but the symbols are international and the same in all languages. For further information, see the SI Brochure (9th edition 2019) from BIPM and ISO 80000-1.

The units are arranged in the following way:

- a) The base SI units are given first. The SI units have been adopted by the General Conference on Weights and Measures (Conférence Générale des Poids et Mesures, CGPM). The use of base SI units, and their decimal multiples and submultiples formed with the SI prefixes are recommended, although the decimal multiples and submultiples are not explicitly mentioned. The order of the units is kg, m, s, A, K, mol, cd.
- b) Some non-SI units are then given, being those accepted by the International Committee for Weights and Measures (Comité International des Poids et Mesures, CIPM), or by the International Organization of Legal Metrology (Organisation Internationale de Métrologie Légale, OIML), or by ISO and IEC, for use with the SI.
- c) Non-SI units that are not recommended are given only in annexes in some parts of ISO 80000 and IEC 80000. These annexes are informative, in the first place for the conversion factors, and are not integral parts of the standard. These deprecated units are arranged in two groups:
 - 1) units in the CGS system with special names, see Annex A;
 - 2) units based on the foot, pound, and some other related units.

0.2.2 Remark on units for quantities of dimension one, or dimensionless quantities

The coherent unit for any quantity of dimension one, also called a dimensionless quantity, is the number one, symbol 1. When the value of such a quantity is expressed, the unit symbol 1 is generally not written out explicitly.

EXAMPLE

Refractive index $n = 1,53 \times 1 = 1,53$

Prefixes shall not be used to form multiples or submultiples of this unit. Instead of prefixes, powers of 10 are recommended.

EXAMPLE

Reynolds number $Re = 1,32 \times 10^3$

Considering that plane angle is generally expressed as the ratio of two lengths and solid angle as the ratio of two areas, in 1995 the CGPM specified that, in the SI, the radian, symbol rad, and steradian, symbol sr, are dimensionless derived units. This implies that the quantities plane angle and solid angle are considered as derived quantities of dimension one. The units radian and steradian are thus equal to one; they may either be omitted, or they may be used in expressions for derived units to facilitate distinction between quantities of different kinds, but having the same dimension.

0.3 Numerical statements in this document

The sign = is used to denote "is exactly equal to" and the sign \approx is used to denote "is approximately equal to".

Numerical values of physical quantities that have been experimentally determined always have an associated measurement uncertainty. This uncertainty should always be specified. In this document, the magnitude of the uncertainty is represented as in the following example.

EXAMPLE

$l = 2,347\ 82(32)\ \text{m}$

In this example, $l = a(b)\ \text{m}$, the numerical value of the uncertainty b indicated in parentheses is assumed to apply to the last (and least significant) digits of the numerical value a of the length l . This notation is used when b represents one standard uncertainty (estimated standard deviation) in the last digits of a . The numerical example given above can be interpreted to mean that the best estimate of the numerical value of the length l , when l is expressed in the unit metre, is 2,347 82 and that the unknown value of l is believed to lie between $(2,347\ 82 - 0,000\ 32)\ \text{m}$ and $(2,347\ 82 + 0,000\ 32)\ \text{m}$ with a probability determined by the standard uncertainty 0,000 32 m and the probability distribution of the values of l .

0.4 Special remarks

0.4.1 General

The items given in IEC 80000-6 are generally in conformity with the International Electrotechnical Vocabulary (IEV), especially IEC 60050-121 and IEC 60050-131. For each quantity, the reference to IEV is given in the form: "See IEC 60050-121:20XX, 121-xx-xxx."

The font used for text is sans serif; that used for quantities is serif.

0.4.2 System of quantities

For electromagnetism, several different systems of quantities have been developed and used depending on the number and the choice of base quantities on which the system is based. However, in electromagnetism and electrical engineering, only the International System of Quantities, ISQ, and the associated International System of Units, SI, are acknowledged and are reflected in the standards of ISO and IEC. The SI has seven base units, among them are the kilogram (kg), the metre (m), the second (s), and the ampere (A).

0.4.3 Sinusoidal quantities

For quantities that vary sinusoidally with time, and for their complex representations, the IEC has standardized two ways to build symbols. Capital and lowercase letters are generally used for electric current (item 6-1) and for voltage (item 6-11.3), and additional symbols for other quantities. These are given in IEC 60027-1.

EXAMPLE 1

The sinusoidal variation with time of an electric current (item 6-1) can be expressed in real representation as

$$i = \sqrt{2} I \cos(\omega t - \varphi)$$

and its complex representation (termed phasor) is expressed as

$$i = I e^{-j\varphi}$$

where i is the instantaneous value of the current, I , is its root-mean-square (RMS) value (see 0.4.4), $(\omega t - \varphi)$ is the phase, φ is the initial phase, and j is the imaginary unit ($j^2 = -1$), in mathematics often denoted by i .

EXAMPLE 2

The sinusoidal variation with time of a magnetic flux (item 6-22.1) can be expressed in real representation as

$$\Phi = \hat{\Phi} \cos(\omega t - \phi) = \sqrt{2} \Phi_{\text{eff}} \cos(\omega t - \phi)$$

where Φ is the instantaneous value of the flux, $\hat{\Phi}$ is its peak value and Φ_{eff} is its RMS value.

0.4.4 Root-mean-square value, RMS value

For a time-dependent quantity a , the positive square root of the mean value of the square of the quantity taken over a given time interval is called root-mean-square value, i.e.

$$\sqrt{\frac{1}{T} \int_0^T a^2 dt}$$

The root-mean-square value of a periodic quantity is usually taken over an integration interval, the range of which is the period multiplied by a natural number. For a sinusoidal quantity $a(t) = \hat{A} \cos(\omega t + \varphi)$, the root-mean-square value is $\hat{A}/\sqrt{2}$.

The root-mean-square value of a quantity may be denoted by adding one of the subscripts "eff" or "RMS" to the symbol of the quantity. In electrical technology, the root-mean-square values of electric current $i(t)$ and voltage $u(t)$ are usually denoted I and U , respectively.

QUANTITIES AND UNITS –

Part 6: Electromagnetism

1 Scope

This part of IEC 80000 gives names, symbols, and definitions for quantities and units of electromagnetism. Where appropriate, conversion factors are also given.

This document is based on classical electromagnetism, i.e. mainly Maxwell's equations. No reference is made to quantum field theories.

2 Normative references

There are no normative references in this document.