

This is a preview - click here to buy the full publication



**IEEE**

**IEC/IEEE 62271-37-013**

Edition 1.0 2015-10

# INTERNATIONAL STANDARD



---

**High-voltage switchgear and controlgear –  
Part 37-013: Alternating-current generator circuit-breakers**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 29.130.10

ISBN 978-2-8322-2871-5

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

CONTENTS .....	2
FOREWORD.....	12
1 General .....	14
1.1 Scope .....	14
1.2 Normative references .....	14
2 Normal and special service conditions.....	15
2.1 Normal service conditions .....	15
2.2 Special service conditions .....	15
3 Terms and definitions .....	15
3.1 General terms .....	16
3.2 Assemblies of switchgear and controlgear .....	18
3.3 Parts of assemblies .....	18
3.4 Switching devices .....	18
3.5 Parts of generator circuit-breakers.....	20
3.6 Operation.....	23
3.7 Characteristic quantities .....	25
3.8 Index of definitions .....	40
4 Ratings.....	44
4.1 Rated voltage $U_r$ .....	44
4.2 Rated insulation level .....	44
4.2.101 Dielectric strength.....	45
4.2.102 Rated power frequency withstand voltage $U_d$ .....	45
4.2.103 Rated lightning impulse withstand voltage $U_p$ .....	45
4.3 Rated frequency $f_r$ .....	45
4.4 Rated normal current $I_r$ and temperature rise.....	45
4.4.1 Rated normal current $I_r$ .....	45
4.4.2 Temperature rise.....	46
4.4.3 Particular points of Table 3 of IEC 62271-1:2007 .....	46
4.4.101 Emergency current ratings during loss of cooling .....	46
4.5 Rated short-time withstand current $I_k$ .....	47
4.6 Rated peak withstand current $I_p$ .....	47
4.7 Rated duration of short circuit $t_k$ .....	47
4.8 Rated supply voltage of closing and opening devices and of auxiliary and control circuits $U_a$ .....	48
4.8.1 General .....	48
4.8.2 Rated supply voltage $U_a$ .....	48
4.8.3 Tolerances.....	48
4.8.4 Ripple voltage .....	49
4.8.5 Voltage drop and supply interruption .....	49
4.9 Rated supply frequency of closing and opening devices and auxiliary circuits.....	49
4.10 Rated pressure of compressed gas supply for controlled pressure systems.....	49
4.11 Rated filling levels for insulation, interruption and/or operation.....	49
4.101 Rated short-circuit current .....	50
4.101.1 General .....	50
4.101.2 Rated system-source short-circuit breaking current.....	50

4.101.3	Rated generator-source short-circuit breaking current.....	52
4.101.4	Rated single-phase-to-earth fault breaking current.....	54
4.102	Rated peak short-circuit making current $I_{MC}$ .....	54
4.103	Rated load making and breaking current.....	54
4.104	Rated out-of-phase making and breaking current.....	55
4.105	Rated transient recovery voltage (TRV) related to the breaking currents.....	55
4.105.1	Representation of TRV waves.....	55
4.105.2	Rated values of TRV.....	56
4.106	Standard operating sequence.....	57
4.106.1	General.....	57
4.106.2	Rated short-circuit current operating sequence.....	58
4.106.3	Rated load current operating sequence.....	58
4.106.4	Rated out-of-phase current operating sequence.....	58
4.107	Rated time quantities.....	58
4.107.1	General.....	58
4.107.2	Rated break-time.....	58
4.107.3	Rated minimum opening time.....	59
4.108	Mechanical operation endurance capability classes M1 and M2.....	59
5	Design and construction.....	59
5.1	Requirements for liquids in generator circuit-breakers.....	59
5.2	Requirements for gases in generator circuit-breakers.....	60
5.3	Earthing of generator circuit-breakers.....	60
5.4	Auxiliary and control equipment.....	60
5.5	Dependent power operation.....	61
5.6	Stored energy operation.....	61
5.7	Independent manual or power operation (independent unlatched operation).....	61
5.8	Operation of releases.....	61
5.8.1	Shunt closing release.....	61
5.8.2	Shunt opening release.....	61
5.8.3	Capacitor operation of shunt releases.....	61
5.8.4	Under-voltage release.....	61
5.8.101	Multiple releases.....	61
5.8.102	Operation limits of releases.....	61
5.8.103	Power consumption of releases.....	61
5.9	Low- and high-pressure interlocking devices.....	62
5.10	Nameplates.....	62
5.10.101	Accessories.....	64
5.10.102	Modification of generator circuit-breakers.....	64
5.11	Interlocking devices.....	64
5.12	Position indication.....	64
5.13	Degrees of protection provided by enclosures.....	64
5.13.1	Protection of persons against access to hazardous parts and protection of the equipment against ingress of solid foreign objects (IP coding).....	65
5.13.2	Protection against ingress of water (IP coding).....	65
5.13.3	Protection of equipment against mechanical impact under normal service conditions (IK coding).....	65
5.14	Creepage distances for outdoor insulators.....	65
5.15	Gas and vacuum tightness.....	65
5.16	Liquid tightness.....	65

5.17	Fire hazard (flammability).....	65
5.18	Electromagnetic compatibility (EMC).....	65
5.19	X-ray emission .....	65
5.20	Corrosion .....	65
5.101	Requirements for simultaneity of poles during single closing and single opening operations.....	65
5.102	General requirement for operation .....	66
5.103	Pressure limits of fluids for operation .....	66
5.104	Vent outlets .....	66
5.105	Warning labels .....	66
5.106	Instructions .....	66
6	Type tests .....	67
6.1	General.....	68
6.1.1	Grouping of tests .....	68
6.1.2	Information for identification of specimens .....	68
6.1.3	Information to be included in type-test reports .....	68
6.2	Dielectric tests .....	68
6.2.1	Ambient air conditions during tests .....	68
6.2.2	Wet test procedure.....	69
6.2.3	Condition of the generator circuit-breaker during dielectric tests.....	69
6.2.4	Criteria to pass the test.....	69
6.2.5	Application of test voltage and test conditions.....	69
6.2.6	Tests of generator circuit-breakers of $U_T \leq 245$ kV .....	69
6.2.7	Tests of generator circuit-breakers of $U_T > 245$ kV .....	70
6.2.8	Artificial pollution tests for outdoor insulators.....	70
6.2.9	Partial discharge tests.....	70
6.2.10	Dielectric tests on auxiliary and control circuits.....	70
6.2.11	Voltage test as a condition check .....	70
6.3	Radio interference voltage (r.i.v.) tests .....	70
6.4	Measurement of the resistance of circuits .....	71
6.4.1	Main circuit.....	71
6.4.2	Auxiliary circuits.....	71
6.5	Temperature-rise tests .....	71
6.5.1	Conditions of the generator circuit-breaker to be tested .....	71
6.5.2	Arrangement of the equipment .....	71
6.5.3	Measurement of the temperature and the temperature rise.....	73
6.5.4	Ambient air temperature .....	73
6.5.5	Temperature-rise tests of the auxiliary and control equipment.....	73
6.5.6	Interpretation of the temperature-rise tests .....	74
6.5.101	Demonstrations of emergency conditions.....	74
6.6	Short-time withstand current and peak withstand current tests .....	74
6.6.1	Arrangement of the generator circuit-breaker and of the test circuit.....	74
6.6.2	Test current and duration .....	74
6.6.3	Behaviour of generator circuit-breaker during test.....	74
6.6.4	Conditions of generator circuit-breaker after test.....	74
6.7	Verification of the degree of protection .....	75
6.7.1	Verification of the IP coding.....	75
6.7.2	Verification of the IK coding.....	75
6.8	Tightness tests.....	75

6.9	Electromagnetic compatibility (EMC) tests .....	75
6.10	Additional tests on auxiliary and control circuits .....	75
6.10.1	General .....	75
6.10.2	Functional tests .....	75
6.10.3	Electrical continuity of earthed metallic parts test.....	75
6.10.4	Verification of the operational characteristics of auxiliary contacts.....	75
6.10.5	Environmental tests .....	75
6.10.6	Dielectric tests .....	76
6.11	X-radiation test procedure for vacuum interrupters .....	76
6.101	Mechanical and environmental tests .....	76
6.101.1	Miscellaneous provisions for mechanical and environmental tests .....	76
6.101.2	Mechanical operation test at ambient air temperature .....	79
6.101.3	Low and high temperature tests.....	81
6.101.4	Sound level tests .....	85
6.102	Miscellaneous provisions for making and breaking tests.....	85
6.102.1	General .....	85
6.102.2	Number of test specimens .....	86
6.102.3	Arrangement of generator circuit-breaker for tests .....	86
6.102.4	General considerations concerning testing methods.....	88
6.102.5	Synthetic tests .....	94
6.102.6	No-load operations before tests.....	94
6.102.7	Alternative operating mechanisms .....	94
6.102.8	Behaviour of generator circuit-breaker during tests .....	95
6.102.9	Condition of generator circuit-breaker after tests.....	96
6.102.10	Demonstration of the most severe switching conditions.....	98
6.102.11	Methods of determining prospective transient recovery voltage waves.....	115
6.103	System-source short-circuit making and breaking tests .....	115
6.103.1	Power factor of test circuit.....	115
6.103.2	Frequency of test circuit .....	115
6.103.3	Earthing of test circuit .....	115
6.103.4	Connection of test circuit to generator circuit-breaker.....	117
6.103.5	Applied voltage for system-source short-circuit making tests .....	117
6.103.6	System-source short-circuit making current .....	117
6.103.7	System-source short-circuit breaking current .....	117
6.103.8	Transient recovery voltage (TRV) for system-source short-circuit breaking tests .....	118
6.103.9	Measurement of transient recovery voltage during test.....	119
6.103.10	Power frequency recovery voltage .....	119
6.103.11	System-source short-circuit test operating sequence.....	119
6.103.12	System-source short-circuit test-duties .....	119
6.104	Load current breaking tests .....	121
6.104.1	General .....	121
6.104.2	Conditions of test severity .....	122
6.104.3	Number of tests .....	122
6.105	Generator-source short-circuit current making and breaking tests.....	122
6.105.1	Power factor of test circuit.....	122
6.105.2	Frequency of test circuit .....	122
6.105.3	Earthing of test circuit .....	123
6.105.4	Connection of the test circuit to the generator circuit-breaker.....	123

6.105.5	Applied voltage for generator-source short-circuit making tests .....	123
6.105.6	Generator-source short-circuit making current .....	124
6.105.7	Generator-source short-circuit breaking current .....	124
6.105.8	Transient recovery voltage (TRV) for generator-source short-circuit breaking tests .....	125
6.105.9	Measurement of transient recovery voltage during test.....	125
6.105.10	Power frequency recovery voltage .....	125
6.105.11	Generator-source short-circuit test operating sequence .....	125
6.105.12	Generator-source short-circuit breaking test-duties .....	125
6.106	Out-of-phase making and breaking tests .....	131
6.106.1	General .....	131
6.106.2	Out-of-phase current switching capability.....	132
6.106.3	Conditions of test severity .....	132
6.106.4	Test circuit.....	134
6.106.5	Applied voltage before out-of-phase making tests .....	136
6.106.6	Transient recovery voltage (TRV) for out-of-phase breaking tests.....	136
6.106.7	Demonstration of the most severe switching conditions during test-duty OP1 .....	136
6.106.8	Demonstration of the most severe switching conditions during test-duty OP2 .....	136
7	Routine tests .....	136
7.1	Dielectric test on the main circuit .....	137
7.2	Tests on auxiliary and control circuits .....	137
7.2.1	Inspection of auxiliary and control circuits, and verification of conformity to the circuit diagrams and wiring diagrams .....	137
7.2.2	Functional tests .....	137
7.2.3	Verification of protection against electrical shock .....	137
7.2.4	Dielectric tests .....	137
7.3	Measurement of the resistance of the main circuit.....	138
7.4	Tightness test .....	138
7.4.1	Controlled pressure systems for gas.....	138
7.4.2	Closed pressure systems for gas.....	138
7.4.3	Sealed pressure systems .....	138
7.4.4	Liquid tightness tests .....	138
7.5	Design and visual checks .....	139
7.101	Mechanical operating tests .....	139
8	Guide to the selection of generator circuit-breakers .....	140
8.101	General.....	140
8.102	General application conditions .....	141
8.102.1	Normal service conditions .....	141
8.102.2	Special service conditions .....	141
8.103	Application consideration .....	143
8.103.1	General .....	143
8.103.2	Rated voltage .....	143
8.103.3	Rated insulation level.....	143
8.103.4	Rated frequency.....	144
8.103.5	Rated normal current .....	144
8.103.6	Short-circuit current rating.....	144
8.103.7	TRV rating for system-source and generator-source short-circuits .....	159
8.103.8	Rated load making and breaking current.....	165

8.103.9	Rated out-of-phase making and breaking current .....	169
8.103.10	Excitation switching current.....	170
8.103.11	Capacitive switching current.....	171
9	Information to be given with enquiries, tenders and orders.....	171
10	Rules for transport, storage, installation, operation and maintenance.....	173
10.1	Conditions during transport, storage and installation .....	173
10.2	Installation .....	174
10.2.1	Unpacking and lifting.....	174
10.2.2	Assembly.....	174
10.2.3	Mounting.....	174
10.2.4	Connections.....	174
10.2.5	Final installation inspection .....	174
10.2.6	Basic input data by the user .....	175
10.2.7	Basic input data by the manufacturer.....	175
10.2.101	Commissioning tests .....	175
10.2.102	Commissioning checks and test programme .....	176
10.3	Operation.....	179
10.4	Maintenance .....	180
10.4.1	General .....	180
10.4.2	Recommendations for the manufacturer.....	180
10.4.3	Recommendations for the user .....	181
10.4.4	Failure report.....	181
11	Safety .....	183
11.1	Precautions by manufacturers .....	183
11.2	Precautions by users.....	183
11.3	Electrical aspects .....	184
11.4	Mechanical aspects.....	184
11.5	Thermal aspects .....	185
11.6	Operation aspects .....	185
12	Influence of the product on the environment.....	185
Annex A (normative)	Tolerances on test quantities during type tests .....	186
Annex B (normative)	Records and reports of type tests according to 6.6, 6.103, 6.104, 6.105 and 6.106 .....	190
B.1	Information and results to be recorded.....	190
B.2	Information to be included in type test reports.....	190
B.2.1	General .....	190
B.2.2	Apparatus tested.....	190
B.2.3	Rated characteristics of generator circuit-breaker, including its operating devices and auxiliary equipment.....	190
B.2.4	Test conditions (for each series of tests) .....	191
B.2.5	Short-circuit making and breaking tests .....	191
B.2.6	Short-time withstand current test .....	192
B.2.7	No-load operation .....	192
B.2.8	Out-of-phase making and breaking tests.....	192
B.2.9	Load current switching tests.....	193
B.2.10	Oscillographic and other records .....	193
Annex C (...)	.....	194
Annex D (normative)	Use of mechanical characteristics and related requirements .....	195

Annex E (informative) Example of the application of a generator circuit-breaker .....	196
E.1 General .....	196
E.2 System characteristics .....	196
E.3 System-source short-circuit current .....	198
E.3.1 AC component of the system-source short-circuit breaking current .....	198
E.3.2 System-source asymmetrical short-circuit breaking current .....	199
E.4 Generator-source short-circuit current .....	201
E.4.1 AC component of the generator-source short-circuit breaking current .....	201
E.4.2 Generator-source asymmetrical short-circuit breaking current .....	202
E.5 Transient recovery voltage .....	204
E.6 Out-of-phase conditions .....	204
E.7 Normal current application .....	207
E.8 Generator circuit-breaker electrical characteristics .....	208
Annex F (informative) For generator circuit-breakers connected to the step-up transformer by shielded cables - An example of the effects of added capacitance on TRV requirements for a system-source fault .....	210
Annex G (informative) Symbols and related terminology .....	213
G.1 Comparison of IEEE and IEC electrical terms and symbols .....	213
G.2 Comparison between TRV terminology and symbols .....	214
Annex H (informative) Determination of the degree of asymmetry for generator-source short-circuit breaking tests .....	216
Annex I (informative) Faults in case of three-winding step-up transformer .....	218
Bibliography .....	221
Figure 1 – Typical oscillogram of a three-phase short-circuit make-break cycle .....	35
Figure 2 – Generator circuit-breaker without resistors – Opening operation .....	36
Figure 3 – Generator circuit-breaker without resistors – Close-open cycle .....	36
Figure 4 – Generator circuit-breaker with opening resistors – Opening operation .....	37
Figure 5 – Generator circuit-breaker with opening resistors – Close-open cycle .....	37
Figure 6 – Example of a three-phase asymmetrical current .....	38
Figure 7 – Examples of possible valid interruptions in a phase with intermediate level of asymmetry after a major loop and a corresponding time $t_1$ .....	39
Figure 8 – Examples of possible valid interruptions in a phase with intermediate level of asymmetry after a minor loop and a corresponding time $t_2$ .....	40
Figure 9 – Effect of various cooling failures and subsequent load reductions on generator circuit-breaker temperature .....	47
Figure 10 – Typical asymmetrical system-source short-circuit current .....	51
Figure 11 – Degree of asymmetry as a function of time after fault initiation .....	52
Figure 12 – Typical asymmetrical generator-source short-circuit current with a strong decrement of the a.c. component .....	53
Figure 13 – 2-parameter representation of prospective TRV waveform for interrupting three-phase symmetrical faults .....	56
Figure 14 – Typical temperature rise test setup for single-phase-enclosed generator circuit-breakers (top view) .....	73
Figure 15 – Test sequences for low and high temperature tests .....	85
Figure 16 – Reference mechanical travel characteristics (idealised curve) .....	89



Figure 17 – Reference mechanical travel characteristics (idealised curve) with the prescribed envelopes centered over the reference curve (+5 %, –5 %), contact separation in this example at time $t = 20$ ms .....	90
Figure 18 – Reference mechanical travel characteristics (idealised curve) with the prescribed envelopes fully displaced upward from the reference curve (+10 %, –0 %), contact separation in this example at time $t = 20$ ms .....	90
Figure 19 – Reference mechanical travel characteristics (idealised curve) with the prescribed envelopes fully displaced downward from the reference curve (+0 %, –10 %), contact separation in this example at time $t = 20$ ms .....	91
Figure 20 – Equivalent testing set-up for unit testing of generator circuit-breakers with more than one separate interrupter units .....	92
Figure 21 – Two valid three-phase symmetrical breaking operations .....	100
Figure 22 – Three-phase asymmetrical breaking operations – Minimum arcing time with intermediate asymmetry after major loop ( $t_{arc\ min\ 1}$ ) .....	102
Figure 23 – Three-phase asymmetrical breaking operations – Maximum arcing time for the first-pole-to-clear after major loop ( $t_{arc\ max\ 1}$ ) .....	103
Figure 24 – Three-phase asymmetrical breaking operations – Minimum arcing time with intermediate asymmetry after minor loop ( $t_{arc\ min\ 2}$ ) .....	104
Figure 25 – Three-phase asymmetrical breaking operations – Maximum arcing time for the last-pole-to-clear after extended major loop ( $t_{arc\ max\ 2}$ ) .....	105
Figure 26 – Single-phase asymmetrical breaking operations – Minimum arcing time with intermediate asymmetry after major loop ( $t_{arc\ min\ 1}$ ) .....	107
Figure 27 – Single-phase asymmetrical breaking operations – Maximum arcing time for the first-pole-to-clear after major loop ( $t_{arc\ max\ 1}$ ) .....	108
Figure 28 – Single-phase asymmetrical breaking operations – Minimum arcing time with intermediate asymmetry after minor loop ( $t_{arc\ min\ 2}$ ) .....	109
Figure 29 – Single-phase asymmetrical breaking operations – Maximum arcing time for the last-pole-to-clear extended major loop ( $t_{arc\ max\ 2}$ ) .....	110
Figure 30 – Earthing of test circuits for three-phase short-circuit tests, first-pole-to-clear factor 1,5 .....	116
Figure 31 – Earthing of test circuits for single-phase short-circuit tests, first-pole-to-clear factor 1,5 .....	116
Figure 32 – Example of a valid prospective test current for test-duty 5 .....	126
Figure 33 – Example of a valid test for test-duty 5 .....	126
Figure 34 – Example of an invalid test for test-duty 5 .....	127
Figure 35 – Second example of a valid test for test-duty 5 .....	127
Figure 36 – Example of a valid prospective test current for test-duties 6A and 6B .....	128
Figure 37 – Example of a valid test for test-duties 6A and 6B .....	128
Figure 38 – Example of a valid test for test-duties 6A and 6B .....	129
Figure 39 – Test circuit for single-phase out-of-phase tests .....	135
Figure 40 – Test circuit for out-of-phase tests using two voltages separated by 120 electrical degrees .....	135
Figure 41 – Test circuit for out-of-phase tests with one terminal of the generator circuit-breaker earthed (subject to agreement of the manufacturer) .....	135
Figure 42 – General circuit diagram of a power station .....	145
Figure 43 – Generator-source short-circuit current .....	147
Figure 44 – Generator-source short-circuit current in case of generator delivering power with lagging or leading power factor prior to fault initiation .....	148
Figure 45 – Short-circuit current for generator-source fault .....	149

Figure 46 – Short-circuit current with circuit-breaker arc voltage after contact separation.....	150
Figure 47 – Single-line diagram of a power station with two generators connected to the high-voltage system by means of a three-winding step-up transformer .....	159
Figure 48 – Single-line diagram of unit generator system.....	161
Figure 49 – Single-line diagram of half-sized transformer unit system .....	161
Figure 50 – Single-line diagram of system with half-sized generators .....	162
Figure 51 – Single-line diagram of power system .....	166
Figure 52 – Equivalent circuit of power system.....	166
Figure 53 – Voltage diagram for lagging power factor load .....	167
Figure 54 – Voltage diagram for unity power factor load.....	167
Figure 55 – Recovery voltage across the generator circuit-breaker .....	167
Figure 56 – TRV curve for the first-pole-to-clear.....	168
Figure E.1 – Single-line station diagram .....	196
Figure E.2 – Asymmetrical generator-source short-circuit current with no arc at the fault location.....	203
Figure E.3 – Asymmetrical generator-source short-circuit current with arc at the fault location .....	204
Figure E.4 – Schematic diagram of power station (single-line diagram as in Figure 48) .....	205
Figure E.5 – Prospective fault current considering the moment of inertia of the synchronous machine and resulting from synchronizing under out-of-phase conditions (out-of-phase angle $\varphi_0 = 90^\circ$ , fault initiation at $U_A = 0$ ).....	207
Figure E.6 – Generator circuit-breaker temperature and load current with loss of coolant .....	208
Figure F.1 – TRV rate-of-rise for system-source faults: transformers rated from 65,5 MVA to 100 MVA .....	211
Figure F.2 – TRV peak ( $u_C$ ) multipliers for system-source faults: transformers rated from 65,5 MVA to 100 MVA .....	211
Figure F.3 – TRV rate-of-rise for system-source faults: transformers rated from 10 MVA to 50 MVA .....	212
Figure F.4 – TRV peak ( $u_C$ ) multipliers for system-source faults: transformers rated from 10 MVA to 50 MVA.....	212
Figure G.1 – 2-parameter TRV envelope representation of 1-cosine TRV when interrupting three-phase symmetrical fault currents.....	215
Figure H.1 – Prospective generator-source short-circuit current (fault initiation at voltage zero) .....	217
Figure I.1 – Single-line diagram of a power station with two generators connected to the high-voltage system by means of a three-winding step-up transformer .....	218
Figure I.2 – Prospective system-source short-circuit current to be interrupted by Generator circuit-breaker #1 in case of three-phase earthed fault occurring at location F in Figure I.1 (only the current in the phase with the highest degree of asymmetry is shown – fault initiation at voltage = 0) .....	219
Figure I.3 – Prospective fault current fed by Generator 2 to be interrupted by Generator circuit-breaker 2 in case of three-phase earthed fault occurring at location F in Figure I.1 (only the current in the phase with the highest degree of asymmetry is shown – fault initiation at voltage = 0) .....	220

Table 1 – Rated insulation levels for a.c. generator circuit-breakers .....	45
Table 2 – Preferred values of supply voltages and their ranges for closing and opening devices and of auxiliary and control circuits of generator circuit-breakers .....	49
Table 3 – TRV parameters for system-source faults .....	56
Table 4 – TRV parameters for generator-source faults .....	57
Table 5 – TRV parameters for load current switching .....	57
Table 6 – TRV parameters for out-of-phase current switching .....	57
Table 7 – Nameplate information .....	62
Table 8 – Type tests .....	68
Table 9 – Conditions during temperature rise test .....	72
Table 10 – Number of operating sequences .....	80
Table 11 – Operations to be performed before and after the test programme .....	80
Table 12 – Test parameters for 50 Hz asymmetrical system-source fault test-duties for the first-pole-to-clear .....	111
Table 13 – Test parameters for 60 Hz asymmetrical system-source fault test-duties for the first-pole-to-clear .....	112
Table 14 – Test parameters for 50 Hz asymmetrical system-source fault test-duties for the last-pole-to-clear .....	113
Table 15 – Test parameters for 60 Hz asymmetrical system-source fault test-duties for the last-pole-to-clear .....	114
Table 16 – Test duties to demonstrate the system-source short-circuit making and breaking current capability for three-phase tests .....	120
Table 17 – Test duties to demonstrate the system-source short-circuit making and breaking current capability for single-phase tests .....	121
Table 18 – Test duties to demonstrate the generator-source short-circuit making and breaking current capability for three-phase tests .....	130
Table 19 – Test duties to demonstrate the generator-source short-circuit making and breaking current capability for single-phase tests .....	131
Table 20 – Test duties to demonstrate the out-of-phase current switching capability for three-phase tests .....	133
Table 21 – Test duties to demonstrate the out-of-phase current switching capability for single-phase tests .....	134
Table A.1 – Tolerances on test quantities for type tests .....	187
Table E.1 – System characteristics .....	197
Table G.1 – Comparison of IEEE and IEC electrical terms and symbols .....	213
Table G.2 – A comparison between the TRV terminology and symbols used in IEC 62271-100 with those used in older IEEE/ANSI standards .....	215
Table I.1 – A comparison between prospective system-source short-circuit currents to be interrupted by Generator circuit-breaker 1 in case of three-phase earthed fault occurring at location F in Figure I.1 .....	219

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

### HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

#### Part 37-013: Alternating-current generator circuit-breakers

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation.

IEEE Standards documents are developed within IEEE Societies and Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of IEEE and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards. Use of IEEE Standards documents is wholly voluntary. *IEEE documents are made available for use subject to important notices and legal disclaimers (see <http://standards.ieee.org/IPR/disclaimers.html> for more information).*

IEC collaborates closely with IEEE in accordance with conditions determined by agreement between the two organizations. This Dual Logo International Standard was jointly developed by the IEC and IEEE under the terms of that agreement.

- 2) The formal decisions of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees. The formal decisions of IEEE on technical matters, once consensus within IEEE Societies and Standards Coordinating Committees has been reached, is determined by a balanced ballot of materially interested parties who indicate interest in reviewing the proposed standard. Final approval of the IEEE standards document is given by the IEEE Standards Association (IEEE-SA) Standards Board.
- 3) IEC/IEEE Publications have the form of recommendations for international use and are accepted by IEC National Committees/IEEE Societies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC/IEEE Publications is accurate, IEC or IEEE cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications (including IEC/IEEE Publications) transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC/IEEE Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and IEEE do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC and IEEE are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or IEEE or their directors, employees, servants or agents including individual experts and members of technical committees and IEC National Committees, or volunteers of IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board, for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC/IEEE Publication or any other IEC or IEEE Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that implementation of this IEC/IEEE Publication may require use of material covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. IEC or IEEE shall not be held responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

International Standard IEC/IEEE 62271-37-013 has been prepared by a joint working group comprised of members both from IEC 17A/WG 52 representing subcommittee 17A: High-voltage switchgear and controlgear, of IEC technical committee 17: Switchgear and controlgear, in cooperation with IEEE WG P62271-37-013<sup>1</sup> representing the Switchgear Committee of the Power and Energy Society of the IEEE, under the IEC/IEEE Dual Logo Agreement.

This publication is published as an IEC/IEEE Dual Logo standard.

The text of this standard is based on the following documents:

FDIS	Report on voting
17A/1074/FDIS	17A/1101/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

International standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62271 series, published under the general title *High-voltage switchgear and controlgear*, can be found on the IEC website.

This standard shall be read in conjunction with IEC 62271-1: 2007, to which it refers and which is applicable unless otherwise specified in this standard. In order to simplify and clarify the structure of this document, the numbering of clauses and subclauses used here is the same as in IEC 62271-1. Amendments to these clauses and subclauses are given under the same numbering, while additional subclauses are numbered from 101.

The IEC Technical Committee and IEEE Technical Committee have decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

<sup>1</sup> A list of IEEE participants can be found at the following address:  
[http://standards.ieee.org/downloads/62271/62271-37-013-2015/62271-37-013-2015\\_wg-participants.pdf](http://standards.ieee.org/downloads/62271/62271-37-013-2015/62271-37-013-2015_wg-participants.pdf).

## HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

### Part 37-013: Alternating-current generator circuit-breakers

#### 1 General

##### 1.1 Scope

This part of IEC 62271 is applicable to three-phase a.c. high-voltage generator circuit-breakers, hereafter called generator circuit-breaker, designed for indoor or outdoor installation and for operation at frequencies of 50 Hz and 60 Hz on systems having voltages above 1 kV and up to 38 kV.

It is applicable to generator circuit-breakers that are installed between the generator and the transformer terminals. Requirements relative to generator circuit-breakers intended for use with generators and transformers rated 10 MVA or more are covered specifically. Generator circuits rated less than 10 MVA and pumped storage installations are considered special applications, and their requirements are not completely covered by this standard.

This standard is also applicable to the operating mechanisms of generator circuit-breakers and to their auxiliary equipment.

##### 1.2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-441:1984, *International Electrotechnical Vocabulary – Chapter 441: Switchgear, controlgear and fuses*

IEC 60060-1:2010, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60296:2012, *Fluids for electrotechnical applications – Unused mineral insulating oils for transformers and switchgear*

IEC 60480:2004, *Guidelines for the checking and treatment of sulphur hexafluoride (SF<sub>6</sub>) taken from electrical equipment and specification for its re-use*

IEC 60529:1989, *Degrees of protection provided by enclosures (IP Code)*

IEC 60529:1989/AMD1:1999

IEC 60529:1989/AMD2:2013

IEC 61180-1, *High-voltage test techniques for low voltage equipment – Part 1: Definitions, test and procedure requirements*

IEC 62262:2002, *Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK code)*

IEC 62271-1:2007, *High-voltage switchgear and controlgear – Part 1: Common specifications*  
IEC 62271-1:2007/AMD1:2011

IEC/IEEE 62271-37-013:2015

– 15 –

© IEC/IEEE 2015

IEC IEEE 62271-37-082:2012, *High-voltage switchgear and controlgear – Part 37-082: Standard practice for the measurement of sound pressure levels on alternating current circuit-breakers*

IEC 62271-100:2008, *High-voltage switchgear and controlgear – Part 100: Alternating current circuit-breakers*

IEC 62271-100:2008/AMD1:2012

IEC 62271-101:2012, *High-voltage switchgear and controlgear – Part 101: Synthetic testing*

IEC TR 62271-306:2012, *High-voltage switchgear and controlgear – Part 306: Guide to IEC 62271-100, IEC 62271-1 and other IEC standards related to alternating current circuit-breakers*

IEEE Std C37.011<sup>TM</sup>-2011, *IEEE Guide for the Application of Transient Recovery Voltage for AC High-Voltage Circuit Breakers (ANSI)*<sup>2</sup>

IEEE Std C37.23<sup>TM</sup>-2003 (Reaff 2008), *IEEE Standard for Metal-Enclosed Bus (ANSI)*

IEEE Std C37.59<sup>TM</sup>-2007, *IEEE Standard Requirements for Conversion of Power Switchgear Equipment*

---

<sup>2</sup> The IEEE standards or products referred to in this clause are trademarks of the Institute of Electrical and Electronics Engineers, Inc.