

This is a preview - click here to buy the full publication



IEEE

IEC/IEEE 63195-2

Edition 1.0 2022-01

PRE-RELEASE VERSION (FDIS)



**Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (Frequency range of 6 GHz to 300 GHz) –
Part 2: Computational procedure**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 17.220.20

Warning! Make sure that you obtained this publication from an authorized distributor.



This is a preview - click here to buy the full publication

106/564/FDIS

FINAL DRAFT INTERNATIONAL STANDARD (FDIS)

PROJECT NUMBER:

IEC/IEEE 63195-2 ED1

DATE OF CIRCULATION:

2021-12-31

CLOSING DATE FOR VOTING:

2022-02-11

SUPERSEDES DOCUMENTS:

106/508/CDV, 106/545A/RVC

IEC TC 106 : METHODS FOR THE ASSESSMENT OF ELECTRIC, MAGNETIC AND ELECTROMAGNETIC FIELDS ASSOCIATED WITH HUMAN EXPOSURE

SECRETARIAT:

Germany

SECRETARY:

Mr Diego Cuartielles

OF INTEREST TO THE FOLLOWING COMMITTEES:

TC 9,TC 27,TC 29,TC 34,SC 62A,SC 62B,TC 69,TC 77,TC 78,TC 96,TC 100,TC 124,CISPR

HORIZONTAL STANDARD:

FUNCTIONS CONCERNED:

EMC

ENVIRONMENT

QUALITY ASSURANCE

SAFETY

SUBMITTED FOR CENELEC PARALLEL VOTING

NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is a draft distributed for approval. It may not be referred to as an International Standard until published as such.

In addition to their evaluation as being acceptable for industrial, technological, commercial and user purposes, Final Draft International Standards may on occasion have to be considered in the light of their potential to become standards to which reference may be made in national regulations.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (Frequency range of 6 GHz to 300 GHz) - Part 2: Computational procedure

PROPOSED STABILITY DATE: 2023

NOTE FROM TC/SC OFFICERS:

Copyright © 2021 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references	9
3 Terms and definitions	10
3.1 Exposure metrics and parameters.....	10
3.2 Spatial, physical, and geometrical parameters associated with exposure metrics.....	11
3.3 Test device technical operating and antenna parameters.....	13
3.4 Computational parameters	13
3.5 Uncertainty parameters.....	14
4 Symbols and abbreviated terms.....	14
4.1 Symbols.....	14
4.1.1 Physical quantities.....	14
4.1.2 Constants	15
4.2 Abbreviated terms.....	15
5 Overview and application of this document	16
5.1 Overview of the numerical evaluation.....	16
5.2 Application of this document	17
5.3 Stipulations.....	18
6 Requirements on the numerical software	18
7 Model development and validation.....	19
7.1 General.....	19
7.2 Development of the numerical model of the DUT.....	19
7.3 Power normalization	20
7.4 Requirements on the experimental test equipment for model validation.....	22
7.4.1 General	22
7.4.2 Ambient conditions and device holder.....	23
7.4.3 Power measurement.....	23
7.5 Testing configurations for the validation of the DUT model.....	24
7.5.1 General	24
7.5.2 Tests to be performed.....	24
7.5.3 Determining the validity of the DUT model	25
7.5.4 Test reduction for additional DUTs.....	25
8 Power density computation and averaging.....	26
8.1 Evaluation surface	26
8.2 Tests to be performed and DUT configurations	26
8.2.1 General	26
8.2.2 Devices with a single radiating element or with multiple elements that do not operate simultaneously	27
8.2.3 Devices with antenna arrays or sub-arrays	27
8.2.4 Devices with multiple antennas or multiple transmitters	28
8.3 Considerations on the evaluation surface and dimensions of the computational domain	29
8.4 Averaging of power density on an evaluation surface	29
8.4.1 General	29

8.4.2	Construction of the averaging area on an evaluation surface	30
8.5	Computation of sPD by integration of the Poynting vector.....	31
8.5.1	General	31
8.5.2	Surface-normal propagation-direction power density into the evaluation surface, sPD_{n+}	31
8.5.3	Total propagating power density into the evaluation surface, sPD_{tot+}	32
8.5.4	Total power density directed into the phantom considering near-field exposure, sPD_{mod+}	32
8.6	Software	33
9	Uncertainty evaluation	33
9.1	General.....	33
9.2	Uncertainty of the sPD and of the $mpsPD$ due to the computational parameters	33
9.2.1	Uncertainty contributions due to the computational parameters	33
9.2.2	Mesh resolution	34
9.2.3	Absorbing boundary conditions	35
9.2.4	Power budget	35
9.2.5	Model truncation	35
9.2.6	Convergence	35
9.2.7	Dielectric properties.....	36
9.2.8	Lossy conductors.....	36
9.3	Uncertainty contribution of the computational representation of the DUT model	36
9.4	Uncertainty of the maximum exposure evaluation	37
9.5	Uncertainty budget.....	38
10	Reporting	39
Annex A (normative)	Code verification	41
A.1	General.....	41
A.2	Interpolation and superposition of vector field components	41
A.3	Computation of the far-field pattern and the radiated power	43
A.4	Implementation of lossy conductors	43
A.5	Implementation of anisotropic dielectrics.....	46
A.6	Computation of the sPD and $psPD$	47
A.6.1	General	47
A.6.2	Planar surfaces	49
A.6.3	Non-planar surfaces	50
A.7	Implementation of the field extrapolation according to the surface equivalence principle	52
Annex B (informative)	Experimental evaluation of the radiated power	53
B.1	General.....	53
B.2	Direct conducted power measurements.....	53
B.3	Radiated power measurement methods	54
B.4	Information provided by the DUT.....	54
Annex C (normative)	Maximum-exposure evaluation techniques	55
C.1	General.....	55
C.2	Evaluation of EM fields radiated by each antenna element.....	55
C.3	Evaluation of the $mpsPD$ by superposition of individual EM fields	56
C.3.1	General	56
C.3.2	Maximization over the entire codebook by exhaustive search	56

C.3.3	Optimization with fixed total conducted power.....	56
C.3.4	Optimization with fixed power at each port.....	56
Annex D (informative)	Examples of the implementation of power density averaging algorithms.....	58
D.1	Example for the evaluation of the <i>psPD</i> on a planar surface	58
D.1.1	General	58
D.1.2	Evaluation of the <i>psPD</i> by direct construction of the averaging area.....	58
D.1.3	Example for the efficient evaluation of the <i>psPD</i> using an equidistant mesh on the evaluation surface	59
D.2	Example for the evaluation of the <i>psPD</i> on a non-planar surface	60
Annex E (informative)	File format for exchange of field data	62
Annex F (informative)	Rationales of the methods applied in IEC/IEEE 63195-1 and this document.....	64
F.1	Frequency range.....	64
F.2	Computation of <i>sPD</i>	64
F.2.1	Application of the Poynting vector for computation of incident power density.....	64
F.2.2	Averaging area	65
Annex G (informative)	Square averaging area on non-planar evaluation surfaces	66
G.1	General.....	66
G.2	Example implementation for the evaluation of the <i>psPD</i> on a non-planar surface using square-shaped averaging area	66
Annex H (informative)	Validation of the maximum-exposure evaluation techniques	67
H.1	General.....	67
H.2	Validation of the exhaustive search.....	67
H.2.1	Validation of the exhaustive search	67
H.2.2	Validation using reconstruction method	67
H.2.3	Validation of optimization with fixed total conducted power or with fixed power at each port.....	67
H.2.4	Validation of the maximum-exposure evaluation of measurement results	67
H.3	Example validation source for maximum-exposure evaluation validation	68
H.3.1	Description	68
H.3.2	Positioning.....	70
H.3.3	Nominal codebook, uncertainty and conducted power P_R	71
H.3.4	Target values.....	71
Annex I (normative)	Supplemental files and their checksums	73
Bibliography.....		74
Figure 1 – Overview of the numerical power density evaluation procedure.....		17
Figure 2 – Power reference planes		22
Figure 3 – Example for configurations of radiating elements as different antenna sub-arrays on the same DUT		27
Figure 4 – Flow chart for the evaluation of power density for DUTs with antenna arrays or sub-arrays as described in 8.2.3		28
Figure 5 – Example of the construction of the averaging area within a sphere with fixed radius according to 8.4		31
Figure A.1 – Configuration of three $\lambda/2$ dipoles, D_1 , D_2 , and D_3 , for the evaluation of the interpolation and superposition of the electric field and magnetic field components.....		42
Figure A.2 – R320 waveguide		45

Figure A.3 – Cross section of the R320 waveguide showing the locations of the E_y components to be recorded.....	46
Figure A.4 – $S_i(x,y)$ computed with Formula (A.4) for the six parameter sets of Table A.6 normalized to their maxima	49
Figure A.5 – Cross sections of the symmetric quarters of the testing geometries (SAR Stars) for the benchmarking of the power density averaging algorithm.....	51
Figure A.6 – Areas for the computation of the sPD on a cone of the SAR Star.....	51
Figure D.1 – Rotated averaging area on the discretized evaluation surface (base mesh)	60
Figure D.2 – Reduction of the area of triangles that are partially included in the averaging sphere	61
Figure H.1 – Main dimensions of patch array stencil	69
Figure H.2 – Main dimensions of the validation device, including polypropylene casing	70
Figure H.3 – Validation device with SAM head in the tilt position	70
Figure H.4 – Validation device with SAM head in the touch position.....	71
Table 1 – Budget of the uncertainty contributions of the computational algorithm for the validation setup or testing setup	34
Table 2 – Budget of the uncertainty of the developed model of the DUT	37
Table 3 – Computational uncertainty budget	38
Table A.1 – Interpolation and superposition of vector field components; maximum permissible deviation from the reference results is 10 %.....	42
Table A.2 – Computation of P_R ; maximum permissible deviation from the reference results is 10 % for the radiated power and for the electric field amplitude of the far-field pattern	43
Table A.3 – Minimum fine and coarse mesh step for used method	46
Table A.4 – Results of the evaluation of the computational dispersion characteristics.....	46
Table A.5 – Results of the evaluation of the representation of anisotropic dielectrics	47
Table A.6 – Parameters for the incident power density distribution of Formula (A.4)	48
Table B.1 – Comparison of the experimental methods for the evaluation of the radiated power	53
Table H.1 – Main dimensions for the patch array stencil	68
Table H.2 – Main dimensions of the validation device	68
Table H.3 – Target values for validation device with the nominal codebook.....	72
Table H.4 – Target values for validation device with infinite codebook	72

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ASSESSMENT OF POWER DENSITY OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM WIRELESS DEVICES IN CLOSE PROXIMITY TO THE HEAD AND BODY (FREQUENCY RANGE OF 6 GHz TO 300 GHz) –

Part 2: Computational procedure

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC document(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation.

IEEE Standards documents are developed within IEEE Societies and Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of IEEE and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards. Use of IEEE Standards documents is wholly voluntary. *IEEE documents are made available for use subject to important notices and legal disclaimers (see <http://standards.ieee.org/ipr/disclaimers.html> for more information).*

IEC collaborates closely with IEEE in accordance with conditions determined by agreement between the two organizations. This Dual Logo International Standard was jointly developed by the IEC and IEEE under the terms of that agreement.

- 2) The formal decisions of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees. The formal decisions of IEEE on technical matters, once consensus within IEEE Societies and Standards Coordinating Committees has been reached, is determined by a balanced ballot of materially interested parties who indicate interest in reviewing the proposed standard. Final approval of the IEEE standards document is given by the IEEE Standards Association (IEEE SA) Standards Board.
- 3) IEC/IEEE Publications have the form of recommendations for international use and are accepted by IEC National Committees/IEEE Societies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC/IEEE Publications is accurate, IEC or IEEE cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications (including IEC/IEEE Publications) transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC/IEEE Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and IEEE do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC and IEEE are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or IEEE or their directors, employees, servants or agents including individual experts and members of technical committees and IEC National Committees, or volunteers of IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board, for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC/IEEE Publication or any other IEC or IEEE Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that implementation of this IEC/IEEE Publication may require use of material covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. IEC or IEEE shall not be held responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

IEC/IEEE 63195-2 was prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure, in cooperation with the International Committee on Electromagnetic Safety (ICES) of the IEEE Standards Association, under the IEC/IEEE Dual Logo Agreement between IEC and IEEE. It is an International Standard.

This document is published as an IEC/IEEE Dual Logo standard.

This publication contains supplemental files that are required for the code verification according to Annex A. Download links and checksums for these files can be found in Annex I.

The text of this International Standard is based on the following IEC documents:

Draft	Report on voting
106/XX/FDIS	106/XX/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with the rules given in the ISO/IEC Directives, Part 2, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC/IEEE 63195 series, published under the general title *Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body*, can be found on the IEC website.

The IEC Technical Committee and IEEE Technical Committee have decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This document provides a method to evaluate the human exposure from wireless devices using computational methods. This document was developed to provide procedures for the numerical modelling and evaluation of such wireless devices operating close to the head, held in the hand or in front of the face, mounted on the body or embedded in garments. It applies to individual transmitters as well as to transmitters operating simultaneously with other transmitters within a product. The choice of technique, i.e. FDTD or FEM, is optional but can be influenced by the application. The advantages of computational procedures include the capability to provide repeatable, non-intrusive methods for determining exposure in or near an object and without the need for expensive hardware equipment. Device categories covered include but are not limited to mobile telephones, radio transmitters in personal computers, desktop and laptop devices, and multi-band and multi-antenna devices. This document specifies:

- requirements on the numerical software (Clause 5);
- model development and validation (Clause 7);
- power density computation and averaging (Clause 8);
- uncertainty evaluation (Clause 9);
- reporting requirements (Clause 10).

To develop this document, IEC Technical Committee 106 (TC 106) and IEEE International Committee on Electromagnetic Safety (ICES), Technical Committee 34 (TC 34) Subcommittee 1 (SC 1) formed Joint Working Group 11 (JWG 11) on computational methods to assess the power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body.

ASSESSMENT OF POWER DENSITY OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM WIRELESS DEVICES IN CLOSE PROXIMITY TO THE HEAD AND BODY (FREQUENCY RANGE OF 6 GHz TO 300 GHz) –

Part 2: Computational procedure

1 Scope

This document specifies computational procedures for conservative and reproducible computations of power density (PD) incident to a human head or body due to radio-frequency (RF) electromagnetic field (EMF) transmitting devices. The computational procedures described are finite-difference time-domain (FDTD) and finite element methods (FEM), which are computational techniques that can be used to determine electromagnetic quantities by solving Maxwell's equations within a specified computational uncertainty. The procedures specified here apply to exposure evaluations for a significant majority of the population during the use of hand-held and body-worn RF transmitting devices. The methods apply to devices that can feature single or multiple transmitters or antennas, and that can be operated with their radiating part or parts at distances up to 200 mm from a human head or body.

This document can be employed to determine conformity with any applicable maximum PD requirements of different types of RF transmitting devices used in close proximity to the head and body, including those combined with other RF transmitting or non-transmitting devices or accessories (e.g. belt-clip), or embedded in garments. The overall applicable frequency range of these protocols and procedures is from 6 GHz to 300 GHz.

The RF transmitting device categories covered in this document include but are not limited to mobile telephones, radio transmitters in personal computers, desktop and laptop devices, and multi-band and multi-antenna devices.

The procedures of this document do not apply to PD evaluation of electromagnetic fields emitted or altered by devices or objects intended to be implanted in the body.

NOTE For the evaluation of the combined exposure from simultaneous transmitters operating on frequencies below 6 GHz, the relevant standards for SAR computation are IEC/IEEE 62704-1:2017 and IEC/IEEE 62704-4:2020.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC/IEEE 62704-1:2017, *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz – Part 1: General requirements for using the finite difference time-domain (FDTD) method for SAR calculations*

IEC/IEEE 62704-4:2020, *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz – Part 4: General requirements for using the finite element method for SAR calculations*

IEC/IEEE 63195-1:2021¹, *Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz) – Part 1: Measurement procedure*

IEEE Std 145, *IEEE Standard for Definitions of Terms for Antennas*

¹ To be published.