

This is a preview - click here to buy the full publication



IEC/PAS 61076-2-110

Edition 1.0 2010-03

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

**Connectors for electronic equipment – Product requirements –
Part 2-110: Circular connectors – Detail specification for circular connectors
M 12 × 1 with screw-locking, for high speed Ethernet and high speed data
communication with frequencies up to 500 MHz and 10 gigabits/s**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

S

ICS 13.220.10

ISBN 978-2-88910-793-3

CONTENTS

FOREWORD.....	4
1 General information.....	7
1.1 Scope.....	7
1.2 Recommended method of termination	7
1.2.1 Number of contacts or contact cavities	7
1.3 Ratings and characteristics	7
1.4 Normative references	7
1.5 Marking.....	8
1.6 Safety aspects.....	8
2 Technical information	8
2.1 Definitions	8
2.2 Survey of styles and variants.....	8
3 Dimensions	8
3.1 General.....	8
3.2 Interface dimensions	9
3.3 Gauges	9
3.3.1 Sizing gauges and retention force gauges	9
4 Characteristics	10
4.1 Climatic category.....	10
4.2 Electrical	10
4.2.1 Rated voltage – Rated impulse voltage – Pollution degree.....	10
4.2.2 Voltage proof.....	10
4.2.3 Current-carrying capacity.....	11
4.2.4 Contact resistance.....	11
4.2.5 Insulation resistance.....	11
4.3 Mechanical.....	11
4.3.1 IP degree of protection	11
4.3.2 Mechanical operation	11
4.3.3 Insertion and withdrawal forces	11
4.3.4 Contact retention in insert.....	12
4.3.5 Polarizing method.....	12
4.3.6 Vibration (sinusoidal).....	12
4.3.7 Shock	12
5 Test schedule.....	12
5.1 General.....	12
5.1.1 Arrangement for contact resistance measurements.....	13
5.1.2 Arrangement for dynamic stress tests (vibration)	13
5.2 Test schedule.....	14
5.2.1 Test group P-Preliminary	14
5.2.2 Test group AP – Dynamic/ Climatic.....	15
5.2.3 Test group BP – Mechanical endurance.....	17
5.2.4 Test group CP – Electrical load	18
5.2.5 Test group DP – Chemical resistivity	18
5.2.6 Test group EP – Connection method tests	19
5.2.7 Test group FP – Electrical transmission requirements	19

Figure 1 – Interface dimensions free connector.....	9
Figure 2 – Gauge dimensions	9
Figure 3 – Contact resistance arrangement.....	13
Figure 4 – Dynamic stress test arrangement.....	14
Table 1 – Gauges	10
Table 2 – Climatic category	10
Table 3 – Rated voltage - Impulse voltage – Pollution degree	10
Table 4 – Voltage proof connectors.....	10
Table 5 – Number of mechanical operations	11
Table 6 – Insertion and withdrawal forces	11
Table 7 – Number of test specimens	13
Table 8 – Test group P	15
Table 9 – Test group AP	15
Table 10 – Test group BP	17
Table 11 – Test group CP	18
Table 12 – Test group DP	18
Table 13 – Test group EP	19
Table 14 – Contact pair.....	19
Table 15 – Test group FP	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CONNECTORS FOR ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS

Part 2-110: Circular connectors – Detail specification for circular connectors M 12 × 1 with screw-locking, for high speed Ethernet and high speed data communication with frequencies up to 500 MHz and 10 gigabits/s

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC/PAS 61076-2-110 has been prepared by subcommittee 48B: Connectors, of IEC technical committee 48: Electromechanical components and mechanical structures for electronic equipment.



The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
48B/2096/PAS	48B/2148/RVD

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.

INTERNATIONAL ELECTROTECHNICAL COMMISSION	IEC 61076-2-110
ELECTRONIC COMPONENTS in accordance with IEC 61076-1	
 	<p>Circular connectors M12 × 1 mm 8 poles, for data communication with frequencies up to 500 MHz</p> <p>Pin and socket connector Rewireable – Non- rewireable</p> <p>Free cable connectors Straight and right angle connectors</p> <p>Fixed connectors</p> <p>Flange mounting Rear mounting Single hole mounting</p>

CONNECTORS FOR ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 2-110: Circular connectors – Detail specification for circular connectors M 12 × 1 with screw-locking, for high speed Ethernet and high speed data communication with frequencies up to 500 MHz and 10 gigabits/s

1 General information

Throughout this detail specification dimensions are in mm.

1.1 Scope

This Publicly Available Specification (PAS) describes M12 circular connectors for use in industrial environments for high speed Ethernet and high speed data transfer. Applications include, but are not limited to, vision systems and data acquisition. Screw locking M12 connectors consist of fixed and free connectors.

Male connectors have round contacts \varnothing 0,6mm.

1.2 Recommended method of termination

The contact terminations shall be of the following types: screw, crimp, insulation piercing, and insulation displacement.

1.2.1 Number of contacts or contact cavities

Connector type H	M12	2 to 8 contacts
------------------	-----	-----------------

1.3 Ratings and characteristics

Rated voltage: 48 V, see 4.2.1, Table 3

Current rating: 0,5 A, see 4.2.3

Insulation resistance: $10^8 \Omega$, see 4.2.5

Climatic category: $-25\text{ }^\circ\text{C} / +85\text{ }^\circ\text{C} / 21$ days see 4.1, Table 2

Contact spacing: see Clause 3

1.4 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-581, *International Electrotechnical Vocabulary – Electromechanical components for electronic equipment*

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*
Amendment 1 (1992)

IEC 60352-2, *Solderless connections – Part 2: Crimped connections – General requirements, test methods and practical guidance*

IEC 60512 (all parts), *Connectors for electronic equipment – Tests and measurements*

IEC 60512-1-100, *Connectors for electronic equipment – Tests and measurements – Part 1-100: General – Applicable publications*

IEC 60529:1989, *Degrees of protection provided by enclosures (IP code)*

IEC 60664-1, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests*

IEC 61076-1, *Connectors for electronic equipment – Product requirements – Part 1: Generic specification*

IEC 61076-2, *Connectors for use in d.c., low-frequency analogue and digital high speed data applications – Part 2: Circular connectors with assessed quality – Sectional specification*

IEC 61076-2-101:2008, *Connectors for electronic equipment – Product requirements – Part 2-101: Circular connectors – Detail specification for M12 connectors with screw-locking*

IEC 61984, *Connectors – Safety requirements and tests*

ISO 1302, *Geometrical Product Specifications (GPS) – Indication of surface texture in technical product documentation*